

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817291.0.7

Page:

1 / 6Date: **July 15, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427			Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO		Manufacturer's Works Order N°: N/A		
Manufacturing Process: HFW			Product Type: Line Pipe					Surface: Bare	
Standard or Specification: API Spec 5L 46th Edition 04/2018					Steel Grade: X65M PSL 2			Ends: Plain End Bevelled	
Dimensions: 16.000 x 0.500 in		Schedule: N/A	Length: 35'MIN 45'MAX		Quantity: 12 PCS 520 FT 43163 LB			Nominal Weight: 82.85 LB/FT	

TENSILE TEST

Heat N°	Sample N°	Zone	Lot N°	Specimen condition				Specimen dimensions		Test temp	Y.S.	U.T.S.	Y.S./U.T.S.	Elongation		
				Ls	Sc	Type	Ori	Size	.5% EUL		Req.	Req. Max.	Lo	Min.	Obt.	
									Min: 65 300		Min: 77 600					
									Max: 87 000		Max: 110 200					
								in	F	psi	psi		in	%	%	
2161576	220920	E1	2161576	B	AM	Ss	T	1.500	RT	76 406	90 982	0.83	2.0	23.0	33.1	
2262234	220722	E1	2262234	B	AM	Ss	T	1.500	RT	75 714	87 026	0.87	2.0	23.0	36.1	
2262235	220723	E1	2262235	B	AM	Ss	T	1.500	RT	74 641	88 228	0.84	2.0	23.0	31.1	

AM: As manufactured

B: Body

E1 / E2: Ends of Sampling

Lo: Initial length

Ls: Location of sample

Max: Maximum

Min: Minimum

Obt: Obtained

Ori: Orientation

Req. Max: Required maximum

Req: Required

RT: Room temperature

Sc: Specimen condition

Ss: Strip specimen

T: Transversal

U.T.S: Ultimate tensile strength

Y.S: Yield strength

Heat N°	Sample N°	Zone	Lot N°	Specimen condition				Specimen dimensions	Test temp	U.T.S.
				Ls	Sc	Type	Ori	Size		Req.
										Min: 77 600
										Max: 110 200
									F	psi
2161576	220920	E1	2161576	W	AM	Ss	T	1.500	RT	80 628
2262234	220722	E1	2262234	W	AM	Ss	T	1.500	RT	88 108
2262235	220723	E1	2262235	W	AM	Ss	T	1.500	RT	91 251

AM: As manufactured

Min: Minimum

Sc: Specimen condition

W: Weld

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817291.0.7

Page:

2 / 6Date: **July 15, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427			Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO		Manufacturer's Works Order N°: N/A		
Manufacturing Process: HFW		Product Type: Line Pipe						Surface: Bare	
Standard or Specification: API Spec 5L 46th Edition 04/2018				Steel Grade: X65M PSL 2			Ends: Plain End Bevelled		
Dimensions: 16.000 x 0.500 in		Schedule: N/A	Length: 35'MIN 45'MAX		Quantity: 12 PCS 520 FT		Nominal Weight: 43163 LB 82.85 LB/FT		

TENSILE TEST

E1 / E2: Ends of Sampling

Ori: Orientation

Ss: Strip specimen

Ls: Location of sample

Req: Required

T: Transversal

Max: Maximum

RT: Room temperature

U.T.S: Ultimate tensile strength

CHEMICAL COMPOSITION

					Composition %																		
					X 100									X 1000									X 100
					C	Mn	Si	Cu	Ni	Cr	Mo	CE-Pcm	P	S	Al	Sn	Nb	V	Ti	Ca	N	B	
H					Max	12	160	45	50	30	30	15	25	25	15	--	--	--	--	--	--	--	10
					Min	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Heat N°	Sample N°	Lot N°	Ls	P	Max	12	160	45	50	30	30	15	25	25	15	--	--	--	--	--	--	10	
				Min	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
2161576	4187078	2161576	B.M.	H	4	135	18	15	4	6	1	13	12	--	20	10	47	47	2	1	8	--	
2262234	4187105	2262234	B.M.	H	4	136	19	13	4	6	1	13	12	--	30	10	44	49	3	1	8	--	
2262235	4187117	2262235	B.M.	H	4	132	19	14	4	6	1	12	11	1	30	10	43	47	2	1	7	--	
2161576	4189275	2161576	B.M.	P	4	140	22	11	3	5	1	14	10	2	35	--	42	55	3	3	--	10	
2161576	4189295	2161576	B.M.	P	4	133	20	14	4	6	1	14	11	2	30	10	43	52	2	3	4	10	
2262234	4187689	2262234	B.M.	P	3	134	21	13	4	6	1	13	13	1	40	10	40	54	3	2	--	10	
2262234	4187709	2262234	B.M.	P	3	133	21	13	4	6	1	13	11	2	41	10	41	53	3	2	--	10	
2262235	4188966	2262235	B.M.	P	4	135	21	13	4	5	1	14	11	2	38	10	40	53	3	5	--	10	
2262235	4188986	2262235	B.M.	P	5	137	21	13	4	6	1	14	11	2	39	10	41	54	3	4	--	10	

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817291.0.7

Page:

3 / 6Date: **July 15, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427			Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO		Manufacturer's Works Order N°: N/A		
Manufacturing Process: HFW			Product Type: Line Pipe					Surface: Bare	
Standard or Specification: API Spec 5L 46th Edition 04/2018					Steel Grade: X65M PSL 2			Ends: Plain End Bevelled	
Dimensions: 16.000 x 0.500 in		Schedule: N/A		Length: 35'MIN 45'MAX		Quantity: 12 PCS 520 FT		Nominal Weight: 43163 LB 82.85 LB/FT	

CHEMICAL COMPOSITION

B.M: Base metal	H: Heat	Max: Maximum	P: Product
CE-Pcm: CE-Pcm	Ls: Location of sample	Min: Minimum	

THROUGH WALL HARDNESS

Required values			Individuals			Average			Hardness type:HRBW		
			Min: -	Max: 94.0	Var: --	Min: --	Max: --	Var: --			
Heat N°	Sample N°	Zone	Lot N°	Pipe N°	Specimen condition		Quad.		Scale		Avg.
					Ls	Sc					
2161576	220920	-	2161576	-	B	AM	-		HRBW		91.1
2262234	220722	-	2262234	-	B	AM	-		HRBW		90.6
2262235	220723	-	2262235	-	B	AM	-		HRBW		90.6

AM: As manufactured	Ls: Location of sample	Quad: Quadrant
Avg: Average	Max: Maximum	Sc: Specimen condition
B: Body	Min: Minimum	Var: Variation

IMPACT TEST

Type: Charpy V			Orientation: T				Unit: ft.lb				Shear area %			
Position:			Temp: 32		Unit: F		Ind.Min.Reg: 11		Req.Min.Avg: 15		Ind.Min.Reg: -		Req.Min.Avg: -	
Heat N°	Sample N°	Lot N°	Ls	Sc	T.T	Size	Results				Results			
					F		1	2	3	Avg.	1	2	3	Avg.
2161576	220920	2161576	B	AM	32	3/4	98	213	170	160	80	100	100	93

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817291.0.7

Page:

4 / 6Date: **July 15, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427			Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO		Manufacturer's Works Order N°: N/A		
Manufacturing Process: HFW			Product Type: Line Pipe					Surface: Bare	
Standard or Specification: API Spec 5L 46th Edition 04/2018					Steel Grade: X65M PSL 2			Ends: Plain End Bevelled	
Dimensions: 16.000 x 0.500 in		Schedule: N/A	Length: 35'MIN 45'MAX		Quantity: 12 PCS 520 FT			Nominal Weight: 43163 LB 82.85 LB/FT	

IMPACT TEST

Type: Charpy V			Orientation: T				Unit: ft.lb				Shear area %			
Position:			Temp: 32		Unit: F		Ind.Min.Reg: 11		Req.Min.Avg: 15		Ind.Min.Reg: -		Req.Min.Avg: -	
Heat N°	Sample N°	Lot N°	Ls	Sc	T.T	Size	Results				Results			
					F	-	1	2	3	Avg.	1	2	3	Avg.
2262234	220722	2262234	B	AM	32	3/4	112	100	119	110	85	85	85	85
2262235	220723	2262235	B	AM	32	3/4	119	209	198	175	80	100	100	93

AM: As manufactured

Ind. Min. Req: Individual Minimum Required

Sc: Specimen condition

Avg: Average

Ls: Location of sample

T.T: Test temperature

B: Body

Req. Min. Avg: Required minimum average

Temp: Temperature

FLATTENING TEST

Standard:				Standard:				Standard:			
Heat N°	Lot N°	Sample N°	Result	Heat N°	Lot N°	Sample N°	Result	Heat N°	Lot N°	Sample N°	Result
2161576	2161576	220920	Good	2262234	2262234	220722	Good	2262235	2262235	220723	Good

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817291.0.7

Page:

5 / 6Date: **July 15, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427		Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO	Manufacturer's Works Order N°: N/A
Manufacturing Process: HFW		Product Type: Line Pipe			Surface: Bare
Standard or Specification: API Spec 5L 46th Edition 04/2018			Steel Grade: X65M PSL 2		Ends: Plain End Bevelled
Dimensions: 16.000 x 0.500 in	Schedule: N/A	Length: 35"MIN 45"MAX	Quantity: 12 PCS 520 FT 43163 LB		Nominal Weight: 82.85 LB/FT

HYDROSTATIC TEST

Pressure		Time	Results
Unit	Value	Seconds	
psi	2,970	5	Satisfactory

SUPPLEMENTARY INFORMATION

Supplementary Information	Supplementary Information
This material has been manufactured, sampled, tested and inspected in accordance with this specification and has been found to meet the requirements called for by the above order. This product is silicon and/or aluminum fully killed. NDT OK; Longitudinal UT and Transverse EMI with ID/OD N-10 Notches (1.0" L and .039" W)	verified by 1/8" TDH BODY TENSILE SOURCED 180° FROM WELD LINE; CVN SAMPLES SOURCED 90° FROM WELD LINE; CVN SAMPLES TESTED BY 8mm STRIKER
Heat Treatment	Heat Treatment
The minimum weld seam heat treatment temperature is 1650F.	
Steel Vendor Name and Manufactured	Steel Vendor Name and Manufactured
2161576,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA 2262234,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA	2262235,NUCOR STEEL HICKMAN,ARMOREL,AR,Melted and Manufactured in USA

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.

**MAVERICK TUBE CORPORATION**

Hickman Plant
5020 N COUNTY RD 967
BLYTHEVILLE, AR 72315
(870) 776-5000 tel
(870) 776-5008 fax

MILL TEST CERTIFICATE

Number:

108817291.0.7

Page:

6 / 6Date: **July 15, 2026**

Customer: MRC Global CPU at Tenaris Hickman, North Co Road 967, Blytheville, AR 723157427		Customer's Order Item: 39080737/SO/70		Customer's Reference: US1119929PO	Manufacturer's Works Order N°: N/A
Manufacturing Process: HFW		Product Type: Line Pipe			Surface: Bare
Standard or Specification: API Spec 5L 46th Edition 04/2018			Steel Grade: X65M PSL 2		Ends: Plain End Bevelled
Dimensions: 16.000 x 0.500 in	Schedule: N/A	Length: 35"MIN 45"MAX	Quantity: 12 PCS 520 FT 43163 LB		Nominal Weight: 82.85 LB/FT

SUMMARY REPORT

Heat N°	Quantity	Length	Weight	Heat N°	Quantity	Length	Weight	Heat N°	Quantity	Length	Weight
	(Pieces)	FT	LB		(Pieces)	FT	LB		(Pieces)	FT	LB
2161576	7	308.766	25,584.682	2262234	2	78.789	6,528.541	2262235	3	133.356	11,050.21

The product certified herein has been manufactured, sampled, tested and inspected in accordance with the stated specifications and has been found to meet the requirements.

We, Tenaris, hereby acknowledge the restrictions as per article 3g(1) of Council Regulation (EU) No 833/2014, as amended, and confirm that our company is compliant with this legislation. Consequently, we, Tenaris, hereby represent and warrant that the steel products covered by this certificate, as listed in Annex XVII of Council Regulation (EU) No 833/2014 of 31 July 2014 and its subsequent amendments, do not originate from Russia. Furthermore, we confirm that the steel products covered by this certificate, as listed in Annex XVII of Council Regulation (EU) No 833/2014 of 31 July 2014 and its subsequent amendments, as required under article 3g(1)(d) (as amended) and related guidelines do not incorporate any steel or iron products as listed in the same Annex XVII originating in Russia when having been processed in a third country. We also acknowledge the equivalent restrictions as per Clause 17e of Norway's Russia Regulations of 15 August 2014 No. 1076 (FOR-2014-08-15-1076) and Regulations 46IA and 46IB of the UK Russia (Sanctions) (EU Exit) Regulations 2019, and confirm that our company is compliant with these laws as well.

CUSTOMER / THIRD PARTY

INSPECTION COMPANY
COMPAÑÍA DE INSPECCIÓN

Company Name: N/A
Employee Name: N/A

TENARIS QUALITY DEPARTMENT SIGNATURE

QUALITY CERTIFICATION DEPT.

Francisco G. Pinilla Portales

CHIEF OF QUALITY CERTIFICATION DEPT.

Kyle McCarthy

This certificate is issued by a computerized system and it is valid with electronic signature. On the original certificate the trade-mark green colored "Tenaris" is stamped. In case the owner of the original certificate would release a copy of it, he must attest its conformity to the original one taking upon himself the responsibility for any unlawful or not allowed use. Any alteration and/or falsification will be subjected to the law.