

26793124

BENTELER Steel/Tube
1 Benteler Drive|Shreveport|LA 71115|USA
Tel.: +1 318-216-4215
qms.shreveport@benteler.com

BENTELER 
Steel/Tube

1266822 321297

INSPECTION CERTIFICATE EN 10204-3.1
EN 10204:2005-01

Document No.: 465-1521734/002/P

Inspection No.:

Page: 1 / 3

Purchase Order No.: 10P45282

Manufacturer: BSTMC Shreveport USA

Kelly Pipe Co., LLC
PO Box 2827
SANTA FE SPRINGS CA 90670
USA

Benteler Order No.: 48010727

Manufacturer's brand:



Dispatch Note No.:

Stamp of the Inspection representative: MI

Product: SEAMLESS STEEL TUBES

Steelmaking process: ELECTRIC FURNACE

Terms of delivery: ASTM-A 53-2020, ASME SA-53, ASME BPVC.II.A-2023, ASTM-A 106-19a, ASME SA-106, ASME BPVC.II.A-2023, API Specification 5L
Forty-Sixth Edition April 2018 incl. Errata 1, May 2018, PSL 2, ANSI/NACE MR0175-2021/ISO 15156-1:2020, ANSI/NACE MR0175-2021/ISO
15156-2:2020, ANSI/NACE MR0103/ISO 17945:2015, ASME B36.10-2022

Dimensions-tolerances: ASTM-A 106-19a, ASME SA-106, ASME BPVC.II.A-2023, ASTM-A 53-2020, ASME SA-53, ASME BPVC.II.A-2023, API Specification 5L
Forty-Sixth Edition April 2018 incl. Errata 1, May 2018

Steel grade: GRADE B, GRADE C, GRADE BN, GRADE X42N

Delivery condition: N

Product marking: S: BENTELER - BENTELER-Sign - API 5L 1072 - API-Sign - Month/Year - A/SA 53 A/SA 106 NACE - 2,375" OD x
0,218" WT - B/C/BN/X42N - PSL2 - SMLS - Heat No. - Tube length feet - 2.970 - 15040598 - 10P45282 - LONGHORN

AEZ = Etching ink marking FK = color marking FS = paint stenciling FSD = Color jet printer FSI = Color jet printer Inside LK = Laser marking PKE = tag marking PS = die stamp TS = Ink jet spray marking

Item	Dimensions	Heat No.	Test pressure	
			PSI	sec
0001	2 NPS - SCH 80 35.000 FT - 45.000 FT	321297	2970	5

Country of melt and pour

Melted & Manufactured in USA
Nucor, Jewett, TX, US

Heat analysis [%]

Item	Heat No.	C	SI	MN	P	S	CR	MO	NI	CU	V	NB	TI	B
0001	321297	0.100	0.309	1.31	0.011	0.0000	0.25	0.07	0.24	0.16	0.051	0.004	0.002	0.0004

1. Formula: $CE_{IIW} = C + (Mn/6) + ((Cr + Mo + V)/5) + ((Cu + Ni)/15) \leq 0.43 \%$

2. Formula: $Cr + Cu + Mo + Ni + V \leq 1.00 \%$

3. Formula: $Nb + V \leq 0.06 \%$

4. Formula: $Nb + Ti + V \leq 0.15 \%$

INSPECTION CERTIFICATE EN 10204-3.1

Document No.:

465-1521734/002/P

Inspection No.:

Page: 2 / 3

Formula results

Item	Heat No.	1. Formula	2. Formula	3. Formula	4. Formula
0001	321297	0.419	0.771	0.055	0.057

Product analysis [%]

Item	Heat No.	C	SI	MN	P	S	CR	MO	NI	CU	V	NB	TI	B
0001	321297	0.100	0.310	1.26	0.012	0.0012	0.24	0.06	0.24	0.16	0.048	0.002	0.003	0.0004
0001	321297	0.100	0.310	1.27	0.012	0.0011	0.24	0.06	0.24	0.16	0.048	0.002	0.003	0.0004

1. Formula: $CE_{IIW} = C + (Mn/6) + ((Cr + Mo + V)/5) + ((Cu + Ni)/15) \leq 0.43 \%$

2. Formula: $Cr + Cu + Mo + Ni + V \leq 1.00 \%$

3. Formula: $Nb + V \leq 0.06 \%$

4. Formula: $Nb + Ti + V \leq 0.15 \%$

Formula results

Item	Heat No.	1. Formula	2. Formula	3. Formula	4. Formula
0001	321297	0.406	0.748	0.050	0.053
0001	321297	0.408	0.748	0.050	0.053

Test results

The tubes have been submitted to a leak tightness test by:	Hydrostatic test: acc. to API 5L; Test pressure/Time-record, the test records/charts shall be available for examination by the inspector			PASSED
The tubes are non destructive tested:	ET - Test standard: acc. to API 5L; ET - Test method: acc. to ASTM-E 309; ET - Test drilled hole: 0.125 IN.; ET - Notch shape/hole: drilled hole			PASSED
Visual inspection:	PASSED	Bending test:	PASSED	Dimensions examination: PASSED

Results of mechanical testing

Tensile test longitudinal at RT, Strip test specimen

Item	Specimen No.	Heat No.	Specimen dimensions	Yield strength	Tensile strength	Elongation	1. Formula	RI 0,5/Rm
Requirements			IN	RT 0,5 % PSI 42100-71800	Rm PSI 70000-95000	A2" %		MAX 0.93
0001	000011	321297	0.752 X 0.229	59466	88038	29.00	19.00	0.68

Elongation formula

1. Formula $AF = 625000 * AXC^{0,2} / U^{0,9}$

INSPECTION CERTIFICATE EN 10204-3.1

Document No.:

465-1521734/002/P

Inspection No.:

Page: 3 / 3

Notched bar Impact test [1 CHARPY_V]

Specimen position: longitudinal (L); Test temperature: -50 °F

Item	Specimen No.	Heat No.	Specimen dimensions			Absorbed energy		Impact strength	Shear fracture					
Requirements			Length	Width	Height	single	average		single	average	single	average	single	average
			mm	mm	mm	ft-lbf	ft-lbf		%	%				
			55	3,33	10,00		MIN 000							
0001	000011	321297	55	3.33	10.00	26			80					
				3.33	10.00	22			75					
				3.33	10.00	18			60	72				

Protection

outside surface varnished

Item	Heat No.	Production No.
0001	321297	15040598

Remark

NACE Standard: Hardness acc. to ANSI/NACE MR0175/ISO 15156: HRC max 22 as per ASTM A370 table 2&3., Hardness acc. to ANSI/NACE MR0103/ISO 17945: HRC max. 22 as per ASTM A370 table 2&3.; Certificate remarks: material free from mercury contamination, Data converted from SI units, No weld repair has been carried out;
Certificate-Remark: LONGHORN

Plant 465, 1 BENTELER DRIVE, LA 71115 Shreveport, 04/14/2025, TEL.: 0318-216-4260

Inspection representative

ME

We certify that the supplied product has been processed, sampled, tested, and inspected in accordance with the agreed specifications and/or references mentioned herein and meet the requirements for the grade indicated. This document was prepared by means of electronic data processing and is valid without signature.

restricted