



PHOENIX FORGING CO INC
800 FRONT ST
CATASAUQUA, PA 18032-2343

Phoenix * Capitol * Camco
CapProducts

Certified Material Test Report

Commanding a Higher Standardsm

Printed: 7/23/2026

Certified: 07/09/2026

HT. 39RRRR

Customer
DNOV LP
1229 DUHON BLVD

P.O. 26811345

Tag 145280

Heat No 8000038766
Heat Code 39RRR
Order # 103017

Material

ASTM A105-2024 / ASME SA105-2025 Edition

MORGAN CITY, LA 70380

Part Number
12811250

Description
36 - 3 X 1 3M THRD TOC

Chemical Properties

C	Mn	P	S	Si	Cu	Ni	Cr	C Eq. Long
0.1900	0.8000	0.0060	0.0210	0.2620	0.1700	0.0700	0.1100	0.3699

Mo	V	Co	Al	Nb	N	Pb	Sn	Ta	Ti
0.0100	0.0330								

Additional Chemical Properties

					CE CSA	Cr + Cu + Ni
					N/A	0.3500

Mechanical Properties

Tensile (PSI)	Yield (PSI)	Elong. % in 2 in. or 4D	R of A %	HBW	HBW2
74200	43700	36	67	148	150

Charpy Minimum Impact - ft/lbs

Fracture Appearance - %

Test 1	Test 2	Test 3	Average	Test Temp.	Test Size	Test 1	Test 2	Test 3	Average

We hereby certify that these parts were manufactured, sampled, tested, and inspected in accordance with the product specifications stated and were found to meet the requirements.

This document is according to EN 10204 Inspection Certificate 3.1 requirements.

These products meet the requirements of the latest editions of NACE MR0175/ISO 15156 and NACE MR0103. No weld repair has been performed on these products. This material was not exposed to mercury or any other metal alloy that is liquid at ambient temperatures during processing or while in our possession.

Meets ASME SA-181-70 2023 Edition. Manufactured in the USA.