



Material Test Report

Quantity		Product		Heat Code		Heat Treatment		Steel Mill													
36	2" XS LR 90° Elbow	A251367		Hot Formed		STEEL DYNAMICS		A 234-24													
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Cb	CE (IIW)	Tens.	Yield	Elong	ROA	BHN	BHN2	Dimensional Specification: B16.9
0.18	0.71	0.011	0.008	0.22	0.18	0.05	0.12	0.020	0.00	0.020	0.001	0.0000	0.002	0.342	69,800	50,000†	23.60	-	155	153	

6" Std Straight Tee										Heat Treat: Normalized										NIPPON		
3704 179244																				A 234-25		
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Cb	CE (IIW)	Tens.	Yield	Elong	ROA	BHN	BHN2	Dimensional Specification: B16.3	
L 0.19	0.84	0.015	0.006	0.24	0.02	0.01	0.02	0.010	0.00	-	< 0.001	0.0001	< 0.001	0.338	73,800	45,600	34.10	-	147	151	WPE	

10											2" XS Straight Tee											3707 HX845											Heat Treat: Normalized											NIPPON										
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Cb	CE (IIV)	Tens.	Yield	Elong	ROA	BHN	BHN2	A 234-24 Dimensional Specification: B16.9																																	
L 0.17	0.75	0.016	0.007	0.16	0.01	0.02	0.04	0.010	0.00	-	-	0.0005	0.000	0.307	68,700	50,000†	26.10	-	161	164																																		
																						Fine Grain Practice																																

Richard Purpura

Richard Purpura
Quality Assurance Department
5/26/2026



**Scan For Online
Report**

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed, No Lead Content, No Mercury Content.
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability.
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbond Quality System Program
- MTR Issued in accordance with EN 10204 Paragraph 3.1
- L denotes ladle chemistry, P denotes product chemistry.

Generated by kcoulas@weldbend.com

Page 1 of 2

Cert #446549