

S.O. No. 508514

[illegible]

Kevin.Jackson , 1/16/2026, 2:17:21 PM

FORM 02
REV. 03
10/01/15



NATIONAL OILWELL VARCO

Process & Flow Technology
8017 Breen Road
Houston, TX 77064
Phone (281) 351-2222

Closure Certification

Customer: **PIPELINE EQUIPMENT INC**

Date: **1/13/2026**

Purchase order: **7476909**

Sales order: **508514**

Assy. No.	Size	QTY	Serial No.	Description
17517625-001	2"	8	AEQ683 - AEQ690	2" 900 NO HINGE XH

National Oilwell Varco does hereby certify the product(s), as described above, is(are) manufactured of material and in accordance with the practices required in the latest edition and addenda of the designated specification(s) indicated below.

- ☐ ASME Boiler and Pressure Vessel Code, Section VIII, Division 1
(Product not code stamped or inspected by an ASME Authorized Inspector)
- ☐ CFR 49 Part 192, Transportation of Natural and Other Gas by Pipeline:
Minimum Federal Safety Standards (Except 192.149b)
- ☐ CFR 49 Part 195, Transportation of Hazardous Liquids by Pipeline
- ☐ ASME B31.3, Process Piping
- ☐ ASME B31.4, Pipeline Transportation Systems For Liquid Hydrocarbons and
Other Liquids
- ☒ ASME B31.8, Gas Transmission And Distribution Piping Systems
- ☐ NACE MR-01-75/ISO 15156, Sulfide Stress Cracking Resistant Metallic Materials
for Oilfield Equipment
- ☒ Design Pressure: 1800 PSIG
- ☒ Design Temp: -20 to 100 °F

Audra Cano

Audra Cano
Quality Coordinator

Ameriforge

An AFG Holdings Company

Material Test Report

Heat Code: ET6

ISO 9001:2015 Certified

Ameriforge Ltd
13770 Industrial Rd. Houston, TX 77015

Sales: (713) 393-4200

NOV-R&M ENERGY SYS 15278	PO: 4033411	Sales Order: 191006	Line: 2
500 CONROE PARK WEST DR	Item Code: 9999H60002-0031R	Qty Shipped: 799	
CONROE, TX 77303	Item Desc: 02.00 150-900CAP A350LF2 17518043-001 NRM CDFRG		
Mill Heat: C217479			
Spec: ASME SA105N/SA350 (17) ASME SA105N/SA350 (17) LF2 CL1 & NOV 61-0072 rev 1 (Caps)			

Element	(%wt)	Ladle	Product	EPCRA	CAS#	Element	(%wt)	Ladle	Product	EPCRA	CAS#
C Carbon	0.19					Cr Chromium	0.11				
Mn Manganese	1.18			Y	7439-96-5	Mo Molybdenum	0.02			Y	7440-47-3
P Phosphorus	0.008					V Vanadium	0.035				
S Sulfur	0.01					Cb Columbium	0.00				
Si Silicon	0.27					Al Aluminum	0.02				
Cu Copper	0.15			Y	7440-50-8	C E	0.43				
Ni Nickel	0.06			Y	7440-02-0	CuNiCrMoV	0.38				

Mechanical Testing		Heat Treat	
Test Lab	AFG	Norm. Temp. (F)	1675
Test Bar Size	SACRIFICIAL PIECE	Norm. (Hrs)	2.00
R3W	143 - 149	Norm. Cooling Type	AIR
Elg (%)	28.8	Other	
RA (%)	64.4	Supplier	STEEL DYNAMICS
Tensile Specimen Size (in)	.352	Country of Melt	USA
Tensile (ksi)	77.0	Country of Forging	USA
Yield (ksi)	49.4	Vacuum Degassed	Y
Gauge Length (in)	1.50		
Charpy Temp (F)	-50		
Charpy (ft lbs)	46 - 40 - 49		
Avg Energy 3 Specimens (ft-lbs)	45		
Min Energy 1 Specimens (ft-lbs)	40		
% Shear	20 - 20 - 20		
Lat. Exp. (in)	.047 - .036 - .051		

2/1/23

The recording of false, fictitious, or fraudulent statement or entries on this document may be punishable as a felony under federal statute.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1980) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.: 1622151

Certification Date: 1/23/2023

Issued By: Michelle Gutierrez

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b

Material Test Report

Heat Code: ET6

Ameriforge Ltd

13770 Industrial Rd. Houston, TX 77015

Sales: (713) 393-4200

ISO 9001:2015 Certified

NOV-R&M ENERGY SYS 500 CONROE PARK WEST DR CONROE, TX 77303	15278	PO: 4033411	Sales Order: 191006	Line: 2
		Item Code: 9999H60002-0031R	Qty Shipped: 799	
		Item Desc: 02.00 150-900CAP A350LF2 17518043-001 NRM CDERG		
		Mill Heat: C217479		
Spec: ASME SA105N/SA350(17)ASME SA105N/SA350(17) LF2 CL1 & NOV 61-0072 rev 1 (Caps)				

Product compliant with NACE MR0175/ISO 15156-2:2015, Annex A (A.2.1.2, A2.1.3).
Product compliant with NACE MR0103/ISO 17945:2015, Section 13.1.1 and 13.1.3.

- * No Weld repair performed.
- * Ladle Chemical Analysis results are reported from the raw material suppliers MTR.
- * Tensile taken from a round specimen. Measurement of elongation after fracture.
- * Yield strength was determined using the .2% offset method, unless specified.
- * All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing.
- * When reported on MTR: Tensile Testing Per ASTM E8; Brinell Hardness Per ASTM E10; Charpy Testing Per ASTM E23
- * AF Global manufactures materials according to a certified Quality Management System conforming to ISO 9001:2015 and PED certified to 2014/68/EU, Annex 1, Section 4.3.
- Unless otherwise noted on PO, Dimensions of all standard pipe flanges and flange fittings (NPS 1/2 to NPS 24) per ASME B16.5-2020, large diameter steel flanges (NPS 26 to 60) per ASME B16.47-2020, Orifice flanges per ASME B16.36-2020.
- * AFGlobal uses the latest edition of ASTM E29 (Standard practice for using significant digits in test data to determine conformance with specifications), to claim conformance or nonconformance to a specification. When a accept/reject determination is required AFGlobal uses a test uncertainty ratio (TUR) of 1:1 or higher as acceptable.
- * DNV PED Certificate No 10000425664-PA-ACCREDIA-USA Valid thru December 03, 2023.

The recording of false, fictitious, or fraudulent statement or entries on this document may be punishable as a felony under federal statute.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1980) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the 'EPCRA' column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.: 1622151

Certification Date: 1/23/2023

Issued By: Michelle Gutierrez

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b


Dusty Bannon - Quality Analyst

Ameriforge

An AFG Holdings Company

Material Test Report

Heat Code: ET6

Ameriforge Ltd

13770 Industrial Rd. Houston, TX 77015

ISO 9001:2015 Certified

Sales: (713) 393-4200

NOV-R&M ENERGY SYS 500 CONROE PARK WEST DR CONROE, TX 77383	15278	PO: 4032305	Sales Order: 189994	Line: 1
		Item Code: 9999H61002-0031R	Qty Shipped: 951	
		Item Desc: 2.00 150-900 HUB A350LF2 -17518204-001 NRM CDFRG		
		Mill Heat: C217479		
Spec: ASME SA350/SA350M(21) LF2 CL1 & NOV 61-0072 Rev 01 (Hubs)				

Element	(%wt)	Ladle	Product	EPCRA	CAS#	Element	(%wt)	Ladle	Product	EPCRA	CAS#
C Carbon	0.19		0.17			Cr Chromium	0.11		0.16	Y	7440-47-3
Mn Manganese	1.15		1.21	Y	7439-96-5	Mo Molybdenum	0.02		0.02		
P Phosphorous	0.008		0.008			V Vanadium	0.04		0.03		
S Sulphur	0.01		0.01			Cb Columbium	0.00		0.01		
Si Silicon	0.27		0.28			Al Aluminum	0.02		0.02		
Cu Copper	0.15		0.15	Y	7440-50-8	C.E.	0.43				
Ni Nickel	0.06		0.06	Y	7440-02-0						

Mechanical Testing		Heat Treat	
Test Lab	AFG	Norm. Temp. (F)	1675
Test Bar Size	SACRIFICIAL PIECE	Norm. (Hrs)	2.30
BBW	143 - 143	Norm. Cooling Type	AIR
Elg (%)	32.9		
RA (%)	70		
Tensile Specimen Size (in)	.250	Supplier	STEEL DYNAMICS
Tensile (ksi)	78.7	Country of Melt	USA
Yield (ksi)	52.8	Country of Forging	USA
Gauge Length (in)	1	Vacuum Degassed	Y
Specimen Orientation	LONGITUDINAL	Fully Killed	YES
LCVN Charpy Temp. (F)	-50	Made to Fine Grain Practices	YES
LCVN (ft-lbs)	90 - 71 - 103		
LAvg 3 (ft-lbs)	86		
L Min (ft-lbs)	71		
% Shear	40 - 30 - 40		
Lat. Exp.	.073 - .054 - .080		

1/12/23

The recording of false, fictitious, or fraudulent statement or entries on this document may be punishable as a felony under federal statute.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.: 1620642

Certification Date: 1/9/2023

Issued By: Michelle Gutierrez

Page 1 of 2

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b

2" Hub

Material Test Report

Heat Code: ET6

Ameriforge Ltd

13770 Industrial Rd. Houston, TX 77015

ISO 9001:2015 Certified

Sales: (713) 393-4200

NOV-R&M ENERGY SYS 500 CONROE PARK WEST DR CONROE, TX 77303	15278	PO: 4032305	Sales Order: 189994	Line: 1
		Item Code: 9999H51002-0031R	Qty Shipped: 951	
		Item Desc: 2.00 150-900 HUB A350LF2 -17518204-001 NRM CDFRG		
		Mill Heat: C217479		
Spec: ASME SA350/SA350M(21) LF2 CL1 & NOV 61-0072 Rev 01 (Hubs)				

Product compliant with NACE MR0175/ISO 15156-2:2015, Annex A (A.2.1.2, A.2.1.3).
Product compliant with NACE MR0103/ISO 17945:2015, Section 13.1.1 and 13.1.3.

- * No Weld repair performed.
- * Ladle Chemical Analysis results are reported from the raw material suppliers MTR.
- * Tensile taken from a round specimen. Measurement of elongation after fracture.
- * Yield strength was determined using the .2% offset method, unless specified.
- * All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing.
- * When reported on MTR: Tensile Testing Per ASTM E8; Brinell Hardness Per ASTM E10; Charpy Testing Per ASTM E23
- * AF Global manufactures materials according to a certified Quality Management System conforming to ISO 9001:2015 and PED certified to 2014/68/EU, Annex 1, Section 4.3.
- Unless otherwise noted on PG, Dimensions of all standard pipe flanges and flange fittings (NPS 1/2 to NPS 24) per ASME B16.5-2020, large diameter steel flanges (NPS 26 to 60) per ASME B16.47-2020, Orifice flanges per ASME B16.36-2020.
- * AFGlobal uses the latest edition of ASTM E29 (Standard practice for using significant digits in test data to determine conformance with specifications), to claim conformance or nonconformance to a specification. When a accept/reject determination is required AFGlobal uses a test uncertainty ratio (TUR) of 1:1 or higher as acceptable.
- * DNV PED Certificate No 10000425664-PA-ACCREDIA-USA Valid thru December 03, 2023.


The recording of false, fictitious, or fraudulent statement or entries on this document may be punishable as a felony under federal statute.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1980) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.: 1620642

Certification Date: 1/9/2023

Issued By: Michelle Gutierrez



Dusty Bannon - Quality Analyst

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b