



U.S.S. SEAMLESS TUBULAR OPS

FAIRFIELD TUBULAR OPERATIONS

CERTIFIED TEST REPORT

(IN ACCORDANCE WITH ISO 10474/EN10204/DIN50049 "type 3.1")

DATE: 06/06/25

TIME: 09:03:21

SERIAL NO: F0153689

EBS NO: 2005870330 1

MILL ORDER/ITEM NO DR14847 01		SHIPPERS NO. N/A		P.O. NUMBER 26693210		VEHICLE I.D. N/A																
SOLD TO ADDRESS DNOV LP PO BOX 40985 HOUSTON TX 77040-0985				MAIL TO ADDRESS DNOV LP PO BOX 40985 HOUSTON TX 77040-0985				VENDOR U.S.S. SEAMLESS TUBULAR OPS FAIRFIELD TUBULAR OPERATIONS 5700 VALLEY ROAD FAIRFIELD, AL 35064														
SPECIFICATION AND GRADE SMLS STANDARD AND LINE PIPE API 5L 46TH EDITION DATED 4/1/18 GRADE B/X42 R N OR Q PSL-2, ASTM A106-19 GRADE B/C, ASTM A53-24 GRADE B, ASME SA106-2023 GRADE B/C, ASME SA53-2023 GRADE B REG MILL COAT PE BEV 30 DEGREE APPLICABLE REQUIREMENTS OF NACE MR0103/ISO 17945-2015 ED AND NACE MR0175/ISO 15156-2 2021 ED																						
MATERIAL COND: AS-ROLLED				O.D.: 6.625 (168.275)		In (mm)		WALL: 0.280 (7.112)		In (mm)												
PRODUCT IDENTIFICATION	TEST TYPE/ ORIENTATION	TEST COND.	GAUGE WIDTH IN	YIELD	EXT %	TENSILE	Y/T	ELONG % (IN 2 ")	HARDNESS SCALE:	MIN HYDRO PSI	DWELL(SEC)											
				PSI	.50	PSI																
				MIN: 42,100		MIN: 70,000	MAX:	MIN:	MIN:	2670	5											
				MAX: 71,800		MAX: 95,000		26.0	MAX:													
EB4609 *NOTE A	STRIP/L/B	AR	1.5	56,500	.50	81,000	0.70	40.0		2670	5											
EB5136 *NOTE A	STRIP/L/B	AR	1.5	55,000	.50	79,500	0.69	40.5		2670	5											
** END OF DATA THIS SHEET **																						
LEGEND: L - LONGITUDINAL T - TRANSVERSE QT - QUENCH & TEMPERED AR - AS ROLLED B - BODY W - WELD U - UPSET NM - NORMALIZED SR - STRESS RELIEVED TR - THERMOMECHANICAL ROLLED																						
PRODUCT IDENTIFICATION	TYPE		C	MN	P	S	SI	CU	NI	CR	MO	AL	N	V	B	TI	CB	CO				C.E.*
EB4609	HEAT		20	91	010	001	22	16	07	10	03	028		00	0004	002	001					.39
EB4609	PROD		19	87	010	001	22	14	07	09	03	030		00	0002	002	000					.37
EB4609	PROD		20	88	011	001	22	14	07	09	03	031		00	0002	002	000					.38
EB5136	HEAT		20	92	008	001	23	13	05	07	02	030		00	0003	001	000					.38
EB5136	PROD		20	88	008	001	23	12	05	06	02	030		00	0002	001	000					.37
EB5136	PROD		19	89	009	001	23	11	05	07	02	027		00	0001	001	000					.37
** END OF DATA THIS SHEET **																						
*C.E. IS BASED ON THE FOLLOWING EQUATION(S): C+MN/6+CR/5+MO/5+V/5+NI/15+CU/15 (EUROPEAN CEV)																						

DECIMAL POSITIONS FOR ELEMENTS ARE INDICATED BY THE LEFT MARGIN, VERTICAL DOTTED LINE OR DECIMAL POINT. ELEMENTS REPORTED IN MASS FRACTION (%)

000000000

KQ269V18

8894670133

0-0-0

PAGE 3 OF

4



U.S.S. SEAMLESS TUBULAR OPS

FAIRFIELD TUBULAR OPERATIONS
CERTIFIED TEST REPORT
(IN ACCORDANCE WITH ISO 10474/EN10204/DIN50049 "type 3.1")DATE: 06/06/25
TIME: 09:03:21
SERIAL NO: F0153689
EBS NO: 2005870330 1

MILL ORDER/ITEM NO DR14847 01		SHIPPERS NO. N/A		P.O. NUMBER 26693210															
MATERIAL COND: AS-ROLLED					O.D.: 6.625 (168.275) in (mm)					WALL: 0.280 (7.112) in (mm)									
PRODUCT IDENTIFICATION	FLAT	BEND	GRAIN SIZE	MIN COLLAPSE	CHARPY V-NOTCH IMPACT TESTING														
					DIR	TEST LOC.	TEMP	SIZE	TEST COND.	FT-LBS				% SHEAR					
												1	2	3	AVG	1	2	3	AVG
EB4609	OK				DEG														
EB5136	OK																		
** END OF DATA THIS SHEET **																			
LEGEND L - LONGITUDINAL T - TRANSVERSE B - BODY W - WELD HAZ - HEAT AFFECTED ZONE																			
TESTING / INSPECTION INFORMATION																			
TEST / INSPECTION				YES	RESULTS / COMMENTS														
FULL LENGTH VISUAL				X															
FULL LENGTH EMI				X	OD _____ OD/ID _____ X L _____ LT _____ X 10.0/10.0% NOTCH														
FULL LENGTH MPI																			
FULL LENGTH UT					ID _____ OD/ID _____ L _____ LT _____														
END AREA INSPECTION (PLAIN END)				X	MPI _____ X UT _____														
SPECIAL END AREA (SEA) INSP					MPI _____ UT _____														
FULL LENGTH DRIFT					DRIFT MANDREL SIZE: _____														
ADDITIONAL NOTES/COMMENTS																			
ALL MANUFACTURING TOOK PLACE IN THE USA. IMPACT STRIKER RADIUS 8MM. MANUFACTURED IN AN ISO 9001 CERTIFIED FACILITY - CERTIFICATE #30727. NO REPAIRS BY WELDING. NO MERCURY OR MERCURY COMPOUNDS ARE ADDED TO THE STEEL AND ALL MERCURY BEARING EQUIPMENT IS PROTECTED BY A DOUBLE BOUNDARY OF CONTAINMENT. *NOTE A SEE ATTACHED REPORT FOR TENSILE RESULTS. *NOTE B SEE ATTACHED REPORT FOR ADDITIONAL NOTES. ** END OF DATA **																			

THIS IS TO CERTIFY THAT THE PRODUCT DESCRIBED HEREIN WAS MANUFACTURED,
SAMPLED, TESTED AND/OR INSPECTED IN ACCORDANCE WITH THE SPECIFICATION
AND FULFILLS THE REQUIREMENTS IN SUCH RESPECTS.PREPARED BY THE OFFICE OF: MICHAEL HENRY -MANAGER, Q.A.
FAIRFIELD TUBULAR OPERATIONS

DATE 06/06/25

000000000

KQ269V18

8894670133

0-0-0

PAGE 4 OF 4

**