


WELDBEND CORPORATION
P O Box 945650
Maitland,FL
PO: S014647269

2		10" XS LR 90 Deg ELBOWS-WPHY 52								EE043		Quench & Tempered										NIPPON	
	C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Cb	CE (SP75)	Tens.	Yield	Elong	ROA	BHN	BHN2	SP75 WPHY 52-08 Dimensional Specification: SP75	
L	0.12	1.26	0.014	0.002	0.29	0.02	0.02	0.11	0.010	0.00	0.000	0.009	0.0001	0.000	0.307	77,000	54,900	35.10	-	160	161		
P	0.07	1.16	0.012	0.005	0.27	0.02	0.03	0.12	0.020	0.01	0.030	0.010	0.0005	0.005									

Test Temperature: -50 °F Percent Shear: 100/100/100 Average: 100
Absorbed Energy (ft/lbs): 327/322/329 Average: 326
Lateral Expansion (mils): 96/95/98 Average: 96

We hereby certify that the material meets the following

- All fittings and flanges meet NACE MRO-175/ISO 15156-Latest Revision.
- All fittings and flanges meet NACE MRO-103 - Latest Revision.
- All non high-yield fittings meet the requirements of ASTM A-234 WPB (AND SA-234)
- All non high-yield flanges meet the requirements of ASTM A-105 WPB (AND SA-105)
- All elbows, tees and reducers are seamless, except as noted.
- Plate for caps and welded fittings.
- Bars, Billets or Blooms for flanges and certain caps and tees.
- MTR only valid with QR code linking to traceability.weldbend.com

† This indicates that the reported yield is capped at 50,000 psi.

Copyright © 2023 Weldbend Corp.

Richard Purpura

Richard Purpura
Quality Assurance Department
7/10/2026



**Scan For Online
Report**

We hereby certify that the material meets the following:

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed. No Lead Content. No Mercury Content.
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability.
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbend Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1
- L denotes ladle chemistry. P denotes product chemistry.

Generated by mhammer@weldbend.com

Page 1 of 2

Cert #450308



6600 South Harlem Avenue
Argo, IL 60501-1930

Material Test Report

WELDBEND CORPORATION
P O Box 945650
Maitland, FL
PO: S014647269

<u>Quantity</u>		<u>Product</u>								<u>Heat Code</u>				<u>Heat Treatment</u>						<u>Steel Mill</u>	
1		8" Class 900 Blind RF								EX6105A				Heat Treat: Normalized						JINDAL STEEL	
<u>C</u>	<u>Mn</u>	<u>P</u>	<u>S</u>	<u>Si</u>	<u>Cu</u>	<u>Ni</u>	<u>Cr</u>	<u>Mo</u>	<u>V</u>	<u>Al</u>	<u>Ti</u>	<u>B</u>	<u>Cb</u>	<u>CE (IIW)</u>	<u>Tens.</u>	<u>Yield</u>	<u>Elong</u>	<u>ROA</u>	<u>BHN</u>	<u>BHN2</u>	A 105-18 Dimensional Specification: B16.5
L 0.20	1.21	0.015	0.003	0.26	0.01	0.01	0.02	0.003	0.00	0.032	0.003	0.0002	0.001	0.407	83,500	50,000†	31.00	77.00	161	156	
 Fine Grain Practice																					

We hereby certify that the material meets the following

- All fittings and flanges meet NACE MRO-175/ISO 15156-Latest Revision.
- All fittings and flanges meet NACE MRO-103 - Latest Revision.
- All non high-yield fittings meet the requirements of ASTM A-234 WPB (AND SA-234)
- All non high-yield flanges meet the requirements of ASTM A-105 WPB (AND SA-105)
- All elbows, tees and reducers are seamless, except as noted.
- Plate for caps and welded fittings.
- Bars, Billets or Blooms for flanges and certain caps and tees.
- MTR only valid with QR code linking to traceability.weldbend.com

† This indicates that the reported yield is capped at 50,000 psi.
Copyright © 2023 Weldbend Corp.

Richard Purpura

Richard Purpura
Quality Assurance Department
7/10/2026



Scan For Online
Report

We hereby certify that the material meets the following:

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed. No Lead Content. No Mercury Content.
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability.
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbend Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1
- L denotes ladle chemistry, P denotes product chemistry.

Generated by mhammer@weldbend.com

Page 2 of 2

Cert #450308