



TRILAD Flanges & Fittings

7200 Mykawa Rd
Houston, TX 77033
(PHONE) (713) 679-2891



ISO 9001

CERTIFIED MATERIAL TEST REPORT EN 10204 3.1

Date of Report: 12/31/2025		Certificate No. 11031 DT.26/06/2025		Page 1 of 1			
Customer:		Cust PO#:		Qty: 18.00			
		Customer Order No: WO36308					
		Allied Fitting, LP SO No:					
Item Description: 5Q9WRS6 6 900# RF WN STD F52			Heat #: TL20068006 ✓ 1 ea.				
Specification: ASTM A694/A694M 2022 F52			Melt Practice: ELECTRIC FURNACE				
Heat C.E.: 0.41							
Heat Treatment		Init Temperature	Tempering Temperature	Time			
QUENCHED AND TEMPERED		910 C	605 C	Q=2.30HRS T=3.30HRS			
Heat Composition							
Heat Product	C 0.20	Mn 1.25	Si 0.19	P 0.018	S 0.008	Cr 0.01	Ni 0.00
	Mo 0.00	Cu 0.00	V 0.00	Nb 0.00	B 0.000		
Mechanical Properties							
Tensile Specimen Size: STD				Tensile Specimen Orientation:			
Impact Specimen Size: 10 X 10				Impact Specimen Orientation: T			
	Hardness	Ultimate Strength	Yield Strength	Elongation	Area Reduction		
Base Weld HAZ	178 180 HBW	585 Mpa	408 Mpa	30 %	73 %		
Full Size Charpy							
	Impact Value	Shear Fracture	Lateral Expansion	Temperature			
Base Value	J 82 79 82	% 57 59 55	MM 0.03 0.02 0.03	-46.00 °C			
Notes							
NACE MR0103/ISO17945:2015 (R2023) NACE MR0175-2021/ISO15156-1:2020 DOMESTIC							

Material in accordance with the latest edition of the applicable Standard to which it is ordered including:

ASME Sect II-A, ASME B16.5, B16.36, B16.47, MSS-SP-44.

NO WELD REPAIR
FREE

MERCURY FREE RADIATION CONTAMINATION

Material conforms to both ASTM (A) and ASME (SA) applicable specifications.
We hereby certify that all information presented on this CMTR conforms to the above specification.

Troy Gorrell

Q.C Inspector