



Certified Material Test Report

Heat Code: 79EH

Heat No: 0470P

Item: 15112012TXB: 2 X 6" XHSM L BK STL NIPL TOE X BEVEL

Material: ASTM A106B-2019a / ASME SA106B-2021 Edition

Chemistry Properties

C	Mn	P	S	Si	Cu	Cr
0.1720	0.6420	0.0180	0.0082	0.2120	0.1720	0.1320
NI	Mo	V	Co	Al	Cb	N
0.0620	0.0150	0.0015			0.0015	
Pb	Sn	Ta	Ti	C Eq. Long		
				0.3243		

Additional Chemical Properties

Mechanical Properties

Tensile(PSI)	71142	Yield(PSI)	46835	Elong.% in 2in.or 4D	35%	Reduction	HBW	HBW 2
							135	137

Charpy Minimum Impact - ft/lbs ----- Fracture Appearance - ft/lbs

Test 1	Test 2	Test 3	Avg.	Test Temp.	Test Size	Test 1	Test 2	Test 3	Avg.

Bend Test Passed |

Hydro Test Passed at 2500 psi

We hereby certify that these parts were manufactured, sampled, and inspected in accordance with the product specifications stated and were found to meet the requirements. This document is according to EN 10204 Inspection Certificate 3.1 requirements. These products meet the requirements of the latest editions of NACE MR0175/ISO 15156 and NACE MR0103. No weld repair has been performed on these products. This material was not exposed to mercury or any other metal alloy that is liquid at ambient temperatures during processing or while in our possession.

Meets ASME SA 106 Grade B Requirements.

Capitol Manufacturing 1125 Capitol Avenue Crowley, LA 70526