

INSPECTION CERTIFICATE

PANTECH STEEL INDUSTRIES SDN. BHD. (509731-A)

LOT 13258 & 13259, Jalan Haji Abd. Manan,

Off Jalan Meru, 42200 Kapar, Selangor, Malaysia.

Tel: 603-3393 1633 Fax: 603-3393 1733 E-mail: info@pantechsteel.com



Quality Management System is certified under ISO 9001. Approval. No.: 0047996
PED 2014/68/EU Annex 1 Clause 4.3
Cert. No.: 0343/PED/MUM/0810070/1

WROUGHT CARBON STEEL BUTTWELDING FITTINGS

INSPECTION DOCUMENT: EN10204:2004 Type 3.1

Certificate No : PSI 138744-05

Date : 25-May-2023

Purchaser :

Order No.	Invoice No.	Starting Material	Specification for Fittings- Seamless										Specification for Inspection					
72016	E000017708	Seamless Pipe	ASTM A234 -19 WPB / ASME SA234 -21 WPB NACE MR0103-15/ NACE MR0175/ISO15156-15*										ASME B16.9 - 18 / ASTM A960 - 20					
Batch No.	Heat No. Pipe	Product & Size				Quantity (pcs)		Visual Examination		Dimensional Inspection		Heat Treatment		Magnetic Particle Testing				
B0524C	12318152	4" x 2" XS CON RED				350		GOOD		GOOD		C & S		N.A				
Specification Min Max Batch No. B0524C		Chemical Composition (%)										Tensile Test ¹			Hardness			
		C	Si	Mn	P	S	Ni	Cr	Mo	Cu	V	Pb	CE	YS	TS	E ²	(HB)	
		x100	x100	x100	x1000	x1000	x100	x100	x100	x100	x1000		x100	(KSI / MPa)		(%)	1	2
		-	10	29	-	-	-	-	-	-	-	-	-	240	415	-	-	
		30	-	106	50	58	40	40	15	40	80	-	50	-	-	-	197	
		12	14	74	17	6	3	6	0	3	4	< 0.10	26	342	436	39.0	132	137

WE CERTIFY THAT ALL PRODUCTS WERE MANUFACTURED, SAMPLED, TESTED, AND INSPECTED SOLELY BY THE MANUFACTURER LISTED AT THE ADDRESS ABOVE IN ACCORDANCE WITH INDICATED SPECIFICATION AND FOUND TO MEET REQUIREMENTS. MATERIAL IS FREE FROM MERCURY AND RADIOACTIVE CONTAMINATION.

TENSILE REQUIREMENT: CONFORMS TO ASTM A370 STANDARD, LONGITUDINAL DIRECTION, GAUGE LENGTH 2" (50mm)

* FULLY KILLED

* HARDNESS ACCORDING TO NACE MR0103/ NACE MR0175/ISO 15156

NOTE:

C: Cold formed at temperature below 620°C

S: Stress relieved in temperature between 595°C - 690°C and cooled in still air.

H: Hot formed in temperature between 620°C - 980°C and cooled in still air.

MT: Magnetic Particle Testing

N: Normalised at 910°C


Q: Heated to 910°C and quench in water.

T: Temper between 590°C - 690°C.

¹: YS = Yield strength TS=Tensile strength E = Elongation

²: For thickness above 7.94 mm, the minimum elongation value, E is 30. Else, E = 48t + 15, where t = specimen thickness, in

Manufactured in Malaysia




Quality Assurance Manager