



6600 South Harlem Avenue
Argo, IL 60501-1930

WELDBEND CORPORATION
PO Box 40985
Houston, TX
PO: 662777768

Material Test Report

<u>Quantity</u>		<u>Product</u>								<u>Heat Code</u>					<u>Heat Treatment</u>					<u>Steel Mill</u>	
1		4" x 3" XS Reducing Tee								25N8					Heat Treat: Normalized					NIPPON	
<u>C</u>	<u>Mn</u>	<u>P</u>	<u>S</u>	<u>Si</u>	<u>Cu</u>	<u>Ni</u>	<u>Cr</u>	<u>Mo</u>	<u>V</u>	<u>Al</u>	<u>Ti</u>	<u>B</u>	<u>Cb</u>	<u>CE (IIW)</u>	<u>Tens.</u>	<u>Yield</u>	<u>Elong</u>	<u>ROA</u>	<u>BHN</u>	<u>BHN2</u>	<u>A 234-23A</u>
L 0.12	1.26	0.014	0.001	0.26	0.01	0.02	0.12	0.010	0.00	-	0.010	0.0000	0.001	0.358	68,000	48,500	33.90	-	147	143	Dimensional Specification: B16.9
																					WPB

We hereby certify that the material meets the following

- All fittings and flanges meet NACE MRO-175/ISO 15156-Latest Revision.
- All fittings and flanges meet NACE MRO-103 - Latest Revision.
- All non high-yield fittings meet the requirements of ASTM A-234 WPB (AND SA-234)
- All non high-yield flanges meet the requirements of ASTM A-105 WPB (AND SA-105)
- All elbows, tees and reducers are seamless, except as noted.
- Plate for caps and welded fittings.
- Bars, Billets or Blooms for flanges and certain caps and tees.
- MTR only valid with QR code linking to traceability.weldbend.com

† This indicates that the reported yield is capped at 50,000 psi.
Copyright © 2023 Weldbend Corp.

Richard Purpura

Richard Purpura
Quality Assurance Department
7/21/2025



Scan For Online
Report

We hereby certify that the material meets the following:

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed. No Lead Content. No Mercury Content.
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability.
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbend Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1
- L denotes ladle chemistry, P denotes product chemistry.

Generated by kcoulas@weldbend.com

Page 1 of 1

Cert #421864