



6600 South Harlem Avenue
Argo, IL 60501-1930

Material Test Report

WELDBEND CORPORATION
PO Box 84160
Baton Rouge, LA
PO: STL-318649

Quantity

Product

Heat Code

Heat Treatment

Steel Mill

14

4" XS LR 90° Elbow

50996K

Hot Formed

<u>C</u>	<u>Mn</u>	<u>P</u>	<u>S</u>	<u>Si</u>	<u>Cu</u>	<u>Ni</u>	<u>Cr</u>	<u>Mo</u>	<u>V</u>	<u>Al</u>	<u>Ti</u>	<u>B</u>	<u>Cb</u>	<u>CE (IIW)</u>
L 0.17	1.11	0.013	0.009	0.19	0.12	0.04	0.05	0.006	0.00	0.031	0.002	-	0.003	0.377

Hot Formed

<u>Tens.</u>	<u>Yield</u>	<u>Elong</u>	<u>ROA</u>	<u>BHN</u>	<u>BHN2</u>
73,200	50,000†	28.70	-	161	161

LIBERTY OSTRAVA

A 234-18 WPB

Dimensional Specification: B16.9



We hereby certify that the material meets the following:

- All fittings and flanges meet NACE MRO-175/ISO 15166-Latest Revision.
- All fittings and flanges meet NACE MRD-103 - Latest Revision.
- All non high-yield fittings meet the requirements of ASTM A-234 WPB (AND SA-234)
- All non high-yield flanges meet the requirements of ASTM A-105 WPB (AND SA-105)
- All elbows, tees and reducers are seamless, except as noted
- Plate for caps and welded fittings.
- Bars, Billets or Blooms for flanges and certain caps and tees.
- MTR only valid with QR code linking to traceability.weldbend.com

† This indicates that the reported yield is capped at 50,000 psi.

Copyright © 2023 Weldbend Corp.

Cert #420499

Richard Purpura

Richard Purpura
Quality Assurance Department
7/1/2025



Scan For Online
Report

We hereby certify that the material meets the following:

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed. No Lead Content. No Mercury Content.
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability.
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbend Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1

Generated by nklimala@weldbend.com

Page 1 of 1