



GALPERTI, INC.

160 Southbelt Industrial Drive
Houston, Texas 77047
PH: 713-433-6700 - FAX 713-433-6560
Email: houstonqualityassurance@galperti-am.com

TEST/CERTIFICATE

EN 10204

INTERNAL JOB

251136

3.1

EDGEN MURRAY CORPORATION

**PO BOX 84160
BATON ROUGE LA 70884-4160**

M.T. CERTIFICATE N.
004457

DATE
07/29/2025

YOUR P.O.
RMS-318581

DATE
07/01/2025

ITEM	DESCRIPTION				QUANTITY	B/P	MATERIAL	HEAT N°	FORGING ORIGIN	#
027/027	8"	600	BL	RF	A105	B1	F			
034/034	3"	900	BL	RF	A105	B1	F			A
035/035	4"	900	BL	RF	A105	B1	F			B
042/042	1"	150	SO	RF	A105	B1	F			C
										D

CHEMICAL ANALYSIS																			
#	C %	MN %	SI %	P %	S %	CR %	NI %	MO %	CU %	V %	SN %	AL %	NB %	TI %	N %	B %	12%	CE%	
A	0.179	1.200	0.190	0.006	0.010	0.080	0.080	0.040	0.140	0.030		0.023	0.004	0.001		0.0001	6.703	0.42	
L																			
B	0.150	1.200	0.210	0.013	0.002	0.120	0.110	0.038	0.300	0.019		0.024	0.004	0.002		0.0003	8.000	0.41	
B	0.150	1.200	0.200	0.012	0.001	0.130	0.100	0.033	0.290	0.023		0.026	0.001	0.002		0.0002		0.41	
C	0.160	1.220	0.250	0.012	0.010	0.100	0.060	0.030	0.210	0.027		0.032	0.001	0.001		0.0003	7.625	0.41	
C	0.150	1.240	0.270	0.009	0.013	0.090	0.070	0.040	0.220	0.022		0.041	0.001	0.001		0.0003		0.40	
D	0.170	1.150	0.170	0.009	0.004	0.140	0.080	0.020	0.120	0.021		0.020	0.001			0.0001	6.764	0.41	
D	0.155	1.160	0.220	0.014	0.007	0.120	0.060	0.012	0.150	0.020		0.025	0.001			0.0004	7.483	0.39	

NOTES
12=Manganese/Carbonio
CE=LONG FORMULA

L = ANALISI COLATA / LADLE ANALYSIS
C = ANALISI DI PRODOTTO / CHECK ANALYSIS

#		MECHANICAL PROPERTIES												
		TENSILE								CHARPY TEST				
		TYPE	Ø DIAMETER mm.	AREA mm.	LENGTH mm.	TEMP. F	TENSILE PSI	YIELD PSI	ELONG %	REDUCT %	TYPE KCU	TEMP. F	VALUES Ft-lbs	HARDNESS HB
A	S		12.50	122.70	50.00	68	70,000	36,000	22.0	30.0		-50	Min. 12 Med. 15	Max. 197
A	O		12.50	122.70	50.00	68	73,200	48,500	35.0	69.0		-50	93 - 50 - 82	139-144
B	S		12.50	122.70	50.00	68	70,000	36,000	22.0	30.0		-50	Min. 12 Med. 15	Max. 197
B	O		12.50	122.70	50.00	68	73,577	51,700	38.2	76.1		-50	111 - 64 - 90	147-144
C	S		12.50	122.70	50.00	68	70,000	36,000	22.0	30.0		-50	Min. 12 Med. 15	Max. 197
C	O		12.50	122.70	50.00	68	71,100	48,700	35.4	72.3		-50	59 - 46 - 40	132-132
D	S		12.50	122.70	50.00	68	70,000	36,000	22.0	30.0		-50	Min. 12 Med. 15	Max. 197
D	O		12.50	122.70	50.00	68	71,000	46,500	37.5	72.6		-50	56 - 63 - 68	135-130

NOTES
Lateral Exp/Shear Area (Average)

A = in.0.05/ 48% B = in.0.07/ 45% C = in.0.04/ 25% D = in.0.05/ 32%

O = OBTAINED
S = STANDARD

#	HEAT TREATMENT	GENERAL NOTES
A	Normalized at 900 dgr.C for 2.1/2 h.-Cooling from 900 dgr.C in still air	ROUGHNESS
B	Normalized at 900 dgr.C for 1.1/2 h.-Cooling from 900 dgr.C in still air	F -STOCK FINISH 125-250 microinch
C	Normalized at 900 dgr.C for 2 h.-Cooling from 900 dgr.C in still air	
D	Normalized at 900 dgr.C for 1 h.-Cooling from 900 dgr.C in still air	
		STANDARD B1 = ASME B16.5 INCH STD 2020

NOTES
Material I.A.W. Nace MR-0175/ISO 15156-2-15ED & NACE MR0103 Steel is fully killed and made to fine grain practice.
A/SA105N-24ED, A694 F42-22ED , A/SA350 LF2N CL1-24ED

TRADE MARK/ LOGO



INT. INSPECT DATE

07/29/2025

INT. INSPECTOR

M. CONTRERAS

INSPECTION AUTHORITY

MARISSA CONTRERAS

An ISO 9001/2015 certified
company.
Certification issued by:
Lloyds register quality
assurance
Certificate No. UQA 10580220



ISO/IEC 17025:2017 Accredited
Certificate No.: L24-571