



6600 South Harlem Avenue
Argo, IL 60501-1930

Material Test Report

WELDBEND CORPORATION
PO Box 40985
Houston, TX
PO: 26594074

Quantity	Product	Heat Code	Heat Treatment	Steel Mill																	
75	2" Class 150 Blind RF	3DF29	Hot Formed	RIVA																	
<u>C</u> L 0.19	<u>Mn</u> 1.04	<u>P</u> 0.013	<u>S</u> 0.007	<u>Si</u> 0.25	<u>Cu</u> 0.16	<u>Ni</u> 0.07	<u>Cr</u> 0.13	<u>Mo</u> 0.020	<u>V</u> 0.00	<u>Al</u> 0.026	<u>Ti</u> 0.017	<u>B</u> 0.0000	<u>Cb</u> 0.002	<u>CE (IIW)</u> 0.409	<u>Tens.</u> 77,000	<u>Yield</u> 50,000†	<u>Elong</u> 32.00	<u>ROA</u> 70.00	<u>BHN</u> 147	<u>BHN2</u> 148	A 105-18 Dimensional Specification: B16.5 A 105
Fine Grain Practice																					
108	4" Std LR 90° Elbow	725189	Hot Formed	SILCOTUB (TENARIS)																	
<u>C</u> L 0.12	<u>Mn</u> 0.89	<u>P</u> 0.015	<u>S</u> 0.004	<u>Si</u> 0.19	<u>Cu</u> 0.18	<u>Ni</u> 0.15	<u>Cr</u> 0.12	<u>Mo</u> 0.030	<u>V</u> 0.00	<u>Al</u> -	<u>Ti</u> -	<u>B</u> -	<u>Cb</u> -	<u>CE (IIW)</u> 0.321	<u>Tens.</u> 68,500	<u>Yield</u> 50,000†	<u>Elong</u> 29.00	<u>ROA</u> -	<u>BHN</u> 158	<u>BHN2</u> 156	A 234-18 WPB Dimensional Specification: B16.9 WPB
Fine Grain Practice																					
72	3" XS LR 90° Elbow	A226206	Hot Formed	PLYMOUTH TUBE CO.																	
<u>C</u> L 0.20	<u>Mn</u> 1.01	<u>P</u> 0.006	<u>S</u> 0.008	<u>Si</u> 0.32	<u>Cu</u> 0.13	<u>Ni</u> 0.07	<u>Cr</u> 0.09	<u>Mo</u> 0.030	<u>V</u> 0.05	<u>Al</u> 0.021	<u>Ti</u> 0.000	<u>B</u> -	<u>Cb</u> 0.000	<u>CE (IIW)</u> 0.416	<u>Tens.</u> 83,700	<u>Yield</u> 50,000†	<u>Elong</u> 22.70	<u>ROA</u> -	<u>BHN</u> 179	<u>BHN2</u> 181	A 234 WPB-13 Dimensional Specification: B16.9 SEGM WPB

We hereby certify that the material meets the following

- All fittings and flanges meet NACE MRO-175/ISO 15156-Latest Revision.
- All fittings and flanges meet NACE MRO-103 - Latest Revision.
- All elbows, tees and reducers are seamless, except as noted.
- Plate for caps and welded fittings.
- Bars, Billets or Blooms for flanges and certain caps and tees.
- MTR only valid with QR code linking to traceability.weldbend.com

† This indicates that the reported yield is capped at 50,000 psi.
Copyright © 2023 Weldbend Corp.

Richard Purpura

Richard Purpura
Quality Assurance Department
12/29/2023



Scan For Online
Report

We hereby certify that the material meets the following:

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed. No Lead Content. No Mercury Content.
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability.
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbend Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1

Cert #379296

Generated by kcoulas@weldbend.com

Page 4 of 5