



PIPE AND TUBE

MILL TEST CERTIFICATE

XIS PIPE AND TUBE, LLC.
451 Louis E. Mikulin Rd.
ryan TX 77807

Customer: MRC Global PO Box Charleston, WV, 25322 877-294-7574	Sales Order: 0630005067 PO: S 8PX 644609	Invoice No.: 1600050047 Date of Issue: 09/04/2024
Certificate No.: 1600050047-15		
Product Description: SL 12.750 0.500 65.48# X52BDRH5BW-20P2		
Specification: SL 48th Edition May 2019		

Test Number A402510	Lot Number LT24101004	Mat Number 332758	Steel Making / Coil Rolling Steel Dynamics Columbus, LLC , Columbus - MS - US / Steel Dynamics Columbus, LLC , Columbus - MS - US
-------------------------------	---------------------------------	-----------------------------	---

Tensile Test - Strip Specimen Gauge Length 2"										Mechanical Properties																											
Loc. / Orien	Size	0.5%EUL Y.S(psi)	U.T.S. Body (psi)	U.T.S. Weld (psi)	Y/T Ratio	E.L. (%)	Hardness (HRA)	Temp (F) -20					CVN					Temp (F) -20					Size	Loc. / Orien	Acceptance Criteria (ft-lbf)(AVG)												
								1	2	3	Avg	1	2	3	Avg	1	2	3	Avg	1	2	3				Avg											
T180°	1 1/2"	63700	73900	75800	0.86	45.4	83	1	2	3	Avg	1	2	3	Avg	1	2	3	Avg	1	2	3	Avg	10x7.5 mm	3T90	15											
								Lateral Expansion (in)					UB					UB					0.084					UB					0.084				

Analysis		Chemical Composition (Max %)																
H/P	C	Si	Mn	P	S	Ni	Cr	Mo	Cu	V	Al	Nb	Ti	B	Ca	N	CEpcm (API Max. A.C.)	CE Results
H	0.06	0.220	0.84	0.009	0.003	0.04	0.06	0.010	0.12	0.003	0.018	0.028	0.015	0.0003	0.0017	0.0073	0.25	0.12
P	0.06	0.200	0.77	0.009	0.000	0.04	0.06	0.010	0.10	0.003	0.013	0.023	0.014	0.0002	0.0025	0.0052	0.25	0.12
P	0.06	0.198	0.76	0.009	0.000	0.04	0.06	0.010	0.09	0.003	0.011	0.023	0.013	0.0002	0.0026	0.0053	0.25	0.12

- Following Controls / Tests have been satisfactorily performed:
- 1. - Hydrostatic Testing: 4,090.00 psi Pressure for 5.00 seconds
 - 2. Ultrasonic Tested to N10 - passed
 - 3. Seam Annealed min 1,600 F
 - 4. Flattening Test Passed

Acronyms:
L = Longitudinal
Y.S. = Yield Strength
E.L. = Elongation
P = Product Analysis
UB = Un-Broken

T = Transverse
U.T.S. = Ultimate Tensile Strength
H = Heat Analysis
A.C. = Acceptance Criteria
N/A = Not Applicable

- Remarks:
- 1. This material meets Grades ASTM A53/A53M-22 Grade B API 5L HFW PS12 X52M,
 - 2. This product meets the requirements of ASME BPVC II.A Specification SA-53B-2023
 - 3. Made and Melted in USA
 - 4: Date of Manufacture 08/2024
 - 5: This product is silicon and/or aluminum fully killed.
 - 6: Certificate meets the requirements of ISO 10474:2013 (Inspection Certificate 3.1.B)
 - 7: This material meets the requirements of NACE MR0175-2021 / ISO 15156:2020

We hereby certify that the material herein has been made and tested in accordance with the above specification and also with the requirement called for by the above order.

Philip Harper

Quality Manager