



MILL TEST CERTIFICATE

Customer: DNOW L.P. PO BOX 40985 Houston,TX,77240-0985 281-823-4700	Sales Order: 0630005623 PO: 26708945	Invoice No.: 1600052474 Date of Issue: 03/27/2025
Certificate No.: 1600052474-3		
Product Description: 5L 10.750 0.500 54.79# X52BDRH5BW-20P2		
Specification: 5L 46th Edition May 2019		

AXIS PIPE AND TUBE, LLC.
1451 Louis E. Mikulin Rd.
Bryan TX 77807
TEL. (979) 703-6847 FAX(979) 703-6847

Heat Number		Lot Number		Mat Number		Steel Making / Coil Rolling																					
A416858		LT25003003		333870		Steel Dynamics Columbus, LLC , Columbus - MS - US / Steel Dynamics Columbus, LLC , Columbus - MS - US																					
Mechanical Properties																											
Tensile Test - Strip Specimen Gauge Length 2"								Temp (F) -20				CVN				Temp (F) -20											
Loc. / Orien	Size	0.5%EUL Y.S(psi)	U.T.S. Body (psi)	U.T.S. Weld (psi)	Y/T Ratio	E.L. (%)	Hardness (HRB)	Body (ft-lbf)				Shear Area (%)				Weld (ft-lbf)				Shear Area (%)				Size	Loc. / Orien	Acceptance Criteria (ft-lbf)(AVG)	
								1	2	3	Avg	1	2	3	Avg	1	2	3	Avg	1	2	3	Avg				
T180°	1 1/2"	70000	81700	79200	0.86	38.9	87	153	192	152	166	95	100	95	97	139	162	174	159	95	100	100	99	10x7.5 mm	3T90	15	
								Lateral Expansion (in)				0.073	0.071	UB	0.072	Lateral Expansion (in)				0.074	UB	UB	0.074				

Analysis (H/P)	Chemical Composition (Max %)																	
	C	Si	Mn	P	S	Ni	Cr	Mo	Cu	V	Al	Nb	Ti	B	Ca	N	CEpcm (API Max. A.C.)	CE Results
H	0.06	0.210	0.84	0.020	0.002	0.06	0.09	0.020	0.13	0.002	0.021	0.026	0.015	0.0004	0.0022	0.0065	0.25	0.13
P	0.06	0.211	0.81	0.015	0.003	0.05	0.08	0.020	0.13	0.003	0.017	0.024	0.014	0.0002	0.0020	0.0098	0.25	0.12
P	0.06	0.212	0.82	0.015	0.003	0.06	0.08	0.020	0.13	0.003	0.017	0.025	0.015	0.0002	0.0020	0.0099	0.25	0.12

Following Controls / Tests have been satisfactorily performed:	
1.- Hydrostatic Testing:	4,860.00 psi Pressure for 5.00 seconds
2: Ultrasonic Tested to N10 - passed	
3: Seam Annealed min 1,600 F	
4: Flattening Test Passed	

Acronyms:	
L = Longitudinal	T = Transverse
Y.S. = Yield Strength	U.T.S. = Ultimate Tensile Strength
E.L. = Elongation	H = Heat Analysis
P = Product Analysis	A.C. = Acceptance Criteria
UB = Un-Broken	N/A = Not Applicable

Remarks:
1: This material meets:Grades ASTM A53/A53M-22 Grade B API 5L HFW PSL2 X52M,
2: This product meets the requirements of ASME BPVC.II.A Specification SA-53B-2023
3: Made and Melted in USA
4: Date of Manufacture 01/2025
5: This product is silicon and/or aluminum fully killed.
6: Certificate meets the requirements of ISO 10474:2013 (Inspection Certificate 3.1.B)
7: This material meets the requirements of NACE MR0175-2021 / ISO 15156:2020

We hereby certify that the material herein has been made and tested in accordance with the above specification and also with the requirement called for by the above order.

Quality Manager