

XIS PIPE AND TUBE, LLC.
451 Louis E. Mikulin Rd.
ryan TX 77807

Customer:	MRC Global	Sales Order:	0630004951	Invoice No.:	1600049615
PO Box:	Charleston, WV 25322	PO:	S 7AA 637379	Date of Issue:	07/20/2024
	877-294-7574				
Certificate No.:	1600049615-6				
Product Description:	SL 12.750 0.500 85.48# X52BDRH5BW.20P2				
Specification:	SL 48th Edition May 2019				

Test Number	Lot Number	Mat Number	Steel Making / Coil Rolling		
B405139	LT24185027	332768	Steel Dynamics Columbus, LLC , Columbus - MS - US / Steel Dynamics Columbus, LLC , Columbus - MS - US		

Tensile Test - Strip Specimen Gauge Length 2"									
Loc. / Orien	Size	0.5%EUL Y.S.(psi)	U.T.S. Body (psi)	U.T.S. Weld (psi)	Y/T Ratio	E.L. (%)	Hardness (HRE)	Temp (F) -20	
T180°	1 1/2"	62300	74300	76300	0.84	42.4	81	CVN	
		Body (ft-lbf)		Shear Area (%)		Weld (ft-lbf)		Temp (F) -20	
		1	2	3	Avg	1	2	3	Avg
		158	175	182	172	90	90	90	90
		Lateral Expansion (in)		Lateral Expansion (in)		Lateral Expansion (in)		Lateral Expansion (in)	
		0.067		0.080		0.085		0.077	
						100		100	
						100		100	
						100		100	
						10x7.5 mm		3190	
								15	

Analysis														
(H/P)	C	Si	Mn	P	S	Ni	Cr	Mo	Chemical Composition (Max %)					CE
									Cu	V	Al	Nb	Ti	B
H	0.06	0.220	0.87	0.011	0.002	0.05	0.07	0.010	0.15	0.002	0.031	0.030	0.017	0.0005
P	0.07	0.221	0.90	0.012	0.002	0.06	0.08	0.010	0.13	0.004	0.024	0.024	0.015	0.0001
P	0.07	0.218	0.77	0.012	0.001	0.05	0.07	0.010	0.14	0.003	0.017	0.026	0.016	0.0004
										Ca				
										N				
										CEPcm (API Max. Acc.)				
										Results				
										0.0018				
										0.0074				
										0.0022				
										0.0067				
										0.25				
										0.13				

Following Controls / Tests have been satisfactorily performed:

1. - Hydrostatic Testing: 4,090.00 psi Pressure for 5.00 seconds

2. Ultrasonic Tested to N10 - passed

3. Seam Annealed min 1,600 F

4. Flattening Test Passed

Acronyms:

L = Longitudinal

Y.S. = Yield Strength

E.L. = Elongation

P = Product Analysis

UB = Un-Broken

T = Transverse

U.T.S. = Ultimate Tensile Strength

H = Heat Analysis

A.C. = Acceptance Criteria

N/A = Not Applicable

Remarks:

1: This material meets Grades ASTM A53/A53M-22 Grade B

2: This product meets the requirements of ASME BPVC II, A Specification SA-53B-2023

3: Made and Melted in USA

4: Date of Manufacture 07/2024

5: This product is silicon and/or aluminum fully killed.

6: Certificate meets the requirements of ISO 10474:2013 (Inspection Certificate 3.1.B)

7: This material meets the requirements of NACE MR0175-2021 / ISO 15156:2020

We hereby certify that the material herein has been made and tested in accordance with the above specification and also with the requirement called for by the above order.

John Pappas

Quality Manager