

190



6600 South Harlem Avenue
Argo, IL 60501-1930

Material Test Report

Product

2" XS LR 90° Elbow

Heat Code

C215639

Heat Treatment

Hot Formed

Steel Mill

MICHIGAN SEAMLESS

A 234-18 WPB

Dimensional Specification: B16.9

C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Co	CE (11W)	Tens	Yield	Elong	ROA	BHN	BHN2
L 0.19	0.87	0.007	0.017	0.25	0.14	0.09	0.13	0.020	0.00	0.022	0.001	0.0000	0.001	0.381	78,900	50,000†	23.50	-	174	177



2" 90° Elbow

We hereby certify that the material meets the following:

- All fittings and flanges meet NACE MRO-175/ISO 15158-Latest Revision.
- All fittings and flanges meet NACE MRO-103 - Latest Revision.
- All non high-yield fittings meet the requirements of ASTM A-234 WPB (AND SA-234).
- All non high-yield flanges meet the requirements of ASTM A-106 WPB (AND SA-106).
- All elbows, tees and reducers are seamless, except as noted.
- Place for caps and welded fittings.
- Bars, Billets or Blooms for flanges and certain caps and tees.
- MTR only valid with QR code linking to traceability.weldbend.com
- † This indicates that the reported yield is capped at 50,000 psi.

Copyright © 2023 Weldbend Corp.

Cert #25940

Richard Purpura

Richard Purpura
Quality Assurance Department
6/3/2024



Scan For Online
Report

We hereby certify that the material meets the following:

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed. No Lead Content. No Mercury Content.
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability.
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbend Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1
- L denotes ladle chemistry, P denotes product chemistry.

Generated by Logan.palch@dnw.com

Page 1 of 1