

# CERTIFIED MILL TEST REPORT



The Best Value  
Price, Quality, Service  
All The Time.

LOG NO. F00000000211173

Page 5 of 9

BONNEY FORGE CORPORATION

P.O. BOX 330 • 14496 CROGHAN PIKE • MOUNT UNION, PA 17066-0330

(814) 542-2545 • (800) 345-7546 • FAX (814) 542-4906

www.bonneyforge.com

CUSTOMER: DNOW L.P.

DATE 10/24/2024

CUSTOMER

BONNEY ORDER NO. B000353620

ORDER NO.: 26675457

SHIP TO: DNOW L.P. (ODESSA)  
5301 WEST MURPHY STREET  
ODESSA TX 79763  
United States

| ITEM   | QUANTITY | LOT NO. | GRADE OR SPECIFICATION NO.                                                                                                                                                                                                                    |         |
|--------|----------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|
|        |          |         | CHEMICAL ANALYSIS, PHYSICAL PROPERTIES, REMARKS:                                                                                                                                                                                              |         |
| 12     | 550      | 51924   | 36-3X1 3000 A105 FLEX T                                                                                                                                                                                                                       | SA/A105 |
| 145280 |          |         | Al 0.021 C 0.190 Co 0.010 Cr 0.100 Cu 0.070 Mn 0.980 Mo 0.010 Nb 0.001<br>Ni 0.040 P 0.009 S 0.019 Si 0.220 V 0.003<br>CE(Long Formula) = 0.38<br>T/S(PSI) 74,498 Y/S(PSI) 47,886 EL(%) 35.55 RA(%) 60.44<br>Brinell Hardness 141 BHN 141 BHN |         |
| 13     | 18       | 51676   | 3 2M A105 TEE T                                                                                                                                                                                                                               | SA/A105 |
| 89626  |          |         | Al 0.021 C 0.200 Co 0.003 Cr 0.070 Cu 0.060 Mn 1.120 Mo 0.005 Nb 0.009<br>Ni 0.020 P 0.008 S 0.020 Si 0.240 V 0.004<br>CE(Long Formula) = 0.41<br>T/S(PSI) 78,295 Y/S(PSI) 49,438 EL(%) 32.55 RA(%) 62.43<br>Brinell Hardness 141 BHN 141 BHN |         |
| 14     | 135      | D965 -  | 2 3000 A105 UNAR T                                                                                                                                                                                                                            | SA/A105 |
| 66578  |          | MALE    | Al 0.023 C 0.200 Co 0.003 Cr 0.130 Cu 0.060 Mn 1.080 Mo 0.005 Nb 0.009<br>Ni 0.020 P 0.008 S 0.021 Si 0.270 V 0.005<br>CE(Long Formula) = 0.41<br>T/S(PSI) 78,400 Y/S(PSI) 45,400 EL(%) 33.00 RA(%) 61.80<br>Brinell Hardness 158 BHN 158 BHN |         |
|        |          | D928    | 2 3000 A105 UNAR T                                                                                                                                                                                                                            | SA/A105 |
| 66578  |          | FEMALE  | Al 0.025 C 0.200 Co 0.004 Cr 0.120 Cu 0.090 Mn 1.060 Mo 0.007 Nb 0.009<br>Ni 0.030 P 0.008 S 0.022 Si 0.230 V 0.004<br>CE(Long Formula) = 0.41<br>T/S(PSI) 78,800 Y/S(PSI) 47,700 EL(%) 28.00 RA(%) 46.70<br>Brinell Hardness 154 BHN 152 BHN |         |

We certify that the data on this sheet is a true copy taken from our records of material furnished us by the production mill, or as obtained by additional laboratory checks.

by 

Billie Jo Clemens

Quality Assurance Representative