



|           |           |
|-----------|-----------|
| Customer: | DNOW LP   |
| P.O. No.  | 662734777 |
| S.O. No.  | 495810    |

[illegible]



# FEAT GROUP S.P.A.

FEAT INDUSTRIALE DIVISION  
Registered Office: 20127 Milano Italy - Via L. Moro 41 - VAT Number: IT 0503090157  
Head Office: 20062 Sesto San Giovanni (MI) Italy - Via del Lavoro 1, 2, 3  
Department: 23881 Cassina Brianza (LC) Italy - Via G. Pirelli 30, Via L. Ariosto 10/25T  
Tel. 02/90716917 - www.featsgroup.com - info@featsgroup.com

FAP

|                                                                                             |                                   |                                        |                       |         |         |         |         |           |       |       |       |       |
|---------------------------------------------------------------------------------------------|-----------------------------------|----------------------------------------|-----------------------|---------|---------|---------|---------|-----------|-------|-------|-------|-------|
| Cert N. 2023/3003016                                                                        |                                   | Date 18/07/2023                        | Page 1                |         |         |         |         |           |       |       |       |       |
|                                                                                             |                                   | NOV PROCESS FLOW TECHNOLOGIES US, INC. |                       |         |         |         |         |           |       |       |       |       |
|                                                                                             |                                   | 8017 BREEN ROAD                        |                       |         |         |         |         |           |       |       |       |       |
|                                                                                             |                                   | 77064 HOUSTON, TX.                     |                       |         |         |         |         |           |       |       |       |       |
| Customer Orders<br>4036380-1                                                                | Delivery Note<br>2023/000/0030897 | Invoice<br>O 0030905                   | Quantity<br>360,00    |         |         |         |         |           |       |       |       |       |
| Feat Code<br>I86025011101                                                                   | Description<br>CAP 2" 150-900 FIN | Customer Code<br>17518102-001          | Customer Drawing<br>4 |         |         |         |         |           |       |       |       |       |
| Material & Specification<br>ASME SA350 Gr. LF2 Cl.1 2019 Edition + Spec. 51063708-SPC Rev.2 |                                   |                                        |                       |         |         |         |         |           |       |       |       |       |
| Heat Number<br>23/78932                                                                     | Steel Mill<br>RIVA ACCIAIO S.P.A. | Trade Mark<br>F-                       | Forging Code<br>AP    |         |         |         |         |           |       |       |       |       |
| CHEMICAL ANALYSIS                                                                           |                                   |                                        |                       |         |         |         |         |           |       |       |       |       |
| Elem.                                                                                       | Al                                | Si                                     | C                     | Cr      | Cu      | Mn      | Mo      | Co        | N     | NO001 | NO003 | NO04  |
| Min                                                                                         | 0,020                             | 2,000                                  | 0,170                 | 0,200   | 0,320   | 0,180   | 1,050   | 0,050     | 0,012 | 0,500 | 0,700 | 0,020 |
| Max                                                                                         | 0,050                             | 0,050                                  | 0,200                 | 0,420   | 0,200   | 0,180   | 1,050   | 0,050     | 0,012 | 0,500 | 0,700 | 0,020 |
| Heat                                                                                        | 0,026                             | 2,022                                  | 0,190                 | 0,390   | 0,190   | 0,110   | 1,050   | 0,040     | 0,009 | 0,250 | 0,324 | 0,000 |
| C.A.                                                                                        |                                   |                                        |                       |         |         |         |         |           |       |       |       |       |
| Elem.                                                                                       | Fe                                | P                                      | S                     | Sn      | Zn      | V       |         |           |       |       |       |       |
| Min                                                                                         | 0,200                             | 0,015                                  | 0,010                 | 0,250   | 0,025   | 0,020   |         |           |       |       |       |       |
| Max                                                                                         | 0,070                             | 0,012                                  | 0,005                 | 0,220   | 0,005   | 0,019   | 0,003   |           |       |       |       |       |
| C.A.                                                                                        |                                   |                                        |                       |         |         |         |         |           |       |       |       |       |
| MECHANICAL PROPERTIES / HEAT TREATMENT                                                      |                                   |                                        |                       |         |         |         |         |           |       |       |       |       |
| Laboratory Order                                                                            | 18. Description                   | 19a1                                   | 19a2                  | 19a3    | 19a4    | 19a5    | 19a6    | 19a7      | 19a8  | 19a9  | 19a10 | 19a11 |
| I86-AP                                                                                      | 101.Rm 02% T +20C                 | 1N/mm2                                 | 250,000               | 485,000 | 655,000 | 536,000 | 581     | 77720,000 |       |       |       |       |
| I86-AP                                                                                      | 101.Rm T +20C                     | 1N/mm2                                 | 22,000                | 30,000  | 30,000  | 17,000  | 17,000  | 17,000    |       |       |       |       |
| I86-AP                                                                                      | 101.A% T +20C                     | %                                      | 0,000                 | 0,000   | 0,000   | 0,000   | 0,000   | 0,000     |       |       |       |       |
| I86-AP                                                                                      | 101.E% T +20C                     | %                                      | 0,000                 | 0,000   | 0,000   | 0,000   | 0,000   | 0,000     |       |       |       |       |
| I86-AP                                                                                      | 101.HW (min. 2 value)             | 12B                                    | 20,000                | 20,000  | 20,000  | 20,000  | 20,000  | 20,000    |       |       |       |       |
| I86-AP                                                                                      | 101.KV T -46C                     | 1J                                     | 111,287               | 125,290 | 125,290 | 125,290 | 125,290 | 125,290   |       |       |       |       |
| I86-AP                                                                                      | 101.UT                            | 1J                                     | 170,000               | 170,000 | 170,000 | 170,000 | 170,000 | 170,000   |       |       |       |       |
| I86-AP                                                                                      | 103                               | 1J                                     | 170,000               | 170,000 | 170,000 | 170,000 | 170,000 | 170,000   |       |       |       |       |

Remarks  
3.1 CERTIFICATE ACCORDING TO EN 10204  
RATIO > 4:1  
Attached:  
by APPROVED Date 18/07/23 Continue

Laboratory  
Ugo Alon  
Ugo Alon  
Product Certification  
Days: 10/20/2023  
Ugo Alon



# FEAT GROUP S.p.A.

FEAT INDUSTRIALE DIVISION

Registered Office: 20122 Milano Italy - Viale L. Moro 31 - VAT Number IT 02020090157  
Head Office: 22042 Bussico Pavia (Lu) Italy - Via del Livello s.r.l.  
Department: 22061 Cassina Suarda (Lu) Italy - Via C. Pelli 20, Via L. Alpago 13/57  
Tel. 0331 9216091 - www.featgroup.com - feat@featgroup.com

Cert. N. 2023/3003016

Date 18/07/2023

Page

2

Heat Treatment Chart

Laboratory  
Ugo Abeti


*Ugo Abeti*

FEAT GROUP S.p.A. states that material hereby certified is in compliance with the quality and technical requirements as described in the customer's order, or FEAT's approval/disapproval.

- 1 - The results of chemical analysis is a true and correct copy of the full certificate issued by the manufacturer of the steel employed or by the laboratory which has determined it.
- 2 - This document is issued on the basis of the results of the analysis of the material, and it is not mandatory or any of its components, or with any other process, or with any other type of material, or of certification, during the manufacturing process independent of the scope.

Product Certification  
Dipartimento

*Dipartimento*



# FEAT GROUP S.P.A.

FEAT INDUSTRIALE DIVISION

Registered Office: 20122 Milano Italy - Viale L. Negro 31 - VAT Number: IT 0820390157

Head Office: 23842 Bosisio Parini (LC) Italy - Via dei Livelli s.n.c.

Departments: 23851 Cesana Brianza (LC) Italy - Via G. Fanti 30, Via L. Arcadio 1/3/5/7

Tel. 00380316591 - www.featgroup.com - feat@featgroup.com

FAR

|                                                                                             |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
|---------------------------------------------------------------------------------------------|--------------------------------------------------------|-------------------------------|--------------------|---------|--------|---------|-------|-----------|-------|-------|-------|-------|-------|-------|
| Cert N. 2023/3004688                                                                        |                                                        | Date 20/12/2023               | Page 1             |         |        |         |       |           |       |       |       |       |       |       |
| NOV PROCESS FLOW TECHNOLOGIES US, INC.                                                      |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
| 8017 BREEN ROAD                                                                             |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
| 77064 HOUSTON, TX.                                                                          |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
| Customer Orders<br>4036382-2                                                                | Delivery Note<br>2023/006/0031414                      | Invoice<br>O 0031434          | Quantity<br>878,00 |         |        |         |       |           |       |       |       |       |       |       |
| Feat Code<br>I86109011202                                                                   | Description<br>Small Yale Hub; 2", 150-900, HX/80; LF2 | Customer Code<br>17518318-001 |                    |         |        |         |       |           |       |       |       |       |       |       |
|                                                                                             |                                                        | Customer Drawing<br>50E023    | Rev<br>18.02       |         |        |         |       |           |       |       |       |       |       |       |
| Material & Specification<br>ASME SA350 Gr. LF2 Cl.1 2019 Edition + Spec. 51063708-SPC Rev.2 |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
| Heat Number<br>23/78932                                                                     | Steel Mill<br>RIVA ACCIAIO S.P.A.                      | Trade Mark<br>F-AR            | Forging Code<br>AR |         |        |         |       |           |       |       |       |       |       |       |
| CHEMICAL ANALYSIS                                                                           |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
| Elem.                                                                                       | Al                                                     | Si                            | C                  | Cr      | Cu     | Mn      | Mo    | N         | NR001 | NR005 | Nb    |       |       |       |
| Min                                                                                         | 0,020                                                  | 2,000                         | 0,170              |         |        | 0,900   | 5,000 |           |       |       |       |       |       |       |
| Max                                                                                         | 0,050                                                  | *****                         | 0,200              | 0,420   | 0,200  | 0,180   | 1,050 | *****     | 0,050 | 0,012 | 0,500 | 0,700 | 1,000 | 0,020 |
| Heat                                                                                        | 0,026                                                  | 2,820                         | 0,180              | 0,390   | 0,100  | 0,110   | 0,140 | 0,010     | 0,010 | 0,009 | 0,250 | 0,320 | 0,320 | 0,000 |
| C.A.                                                                                        |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
| Elem.                                                                                       | Nb+V                                                   | Ni                            | P                  | S       | Se     | Sn      | Ta    | V         |       |       |       |       |       |       |
| Min                                                                                         |                                                        |                               |                    |         | 0,150  |         | 0,015 |           |       |       |       |       |       |       |
| Max                                                                                         | 0,030                                                  | 0,200                         | 0,015              | 0,010   | 0,250  | 0,025   | 0,025 | 0,020     |       |       |       |       |       |       |
| Heat                                                                                        | 0,003                                                  | 0,070                         | 0,012              | 0,005   | 0,005  | 0,019   | 0,003 |           |       |       |       |       |       |       |
| C.A.                                                                                        |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
| MECHANICAL PROPERTIES / HEAT TREATMENT                                                      |                                                        |                               |                    |         |        |         |       |           |       |       |       |       |       |       |
| Laboratory Order                                                                            | IN                                                     | Description                   | UM1                | Min     | Max    | Value   | UM2   | Value     |       |       |       |       |       |       |
| I86-AR                                                                                      | 101                                                    | Re 02% T +20C                 | N/mm2              | 250,000 |        | 404,000 | PSI   | 58580,000 |       |       |       |       |       |       |
| I86-AR                                                                                      | 101                                                    | Re T +20C                     | N/mm2              | 485,000 |        | 655,000 | PSI   | 78155,000 |       |       |       |       |       |       |
| I86-AR                                                                                      | 101                                                    | A% T +20C                     | %                  | 22,000  |        | 35,900  |       |           |       |       |       |       |       |       |
| I86-AR                                                                                      | 101                                                    | A% T +20C                     | %                  | 30,000  |        | 76,900  |       |           |       |       |       |       |       |       |
| I86-AR                                                                                      | 101                                                    | BBW (min.2 value)             | HB                 |         | 0,000  | 197,000 |       | 169,000   |       |       |       |       |       |       |
| I86-AR                                                                                      | 102                                                    |                               | HB                 |         | 0,000  | 197,000 |       | 173,000   |       |       |       |       |       |       |
| I86-AR                                                                                      | 101                                                    | KV T -45C                     | J                  |         | 20,000 |         |       | 203,000   |       |       |       |       |       |       |
| I86-AR                                                                                      | 102                                                    |                               | J                  |         | 20,000 |         |       | 178,000   |       |       |       |       |       |       |
| I86-AR                                                                                      | 103                                                    |                               | J                  |         | 20,000 |         |       | 233,000   |       |       |       |       |       |       |

Remarks

3.1 CERTIFICATE ACCORDING TO EN 10920 Manufacture

RATIO > 4:1

Attached:

Heat Treatment Chart

by g'Hub Date 2/22/24

g'Hub

Laboratory  
Ugo Abeti

Ugo Abeti

FEAT GROUP S.p.A. states that material hereby certified is in compliance with the quality and technical requirements as described in the customer's order, or FEAT agreement.

1 - The results of chemical analysis is a true and correct copy of the test certificate issued by the manufacturer of the same employed or by the laboratory which has determined it.

2 - The chemical or components supplied under the above order number do not come in direct contact with mercury or any of its components or with any mercury containing devices employing a single boundary of containment, during the manufacturing process inspection or storage.

Product Certification  
Dagmar Tschewke

Dagmar Tschewke



# FEAT GROUP S.p.A.

## FEAT INDUSTRIALE DIVISION

Registered Office: 20122 Milano Italy - Viale L. Majno 31 - VAT Number IT 0820390157  
Head Office: 23042 Borsico Parrò (LC) Italy - Via de Livelli s.n.c.  
Depot/branches: 23061 Cassina Brianza (LC) Italy - Via G. Pirelli 3D, Via L. Ardito 1/3/5/7  
Tel. 00390376951 - [www.featgroup.com](http://www.featgroup.com) - [feat@featgroup.com](mailto:feat@featgroup.com)

Cert N. 2023/3004688

Date 20/12/2023

Page

2

Laboratory  
Ugo Abeti

*Ugo Abeti*

FEAT GROUP S.p.A. states that material hereby certified is in compliance with the quality and technical requirements as described in the customer's order or FEAT's acknowledgment.

1 - The results of chemical analyses is a true and correct copy of the test certificate issued by the manufacturer of the steel employed or by the laboratory which has determined it.

2 - The material or components shipped under the above order number did not come in direct contact with mercury or any of its compounds or with any mercury containing devices employing a single boundary of containment, during the manufacturing process, inspection or storage.

Product Certification  
Dagis Tapanella

*Dagis Tapanella*