



INSPECTION CERTIFICATE (EN 10204-3.1)

ARAHA DAGANG SDN.BHD.

(202899-M)

No.10, Jalan Jasmine 3, SEK BB10, Bandar Bukit Beruntung, 48300 Selangor Darul Ehsan, Malaysia.

Tel : 603-60281863, 60281866, 60281833 Fax : 603-60282863

Purchaser : DODSON GLOBAL, INC.
Order No : 370424-408, HOUSTON, TX
Starting Material : SEAMLESS PIPE
Country Of Original : MALAYSIA

Certificate No : AD/01/24/9518L
Date : 29-Jan-24

No	Manufacturing No. (Heat ID No.)	Raw Material Heat No	Article, Size & Grade	Heat Treatment (*)	Quantity	Specification for Inspection	ASME B16.9 (2018)
1	C482K5	19300973	8" L.R. 90 XH ELLBOW WPB	A	5	Specification for Material	NACE MR 0175 / ISO 15156 (2015)
2	C482K7	19300973	8" L.R. 90 XH ELLBOW WPB	A	85	Appearance (Visual)	ASTM A234 (2019)
3	DM575	13322561	3" L.R. 45 XH ELLBOW WPB	A	301	Dimension	Satisfactory
4	DM577	13322561	3" L.R. 45 XH ELLBOW WPB	A	199	Certification	Issued in agreement with TUV SUD industrie
5	EY230	23214137	10" S.R. 90 STD ELLBOW WPB	A	20		service GmbH. QS approved acc. to PED, Annex I,
6	EY231	19300976	10" S.R. 90 STD ELLBOW WPB	A	209		Para.4.3 by Notified Body 0036" (PED 2014 / 68 / EU)
7	EY232	19300976	10" S.R. 90 STD ELLBOW WPB	A	202		Certificate no. DGR-0036-QS-W 1056/2022/MUC-01
8	EY233	19300976	10" S.R. 90 STD ELLBOW WPB	A	69	Note : INVOICE NO	AD/EX/1872/24
9	HG837	12319539	4" XH TEE WPB	S	48		
10	HG838	1736786V	4" XH TEE WPB	S	351		

Specification		Chemical Composition											Tension Test (20°C)			Hardness (HB)	Pipe Maker	(*)Steel Making Process	
		C	SI	Mn	P	S	Cu	Ni	Cr	Mo	V	NB	Yield Strength	Tensile strength	Elongation				
		x100	x100	x100	x1000	x1000	x100	x100	x100	x100	x100	x100							P.S.I [MPA]
Min			10	29									35,000	60,000	30	197 HB MAX			
Max		30		106	50	58	40	40	40	15	8			95,000					
Heat No.																			
1	19300973	19	23	41	9	3	5.1	<1	6.1	<1	<1	<1	L	44700	65300	31.2	134-137	HENGYANG STEEL	Y
2	19300973	19	23	41	9	3	5.1	<1	6.1	<1	<1	<1	L	44700	65300	31.2	134-137	HENGYANG STEEL	Y
3	13322561	19	24	43	8	4	4	4	9	2	<1	1	L	59700	77600	44	159-163	BAOSTEEL	Y
4	13322561	19	24	43	8	4	4	4	9	2	<1	1	L	59700	77600	44	159-163	BAOSTEEL	Y
5	23214137	14	21	85	11	4.4	6.7	4.2	9.1	2.7	<1	<1	L	59100	76500	31	156-159	HENGYANG	Y
6	19300976	20	20	38	14	11.4	5.4	<1	6.4	<1	<1	<1	L	51700	67900	38.8	140-143	HENGYANG	Y
7	19300976	20	20	38	14	11.4	5.4	<1	6.4	<1	<1	<1	L	51700	67900	38.8	140-143	HENGYANG	Y
8	19300976	20	20	38	14	11.4	5.4	<1	6.4	<1	<1	<1	L	51700	67900	38.8	140-143	HENGYANG	Y
9	12319539	18	23	43	9	2	2	2	6	2	<1	<1	L	56500	72900	37.6	149-152	BAOSTEEL	Y
10	1736786V	15	21	84	14	1.8	7.7	2.6	4.2	<1	<1	<1	L	49300	68900	35	140-143	HENGYANG	Y

(*)

A) Hot Forming operation : at a temperature between 690°C ~ 980°C and cooled in still air.

S) Cold Forming operation : Normalizing at a temperature between 850°C ~ 910°C and cooled in still air.

Y = Basic oxygen process

L = Longitudinal

E = Electric furnace

T = Transverse

We hereby certify that the product described herein has been manufactured in accordance with the specification concerned and also with the purchaser's requirement and the result of all examination and test are acceptable.



Factory Manager