



WELDBEND CORPORATION
PO Box 40985
Houston, TX
PO: 662734734

Material Test Report

<u>Quantity</u>		<u>Product</u>								<u>Heat Code</u>				<u>Heat Treatment</u>				<u>Steel Mill</u>			
23		2" Class 1500 Welding Neck XSB RF								KV4				Heat Treat: Normalized				CMC STEEL			
<u>C</u>	<u>Mn</u>	<u>P</u>	<u>S</u>	<u>Si</u>	<u>Cu</u>	<u>Ni</u>	<u>Cr</u>	<u>Mo</u>	<u>V</u>	<u>Al</u>	<u>Ti</u>	<u>B</u>	<u>Cb</u>	<u>CE (IIW)</u>	<u>Tens.</u>	<u>Yield</u>	<u>Elong</u>	<u>ROA</u>	<u>BHN</u>	<u>BHN2</u>	<u>A 105-24</u>
19	0.99	0.008	0.016	0.20	0.26	0.07	0.08	0.018	0.01	0.000	0.001	0.0001	0.001	0.398	76,400	45,300	32.30	62.10	150	148	Dimensional Specification: 816.5
															A 105						

3DL55														Heat Treat: Normalized						RIVA	
2" Class 1500 Blind RF																				A 105-23	
																				Dimensional Specification: B16.5	
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Cb	CE (IIW)	Tens.	Yield	Elong	ROA	BHN	BHN2	
0.18	1.03	0.013	0.004	0.25	0.20	0.08	0.12	0.020	0.00	0.026	0.020	0.0000	0.002	0.399	76,300	50,000†	34.50	68.90	150	151	
 Fine Grain Practice																				A 105	

- All fittings and flanges meet NACE MRO-175/ISO 15156-Latest Revision.
- All fittings and flanges meet NACE MRO-103 - Latest Revision.
- All non high-yield fittings meet the requirements of ASTM A-234 WPB (AND SA-234)
- All non high-yield flanges meet the requirements of ASTM A-105 WPB (AND SA-105)
- All elbows, tees and reducers are seamless, except as noted.
- Plate for caps and welded fittings.
- Bars, Billets or Blooms for flanges and certain caps and tees.
- MTR only valid with QR code linking to [traceability.weldbend.com](#)

† This indicates that the reported yield is capped at 50,000 psi.

Copyright © 2023 Weldbend Corp.

Cert #416745

Richard Purpura

Richard Purpura
Quality Assurance Department
5/20/2025



Scan For Online
Report

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed. No Lead Content. No Mercury Content.
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability.
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbend Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1

Generated by kcoulas@weldbend.com