

BALON. CORPORATION
(Ball Valves, Check Valves, Needle Valves)

3245 S. Hattie Avenue
Oklahoma City, OK 73129
Telephone: (405) 677-3321
Facsimile: (405) 677-3917

Declaration of Compliance

Balon Stock No.: 2F-F3M-SE

Part	Material	Supplier Location
BODY	ASTM A105N	WISCONSIN, USA
ADAPTER	ASTM A105N	OHIO, USA
STEM	ASTM A311 B	NEBRASKA, USA
BALL	ASTM A105N	OHIO, USA
SEAT	CELCON	CONNECTICUT, USA

General Valve Information

2" Full Port S.E. 3,000# WP Steel Ball Valve	Min Temp F° / C°	-20 / -29
Pipe Size	2	
Port Type	Full	
Class or MAWP	W.P. 3000	
End Connection	NPT F x F	
	Option(s)	No

Scope of Industry Compliance

Balon declares the valve(s) referenced in this Declaration of Compliance meet the order requirements provided to Balon.

Balon designs and manufactures all of its products exclusively from U.S. origin materials. Balon performs all machining, assembly, and testing in its plant in Oklahoma City, OK, USA. Every step in the manufacture of each Balon valve is performed in the United States of America. Accordingly, all Balon products and components are produced in the United States and comply with requirements of the Buy American Act of 1933, the Buy America provisions of the Surface Transportation Assistance Act of 1982, the Buy American provisions of the American Recovery and Reinvestment Act (ARRA) of 2009, the AIS Requirements mandated by Section 746 of Title VII of the Consolidated Appropriations Act of 2017, and Executive Order 13811 (July 15, 2019).

Balon maintains a registered Quality Management System (QMS) that API certifies annually as fully complying with API Spec Q1. Balon's QMS is also certified to meet the requirements of the European Pressure Equipment Directive (PED) and CSA Standard Z245.15. All Balon valves are designed and manufactured in accordance with the requirements of the QMS.

Balon is an API 6D licensed manufacturer. Balon certifies that all flanged end valves, weld end valves, and all API pattern water check valves meet the design requirements of API Standard 6D. Balon ball valves have outperformed the fire safety requirements of API 6FA in testing at independent laboratories. Balon further certifies that all Balon ball valves are Low Emission products per API 641 (fugitive emissions test method and acceptability criteria for quarter turn valves) as documented by an independent laboratory.

All Balon valves marked "NACE" meet material and manufacturing requirements, including any applicable welding and heat-treat requirements, of NACE Standard MR-01-75; ISO 15156-2 2015, Region 3 and ISO 15156-3.

Each reference to a statute, executive order, or industry specification in this Declaration refers to the revision or version in effect on the date of manufacture. A chart listing the effective dates of the industry specifications referenced in this Declaration is available at <http://www.balon.com/StandardsChart>.

Quality Manager: *Brad O'Neil*

Date: 04/28/2021