



6600 South Harlem Avenue
Argo, IL 60501-1930

Material Test Report

WELDBEND CORPORATION
P O Box 945650
Maitland, FL
PO: S014587470

Quantity				Product				Heat Code				Heat Treatment				Steel Mill				
23				4" Class 900 Weld Neck XS8 RF				JN4				Heat Treat: Normalized				CMC STEEL				
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Cb	CE (IIV)	Tens.	Yield	Elong	ROA	BHN	BHN2
L 0.20	1.07	0.010	0.017	0.23	0.28	0.08	0.05	0.022	0.00	0.020	0.001	0.0001	0.000	0.417	80,100	50,000	32.30	54.10	156	157
															A 106-21 Dimensional Specification: #16.5					
															A 105					

4		4" XS Straight Tee										24N15					Heat Treat: Normalized										NIPPON																
<u>C</u>		<u>Mn</u>		<u>P</u>		<u>S</u>		<u>Si</u>		<u>Cu</u>		<u>Ni</u>		<u>Cr</u>		<u>Mo</u>		<u>V</u>		<u>Al</u>		<u>Ti</u>		<u>B</u>		<u>Cb</u>		<u>CE (IIV)</u>		<u>Tens</u>		<u>Yield</u>		<u>Elong</u>		<u>ROA</u>		<u>BHN</u>		<u>BHN2</u>		A 234-18 WPB Dimensional Specification: #16.9	
L 0.11		1.26		0.010		0.001		0.26		0.01		0.02		0.12		0.010		0.00		0.034		0.010		0.0001		0.000		0.348		68,500		50,000†		32.30		-		152		152			

8		4" x 2" XS Reducing Tee										25N414		Heat Treat: Normalized										V & M STAR			
	C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Cb	CE (IIV)	Tens	Yield	Elong	ROA	BHN	BHN2						
L	0.21	0.72	0.007	0.008	0.20	0.22	0.07	0.10	0.020	0.00	0.048	0.002	0.0004	0.000	0.374	76,400	50,000†	33.80	-	165	162						
																						WPB					

We hereby certify that the material meets the following:

- All fittings and flanges meet NACE MR0175/ISO 15156-Latest Revision
- All fittings and flanges meet NACE MR0103 - Latest Revision
- All non high-yield fittings meet the requirements of ASTM A 234 WPB / ASME SA 234
- All non high-yield flanges meet the requirements of ASTM A 105 WPB / ASME SA 105
- All elbows, tees and reducers are seamless, except as noted
- Plate for caps and welded fittings
- Bars, billets or blooms for flanges and certain caps and tees

• MTR only valid with QR code linking to traceability.weldbend.com

† This indicates that the reported yield is capped at 50,000 psi

Copyright © 2025 Weldbend Corp.

Cert #446582

Richard Purpura

Richard Purpura
Quality Assurance Department
5/26/2026



Scan For Online
Report

We hereby certify that the material meets the following:

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed: No Lead Content, No Mercury Content
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbend Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1

Generated by mcabada@weldbend.com

Page 1 of 2