



Material Test Report

WELDBEND CORPORATION
P O Box 945650
Maitland,FL
PO: S014587470

EX6057A														Heat Treat: Normalized						JINDAL STEEL	
B" Class 900 Blind RF														A 104-18						Dimensional Specification: B16.5	
Fine Grain Practice														A 105							
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Al	Ti	B	Ch	CE (IIV)	Tens	Yield	Elong	ROA	BHN	BHN2	
0.20	1.23	0.016	0.003	0.26	0.01	0.01	0.02	0.003	0.00	0.032	0.003	0.0003	0.001	0.411	81,500	49,000	32.00	75.00	172	167	

We hereby certify that the material meets the following:

- All fittings and flanges meet NACE MR0175/ISO 15156-Latest Revision
- All fittings and flanges meet NACE MR0103 -Latest Revision
- All non high-yield fittings meet the requirements of ASTM A 234 WPB / ASME SA 234
- All non high-yield flanges meet the requirements of ASTM A 105 WPB / ASME SA 105
- All elbows, tees and reducers are seamless, except as noted
- Plate for caps and welded fittings
- Bars, Billets or Blooms for flanges and certain caps and tees
- MTR only valid with QR code linking to tracability.weldbond.com

† This indicates that the reported yield is capped at 50,000 psi

Copyright © 2025 Weldbond Corp.

Cert #446582

Richard Purpura

Richard Purpura
Quality Assurance Department
5/26/2026



**Scan For Online
Report**

We hereby certify that the material meets the following:

- ISO 9001:2015 CERTIFIED MANUFACTURER
- Test Results herein are correct as contained in test records retained by the company in accordance with PED Annex 1, Paragraph 4.3 of 2014/68/EU
- No Weld Repair Performed, No Lead Content, No Mercury Content
- Knowingly making false, fictitious, or fraudulent statements on a MTR may result in legal liability
- Material has been manufactured/supplied and tested in accordance with the most current version of the Weldbond Quality System Program
- MTR issued in accordance with EN 10204 paragraph 3.1

Generated by mcabada@weldbend.com

Page 2 of 2