

FORM U-2A MANUFACTURER'S PARTIAL DATA REPORT (ALTERNATIVE FORM)

A Part of a Pressure Vessel Fabricated by One Manufacturer for Another Manufacturer
As Required by the Provisions of the ASME Boiler and Pressure Vessel Code Rules, Section VIII, Division 1

1. Manufactured and certified by Sypris Technologies, Inc. Tube Turns Products, 2612 Howard Street, Louisville, KY 40211 United States
(Name and address of Manufacturer)
2. Manufactured for PIPELINE EQUIPMENT, INC., 8403 SOUTH 89TH WEST AVE, TULSA, OK 74131
(Name and address of Purchaser)

3. Location of installation Unknown
(Name and address)

4. Type: 12" CL900 Horizontal D-Bolt Closure, Right-hand Hinge Y105130 - Y105131 N/A
(Description of vessel part (shell, two-piece head, tube bundle)) (Manufacturer's serial number) (CRN)
N/A 26.005-C1 R0 Sypris Technologies, Inc. Tube Turns Products 2026
(National Board number) (Drawing number) (Drawing prepared by) (Year built)

5. ASME Code, Section VIII, Div. 1 2025 Edition N/A N/A
(Edition and Addenda, if applicable (date)) (Code Case number) (Special service per UG-120(d))
6. Shell (a) Number of course(s): N/A (b) Overall length N/A

Course(s)			Material	Thickness		Long. Joint (Cat. A)			Circum. Joint (Cat. A, B & C)			Heat Treatment	
No.	Diameter	Length	Spec./Grade or Type	Nom.	Corr.	Type	Full, Spot, None	Eff.	Type	Full, Spot, None	Eff.	Temp.	Time
One	N/A OD	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Body Flanges on Shells												
No.	Type	ID	OD	Flange Thk	Min Hub Thk	Material	How Attached	Location	Bolting			
									Num & Size	Bolting Material	Washer (OD, ID, Thk)	Washer Material

7. Heads: (a) SA516 Grade 70(N) (b) N/A
(Material spec. number, grade or type) (H.T. - time and temp.) (Material spec. number, grade or type) (H.T. - time and temp.)

	Location (Top, Bottom, Ends)	Thickness		Radius		Elliptical Ratio	Conical Apex Angle	Hemispherical Radius	Flat Diameter	Side to Pressure		Category A		
		Min.	Corr.	Crown	Knuckle					Convex	Concave	Type	Full, Spot, None	Eff.
(a)	Top	1.490"	0.0	11.750"	2.000"	N/A	N/A	N/A	N/A	X	X	S	N/A	N/A

Body Flanges on Heads												
	Location	Type	ID	OD	Flange Thk	Min Hub Thk	Material	How Attached	Bolting			
									Num & Size	Bolting Material	Washer (OD, ID, Thk)	Washer Material

8. MAWP 1800 PSI 15 PSI at max. temp. 100 °F 100 °F Min. design metal temp. -20 °F at 1800 PSI Int / 15 PSI Ext
(Internal) (External) (Internal) (External)

9. Impact test Yes, Head, and Yoke at test temperature of -50°F
(Indicate yes or no and the component(s) impact tested)

10. Hydro., pneu., or comb. test pressure N/A Proof Test N/A

11. Nozzles, inspection, and safety valve openings:											
Purpose (Inlet, Outlet, Drain, etc.)	No.	Diameter or Size	Type	Material		Nozzle Thickness		Reinforcement	Attachment Details		Location (Insp. Open.)
				Nozzle	Flange	Nom.	Corr.		Nozzle	Flange	
Pressure Warning	2	.625"	N/A	SA479 304L	N/A	0.188"	0.000"	Integral	UW16.1(a)	N/A	N/A
Unknown	1	2.000"	TOL	SA350 LF2 CL1	N/A	3000#	0.000"	Integral	UW16.1(a)	N/A	N/A


12. Identification of part(s)							
Name of Part	Quantity	Line No.	Mfr's Identification No.	Mfr's Drawing No.	CRN	National Board No.	Year Built

13. Supports: Skirt N/A Lugs N/A Legs N/A Other N/A Attached N/A
(Yes or no) (Number) (Number) (Describe) (Where and how)

14. Remarks: Temperature rating is for metal parts only; use of an appropriate O-Ring Gasket is the responsibility of the user.
Parts were not pressure tested prior to shipment.
The closure described in this report was designed by Sypris Technologies, Inc. Tube Turns Products

Materials:	Head: SA516 Grade 70(N) (Qty 1; DSOH, Qty 1; DPAK)	Yoke: SA350 LF2 CL1 / A694 F42 (FR923)
	Pressure Warning Device Plug: SA479 Type 410	Pressure Warning Device Nipple: SA479 Type 304L
	TOL: SA350 LF2 CL1 (52141)	Bolts: SA193 Gr B7 Size: 1.125"

(07/21)



Manufactured by Sypris Technologies, Inc. Tube Turns Products, 2612 Howard Street, Louisville, KY 40211 United States

Manufacturer's Serial No. Y105130 – Y105131 CRN N/A National Board No. N/A

CERTIFICATE OF SHOP/FIELD COMPLIANCE

We certify that the statements made in this report are correct and that all details of material, construction, and workmanship of this pressure vessel part conform to the ASME BOILER AND PRESSURE VESSEL CODE, Section VIII, Division 1.

U or PRT VIII-1 Certificate of Authorization number 4936 Expires March 16, 2029


Date 26-March-26 Name Sypris Technologies, Inc. Tube Turns Products Signed [Signature]
(Manufacturer) (Representative)

CERTIFICATE OF SHOP/FIELD INSPECTION

I, the undersigned, holding a valid commission issued by the National Board of Boiler and Pressure Vessel Inspectors and employed by The Hartford Steam Boiler Inspection and Insurance Company of Hartford, Connecticut have inspected the pressure vessel part described in this Manufacturer's Data Report on 03/26 2026 and state that, to the best of my knowledge and belief, the Manufacturer has constructed this pressure vessel part in accordance with ASME BOILER AND PRESSURE VESSEL CODE, Section VIII, Division 1. By signing this certificate neither the Inspector nor the Inspector's employer makes any warranty, expressed or implied, concerning the pressure vessel part described in this Manufacturer's Data Report. Furthermore, neither the Inspector nor the Inspector's employer shall be liable in any manner for any personal injury or property damage or a loss of any kind arising from or connected with this inspection.

Date 03/26 2026 Signed [Signature] Commissions 18094
(Authorized Inspector) (National Board Authorized Inspector Commission number)

(07/25)



SYPRIS[®]
TECHNOLOGIES
Tube Turns Products

2612 Howard Street
Louisville, Ky. 40211
Telephone 502 774-6011

TTF-0070 Rev. 2

CERTIFIED TEST REPORT

S O L O D	PIPELINE EQUIPMENT, INC. 8403 SOUTH 89TH WEST AVE TULSA, OK 74131	Customer Order Number 74769-01	
		Sypris TTP Order Number 9240 - 01	
		Total Quantity 2	Report Revision 0

Description: 12" CL900 D-Bolt, with 0.500" Wall, Horizontal, Right-hand Hinge, 2" Thredolet, Carbon Steel per Drawing 26.005-C1 R0

Design: FV/1800 PSI @ 100°F, MDMT = -20°F, Rated Metal Parts Only, with Corrosion Allowance of 0"

Serial Number(s): Y105130

Quantity: 1 of 2

Hub: Hub: ASME SA350 LF2 CL1/A694 F52;

HEAT NUMBER: 4000029937 ®

HEAT NUMBER: 4000029937											
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb	B
0.19	1.17	0.009	0.007	0.214	0.13	0.06	0.07	0.01	0.04	0.016	0.0001
Yield: 53000 PSI			Tensile: 79000 PSI			Elong.: 30 %		Red. of Area: 64 %			
Hardness: ≤ 197 BHN				C.E.: 0.42							
Impact Tested @ -50 °F: 14, 26, 35 Ft-Lbs. = 25 Ft-Lbs. Average											

Head: ASME SA516 Grade 70 Normalized;

HEAT NUMBER: DSOH

TENSILE STRENGTH Grade 70 Normalized,						HEAT NUMBER: DSOH				
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb
0.19	1.13	0.006	0.001	0.23	0.21	0.13	0.15	0.03	0.004	0.003
Yield: 52000 PSI		Tensile: 76000 PSI			Elong.: 49 %			Alum: 0.026		
Impact Tested @ -50 °F: 88; 88; 97 F. Lbs. = 91 Ft. Lbs. Average										

Yoke : ASME SA350 LF2 CL1/A694 F42;

HEAT NUMBER: FR923


HEAT NUMBER: FR923											
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb	B
0.15	1.01	0.01	<0.001	0.26	0.12	0.32	0.19	0.11	0.05	0.009	0.0002
Yield: 49000 PSI		Tensile: 75000 PSI		Elong.: 33 %		Red. of Area: 68 %					
Hardness: ≤ 197 BHN				C.E.: 0.42							
Impact Tested @ -50 °F: 64, 102, 78 Ft-Lbs. = 81.33334 Ft-Lbs. Average											

Thredolet: ASME SA350 LF2 CLASS 1;

HEAT NUMBER: 52141

HEAT NUMBER: 52141										
C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb
0.2	1.06	0.005	0.02	0.2	0.03	0.01	0.11	0.002	0	0.011
Yield: 49403 PSI		Tensile: 76097 PSI		Elong.: 35.75 %			Red. of Area: 62.51 %			
Hardness: ≤ 197 BHN				C.E.: 0.40						
Impact Tested @ -50 °F: 53, 59, 17 Ft-Lbs. = 43.00 Ft-Lbs. Average										

I HEREBY CERTIFY THIS REPORT TO BE CORRECT ACCORDING TO THE RECORDS OF THE CORPORATION



SYPRIS[®]
TECHNOLOGIES
Tube Turns Products

2612 Howard Street
Louisville, Ky. 40211
Telephone 502 774-6011

TTF-0070 Rev. 2

CERTIFIED TEST REPORT

S O L O D	PIPELINE EQUIPMENT, INC. 8403 SOUTH 89TH WEST AVE TULSA, OK 74131	Customer Order Number 74769-01	
		Sypris TTP Order Number 9240 - 01	
		Total Quantity 2	Report Revision 0

Description: 12" CL900 D-Bolt, with 0.500" Wall, Horizontal, Right-hand Hinge, 2" Threadolet, Carbon Steel per Drawing 26.005-C1 R0

Design: FV/1800 PSI @ 100°F, MDMT = -20°F, Rated Metal Parts Only, with Corrosion Allowance of 0"

Serial Number(s): Y105131

Quantity: 1 of 2

Hub: ASME SA350 LF2 CL1/A694 F52;

HEAT NUMBER: 4000029937 ®

C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb	B
0.19	1.17	0.009	0.007	0.214	0.13	0.06	0.07	0.01	0.04	0.016	0.0001
Yield: 53000 PSI			Tensile: 79000 PSI			Elong.: 30 %		Red. of Area: 64 %			
Hardness: ≤ 197 BHN				C.E.: 0.42							
Impact Tested @ -50 °F: 14, 26, 35 Ft-Lbs. = 25 Ft-Lbs. Average											

Head: ASME SA516 Grade 70 Normalized;

HEAT NUMBER: DPAK

C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb
0.21	0.93	0.012	0.002	0.17	0.179	0.08	0.12	0.03	0.00	0.00
Yield: 49600 PSI		Tensile: 75300 PSI			Elong.: 42.1 %			Alum: 0.04		
Impact Tested @-50 °F: 33; 38; 30 F. Lbs. = 33.66667 Ft. Lbs. Average										

Yoke: ASME SA350 LF2 CL1/A694 F42;

HEAT NUMBER: FR923

C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb	B
0.15	1.01	0.01	<0.001	0.26	0.12	0.32	0.19	0.11	0.05	0.009	0.0002
Yield: 49000 PSI			Tensile: 75000 PSI			Elong.: 33 %			Red. of Area: 68 %		
Hardness: ≤ 197 BHN				C.E.: 0.42							
Impact Tested @ -50 °F: 64, 102, 78 Ft-Lbs. = 81.33334 Ft-Lbs. Average											

Thredolet: ASME SA350 LF2 CLASS 1;

HEAT NUMBER: 52141

C	Mn	P	S	Si	Cu	Ni	Cr	Mo	V	Cb
0.2	1.06	0.005	0.02	0.2	0.03	0.01	0.11	0.002	0	0.011
Yield: 49403 PSI		Tensile: 76097 PSI		Elong.: 35.75 %		Red. of Area:62.51 %				
Hardness: ≤ 197 BHN				C.E.: 0.40						
Impact Tested @ -50 °F: 53, 59, 17 Ft-Lbs. = 43.00 Ft-Lbs. Average										

I HEREBY CERTIFY THIS REPORT TO BE CORRECT ACCORDING TO THE RECORDS OF THE CORPORATION

Chris Thomasson

Quality Assurance
March 26, 2026