

**BALON CORPORATION**  
(Ball Valves, Check Valves, Needle Valves)

3245 S. Hattie Avenue  
Oklahoma City, OK. 73129  
Telephone: (405) 677-3321  
Facsimile: (405) 677-3917

DNOW L.P. (640000)  
359 OLD UNDERWOOD RD.  
SUITE B DOOR 258  
LA PORTE, TX. 77571

77746

July 21, 2017

PN: LS-07592

**Certificate of Compliance to API Standard 641**  
**Type Testing of Quarter-Turn Valves for Fugitive Emissions**

Balon certifies that an independent laboratory has tested a sufficient number of samples to confirm that every Balon ball valve listed in Balon's catalog or on its website, including any valve part number referenced above, is fully compliant with API Standard 641. This certification covers all Balon ball valves in sizes from one-quarter inch (1/4") through twelve inch (12"), in both floating and trunnion design.



Thomas Davies  
Quality Manager  
Balon Corporation

**BALON CORPORATION**  
(Ball Valves, Check Valves, Needle Valves)

3245 S. Hattie Avenue  
Oklahoma City, OK. 73129  
Telephone: (405) 677-3321  
Facsimile: (405) 677-3917

July 21, 2017

DNOW L.P. (640000)  
359 OLD UNDERWOOD RD.  
SUITE B DOOR 258  
LA PORTE, TX. 77571

PN: LS-07592

**CERTIFICATE OF NACE COMPLIANCE**

Balon certifies that the valves listed above meet the requirements of the current edition of NACE Standard MR-01-75: ISO 15156-2, Region 3 and ISO 15156-3.



Thomas Davies  
Quality Manager  
Balon Corporation

**BALON CORPORATION**  
(Ball Valves, Check Valves, Needle Valves)

3245 S. Hattie Avenue  
Oklahoma City, OK. 73129  
Telephone: (405) 677-3321  
Facsimile: (405) 677-3917

July 21, 2017

DNOW L.P. (640000)  
359 OLD UNDERWOOD RD.  
SUITE B DOOR 258  
LA PORTE, TX. 77571

PN: LS-07592

**CERTIFICATE OF ORIGIN and API Q1 COMPLIANCE**

All Balon valves are manufactured by Balon Corporation. All raw materials purchased by Balon are domestic. Balon's machining, assembly and testing are performed in Balon's plant in Oklahoma City, State of Oklahoma, United States of America.

This certificate verifies that all Balon valves, including the referenced valves, have been designed and manufactured in accordance with the requirements of API Q1 Quality Management System.



Thomas Davies  
Quality Manager  
Balon Corporation

**BALON CORPORATION**  
(Ball Valves, Check Valves, Needle Valves)

3245 S. Hattie Avenue  
Oklahoma City, OK. 73129  
Telephone: (405) 677-3321  
Facsimile: (405) 677-3917

July 21, 2017

DNOW L.P. (640000)  
359 OLD UNDERWOOD RD.  
SUITE B DOOR 258  
LA PORTE, TX. 77571

PN: LS-07592

**Certification of Compliance with the Buy America Act and Buy American Act**

Balon sources all of its inputs (including without limitation, all steel and iron products and components) exclusively from U.S. vendors and exclusively uses 100% domestic origin material produced in the United States. Specifically, Balon only uses:

- aluminum-bronze, alloy steel, carbon steel, stainless steel, and ductile iron castings melted and poured in U.S. foundries; and
- forged and rolled steel products, including screws, bolts, studs, nuts and other fasteners, made exclusively from steel produced in a U.S. foundry.

Additionally, Balon performs all machining, assembly, and testing operations on its products in Balon's plant in Oklahoma City, Oklahoma. No step in the manufacture of any Balon product is performed outside of the United States.

Accordingly, all Balon products and components are produced in the United States and comply with requirements of the Buy American Act of 1933, the Buy America provisions of the Surface Transportation Assistance Act of 1982, and the Buy American provisions of the American Recovery and Reinvestment Act (ARRA) of 2009. **Therefore, Balon hereby certifies that in providing products to your company, Balon will comply with the requirements of: (i) 49 U.S.C. 5323(j)(1) and the applicable regulations in 49 CFR part 661; and (ii) 23 U.S.C. 313 and the applicable regulations in 23 CFR 635.**



Thomas Davies  
Quality Manager  
Balon Corporation

**VALBRUNA**

SLATER STAINLESS, INC.  
2400 Taylor Street West, P.O. Box 630  
Fort Wayne, Indiana USA 46801  
Phone: 260-434-2892 Fax: 260-434-2905

**Product Certification Report**Report Number: **4782400**

Certified on May 09, 2012 Page 1 of 1

|                                                     |                       |                                             |                                   |                                    |                                         |
|-----------------------------------------------------|-----------------------|---------------------------------------------|-----------------------------------|------------------------------------|-----------------------------------------|
| Order I.D.<br><b>1200364 001</b>                    |                       | Order Date<br><b>2/07/12</b>                |                                   | Commodity Code<br><b>316HX1.75</b> |                                         |
| Dim 1<br><b>1.7500</b>                              | Dim 2<br><b>.0000</b> | Dim 3<br><b>.0000</b>                       | Heat I.D.<br><b>255599</b>        | Customer I.D.<br><b>002471</b>     | Customer Purchase Order<br><b>32387</b> |
| Product Shape<br><b>Cold Drawn Hex</b>              |                       | Product Surface<br><b>Cold Drawn Finish</b> |                                   |                                    | Customer Grade<br><b>316/316L</b>       |
| Length (Inches)<br><b>132.000 Min. 156.000 Max.</b> |                       |                                             | Bill of Lading #<br><b>417078</b> | Weight                             |                                         |

Ship  
To

**VALBRUNA STAINLESS, INC.**  
**4747 OATES ROAD**  
**HOUSTON, TX 77013**

Sold  
To

**VALBRUNA STAINLESS, INC.**  
**4747 OATES ROAD**  
**HOUSTON, TX. 77013**

BALON CODE AC8 ADAP LS-07592/1059/10561 SF-1090/1093/1096-SS p-1090/1093/1096-ss

**Lifts: 0030 0032 0036 0038 0041 0042**

|              |                   |              |
|--------------|-------------------|--------------|
| CONDITION A  | QQ-S-763F         | ASTMA 276-10 |
| ASTMA 479-11 | ASMESA 479-10     | AMS 5653G    |
| AMS 5648L    | SAE-AMS QQ-S-763B |              |

**CHEMICAL ANALYSIS**

|      |      |      |      |     |       |       |      |     |     |      |
|------|------|------|------|-----|-------|-------|------|-----|-----|------|
| C    | Mn   | P    | S    | Si  | Cr    | Ni    | Mo   | Cu  | Co  | N    |
| .011 | 1.55 | .030 | .030 | .54 | 16.67 | 10.06 | 2.00 | .55 | .10 | .059 |

**BRINELL HARDNESS ASTM E10-08**

HBW  
201

**TENSILE PROPERTIES ASTM E8-08**

|          |             |          |      |
|----------|-------------|----------|------|
| TS (PSI) | .2%YS (PSI) | %EL (2") | %RA  |
| 93100    | 65300       | 46.5     | 72.5 |

**MACRO ASTM E340-00/E381-01**

MACRO  
OK

**GRAIN SIZE ASTM E112-10**

|            |         |                 |
|------------|---------|-----------------|
| GRAIN SIZE | Etchant | Magnification X |
| 8          | Oxalic  | 100             |

**ASTM A262-10 PR E(A Utilized)**

|        |         |                 |
|--------|---------|-----------------|
| OXALIC | Etchant | Magnification X |
| OK     | Oxalic  | 500             |

No welding or weld repair done.

Material when shipped is free from contamination by mercury, radium, alpha source, and low melting elements.

Chemical testing to one or more of the listed ASTM methods: E415-08, E572-02a, E1019-08, E1085-95, E1086-08

Location of tensile fracture: inside middle of gage length.

Chemical Analysis performed at Acciaierie Valbruna, Italy.

No mercury or low melting alloy contamination. No weld repair.

Material melted in Italy, manufactured in the United States.

Material conforms to listed specifications and is DFARS compliant.

Quality system is compliant with ISO 9001:2008. Produced in accordance with EN 10204 3.1.

Results relate only to the items tested. Certification shall not be reproduced except in full, without written approval of Valbruna Stainless Inc. The recording of false, fictitious, or fraudulent statements on this document may be punished as a felony under federal statutes, including Federal law, Title 18, Chapter 47. Consult material safety data sheet (MSDS) for hazard info. I hereby certify that the reported figures are correct as contained in the records of the corporation.

Manager Laboratory Services

Dennis Hackett



# CERTIFICATION

1800 Innovation Way, Module 4, Hartford, WI 53027 Phone: (262) 673-2700

TO: **BALON CORPORATION**  
**QUALITY CONTROL**  
**3700 S. EASTERN AVENUE**  
**OKLAHOMA CITY, OK 73129-**

FAX NO:

| INVOICE NUMBER                               | PURCHASE ORDER | YOUR PART NO | BP NO          | REV NO      |
|----------------------------------------------|----------------|--------------|----------------|-------------|
| 0826873                                      | 96166          | C-1089-SS    | C-1089         | B-MKD       |
| ALLOY GRADE                                  | PIECES SHIPPED | SHIPPED ON   | REQUIREMENT NO | OUR PART NO |
| CF-8M                                        | 880            | 6/01/17      | 977802         | 15150       |
| PART NAME: BODY, 3/4F-S03, S05-SE BALL VALVE |                |              |                |             |

## CHEMICAL CERTIFICATION

| HEAT     | C    | MN    | SI    | CR     | NI     | MO    | P    | S    | FE  |
|----------|------|-------|-------|--------|--------|-------|------|------|-----|
| SPEC MAX | .080 | 1.500 | 1.500 | 21.000 | 12.000 | 3.000 | .040 | .040 | BAL |
| SPEC MIN |      |       |       | 18.000 | 9.000  | 2.000 |      |      | BAL |
| 96685    | .044 | 1.061 | 1.401 | 18.600 | 9.863  | 2.223 | .030 | .013 | BAL |
| 96688    | .021 | 1.138 | 1.406 | 18.550 | 9.569  | 2.200 | .029 | .014 | BAL |
| 96689    | .031 | 1.084 | 1.357 | 18.760 | 10.007 | 2.222 | .030 | .013 | BAL |
| 96690    | .022 | 1.010 | 1.364 | 18.800 | 9.832  | 2.230 | .030 | .012 | BAL |
| 96691    | .027 | 1.097 | 1.368 | 18.840 | 9.864  | 2.213 | .028 | .008 | BAL |
| 96697    | .026 | 1.112 | 1.385 | 18.810 | 9.862  | 2.206 | .031 | .007 | BAL |
| 96699    | .033 | 1.072 | 1.390 | 18.960 | 10.161 | 2.280 | .031 | .008 | BAL |
| 96700    | .031 | 1.172 | 1.426 | 18.760 | 9.718  | 2.247 | .029 | .008 | BAL |
| 96701    | .029 | 1.155 | 1.409 | 18.530 | 9.678  | 2.239 | .029 | .008 | BAL |

## HEAT TREAT CERTIFICATION

HEAT TREATED TO: SIGNICAST SPEC NO: 3301 - SOLUTION ANNEAL

| SPECIFICATION |                       |
|---------------|-----------------------|
|               | HARDNESS: HRB 100 MAX |

### HARDNESS TEST RESULTS


| LOT  | TEST LOCATION         | MIN VALUE | MAX VALUE | AVG RESULTS |
|------|-----------------------|-----------|-----------|-------------|
| 0012 | Suitable Flat Surface | 78.1 HRB  | 82.4 HRB  | 80 HRB      |
| 0013 | Suitable Flat Surface | 76.5 HRB  | 81.4 HRB  | 79.5 HRB    |

MATERIAL IS ALLOY GRADE CF-8M PER ASTM A351.

Electronically Signed and Certified by: DALE MOORE

at: 6/2/2017 7:39:55 AM

"SHIPPING TECHNICIAN"



**MADE** BETTER  
FASTER  
SMARTER **IN AMERICA**