



MILL TEST REPORTS

Bonney Forge
14496 Croghan Pike
Mt. Union, PA 17066

CERTIFIED MILL TEST REPORT

Edgen Murray 4/25/2025

LOT NO.
d983 Male

CHEMICAL ANALYSIS, PHYSICAL PROPERTIES, REMARKS

2" X 2" 3M A105 MSS-SP-83 Union Threaded

C	0.200	MN	1.070	P	0.006	S	0.022	SI	0.240
NI	0.020	CR	0.120	MO	0.004	CU	0.050	CO	0.003
V	0.003	AL	0.022	Nb	0.011				

$$CE(\text{LONG FORMULA}) = 0.408$$

T/S(PSI)78300	Y/S(PSI)48400	EL(%)31.000	RA(%)56.900
---------------	---------------	-------------	-------------

BRINELL HARDNESS 164, 166

j108 Female

2" X 2" 3M A105 MSS-SP-83 Union Threaded

C	0.210	MN	1.070	P	0.005	S	0.017	SI	0.200
NI	0.010	CR	0.120	MO	0.001	CU	0.030	CO	0.002
V	0.004	AL	0.024	Nb	0.009				

$$CE(\text{LONG FORMULA}) = 0.416$$

T/S(Psi) 74800 Y/S(Psi) 43300 EL(%) 36.000 RA(%) 60.100

BRINELL HARDNESS 156, 156

[Click here for Original Steel Mill Certification](#)

h6cu Nut

2" X 2" 3M A105 MSS-SP-83 Union Threaded

C	0.180	MN	1.110	P	0.010	S	0.020	SI	0.260
NI	0.070	CR	0.140	MO	0.020	CU	0.220	CO	0.006
V	0.037	AL	0.025	CB	0.000				

$$CE(\text{LONG FORMULA}) = 0.424$$

T/S(PSI) 79723 Y/S(PSI) 52444 EL(%) 32.350 RA(%) 57.970

BRINELL HARDNESS 153, 153

Our Order 2492378-20-1 **Your Order** 74769-03

Heat D983-J108-H6CU

Packing List 407195-4 (1/14/2026)

Image 542716

Desc Forged Union ASTM A/SA105 NPT Threaded,2" 3000#

[Click here for Original Steel Mill Certification](#)

1. CERTIFYING ASTM A105-21 / ASME SA105-21 EDITION.
2. THE MATERIAL SUPPLIED MEETS THE REQUIREMENTS OF NACE MR0175/ISO 15156-2.
3. THE MATERIAL SUPPLIED WAS INSPECTED AND MANUFACTURED IN ACCORDANCE WITH EN DIN 10204:2004 EDITION TYPE 3.1 INSPECTION DOCUMENT.
4. THE ELONGATION TEST RESULTS ARE OBTAINED USING STANDARD ROUND SPECIMEN, 2 INCH OR 50 MM GAGE LENGTH.

THIS DOCUMENT HAS BEEN ELECTRONICALLY SUBMITTED.

Cancel

Logout