

Our Order 2492378-16-1 Your Order 74769-03  
Heat J229  
Desc Forged Hex Plug ASTM A/SA105 NPT Threaded,0.50"

Packing List 407195-4 (1/14/2026)

Image 553209

Job: 74769  
PO: 7476903  
BOM: 29  
Pages: 1  
Heat: J229

## CERTIFIED MILL TEST REPORT



The Best Value -  
Price, Quality, Service  
All The Time.

LOG NO. F00000000230916

Page 1 of 3

BONNEY FORGE CORPORATION

P.O. BOX 330 • 14496 CROGHAN PIKE • MOUNT UNION, PA 17066-0330

(814) 542-2545 • (800) 345-7546 • FAX (814) 542-4906

www.bonneyforge.com

CUSTOMER: EDGEN MURRAY CORPORATION

DATE 10/25/2025

CUSTOMER


BONNEY ORDER NO. B000372402

ORDER NO.: RMS-322486

SHIP TO: EDGEN MURRAY CORPORATION  
8445 MILLER RD 2  
HOUSTON TX 77049  
United States

| ITEM                                                                   | QUANTITY | LOT NO. | GRADE OR SPECIFICATION NO.                       |         |
|------------------------------------------------------------------------|----------|---------|--------------------------------------------------|---------|
|                                                                        |          |         | CHEMICAL ANALYSIS, PHYSICAL PROPERTIES, REMARKS: |         |
| 1                                                                      | 50       | J125    | 1/4 3M/6M A105 HXPL T                            | SA/A105 |
| C 0.170 Cb 0.000 Co 0.000 Cr 0.100 Cu 0.160 Mn 0.740 Mo 0.010 Ni 0.060 |          |         |                                                  |         |
| P 0.009 S 0.014 Si 0.190 V 0.003                                       |          |         |                                                  |         |
| CE(Long Formula) = 0.33                                                |          |         |                                                  |         |
| T/S(PSI) 0 Y/S(PSI) 0 EL(%) 0.00 RA(%) 0.00                            |          |         |                                                  |         |
| Brinell Hardness 150 BHN 159 BHN                                       |          |         |                                                  |         |
| 2                                                                      | 400      | J229    | 1/2 3M/6M A105 HXPL T                            | SA/A105 |
| C 0.160 Cr 0.080 Cu 0.080 Mn 0.730 Mo 0.020 Ni 0.050 P 0.007 S 0.002   |          |         |                                                  |         |
| Si 0.180 V 0.002                                                       |          |         |                                                  |         |
| CE(Long Formula) = 0.31                                                |          |         |                                                  |         |
| T/S(PSI) 0 Y/S(PSI) 0 EL(%) 0.00 RA(%) 0.00                            |          |         |                                                  |         |
| Brinell Hardness 141 BHN 156 BHN                                       |          |         |                                                  |         |
| Country Of Origin (Melt): UNITED STATES                                |          |         |                                                  |         |
| 3                                                                      | 200      | J249    | 3/4 3M/6M A105 HXPL T                            | SA/A105 |
| C 0.160 Cr 0.080 Cu 0.080 Mn 0.730 Mo 0.020 Ni 0.050 P 0.007 S 0.002   |          |         |                                                  |         |
| Si 0.180 V 0.002                                                       |          |         |                                                  |         |
| CE(Long Formula) = 0.31                                                |          |         |                                                  |         |
| T/S(PSI) 0 Y/S(PSI) 0 EL(%) 0.00 RA(%) 0.00                            |          |         |                                                  |         |
| Brinell Hardness 139 BHN 150 BHN                                       |          |         |                                                  |         |
| Country Of Origin (Melt): UNITED STATES                                |          |         |                                                  |         |
| 5                                                                      | 500      | 52200   | 1 3000 A105 90EL S                               | SA/A105 |
| Al 0.023 C 0.190 Co 0.010 Cr 0.110 Cu 0.120 Mn 0.980 Mo 0.020 Nb 0.001 |          |         |                                                  |         |
| Ni 0.050 P 0.008 S 0.018 Si 0.200 V 0.003                              |          |         |                                                  |         |
| CE(Long Formula) = 0.39                                                |          |         |                                                  |         |
| T/S(PSI) 75,299 Y/S(PSI) 45,756 EL(%) 34.55 RA(%) 66.43                |          |         |                                                  |         |
| Brinell Hardness 139 BHN 139 BHN                                       |          |         |                                                  |         |
| Country Of Origin (Melt): UNITED STATES                                |          |         |                                                  |         |

We certify that the data on this sheet is a true copy taken from our records of material furnished us by the production mill, or as obtained by additional laboratory checks.

by 

Billie Jo Clemens

Quality Assurance Representative

CMTR: Rev 3