

Material Test Report

An AFG Holdings Company

Heat Code: MF4

Ameriforge Ltd

13770 Industrial Rd. Houston, TX 77015

Sales: (713) 393-4200

ISO 9001:2015 Certified

NOV-R&M ENERGY SYS	15278	PO: 4057617	Sales Order: 202469	Line: 1
500 CONROE PARK WEST DR		Item Code: 9999H61985-0031R	Qty Shipped: 215	
CONROE, TX 77303		Item Desc: 4.00 150-900 HUB A350LF2 - 17518507-001 NRM CDFRG		
		Mill Heat: A252675		
Spec: ASME SA350/SA350M(24) LF2 CL1 & NOV 61-0072 (14) Rev 01 (Hubs)				

Element	(%wt)	Ladle	Product	EPCRA	CAS#	Element	(%wt)	Ladle	Product	EPCRA	CAS#
C	Carbon	0.18	✓ 0.19			Mo	Molybdenum	0.02	✓ 0.02		
Mn	Manganese	1.12	✓ 1.15	Y	7439-96-5	V	Vanadium	0.03	✓ 0.03		
P	Phosphorous	0.007	✓ 0.005			Cb	Columbium	0.00	✓ 0.00		
S	Sulphur	0.00	✓ 0.00			Al	Aluminum	0.03	✓ 0.03		
Si	Silicon	0.26	✓ 0.28			C.E.		0.41	✓		
Cu	Copper	0.12	✓ 0.12	Y	7440-50-8	CuNiCrMoV		0.31			
Ni	Nickel	0.05	✓ 0.05	Y	7440-02-0	CrMo		0.11			
Cr	Chromium	0.09	✓ 0.10	Y	7440-47-3						

4" Hub

Mechanical Testing		Heat Treat	
Test Lab	AFG	Norm. Temp. (F)	1675
Test Bar Size	4" 150-900 HUB TP AT 1/2 L	Norm. (Hrs)	2.5
HBW	140 - 140 ✓	Norm. Cooling Type	AIR
Elg (%)	33 ✓		
RA (%)	69 ✓		
Tensile Specimen Size (in)	.245	Other	
Tensile (ksi)	78 ✓	Country of Melt	USA
Yield (ksi)	49 ✓	Country of Forging	USA
Gauge Length (in)	1	Made to Fine Grain Practice	YES
Specimen Orientation	LONGITUDINAL		
LCVN Charpy Temp. (F)	-50 ✓		
LCVN (ft lbs)	85 - 62 - 63 ✓		
LAvg 3(ft-lbs)	70 ✓		
L Min (ft-lbs)	62		
% Shear	50 - 40 - 30		
Lat. Exp.	.08 - .059 - .06		


 3/17/26

The recording of false, fictitious, or fraudulent statement or entries on this document may be punishable as a felony under federal statute.

EPSCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPSCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPSCRA Section 313.

Certification No.: 1693108

Certification Date: 3/12/2026

Issued By: Terri Gibson

Page 1 of 2

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b

Material Test Report

Heat Code: MF4

Ameriforge Ltd

13770 Industrial Rd. Houston, TX 77015

ISO 9001:2015 Certified

Sales: (713) 393-4200

NOV-R&M ENERGY SYS	15278	PO: 4057617	Sales Order: 202469	Line: 1
500 CONROE PARK WEST DR		Item Code: 9999H61985-0031R		Qty Shipped: 215
CONROE, TX 77303		Item Desc: 4.00 150-900 HUB A350LF2 - 17518507-001 NRM CDFRG		
		Mill Heat: A252675		
Spec: ASME SA350/SA350M(24) LF2 CL1 & NOV 61-0072 (14) Rev 01 (Hubs)				

TAG H61985

Product compliant with NACE MR0175/ISO 15156-2:2021, Annex A (A.2.1.2, A2.1.3).
Product compliant with NACE MR0103/ISO 17945:2015, Section 13.1.1 and 13.1.3.

- * No Weld repair performed.
 - * Ladle Chemical Analysis results are reported from the raw material suppliers MTR.
 - * Tensile taken from a round specimen. Measurement of elongation after fracture.
 - * Yield strength was determined using the .2% offset method, unless specified.
 - * All material supplied under this order is certified to be free of mercury contamination and no mercury bearing equipment was used in manufacturing, fabrication or testing.
 - * When reported on MTR: Tensile Testing Per ASTM E8; Brinell Hardness Per ASTM E10; Charpy Testing Per ASTM E23
 - * AF Global manufactures materials according to a certified Quality Management System conforming to ISO 9001:2015 and PED certified to 2014/68/EU, Annex 1, Section 4.3.
- Unless otherwise noted on PO, Dimensions of all standard pipe flanges and flange fittings (NPS 1/2 to NPS 24) per ASME B16.5-2020, large diameter steel flanges (NPS 26 to 60) per ASME B16.47-2020, Orifice flanges per ASME B16.36-2020.
- * AFGlobal uses the latest edition of ASTM E29 (Standard practice for using significant digits in test data to determine conformance with specifications), to claim conformance or nonconformance to a specification. When a accept/reject determination is required AFGlobal uses a test uncertainty ratio (TUR) of 1:1 or higher as acceptable.
 - * DNV PED Certificate No 10000425664-PA-DNV-USA Valid thru December 03, 2026.

The recording of false, fictitious, or fraudulent statement or entries on this document may be punishable as a felony under federal statute.

EPCRA Supplier Notification: This product may contain one or more toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) and 40 C.F.R. Part 372. Potentially reportable chemicals are indicated with a checkmark in the "EPCRA" column and a Chemical Abstract Services (CAS) registry number is provided for each such chemical in addition to the percent by weight of the chemical present in this product. It is your responsibility alone to determine whether your facility is required to submit a Toxic Release Inventory Report under EPCRA Section 313.

Certification No.: 1693108
Certification Date: 3/12/2026
Issued By: Terri Gibson



Dusty Bannon - Quality Analyst

This report is issued in compliance with the requirements of EN10204 3.1 / ISO 10474 3.1.b