

Our Order 2492378-4-1 Your Order 74769-03  
Heat MH0359

Packing List 407195-4 (1/14/2026)

Image 508911

Desc Pipe SMLS ASTM A106-B/C, A53-B, API 5L B/X42,4.500 x .337 - 4" XH SRL



2669 Martin Luther King Jr Blvd  
Youngstown, OH 44510

**VALLOUREC STAR LP**  
Seamless Tubular Products

Certified Test Report  
08/09/2022  
Revision: 0

Order: Y-221122676-001 Desc: Seamless Line Pipe- Normalized Rolled Customer: Edgen Murray Corp.  
Grade: API 5L X42/B NBN PSL2 46th Edition May 01, 2019 Customer Order: DIS-265853  
OD(in): 4.500 Wall(in): 0.337 Lbs/Ft: 15.00 Length: Double Random  
End Finish: Plain End Beveled  
Comments: Melted and Manufactured in Youngstown, Ohio USA  
Pipe is also manufactured to: ASTM A106B/C-19a, ASTM A53B-20, ASME SA106B/C-2021, ASME SA53B-2021. Vallourec Star's QA program meets the requirements of DIN EN10204-2004 Type 3.1, Satisfies NACE MR0175/ISO15156:2015 and ANSINACE MR0103/ISO17945:2015.  
No repair welding has been conducted. Material is free from Mercury.

#### Mechanical Properties

| Orientation  | Type  | Position | Tensile Size Specimen Cross Section |            |             | Strength (ksi) |         |           | Elongation  |         |      |
|--------------|-------|----------|-------------------------------------|------------|-------------|----------------|---------|-----------|-------------|---------|------|
|              |       |          | Width (in)                          | Thick (in) | Area (sqin) | Yield          | Tensile | Y/T Ratio | Gage Length | % Elong | % RA |
| Longitudinal | Strip | Lead     | 1.000                               | 0.350      | 0.3500      | 45.7           | 72.7    | 0.63      | 2           | 39.4    | 60.2 |

Required Min/Max Yield Strength (ksi): 42.1/71.8

Required Min/Max Tensile Strength (ksi): 70/95

Calculated Max Internal Yield (psi): 5995

Required Min Elongation(%): 30

#### Supplemental Requirements

|                       |              |
|-----------------------|--------------|
| Flattening Test       | Passed       |
| Hardness 3 Point      | 85 avg HIRBW |
| Hydrostatic Pressure  | 4730 psi     |
| Hydrostatic Hold Time | 5 seconds    |

#### Chemical Analysis Chem Spec: 67

| WT%       | C    | Mn   | P     | S     | Si   | Cu   | Ni   | Cr   | Mo   | Sn    | Nb    | V     | Al    | Ca     | B      | Ti    | N      | C.E. |
|-----------|------|------|-------|-------|------|------|------|------|------|-------|-------|-------|-------|--------|--------|-------|--------|------|
| Heat      | 0.18 | 0.82 | 0.009 | 0.007 | 0.24 | 0.19 | 0.06 | 0.09 | 0.02 | 0.008 | 0.000 | 0.002 | 0.036 | 0.0018 | 0.0002 | 0.003 | 0.0084 | 0.36 |
| Product 1 | 0.18 | 0.84 | 0.009 | 0.007 | 0.23 | 0.19 | 0.06 | 0.09 | 0.03 | 0.008 | 0.000 | 0.002 | 0.036 | 0.0019 | 0.0001 | 0.003 | 0.0079 | 0.36 |
| Product 2 | 0.18 | 0.83 | 0.009 | 0.008 | 0.23 | 0.19 | 0.06 | 0.09 | 0.02 | 0.007 | 0.000 | 0.002 | 0.036 | 0.0020 | 0.0001 | 0.003 | 0.0068 | 0.36 |

Charpy Impact Testing - Not required per API.

This material has been produced and tested in accordance with the requirements of applicable specifications unless otherwise listed below. We hereby certify that the above test results are representative of those contained in the records of the company. Any modification to this certification as provided by Vallourec Star without the expressed written consent of Vallourec Star negates the validity of this test report. Vallourec Star is not responsible for the inability of this material to meet specific applications.

THIS CERTIFICATE IS NOTARIZED ONLY WHEN REQUESTED.

Signed: *Jeff Schultz*

Name: Jeff Schultz, Lab Supervisor

Date Approved: 08/09/2022

This document is uncontrolled when printed. Always refer to the MTR System for the most current version. FS-VMS-8.2.4.1.1 Rev 7

APPROVED

Kevin Jackson, 2/6/2026, 3:15:33 PM



2669 Martin Luther King Jr Blvd  
Youngstown, OH 44510

VALLOUREC STAR LP  
Seamless Tubular Products

Certified Test Report  
08/09/2022  
Revision: 0

|                                                        |                                             |                              |                       |
|--------------------------------------------------------|---------------------------------------------|------------------------------|-----------------------|
| Order: Y-221122676-001                                 | Desc: Seamless Line Pipe- Normalized Rolled | Customer: Edgen Murray Corp. | SLN / (Heat): MH0359  |
| Grade: API 5L X42/B NBN PSL2 46th Edition May 01, 2019 |                                             | Customer Order: DIS-285853   | Split: 00             |
| OD(In): 4.500                                          | Wall(In): 0.337                             | Lbs/Ft: 15.00                | Length: Double Random |
| End Finish: Plain End Beveled                          |                                             |                              |                       |
| Inspection Company: L Bay                              |                                             |                              |                       |

Non-Destructive Evaluation Criteria

| EMI CHANNELS                                               |                                    |
|------------------------------------------------------------|------------------------------------|
| ID                                                         | 10% Longitudinal<br>10% Transverse |
| OD                                                         | 5% Longitudinal<br>5% Transverse   |
| FULL LENGTH WALL THICKNESS CHECK                           |                                    |
| 87.5% Wall Reduction<br>Required Volumetric Coverage: 100% |                                    |

| ADDITIONAL REQUIREMENTS                        |
|------------------------------------------------|
| Notch Length 1.5" Max<br>Notch Width .020" Max |