



03669

DNOW L.P.

Description:

3/4 SOLID A234WPB SP95 GALV HEX BULL PLUG

**** Specifications - Heat Code W23322 ZZ: ****

A105/A105M-21, SA105, A234-18 WPB, SA234 WPB, ASME B16.5,

B16.9, B16.11, B16.36, B1.20.1, MSS SP-25, SP-44, SP-79,

P-83, SP-95, API-605, A.W.W.A.

STARTING MATERIAL: BAR/BILLET/FORGING

A234-18 WPBN, SA234 WPBN

Chemical Composition:

C:	Mn:	P:	S:	Si:	Cr:	Ni:	Mo:
0.180	0.830	0.012	0.029	0.210	0.140	0.090	0.020
Cu:	V:	Al:	Ca:	N:	Sn:	Pb:	Ti:
0.200	0.034	0.003	0.001	0.009	0.011	0.001	0.001
B:	Co:	C.E.:					
.0003	.002	.376					

Mechanical Properties:

Tensile(PSI):	Yield(PSI):	Elong(%):	RA(%):	Hardness:
75000	56000	32.00	67.00	HB 151-156

Impact Results:

Test Temp:	Achieved Values:
-50F	28-43-59 FTLBS

Comments:

Normalized

Meets Nace MR-01-75/2015, MR-01-03/2015, ISO 15156/2015

We certify only the chemistry and physical results shown for the referenced Heat Code as furnished by the Producing Mill. The Description is the responsibility of the requesting party. This document was electronically transmitted and is in accordance with EN10204 3.1/DIN50049 3.1B.