

Local Action Diagrams

**Super awesome package for local action
diagrams.**

0.1

29 January 2023

Marcus Chijoff

Marcus Chijoff

Email: marcus.chijoff@uon.edu.au

Homepage: <https://newcastle.edu.au>

Address: No

Contents

1	Introduction	3
2	Creating Local Action Diagrams	4
2.1	Creating Local Action Diagrams	4
3	Local Action Diagram Attributes and Operations	5
3.1	Local Action Diagram Attributes	5
3.2	Local Action Diagram Operations	6
4	Input/Output and Visualisation	7
4.1	Reading and Writing Local Action Diagrams To Files	7
4.2	Visualising Local Action Diagrams and Δ -trees.	8
	Index	9

Chapter 1

Introduction

A local action diagram $\Delta = (\Gamma, (G(v)), (X_a))$ consists of:

- a directed graph Γ ,
- a closed permutation group $G(v)$ for each $v \in V(\Gamma)$, and
- a set X_a for each $a \in A(\Gamma)$ such that each X_a is disjoint and X_a is an orbit of the action of $G(o(a))$ on $X_v := \bigsqcup_{a \in o^{-1}(v)} X_a$.

The definition of digraph used is different to that of the `Digraphs` package. For our purposes, a digraph Γ consists of:

- a vertex set V ,
- an arc set A ,
- a map $o : A \rightarrow V$ assigning each arc to an *origin* vertex, and
- a bijection $r : A \rightarrow A$ (denoted by $a \mapsto \bar{a}$) such that $r^2 = \text{id}$.

The bijection r defines a reverse arc for each arc of the graph. This is more specific than the definition in the `digraphs` package which does not require a reverse mapping.

The local action diagrams package provides a category for local action diagrams. It is built in the `IsDigraph` category from the `Digraphs` package.

Chapter 2

Creating Local Action Diagrams

2.1 Creating Local Action Diagrams

2.1.1 IsLocalActionDiagram (for IsDigraph)

▷ `IsLocalActionDiagram(lad)` (filter)

Returns: true if `lad` is of the category `IsLocalActionDiagram` and false otherwise.

Every local action diagram belongs to the `IsLocalActionDiagram` category. Every local action diagram is immutable.

2.1.2 Constructing From Data

▷ `LocalActionDiagramFromData(D, vertex_labels, edge_labels, rev)` (operation)

▷ `LocalActionDiagramFromDataNC(D, vertex_labels, edge_labels, rev)` (operation)

Returns: A local action diagram.

Constructs a local action diagram, checking that the arguments given are a valid local action diagram. The argument `D` is a digraph and `rev` must be a compatible involution on the edges of `D`. The argument `vertex_labels` is a list of vertex labels such that `vertex_labels[i]` is the group labelling vertex `i` of `D`.

The argument `edge_labels` is a list of edge labels. The edges of `D` are stored in lexicographical order and `edge_labels[i]` is the set labelling edge `i` of `D` (when sorted in lexicographical order).

The NC variant of the operation does not check that the arguments given are a valid local action diagram.

2.1.3 LocalActionDiagramUniversalGroup (for IsPermGroup)

▷ `LocalActionDiagramUniversalGroup(F)` (operation)

Returns: A local action diagram.

Constructs a local action diagram corresponding to the Burger-Mozes group $U(F)$ where F is a permutation group. This diagram has a single vertex labelled by the group F and a self-reverse loop for each orbit of the action of F .

Chapter 3

Local Action Diagram Attributes and Operations

3.1 Local Action Diagram Attributes

3.1.1 LocalActionDiagramVertexLabels (for IsLocalActionDiagram)

▷ LocalActionDiagramVertexLabels(*lad*) (attribute)

Returns: A list of groups.

Returns the groups labelling the vertices of *lad*. Entry *i* of the list corresponds to the group labelling vertex *i* of the digraph.

3.1.2 LocalActionDiagramEdges (for IsLocalActionDiagram)

▷ LocalActionDiagramEdges(*lad*) (attribute)

Returns: A list of lists.

Returns a list of edges of *lad*. Each edge is stored as a list [*i*, *j*] where *i* is the origin vertex and *j* is the terminus vertex. The list is stored in lexicographical order.

3.1.3 LocalActionDiagramEdgeLabels (for IsLocalActionDiagram)

▷ LocalActionDiagramEdgeLabels(*lad*) (attribute)

Returns: A list of lists.

Returns the edge labels of *lad*. Entry *i* of the list corresponds to the label of edge *i* of the digraph.

3.1.4 LocalActionDiagramEdgeReversal (for IsLocalActionDiagram)

▷ LocalActionDiagramEdgeReversal(*lad*) (attribute)

Returns: A permutation.

Returns the reversal mapping of the local action digram *lad*.

3.2 Local Action Diagram Operations

3.2.1 LocalActionDiagramScopos (for IsLocalActionDiagram)

▷ LocalActionDiagramScopos(*lad*) (attribute)

Returns: A list of lists.

Returns a list of all scopos of *lad*. Each entry of the list is a list of edges in the scopo. This list will always contain the empty scopo [].

3.2.2 LocalActionDiagramGroupType (for IsLocalActionDiagram)

▷ LocalActionDiagramGroupType(*lad*) (attribute)

Returns: A string.

Returns the group type the local action diagram corresponds to. This is either "Fixed Vertex", "Edge Inversion", "Lineal", "Focal", or "General". Note that all "Horocyclic" local action diagrams have infinitely many vertices and so can never be the type returned by this function.

3.2.3 LocalActionDiagramIsDiscrete (for IsLocalActionDiagram)

▷ LocalActionDiagramIsDiscrete(*lad*) (attribute)

Returns: true or false.

Returns true if *lad* corresponds to a discrete group and false otherwise.

Chapter 4

Input/Output and Visualisation

4.1 Reading and Writing Local Action Diagrams To Files

Local action diagrams made in GAP can be written to a file. They can also be read from the file into GAP. The format of these files are as follows:

Example

```
<Digraph String>
<Vertex Labels>
<Edge Labels>
<Edge Reversal Map>
<List of Other Attributes>
```

Multiple local action diagrams can be stored in the same file.

4.1.1 Writing Local Action Diagrams

- ▷ `WriteLocalActionDiagram(lad, filename[, directory])` (operation)
- ▷ `WriteLocalActionDiagram(lad_list, filename[, directory])` (operation)

Returns: true if writing to the file was successful and false otherwise.

Writes the local action diagram *lad* or every local action diagram in the list *lad_list* to the file *filename.lad*. The list *lad_list* must be a dense list of local action diagrams.

If the optional argument *directory* is specified then the file is written to that directory. Otherwise the file is written to the current directory of the GAP session — i.e. `DirectoryCurrent()`. The argument *directory* can either be in the category `IsDirectory` or `IsString`.

If the file *filename.lad* does not exist in the directory then it is create; otherwise the file is appended to.

4.1.2 Reading Local Action Diagrams

- ▷ `ReadLocalActionDiagram(filename[, directory])` (operation)

Returns: A list of local action diagrams if reading the file was successful or raises an error and returns fail otherwise.

Reads the file *filename*. If the optional argument *directory* is specified then the file is read from that directory. Otherwise the file is read from the current directory of the GAP session — i.e.

`DirectoryCurrent()`. The argument *directory* can either be in the category `IsDirectory` or `IsString`.

It is expected that the file was written with the `WriteLocalActionDiagram` function. Some basic error checking of the file is implemented as it is read but this will not catch all errors in the file.

4.2 Visualising Local Action Diagrams and Δ -trees.

Stuff goes here soon.

Index

IsLocalActionDiagram
 for IsDigraph, [4](#)

LocalActionDiagramEdgeLabels
 for IsLocalActionDiagram, [5](#)

LocalActionDiagramEdgeReversal
 for IsLocalActionDiagram, [5](#)

LocalActionDiagramEdges
 for IsLocalActionDiagram, [5](#)

LocalActionDiagramFromData
 for IsDigraph, IsList, IsList, IsPerm, [4](#)

LocalActionDiagramFromDataNC
 for IsDigraph, IsList, IsList, IsPerm, [4](#)

LocalActionDiagramGroupType
 for IsLocalActionDiagram, [6](#)

LocalActionDiagramIsDiscrete
 for IsLocalActionDiagram, [6](#)

LocalActionDiagramScopos
 for IsLocalActionDiagram, [6](#)

LocalActionDiagramUniversalGroup
 for IsPermGroup, [4](#)

LocalActionDiagramVertexLabels
 for IsLocalActionDiagram, [5](#)

ReadLocalActionDiagram
 for IsString, [7](#)

WriteLocalActionDiagram
 for IsList, IsString, [7](#)
 for IsLocalActionDiagram, IsString, [7](#)