



Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	The organization recently experienced a DDoS attack, which compromised the internal network for two hours until it was resolved. During the attack, the organization's network services suddenly stopped responding due to an incoming flood of ICMP packets. Normal internal network traffic could not access any network resources. The incident management team responded by blocking incoming ICMP packets, stopping all non-critical network services offline, and restoring critical network services.
Identify	A malicious actor attacked the company with an ICMP flood attack. The entire internal network was compromised. All of the critical network resources needed to be secured and restored.
Protect	The security team added a new firewall rule to cap the rate of incoming ICMP packets and an IDS/IPS system to filter out some ICMP traffic based on untrusted characteristics.
Detect	The security team configured the source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets and implemented network monitoring software to detect abnormal traffic patterns.

Respond	For future events, the cybersecurity team will isolate affected systems to prevent further disruption to the network. They will attempt to restore any critical systems and services that were disrupted by the event. Then, the team will analyze network logs to check for suspicious activity. The team will also report all incidents to upper management and appropriate legal authorities, if necessary.
Recover	To recover from a DDoS attack by ICMP flooding, access to network services need to be restored to a normal functioning state. In the future, external ICMP flood attacks can be blocked at the firewall. Then, all non-critical network services should be stopped to reduce internal network traffic. Next, critical network services should be restored first. Finally, once the flood of ICMP packets have timed out, all non-critical network systems and services can be brought back online.

Reflections/Notes: