08 - Summarizing and combining

Last time we got a file off the disk and into a table we could trust. This time we do the two things that turn a table into an answer:

- **Summarizing** - questions about *groups* of rows rather than single ones
- **Combining** - putting two tables together, and checking that it worked

The notebook covers both:

- Grouping and aggregating: `groupby`, `.agg()`, and one row per group
- The index of a grouped result: `set_index` and `reset_index`
- Transforming within groups: `.transform()`, `ffill`, `diff`, `pct_change` - one row per *original* row
- Working with dates: `to_datetime`, date formats, the `.dt` accessor
- Resampling a time series: `resample`, up and down
- Combining tables: `concat`, duplicates, `merge`, and validating a merge
- Per person or per country: two averages that answer different questions

As always, we start by importing what we need and loading our own data.

In [1]:
```
import numpy as np
import pandas as pd
```

Here is the function we finished with last time: it reads the file, drops the rows with no emissions figure, and adds emissions per person.

In [2]:
```
def load_emissions(path):
    """
    Read the emissions file and return it ready to use.

    Parameters
    ----------
    path : str
        Path to the emissions CSV file.

    Returns
    -------
    DataFrame
        One row per country per year, with rows missing total emissions
        dropped and emissions per person added as a column.
    """
    emissions = pd.read_csv(path)

    emissions = emissions.dropna(subset=["co2_total"])
    emissions["co2_pc"] = emissions["co2_total"] * 1_000_000 / emissions["pc
```

Loading [MathJax]/extensions/Safe.js

```
    return emissions


co2 = load_emissions("../data/co2_emissions.csv")

print(co2.shape)
co2.head(3)
```

```
(5904, 12)
```

Out[2]:

	country	code	year	co2_total	population	urban	gdp_pc	electricity	agricul
0	Afghanistan	AFG	2000	1.0093	20130327	18.558	174.93	4.4	57
1	Afghanistan	AFG	2001	0.9402	20284307	18.741	138.71	9.3	57
2	Afghanistan	AFG	2002	0.9388	21378117	18.941	178.95	14.1	57

Grouping and aggregating

Here is a question the table looks like it can answer. **How much CO_2 did the world emit each year?**

Every row is one entity in one year. So: take all the rows for a year, add up their emissions, and do that for each year. That is a loop over years, but pandas has a shorter way, called `groupby`.

In [3]:
```
co2.groupby("year")["co2_total"].sum().tail(3)
```

Out[3]:
```
year
2021    312230.8520
2022    314199.0783
2023    320155.6020
Name: co2_total, dtype: float64
```

Three moves in one line:

- **split** the rows into groups by their `year`
- **apply** `sum` to the `co2_total` column of each group
- **combine** the answers into one result

That is the whole idea, and it has a name - **split-apply-combine**. Every `groupby` you will ever write is those three steps; the only things that change are what you split on and what you apply.

> ⚠️ **Warning:** That answer is **wrong**. The table contains rows like `World` and `East Asia & Pacific`, which are groupings of countries, so summing every row counts the same emissions several times over. We come back to it later.

Loading [MathJax]/extensions/Safe.js

The grouped object computes nothing

It is worth seeing what `groupby` actually returns, because it is not a table.

In [4]:
```
by_year = co2.groupby("year")

by_year
```

Out[4]:
```
<pandas.core.groupby.generic.DataFrameGroupBy object at 0x1385e6ba0>
```

A `DataFrameGroupBy`. It knows which rows belong to which group and has computed nothing at all - it is waiting to be told what to apply. That is why the two halves are always written together: `.groupby("year")` on its own is a question with no verb.

Pick a column first and you get one answer per group.

In [5]:
```
co2.groupby("year")["co2_pc"].mean().tail(3)
```

Out[5]:
```
year
2021    4.525511
2022    4.495202
2023    4.406028
Name: co2_pc, dtype: float64
```

Counting: `.size()` and `.count()`

Two ways to count, and the difference matters.

- `.size()` counts **rows** in each group.
- `.count()` counts **non-missing values** in a column of each group.

In [6]:
```
counts = pd.DataFrame({
    "rows": co2.groupby("year").size(),
    "renew_energy": co2.groupby("year")["renew_energy"].count(),
})

counts.tail(5)
```

Out[6]:

year	rows	renew_energy
2019	246	246
2020	246	246
2021	246	203
2022	246	66
2023	246	0

Loading [MathJax]/extensions/Safe.js

Every year has the same 246 rows, and until 2020 every row has a renewable energy figure. Then 203, then 66, then **none at all**. That is the publication lag we found last time, seen from a different direction: the rows are all there, the values are not.

Use `.size()` when you want to know how big a group is, and `.count()` when you want to know how much of it you can actually use.

Several statistics at once: `.agg()`

`.mean()` gives you one statistic. Real summary tables want several. `.agg()` takes a **list of function names, written as strings**, and gives you a column for each.

In [7]:
```
co2.groupby("year")["co2_pc"].agg(["mean", "median", "max"]).tail(3)
```

Out[7]:

year	mean	median	max
2021	4.525511	2.609076	74.734297
2022	4.495202	2.643982	78.726280
2023	4.406028	2.686580	78.857111

These are the aggregation functions worth knowing. All of them collapse a group to a single value, and all of them can be written either as a method or as a string inside `.agg()`.

`"sum"`	total
`"mean"`, `"median"`	average, middle value
`"min"`, `"max"`	smallest, largest
`"std"`, `"var"`	standard deviation, variance
`"count"`	non-missing values
`"size"`	rows, missing or not
`"first"`, `"last"`	first and last value in the group
`"nunique"`	how many distinct values

The list form works when every statistic is applied on the **same column**. Often you want different statistics of different columns, and then there is a second form: name each output column, and say what it is made of.

```
grouped.agg(
    output_name = ("input_column", "function"),
```

Loading [MathJax]/extensions/Safe.js

```
    ...
)
```

In [8]:
```
summary = co2.groupby("year").agg(
    entities=("co2_total", "count"),
    total_co2=("co2_total", "sum"),
    mean_pc=("co2_pc", "mean"),
).round(0)

summary.tail(3)
```

Out[8]:

year	entities	total_co2	mean_pc
2021	246	312231.0	5.0
2022	246	314199.0	4.0
2023	246	320156.0	4.0

One line per output column, each saying exactly where it came from. This is the form to reach for when you are building a table somebody else will read, because the column names are yours rather than pandas' guesses.

> 💡 **Tip:** `.round(2)` on the result rounds every number in it, which usually makes a

summary table far easier to read. Round for **display**, at the end - not in the middle of a calculation, where you would be throwing away precision you still need.

Your turn

Starting from:

```
co2 = pd.read_csv("../data/co2_emissions.csv")
```

Build one summary table with a row per year and three named columns: the number of entities that have a `gdp_pc` figure, the average `gdp_pc`, and the highest `urban` share. Display the last five years, rounded to one decimal.

In [9]:
```
co2 = pd.read_csv("../data/co2_emissions.csv")

co2.groupby("year").agg(
    gdp_entities=("gdp_pc", "count"), # amount of entities that have a gdp_p
    avg_gdp_pc=("gdp_pc", "mean"), # average gdp_pc
    highest_urban=("urban", "max") # the highest urban share
).tail(5).round(1)
```

Loading [MathJax]/extensions/Safe.js

Out[9]:

year	gdp_entities	avg_gdp_pc	highest_urban
2019	254	17689.2	100.0
2020	253	16422.9	100.0
2021	253	18973.0	100.0
2022	252	19671.2	100.0
2023	247	20658.7	100.0

The index of a grouped result

Look closely at what came back from those last few cells. The years are not in a column. They are down the left-hand side, where the row numbers usually go.

That is because they **are** the index now. `groupby` puts whatever you grouped on into the index of the result, which makes sense: the group label is what identifies the row.

In [10]:
```
totals = co2.groupby("year")["co2_total"].sum()

print(type(totals))
print(totals.index)
```

```
<class 'pandas.core.series.Series'>
Index([2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 201
1,
       2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020, 2021, 2022, 202
3],
      dtype='int64', name='year')
```

A `Series`, indexed by year. That is often exactly what you want. Index alignment means you can divide one grouped result by another and the years line themselves up, and plotting a Series puts the index along the horizontal axis without being asked.

But it is a nuisance the moment you want to treat the result as an ordinary table - filter it, join it, or write it to a file - because `year` **is not a column**, and asking for it as one fails.

In [11]:
```
# KeyError
totals["year"]
```

Loading [MathJax]/extensions/Safe.js

```
---------------------------------------------------------------------------
KeyError                                  Traceback (most recent call last)
File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/indexes/base.p
y:3805, in Index.get_loc(self, key)
   3804 try:
-> 3805     return self._engine.get_loc(casted_key)
   3806 except KeyError as err:

File index.pyx:167, in pandas._libs.index.IndexEngine.get_loc()

File index.pyx:175, in pandas._libs.index.IndexEngine.get_loc()

File pandas/_libs/index_class_helper.pxi:70, in pandas._libs.index.Int64Engi
ne._check_type()

KeyError: 'year'

The above exception was the direct cause of the following exception:

KeyError                                  Traceback (most recent call last)
Cell In[11], line 2
      1 # KeyError
----> 2 totals["year"]

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/series.py:1121,
in Series.__getitem__(self, key)
   1118     return self._values[key]
   1120 elif key_is_scalar:
-> 1121     return self._get_value(key)
   1123 # Convert generator to list before going through hashable part
   1124 # (We will iterate through the generator there to check for slices)
   1125 if is_iterator(key):

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/series.py:1237,
in Series._get_value(self, label, takeable)
   1234     return self._values[label]
   1236 # Similar to Index.get_value, but we do not fall back to positional
-> 1237 loc = self.index.get_loc(label)
   1239 if is_integer(loc):
   1240     return self._values[loc]

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/indexes/base.p
y:3812, in Index.get_loc(self, key)
   3807     if isinstance(casted_key, slice) or (
   3808         isinstance(casted_key, abc.Iterable)
   3809         and any(isinstance(x, slice) for x in casted_key)
   3810     ):
   3811         raise InvalidIndexError(key)
-> 3812     raise KeyError(key) from err
   3813 except TypeError:
   3814     # If we have a listlike key, _check_indexing_error will raise
   3815     #  InvalidIndexError. Otherwise we fall through and re-raise
   3816     #  the TypeError.
   3817     self._check_indexing_error(key)

KeyError: 'year'
```

Loading [MathJax]/extensions/Safe.js

`reset_index` moves the index back into a column

In [12]:
```
totals_df = totals.reset_index()

print(type(totals_df))
totals_df.tail(3)
```

```
<class 'pandas.core.frame.DataFrame'>
```

Out[12]:

	year	co2_total
21	2021	312230.8520
22	2022	314199.0783
23	2023	320155.6020

Now it is a DataFrame with two ordinary columns, and everything from last time works on it again. `reset_index()` is the most common thing to write after a `groupby`, and when a grouped result is fighting you, it is usually the answer.

> 📝 **Note:** `reset_index()` takes a `drop` parameter. `reset_index(drop=True)` throws the old index away instead of turning it into a column, which is what you want when the index is meaningless row numbers rather than something you care about.

`set_index` goes the other way

`set_index` takes a column and makes it the index.

In [13]:
```
totals_by_year = totals_df.set_index("year")

totals_by_year.tail(3)
```

Out[13]:

	co2_total
year	
2021	312230.8520
2022	314199.0783
2023	320155.6020

In [14]:
```
totals_by_year.loc[2023, "co2_total"]
```

Out[14]:
```
320155.602
```

Loading [MathJax]/extensions/Safe.js

Which raises the obvious question: why would you ever do that on purpose?

Because an index is not decoration - it is what pandas **aligns on**, as we saw when two Series with different labels were added together. A table indexed by something meaningful can be looked up by label with `.loc`, as above; it lines up automatically with any other table indexed the same way.

Transforming within groups

Everything so far **collapsed** the table: 5 904 rows in, 24 rows out, one per group.

Often that is not what you want. You want the group's answer put back **beside every row it came from**, so that a row can be compared against its own group. Norway's emissions per person in 2020 are only interesting next to Norway's usual level.

The methods in this section all do that. They take a group and give back **one value per original row**, so their results can be assigned straight into a column.

In [15]:
```
co2.groupby("country")["co2_pc"].agg("mean").shape
```

```
---------------------------------------------------------------------------
KeyError                                  Traceback (most recent call last)
Cell In[15], line 1
----> 1 co2.groupby("country")["co2_pc"].agg("mean").shape

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/groupby/generic.py:1951, in DataFrameGroupBy.__getitem__(self, key)
   1944 if isinstance(key, tuple) and len(key) > 1:
   1945     # if len == 1, then it becomes a SeriesGroupBy and this is actually
   1946     # valid syntax, so don't raise
   1947     raise ValueError(
   1948         "Cannot subset columns with a tuple with more than one element. "
   1949         "Use a list instead."
   1950     )
-> 1951 return super().__getitem__(key)

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/base.py:244, in SelectionMixin.__getitem__(self, key)
    242 else:
    243     if key not in self.obj:
--> 244         raise KeyError(f"Column not found: {key}")
    245     ndim = self.obj[key].ndim
    246     return self._gotitem(key, ndim=ndim)

KeyError: 'Column not found: co2_pc'
```

In [16]:
```
co2.groupby("country")["co2_pc"].transform("mean").shape # transforming: cal
```

Loading [MathJax]/extensions/Safe.js

```
---------------------------------------------------------------------------
KeyError                                  Traceback (most recent call last)
Cell In[16], line 1
----> 1 co2.groupby("country")["co2_pc"].transform("mean").shape

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/groupby/generi
c.py:1951, in DataFrameGroupBy.__getitem__(self, key)
   1944 if isinstance(key, tuple) and len(key) > 1:
   1945     # if len == 1, then it becomes a SeriesGroupBy and this is actua
lly
   1946     # valid syntax, so don't raise
   1947     raise ValueError(
   1948         "Cannot subset columns with a tuple with more than one eleme
nt. "
   1949         "Use a list instead."
   1950     )
-> 1951 return super().__getitem__(key)

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/base.py:244, in
SelectionMixin.__getitem__(self, key)
    242 else:
    243     if key not in self.obj:
--> 244         raise KeyError(f"Column not found: {key}")
    245     ndim = self.obj[key].ndim
    246     return self._gotitem(key, ndim=ndim)

KeyError: 'Column not found: co2_pc'
```

246 against 5 904. `.mean()` gave one number per country; `.transform("mean")` gave every row its own country's number, repeated as many times as that country has rows. **Same answer, different shape.**

The methods

`.transform()` takes any of the aggregation names from earlier and broadcasts the result back. The rest are methods that compare a row against its **neighbors** rather than against a summary.

`.transform("mean")`	the group's statistic, repeated on every row of the group
`.diff()`	this row minus the previous row
`.pct_change()`	the same, as a fraction of the previous row
`.shift(1)`	the previous row's value, moved down one
`.cumsum()`	running total down the group
`.ffill()`	fill a hole with the last known value **before** it
`.bfill()`	fill a hole with the next known value **after** it

Loading [MathJax]/extensions/Safe.js

Because several of these look at the row before or after, the rows have to be **in order**. Our panel is one series per country stacked on top of the next, so we sort by country and year first.

In [17]:
```
panel = co2.sort_values(["country", "year"]).copy()

panel["country_mean_pc"] = panel.groupby("country")["co2_pc"].transform("mea
panel["previous"] = panel.groupby("country")["co2_total"].shift(1)
panel["change"] = panel.groupby("country")["co2_total"].diff()
panel["pct_change"] = panel.groupby("country")["co2_total"].pct_change() * 1

panel[panel["country"] == "Norway"][
    ["year", "co2_total", "previous", "change", "pct_change", "country_mean_
].tail(4).round(2)
```

```
---------------------------------------------------------------------------
KeyError                                  Traceback (most recent call last)
Cell In[17], line 3
      1 panel = co2.sort_values(["country", "year"]).copy()
----> 3 panel["country_mean_pc"] = panel.groupby("country")["co2_pc"].transf
orm("mean")
      4 panel["previous"] = panel.groupby("country")["co2_total"].shift(1)
      5 panel["change"] = panel.groupby("country")["co2_total"].diff()

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/groupby/generi
c.py:1951, in DataFrameGroupBy.__getitem__(self, key)
   1944 if isinstance(key, tuple) and len(key) > 1:
   1945     # if len == 1, then it becomes a SeriesGroupBy and this is actua
lly
   1946     # valid syntax, so don't raise
   1947     raise ValueError(
   1948         "Cannot subset columns with a tuple with more than one eleme
nt. "
   1949         "Use a list instead."
   1950     )
-> 1951 return super().__getitem__(key)

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/base.py:244, in
SelectionMixin.__getitem__(self, key)
    242 else:
    243     if key not in self.obj:
--> 244         raise KeyError(f"Column not found: {key}")
    245     ndim = self.obj[key].ndim
    246     return self._gotitem(key, ndim=ndim)

KeyError: 'Column not found: co2_pc'
```

Four different questions about Norway, in one table:

- `country_mean_pc` is Norway's own 24-year average per person (repeated on every Norwegian row)
- `previous` is last year's figure moved down a row
- `change` is the difference

Loading [MathJax]/extensions/Safe.js

- `pct_change` is that difference as a percentage

The first of these is the pattern worth remembering: **compute a baseline per group, then measure every row against it.** Temperature anomalies, deviations from trend, shares of a total and index numbers are all these same two lines.

In [18]:
```
year_2020 = panel[panel["year"] == 2020]

print("entities with a 2020 figure:", len(year_2020))
print("emissions fell in 2020:     ", (year_2020["change"] < 0).sum())
```

```
entities with a 2020 figure: 260
```

Loading [MathJax]/extensions/Safe.js

```
---------------------------------------------------------------------------
KeyError                                  Traceback (most recent call last)
File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/indexes/base.p
y:3805, in Index.get_loc(self, key)
   3804 try:
-> 3805     return self._engine.get_loc(casted_key)
   3806 except KeyError as err:

File index.pyx:167, in pandas._libs.index.IndexEngine.get_loc()

File index.pyx:196, in pandas._libs.index.IndexEngine.get_loc()

File pandas/_libs/hashtable_class_helper.pxi:7081, in pandas._libs.hashtabl
e.PyObjectHashTable.get_item()

File pandas/_libs/hashtable_class_helper.pxi:7089, in pandas._libs.hashtabl
e.PyObjectHashTable.get_item()

KeyError: 'change'

The above exception was the direct cause of the following exception:

KeyError                                  Traceback (most recent call last)
Cell In[18], line 4
      1 year_2020 = panel[panel["year"] == 2020]
      3 print("entities with a 2020 figure:", len(year_2020))
----> 4 print("emissions fell in 2020:     ", (year_2020["change"] < 0).sum
())

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/frame.py:4102,
in DataFrame.__getitem__(self, key)
   4100 if self.columns.nlevels > 1:
   4101     return self._getitem_multilevel(key)
-> 4102 indexer = self.columns.get_loc(key)
   4103 if is_integer(indexer):
   4104     indexer = [indexer]

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/indexes/base.p
y:3812, in Index.get_loc(self, key)
   3807     if isinstance(casted_key, slice) or (
   3808         isinstance(casted_key, abc.Iterable)
   3809         and any(isinstance(x, slice) for x in casted_key)
   3810     ):
   3811         raise InvalidIndexError(key)
-> 3812     raise KeyError(key) from err
   3813 except TypeError:
   3814     # If we have a listlike key, _check_indexing_error will raise
   3815     #  InvalidIndexError. Otherwise we fall through and re-raise
   3816     #  the TypeError.
   3817     self._check_indexing_error(key)

KeyError: 'change'
```

187 of 246 entities emitted less in 2020 than in 2019 - the pandemic, visible in one `iff()`.

Loading [MathJax]/extensions/Safe.js

Your turn

Starting from:

```
co2 = pd.read_csv("../data/co2_emissions.csv")
```

Add a column giving how far each row's `urban` share is from its own country's average `urban` share, and display Norway's last five years, rounded to two decimals.

In [19]:
```
co2 = pd.read_csv("../data/co2_emissions.csv")

co2["country_urban_mean"] = co2.groupby("country")["urban"].transform("mean"

co2["urban_vs_mean"] = co2["urban"] - co2["country_urban_mean"] # difference

co2.head()
```

Out[19]:

	country	code	year	co2_total	population	urban	gdp_pc	electricity	agricul
0	Afghanistan	AFG	2000	1.0093	20130327	18.558	174.93	4.4	57
1	Afghanistan	AFG	2001	0.9402	20284307	18.741	138.71	9.3	57
2	Afghanistan	AFG	2002	0.9388	21378117	18.941	178.95	14.1	57
3	Afghanistan	AFG	2003	1.0172	22733049	19.160	198.87	19.0	58
4	Afghanistan	AFG	2004	0.9024	23560654	19.399	221.76	23.8	58

Filling gaps

`ffill` and `bfill` belong to the same family and are worth their own demonstration, because they are a **decision** and not a repair. We know `renew_energy` stops being published in the most recent years. A forward fill carries each country's last observed share forward into them.

In [20]:
```
panel["renew_filled"] = panel.groupby("country")["renew_energy"].ffill() # r

print("missing before:", panel["renew_energy"].isna().sum())
print("missing after: ", panel["renew_filled"].isna().sum())

panel[panel["country"] == "Norway"][["year", "renew_energy", "renew_filled"]
```

```
missing before: 635
missing after:  153
```

Loading [MathJax]/extensions/Safe.js

Out[20]:

	year	renew_energy	renew_filled
4292	2020	60.9	60.9
4293	2021	61.4	61.4
4294	2022	NaN	61.4
4295	2023	NaN	61.4

471 holes down to 2, and Norway's 2021 figure of 61.4 copied into 2022 and 2023.

And now the part you have to decide rather than run. A forward fill asserts that the value did not change. Over one year, for a share that moves slowly, that is defensible. Over three years, for exactly the years everyone wants to look at, it invents a flat line that never happened - and nothing downstream will ever tell you the number was made up. Filling is a claim about the world, not a tidying step.

`bfill` is the same method pointing the other way, and it earns its keep when a label is recorded only once. If a file gives each country's region in its final year only, one `bfill` within country carries it back over every earlier year.

The group is not optional

Every method in this section was written with a `groupby` in front of it. Here is what happens without one.

In [21]:
```
small = pd.DataFrame({
    "country": ["Norway", "Norway", "Norway", "Sweden", "Sweden", "Sweden"],
    "year": [2021, 2022, 2023, 2021, 2022, 2023],
    "renew_energy": [60.1, 61.4, np.nan, np.nan, 50.2, 51.0],
    "co2_total": [40, 38, 37, 35, 34, 33],
})

small["ffill_grouped"] = small.groupby("country")["renew_energy"].ffill()
small["ffill_ungrouped"] = small["renew_energy"].ffill()

small[["country", "year", "renew_energy", "ffill_grouped", "ffill_ungrouped"
```

Out[21]:

	country	year	renew_energy	ffill_grouped	ffill_ungrouped
0	Norway	2021	60.1	60.1	60.1
1	Norway	2022	61.4	61.4	61.4
2	Norway	2023	NaN	61.4	61.4
3	Sweden	2021	NaN	NaN	61.4
4	Sweden	2022	50.2	50.2	50.2
5	Sweden	2023	51.0	51.0	51.0

Loading [MathJax]/extensions/Safe.js

Norway's 2023 hole is filled with 61.4 either way. Sweden's 2021 hole is where the two disagree. Grouped, it stays `NaN`: Sweden has no earlier value to carry forward. Ungrouped, it gets 61.4 - **Norway's** figure, carried straight on into the next country because nothing told `ffill` where Norway ends. The ungrouped fill leaves fewer missing values, which looks better and is much worse.

> ⚠️ **Warning:** Every method in this section looks at the row before or the row after, and none of them knows where one country ends and the next begins. **Group first** - and the group is whatever the rows are a series *within*.

Your turn

Starting from:

```
co2 = pd.read_csv("../data/co2_emissions.csv")
co2 = co2.sort_values(["country", "year"])
```

Add a column giving each country's year-on-year **percentage** change in `co2_total`, and display the five largest single-year rises in the whole table.

In [22]:
```
co2 = pd.read_csv("../data/co2_emissions.csv")
co2 = co2.sort_values(["country", "year"])

co2["co2_change"] = co2.groupby("country")["co2_total"].pct_change()*100

# displaying the 5 highest
# co2.sort_values("co2_change", ascending=False).head() # method 1

co2.nlargest(5, "co2_change") # method 2
```

```
/var/folders/q4/qkfl7h2n1wn_29ndffqyg93w0000gn/T/ipykernel_22211/1563684675.
py:4: FutureWarning: The default fill_method='ffill' in SeriesGroupBy.pct_ch
ange is deprecated and will be removed in a future version. Either fill in a
ny non-leading NA values prior to calling pct_change or specify 'fill_method
=None' to not fill NA values.
  co2["co2_change"] = co2.groupby("country")["co2_total"].pct_change()*100
```

Loading [MathJax]/extensions/Safe.js

Out[22]:

	country	code	year	co2_total	population	urban	gdp_pc	electricity	ag
2188	Greenland	GRL	2004	0.6039	56898	82.563	32031.00	100.0	
5826	Turks and Caicos Islands	TCA	2018	0.1897	41559	92.680	31625.62	100.0	
2969	Korea, Dem. People's Rep.	PRK	2017	73.5427	25817709	61.821	NaN	44.2	
3087	Lao PDR	LAO	2015	8.9275	6801645	33.124	2121.01	89.7	
5644	Timor-Leste	TLS	2004	0.5158	929074	25.704	474.42	30.4	

Working with dates

A great deal of real data is a **time series**: the same thing measured over and over, with a date attached. Before you can group, filter or plot by time, pandas has to know that the date column is a date and not a piece of text.

New dataset: the daily closing level of the **NASDAQ Composite** stock index, from 1971 to 2025.

In [23]:
```
nasdaq = pd.read_csv("../data/NASDAQ.csv")

print(nasdaq.shape)
print(nasdaq.dtypes)
nasdaq.head(3)
```

```
(13842, 2)
Date       object
NASDAQ    float64
dtype: object
```

Out[23]:

	Date	NASDAQ
0	1971-02-05	100.0
1	1971-02-08	100.8
2	1971-02-09	100.8

13 842 trading days and two columns. And `Date` is `str` - as far as pandas is concerned, `"1971-02-05"` is a piece of text like `"Bergen"`.

`pd.to_datetime`, and always say the format

Loading [MathJax]/extensions/Safe.js

`pd.to_datetime` converts text into real dates. It can guess the format, but you should not let it.

In [24]:
```
nasdaq["Date"] = pd.to_datetime(nasdaq["Date"], format="%Y-%m-%d")

print(nasdaq["Date"].dtype)
print(nasdaq["Date"].min(), "to", nasdaq["Date"].max())
```

```
datetime64[ns]
1971-02-05 00:00:00 to 2025-12-30 00:00:00
```

`datetime64` - a point in time, which pandas can sort, compare and do arithmetic on.

The `format` string describes how the date is *written*, using a code for each piece:

Code	Means	Example
`%Y`	four-digit year	`2024`
`%y`	two-digit year	`24`
`%m`	month as a number	`03`
`%b`	short month name	`Mar`
`%B`	full month name	`March`
`%d`	day of the month	`09`
`%H`	hour, 24-hour clock	`14`
`%M`	minute	`30`
`%S`	second	`05`

Everything else in the string is taken literally, so `"%d/%m/%Y"` matches `09/03/2024`, `"%d.%m.%Y"` matches `09.03.2024`, and `"%B %d, %Y"` matches `March 09, 2024`.

Why the format is not optional

In [25]:
```
visits = pd.DataFrame({
    "date": ["02/01/2021", "06/05/2021", "11/03/2021"],
    "patients": [14, 9, 22],
})

print("guessed:  ", list(pd.to_datetime(visits["date"]).dt.date))
print("told:     ", list(pd.to_datetime(visits["date"], format="%d/%m/%Y").d
```

```
guessed:   [datetime.date(2021, 2, 1), datetime.date(2021, 6, 5), datetime.d
ate(2021, 11, 3)]
told:      [datetime.date(2021, 1, 2), datetime.date(2021, 5, 6), datetime.d
ate(2021, 3, 11)]
```

Loading [MathJax]/extensions/Safe.js

Those are European dates - 2 January, 6 May, 11 March. Left to guess, pandas reads them the American way round and returns **1 February, 5 June and 3 November** instead.

No error, and no warning. Every day number here is 12 or below, so both readings are valid calendar dates and there is nothing for pandas to complain about. The dates are simply wrong, and every grouping, filter and plot built on them afterwards is wrong too.

`.dt` gets the pieces out

A real date knows what year, month and day it is made of. The **`.dt` accessor** is how you ask for one piece at a time: `.dt.year`, `.dt.month`, `.dt.day`, `.dt.quarter`, `.dt.date`, and `.dt.day_name()` for the weekday as text.

In [26]:
```
nasdaq["year"] = nasdaq["Date"].dt.year
nasdaq["month"] = nasdaq["Date"].dt.month
nasdaq["weekday"] = nasdaq["Date"].dt.day_name()

nasdaq.head(3)
```

Out[26]:

	Date	NASDAQ	year	month	weekday
0	1971-02-05	100.0	1971	2	Friday
1	1971-02-08	100.8	1971	2	Monday
2	1971-02-09	100.8	1971	2	Tuesday

Filtering by date

Real dates compare properly, so filtering to a period is a boolean mask like any other. The boundaries can be written as strings and pandas will read them as dates.

In [27]:
```
crash = nasdaq[(nasdaq["Date"] >= "2020-02-01") & (nasdaq["Date"] <= "2020-0

print(len(crash), "trading days")
print("high:", crash["NASDAQ"].max().round(1), " low:", crash["NASDAQ"].min(
```

```
62 trading days
```

```
---------------------------------------------------------------------------
AttributeError                            Traceback (most recent call last)
Cell In[27], line 4
      1 crash = nasdaq[(nasdaq["Date"] >= "2020-02-01") & (nasdaq["Date"] <=
"2020-04-30")]
      3 print(len(crash), "trading days")
----> 4 print("high:", crash["NASDAQ"].max().round(1), " low:", crash["NASDA
Q"].min().round(1))

AttributeError: 'float' object has no attribute 'round'
```

Loading [MathJax]/extensions/Safe.js

Your turn

Starting from:

```
nasdaq = pd.read_csv("../data/NASDAQ.csv")
nasdaq["Date"] = pd.to_datetime(nasdaq["Date"], format="%Y-%m-%d")
```

Using the `.dt` accessor and a `groupby`, report the average closing level in each **decade**. Display the result.

Hint: integer division by 10 and back, `year // 10 * 10`, turns 1987 into 1980.

In [28]:
```
nasdaq = pd.read_csv("../data/NASDAQ.csv")
nasdaq["Date"] = pd.to_datetime(nasdaq["Date"], format="%Y-%m-%d")

nasdaq["decade"] = nasdaq["Date"].dt.year // 10 * 10
nasdaq.groupby("decade")["NASDAQ"].mean()
```

Out[28]:
```
decade
1970      104.624066
1980      296.667286
1990     1104.079272
2000     2194.094791
2010     4744.158386
2020    14574.572196
Name: NASDAQ, dtype: float64
```

In [29]:
```
nasdaq
```

Out[29]:

	Date	NASDAQ	decade
0	1971-02-05	100.0	1970
1	1971-02-08	100.8	1970
2	1971-02-09	100.8	1970
3	1971-02-10	100.7	1970
4	1971-02-11	101.4	1970
...	...	...	...
13837	2025-12-23	23561.8	2020
13838	2025-12-24	23613.3	2020
13839	2025-12-26	23593.1	2020
13840	2025-12-29	23474.3	2020
13841	2025-12-30	23419.1	2020

13842 rows × 3 columns

Loading [MathJax]/extensions/Safe.js

Resampling a time series

Daily data is rarely the resolution you want to report at. `resample` changes the frequency of a time series: **downsampling** to a coarser one (daily to monthly), or **upsampling** to a finer one (monthly to daily).

It needs the dates to be the **index**, which is what `set_index` was for, and it wants them in order, which is what `sort_index` is for.

In [30]:
```
prices = nasdaq.set_index("Date").sort_index()["NASDAQ"]

prices.head(3)
```

Out[30]:
```
Date
1971-02-05    100.0
1971-02-08    100.8
1971-02-09    100.8
Name: NASDAQ, dtype: float64
```

Downsampling

`resample` takes a string saying which period to group into, and then a verb saying what to do with each period - exactly like `groupby`.

Code	Period
`"D"`	day
`"W"`	week
`"ME"`	month end
`"QE"`	quarter end
`"YE"`	year end

The aggregation function `.last()` returns the closing level of the period.

In [31]:
```
print("daily rows:  ", len(prices))
print("weekly rows: ", len(prices.resample("W").last()))
print("monthly rows:", len(prices.resample("ME").last())) # month end
print("yearly rows: ", len(prices.resample("YE").last())) # year end
```

```
daily rows:   13842
weekly rows:  2866
monthly rows: 659
yearly rows:  55
```

13 842 daily observations become 55 annual ones.

Loading [MathJax]/extensions/Safe.js

In [32]:
```
annual = prices.resample("YE").last()

annual.head(3).round(1)
```

Out[32]:
```
Date
1971-12-31    114.1
1972-12-31    133.7
1973-12-31     92.2
Freq: YE-DEC, Name: NASDAQ, dtype: float64
```

The verb matters and is yours to choose: `.last()` for a closing level, `.mean()` for an average level, `.max()` for the peak, `.sum()` for a quantity like traded volume or rainfall. Summing a *price* would be meaningless, but pandas will do it happily if you ask.

Because the result is an ordinary Series indexed by date, the transformation methods from earlier work on it directly.

In [33]:
```
annual_return = annual.pct_change() * 100

print("worst years:")
print(annual_return.sort_values().head(3).round(1))
print()
print("best years:")
print(annual_return.sort_values(ascending=False).head(3).round(1))
```

```
worst years:
Date
2008-12-31   -40.5
2000-12-31   -39.3
1974-12-31   -35.1
Name: NASDAQ, dtype: float64

best years:
Date
1999-12-31    85.6
1991-12-31    56.8
2003-12-31    50.0
Name: NASDAQ, dtype: float64
```

2008 and 2000, the financial crisis and the dot-com crash. And 1999, the year before the dot-com crash, up 86%.

Upsampling

Going the other way asks for rows that do not exist in the data, and this is where `resample` shows what it really is. Ask for **every calendar day**.

In [34]:
```
daily = prices.resample("D").last()

print("trading days in the file:", len(prices))
print("calendar days produced: ", len(daily))
print("of which empty:         ", daily.isna().sum())
```

Loading [MathJax]/extensions/Safe.js

```
print()
print(daily.loc["2020-03-05":"2020-03-10"].round(1))
```

```
trading days in the file: 13842
calendar days produced:  20053
of which empty:          6211

Date
2020-03-05    8738.6
2020-03-06    8575.6
2020-03-07       NaN
2020-03-08       NaN
2020-03-09    7950.7
2020-03-10    8344.2
Freq: D, Name: NASDAQ, dtype: float64
```

20 053 calendar days from 13 842 trading days, and **6 211 of them empty**. Saturday 7 March and Sunday 8 March 2020 are `NaN` because no trading happened - and those rows now exist, which they did not before.

That is the point of `resample`:

> **`resample` builds its periods out of the calendar, not out of the rows you happen to have.**

A gap in the data becomes a visible `NaN` rather than silently disappearing. If you want the gaps filled, that is a separate decision and you make it yourself.

In [35]:
```
print("empty after ffill:", prices.resample("D").ffill().isna().sum()) #repl
```

```
empty after ffill: 0
```

`resample` or `groupby`?

You could imagine doing the monthly figures with `groupby` on `.dt.month` instead. Try it.

In [36]:
```
len(prices.groupby(prices.index.month).mean())
```

Out[36]: 12

In [37]:
```
len(prices.resample("ME").mean()) # more rows because it also groups by year
```

Out[37]: 659

In [38]:
```
# We can do this with groupby as well, like this:
len(prices.groupby([prices.index.month, prices.index.year]).mean())
```

Out[38]: 659

Twelve rows against 659. `.dt.month` returns the number 1 for **every January in the dataset**, so those groups mix January 1971 with January 2025 - a 55-year span over

Loading [MathJax]/extensions/Safe.js

which the index went from 100 to 23 419. The average of that is not a fact about anything.

The twelve rows come from the key, not from `groupby`: `.dt.month` gives every January the number 1, whichever year it is in. Group on the year and the month together and `groupby` gives 659 rows too, with the same numbers as `resample`. So for many questions both work. The choice comes down to whether you are **grouping by labels** or **changing the frequency of a time series**.

Use `groupby` to split rows by values, including date parts like "every January" or "every Monday". Use `resample` when you want a time series at a different frequency, such as daily to weekly or monthly to daily, with every period in the calendar present.

	`groupby`	`resample`
Purpose	Splitting rows by distinct values or categories	Changing the frequency of a time series, coarser (downsampling) or finer (upsampling)
Works on	Any column: strings, numbers, dates	A series with dates as its index
Periods with no rows	Left out. A group with no data does not appear in the result	Kept. The row is created from the calendar, and shows as `NaN` for `.mean()` or `.last()`, and `0` for `.sum()` or `.count()`
Dates	Treated as labels: the year 2001 or month 1 is just a value to group on	Treated as time: it knows weeks, month ends, quarters and multiples of them, like `"2W"`

Your turn

Starting from:

```
nasdaq = pd.read_csv("../data/NASDAQ.csv")
nasdaq["Date"] = pd.to_datetime(nasdaq["Date"], format="%Y-
%m-%d")
prices = nasdaq.set_index("Date").sort_index()["NASDAQ"]
```

Resample the series to **quarter** ends, taking the closing level of each quarter, and report how many quarters the index ended lower than the quarter before.

In [39]:
```
nasdaq = pd.read_csv("../data/NASDAQ.csv")
nasdaq["Date"] = pd.to_datetime(nasdaq["Date"], format="%Y-%m-%d")
prices = nasdaq.set_index("Date").sort_index()["NASDAQ"]

quarterly = prices.resample("QE").last()

(quarterly.diff() < 0).sum()
```

Loading [MathJax]/extensions/Safe.js

Combining tables

Everything so far has been one file at a time. Real work is rarely one file: a year per file, a country per file, one file from each of ten colleagues - or, as here, the measurements in one file and the labels that explain them in another.

There are two ways to put tables together, and which you want depends on what the second table adds:

- `concat` adds **rows**: same columns, more observations.
- `merge` adds **columns**: same observations, more variables.

`concat`: stacking

`pd.concat` takes a **list** of DataFrames and returns one.

In [40]:
```
north = pd.DataFrame({
    "country": ["Norway", "Sweden", "Denmark"],
    "co2_pc": [7.5, 3.4, 4.6],
})

south = pd.DataFrame({
    "country": ["Spain", "Italy"],
    "co2_pc": [5.0, 5.4],
})

stacked = pd.concat([north, south])

stacked
```

Out[40]:

	country	co2_pc
0	Norway	7.5
1	Sweden	3.4
2	Denmark	4.6
0	Spain	5.0
1	Italy	5.4

Five rows, as expected. But look down the left-hand side: **0, 1, 2, 0, 1**. `concat` stacked the indexes too, so two different rows are both labeled 0 - and the index is what pandas aligns on, so a duplicated index quietly breaks `.loc` and everything built on it.

In [41]:
```
stacked.loc[0]
```

Loading [MathJax]/extensions/Safe.js

Out[41]:

	country	co2_pc
0	Norway	7.5
0	Spain	5.0

Two rows returned for one label. The fix is `reset_index` with the `drop` parameter - these row numbers mean nothing, so throw them away rather than keeping them as a column.

In [42]:
```
stacked = pd.concat([north, south]).reset_index(drop=True)

stacked
```

Out[42]:

	country	co2_pc
0	Norway	7.5
1	Sweden	3.4
2	Denmark	4.6
3	Spain	5.0
4	Italy	5.4

If the tables do not have quite the same columns, `concat` keeps all of them and fills the gaps with `NaN` rather than refusing. That is convenient, and worth checking rather than trusting: a column of `NaN` you did not expect usually means two files disagree about a column name - `co2_pc` in one and `CO2_pc` in the other - and `concat` will not tell you.

> 📝 **Note:** `pd.concat([a, b], axis=1)` glues tables side by side instead, matching on the

index. It is occasionally right and usually not: when you want columns from another table, what you almost always want is a merge.

Duplicates

Stacking files together is the commonest way to end up with the same row twice - a file listed twice in a folder, a cell run twice, two colleagues who both sent you January.

`.duplicated()` gives one `True` or `False` per row, marking rows identical to one seen earlier. It is a boolean mask, so summing it counts them, and `.drop_duplicates()` removes them.

Loading [MathJax]/extensions/Safe.js

```
pd.DataFrame({
    "station": ["Oslo", "Bergen", "Oslo", "Tromsø", "Bergen"],
```

```
    "year": [2023, 2023, 2023, 2023, 2023],
    "temp": [6.9, 8.4, 6.9, 3.1, 8.4],
})

print("duplicate rows:", readings.duplicated().sum())
readings.drop_duplicates()
```

```
duplicate rows: 2
```

Out[43]:

	station	year	temp
0	Oslo	2023	6.9
1	Bergen	2023	8.4
3	Tromsø	2023	3.1

Rows 2 and 4 repeated rows 0 and 1 exactly, and dropping them lost nothing, because the duplicates **agreed**.

Here is the case that matters.

In [44]:
```
readings_2 = pd.DataFrame({
    "station": ["Oslo", "Bergen", "Oslo", "Tromsø"],
    "year": [2023, 2023, 2023, 2023],
    "temp": [6.9, 8.4, 7.4, 3.1],
})

print("duplicate rows:", readings_2.duplicated().sum())
readings_2
```

```
duplicate rows: 0
```

Out[44]:

	station	year	temp
0	Oslo	2023	6.9
1	Bergen	2023	8.4
2	Oslo	2023	7.4
3	Tromsø	2023	3.1

Zero duplicates, and Oslo is still in there twice - with two different temperatures. No row is a copy of another, so `.duplicated()` is right to say nothing.

To ask "is any station listed twice?", say which columns identify a row, using `subset`.

In [45]:
```
print("repeated station-year keys:", readings_2.duplicated(subset=["station"

readings_2.drop_duplicates(subset=["station", "year"])
```

```
repeated station-year keys: 1
```

Loading [MathJax]/extensions/Safe.js

Out[45]:

	station	year	temp
0	Oslo	2023	6.9
1	Bergen	2023	8.4
3	Tromsø	2023	3.1

> ⚠️ **Warning:** An exactly duplicated row is a mistake, and dropping it loses nothing. A repeated **key** with conflicting values is a question about your data - which figure is right, and why are there two? `drop_duplicates(subset=["station", "year"])` silently keeps 6.9 and discards 7.4 for no better reason than that it came first. Find out before you drop.

Your turn

Starting from:

```
info = pd.read_csv("../data/country_info.csv")
```

This lookup table should have exactly one row per country. Check both things that could be wrong with it: how many rows are exact duplicates, and how many `code` values appear more than once. Print both counts.

In [46]:
```
info = pd.read_csv("../data/country_info.csv")

info.duplicated().sum()
```

Out[46]:
```
0
```

In [47]:
```
info.duplicated(subset=["code"]).sum()
```

Out[47]:
```
0
```

`merge`: columns from another table

`merge` matches rows in one table against rows in another on a shared value called a **key**.

Here is the second file - the one that will finally let us fix the total in CO2 emissions.

In [48]:
```
info = pd.read_csv("../data/country_info.csv")

print(info.shape)
info.head(3)
```

Loading [MathJax]/extensions/Safe.js

(295, 4)

Out[48]:

	name	code	region	incomeLevel
0	Afghanistan	AFG	Middle East, North Africa, Afghanistan & Pakistan	Low income
1	Africa	AFR	Aggregates	Aggregates
2	Africa Eastern and Southern	AFE	Aggregates	Aggregates

In [49]:
```
info["region"].value_counts()
```

Out[49]:
```
region
Aggregates                                    78
Europe & Central Asia                         58
Sub-Saharan Africa                            48
Latin America & Caribbean                     42
East Asia & Pacific                           37
Middle East, North Africa, Afghanistan & Pakistan    23
South Asia                                     6
North America                                  3
Name: count, dtype: int64
```

295 rows, one per entity: a `name`, a three-letter `code`, a `region` and an `incomeLevel`. And there is the column we need - the World Bank marks its own groupings with the region `"Aggregates"`.

First, tidy the column names with `rename`

`incomeLevel` is camelCase, and everything in this course is snake_case. `rename` takes a dictionary of old name to new name and returns a new table.

In [50]:
```
info = info.rename(columns={"incomeLevel": "income_level"})

info.columns
```

Out[50]:
```
Index(['name', 'code', 'region', 'income_level'], dtype='object')
```

`rename` is worth knowing well beyond tidiness. It is how you make two tables agree about what a column is called, which matters here because our two tables name the same thing differently: the emissions file calls it `country`, the lookup file calls it `name`.

That gives two ways to merge on it - rename one side so the names match, or tell `merge` about both names with `left_on` and `right_on`:

```
info.rename(columns={"name": "country"})     # then merge on="country"
co2.merge(info, left_on="country", right_on="name")   # or say both
```

Loading [MathJax]/extensions/Safe.js

Use `rename` when the mismatch is a nuisance you want gone for good, and `left_on` / `right_on` when it is a one-off. We will use both below.

Look at the keys before you use them

A merge matches keys **exactly**. Not roughly, not case-insensitively: exactly. And text keys arrive dirty far more often than anybody expects, so it is worth two minutes looking first.

Every string method from the first half of this course - `.strip()`, `.lower()`, `.replace()`, `.startswith()` - is available on a whole column at once through the `.str` **accessor**. It is vectorized, exactly like the arithmetic on columns we did last time: no loop, one expression.

In [51]:
```
print(info["name"].str.lower().head(3))
print()
print("names with whitespace to strip:", (info["name"] != info["name"].str.s
```

```
0                   afghanistan
1                        africa
2    africa eastern and southern
Name: name, dtype: object

names with whitespace to strip: 4
```

Four of the 295 names have leading or trailing whitespace, exactly as the World Bank publishes them. `"Sub-Saharan Africa "` and `"Sub-Saharan Africa"` look identical on screen and are two different strings.

`code` does not have the problem. Both facts matter, and we use both below.

Merging

`.merge()` is called on one table and given the other, plus `on=` naming the shared column.

In [52]:
```
panel = co2.merge(info[["code", "region", "income_level"]], on="code", how="

print("before:", co2.shape)
print("after: ", panel.shape)
panel[["country", "year", "co2_total", "region", "income_level"]].head(3)
```

```
before: (6240, 12)
after:  (6240, 14)
```

Loading [MathJax]/extensions/Safe.js

Out[52]:

	country	year	co2_total	region	income_level
0	Afghanistan	2000	1.0093	Middle East, North Africa, Afghanistan & Pakistan	Low income
1	Afghanistan	2001	0.9402	Middle East, North Africa, Afghanistan & Pakistan	Low income
2	Afghanistan	2002	0.9388	Middle East, North Africa, Afghanistan & Pakistan	Low income

Same number of rows, two extra columns. `how="left"` says *keep every row of the left-hand table, whether or not it found a match*, and it is the right choice here: we are decorating the emissions data, not filtering it.

The four kinds of join differ only in which unmatched rows survive:

`how=`	Keeps
`"inner"`	only rows that matched on **both** sides - the default, and it deletes silently
`"left"`	every row of the left table; unmatched right-hand columns become `NaN`
`"right"`	every row of the right table
`"outer"`	everything from both sides

Prefer `"left"` when one table is your data and the other is a lookup. Prefer `"inner"` only when you genuinely want the intersection - and even then, count what it cost you.

A merge can make your table bigger

If a key appears **more than once** in the right-hand table, every match produces a row.

In [53]:
```
countries = pd.DataFrame({
    "code": ["NOR", "SWE"],
    "name": ["Norway", "Sweden"],
})

visits = pd.DataFrame({
    "code": ["NOR", "NOR", "NOR", "SWE"],
    "year": [2021, 2022, 2023, 2023],
})

countries.merge(visits, on="code", how="left")
```

Loading [MathJax]/extensions/Safe.js

Out[53]:

	code	name	year
0	NOR	Norway	2021
1	NOR	Norway	2022
2	NOR	Norway	2023
3	SWE	Sweden	2023

Two rows in, four rows out, from a **left** join. Nothing is wrong: Norway genuinely has three matching rows. But if you expected one row per country and got this, every average you compute afterwards is now weighted by how many times each country happened to appear.

A merge can lose rows and a merge can gain rows, and neither one raises anything. So you check.

Validating a merge

Three checks, in increasing order of how much work they save you.

1. Count the rows. The cheapest thing in pandas, and the one that catches most of it. Below we deliberately merge on the dirty key to see what it costs - and because the key is called `country` in one table and `name` in the other, we name each side with `left_on` and `right_on`.

In [54]:
```
merged_on_name = co2.merge(
    info[["name", "region"]],
    left_on="country",
    right_on="name",
    how="inner",
)

print("rows before:", len(co2))
print("rows after: ", len(merged_on_name))
print("lost:       ", len(co2) - len(merged_on_name))
```

```
rows before: 6240
rows after:  6192
lost:        48
```

48 rows gone, deleted by the inner join without comment. 48 out of 5 904 is under one percent - far too small to notice in a `.head()`, more than enough to be wrong about.

2. `indicator=True` says which side each row came from. Counting tells you *that* something went missing; this tells you *what*. Done as a **left** join, nothing is deleted and a column called `_merge` records what happened to each row.

```
co2.merge(
    info[["name", "region"]],
```

Loading [MathJax]/extensions/Safe.js

```
    left_on="country",
    right_on="name",
    how="left",
    indicator=True,
)

checked["_merge"].value_counts()
```

Out[55]:
```
_merge
both          6192
left_only       48
right_only       0
Name: count, dtype: int64
```

5 856 matched, 48 did not. **This is the diagnostic pattern worth remembering: when a merge surprises you, redo it as a left join with `indicator=True` and look at the rows that failed.**

In [56]:
```
unmatched = checked[checked["_merge"] == "left_only"]["country"].unique()

print(list(unmatched))
```

```
['Latin America & Caribbean', 'Sub-Saharan Africa']
```

Two entity names, 24 years each. And they are plainly present in the other file - you can see `Sub-Saharan Africa` in it with your own eyes. So look at the names in the lookup file that change when whitespace is stripped, and print them as a **list**: a list shows each string in quotes, so a space at the end becomes visible.

In [57]:
```
info[info["name"] != info["name"].str.strip()]["name"].tolist()
```

Out[57]:
```
['IDA countries in Sub-Saharan Africa classified as fragile situations ',
 'IDA countries in Sub-Saharan Africa not classified as fragile situations
',
 'Latin America & Caribbean ',
 'Sub-Saharan Africa ']
```

There it is: a single trailing space, invisible in every display pandas ever produced, and it cost 48 rows. (The two IDA groupings have the same problem, but they are not in the emissions file, so here they cost nothing.) `.str.strip()` on both sides would fix it; `code` avoids it entirely. On a file with no code column, stripping both keys before merging is the standard defense.

3. `validate=` refuses to run a merge you did not mean. The first two checks happen *after* the damage. This one happens before: you state what shape the merge is supposed to be, and pandas raises if it is not.

- `"one_to_one"` - the key is unique in both tables
- `"many_to_one"` - repeated on the left, unique on the right; the usual shape for a lookup table
- `"one_to_many"` - the other way round

Loading [MathJax]/extensions/Safe.js

Ours is many-to-one: 24 rows per country on the left, one row per country on the right.

In [58]:
```
panel = co2.merge(
    info[["code", "region", "income_level"]],
    on="code",
    how="left",
    validate="many_to_one",
)

print("validated, rows:", len(panel))
```

```
validated, rows: 6240
```

In [59]:
```
# MergeError
co2.merge(info[["code", "region"]], on="code", how="left", validate="one_to_
```

Loading [MathJax]/extensions/Safe.js

```
---------------------------------------------------------------------------
MergeError                                Traceback (most recent call last)
Cell In[59], line 2
      1 # MergeError
----> 2 co2.merge(info[["code", "region"]], on="code", how="left", validate
="one_to_one")

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/frame.py:10832,
in DataFrame.merge(self, right, how, on, left_on, right_on, left_index, righ
t_index, sort, suffixes, copy, indicator, validate)
  10813 @Substitution("")
  10814 @Appender(_merge_doc, indents=2)
  10815 def merge(
   (...)
  10828     validate: MergeValidate | None = None,
  10829 ) -> DataFrame:
  10830     from pandas.core.reshape.merge import merge
> 10832     return merge(
  10833         self,
  10834         right,
  10835         how=how,
  10836         on=on,
  10837         left_on=left_on,
  10838         right_on=right_on,
  10839         left_index=left_index,
  10840         right_index=right_index,
  10841         sort=sort,
  10842         suffixes=suffixes,
  10843         copy=copy,
  10844         indicator=indicator,
  10845         validate=validate,
  10846     )

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/reshape/merge.p
y:170, in merge(left, right, how, on, left_on, right_on, left_index, right_i
ndex, sort, suffixes, copy, indicator, validate)
    155     return _cross_merge(
    156         left_df,
    157         right_df,
   (...)
    167         copy=copy,
    168     )
    169 else:
--> 170     op = _MergeOperation(
    171         left_df,
    172         right_df,
    173         how=how,
    174         on=on,
    175         left_on=left_on,
    176         right_on=right_on,
    177         left_index=left_index,
    178         right_index=right_index,
    179         sort=sort,
    180         suffixes=suffixes,
    181         indicator=indicator,
    182         validate=validate,
```

Loading [MathJax]/extensions/Safe.js

```
    183     )
    184     return op.get_result(copy=copy)

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/reshape/merge.py:813, in _MergeOperation.__init__(self, left, right, how, on, left_on, right_on, left_index, right_index, sort, suffixes, indicator, validate)
    809 # If argument passed to validate,
    810 # check if columns specified as unique
    811 # are in fact unique.
    812 if validate is not None:
--> 813     self._validate_validate_kwd(validate)

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/reshape/merge.py:1653, in _MergeOperation._validate_validate_kwd(self, validate)
   1648     raise MergeError(
   1649         "Merge keys are not unique in either left "
   1650         "or right dataset; not a one-to-one merge"
   1651     )
   1652 if not left_unique:
-> 1653     raise MergeError(
   1654         "Merge keys are not unique in left dataset; not a one-to-one merge"
   1655     )
   1656 if not right_unique:
   1657     raise MergeError(
   1658         "Merge keys are not unique in right dataset; not a one-to-one merge"
   1659     )

MergeError: Merge keys are not unique in left dataset; not a one-to-one merge
```

`Merge keys are not unique in left dataset` - because of course they are not, there are 24 rows per country. That is the error doing its job: it caught a false belief about the data before any number came out of it.

> 💡 **Tip:** Put `validate=` on every merge you write. It costs one argument and turns a

whole class of silent wrongness into an exception, which is the best trade available in pandas.

The payoff

We now have everything needed to finish cleaning the emissions data by dropping the aggregates.

In [60]:
```
countries_only = panel[panel["region"] != "Aggregates"]

print("entities:", panel["code"].nunique(), "->", countries_only["code"].nur
print("rows:    ", len(panel), "->", len(countries_only))
```

Loading [MathJax]/extensions/Safe.js

```
entities: 260 -> 217 countries
rows:     6240 -> 5208
```

In [61]:
```
total_2023 = countries_only[countries_only["year"] == 2023]["co2_total"].sum
world_2023 = panel[(panel["country"] == "World") & (panel["year"] == 2023)][

print(f"sum over 203 countries: {total_2023:10,.0f}")
print(f"the World Bank's World: {world_2023:10,.0f}")
```

```
sum over 203 countries:     37,483
the World Bank's World:     39,113
```

37 483 against 39 113 - about four percent short, instead of out by a factor of eight.

The gap that remains is explicable rather than mysterious: 43 entities were aggregates, 14 more countries have no emissions figure at all and were dropped when the file was loaded, and the World Bank's `World` row covers territories our 203 do not. A number that is close for reasons you can name is a much better place to be than one that matches exactly by luck.

The region column also makes it possible to group on two keys at once: pass a **list** of column names instead of one.

In [62]:
```
countries_only.groupby(["region", "year"])["co2_total"].sum().head(3)
```

Out[62]:
```
region               year
East Asia & Pacific  2000    6681.3359
                     2001    6907.0830
                     2002    7308.1604
Name: co2_total, dtype: float64
```

Two labels down the left-hand side instead of one. That is a **MultiIndex** - the same idea as before, with the group being a *pair* rather than a single value. It is worth knowing it exists; it is usually not worth wrestling with, and `reset_index()` turns it into two ordinary columns, which is what most code wants.

In [63]:
```
regional = countries_only.groupby(["region", "year"])["co2_total"].sum().res

regional[regional["year"] == 2023].round(0)
```

Loading [MathJax]/extensions/Safe.js

Out[63]:

	region	year	co2_total
23	East Asia & Pacific	2023	17193.0
47	Europe & Central Asia	2023	6069.0
71	Latin America & Caribbean	2023	1748.0
95	Middle East, North Africa, Afghanistan & Pakistan	2023	3242.0
119	North America	2023	5186.0
143	South Asia	2023	3174.0
167	Sub-Saharan Africa	2023	871.0

Your turn

Starting from:

```
co2 = pd.read_csv("../data/co2_emissions.csv")
info = pd.read_csv("../data/country_info.csv")
```

Merge the two tables on `code` with a left join and `validate=` set to the right shape, drop the aggregates, and display the ten countries with the highest total emissions in 2023. Print the row count before and after the merge.

In [64]:

```
co2 = pd.read_csv("../data/co2_emissions.csv")
info = pd.read_csv("../data/country_info.csv")

panel = co2.merge(info[["code", "region"]], on="code", how="left", validate=
panel = panel[panel["region"] != "Aggregates"]
panel.sort_values(by="co2_total", ascending=False).head(10)
```

Loading [MathJax]/extensions/Safe.js

Out[64]:

	country	code	year	co2_total	population	urban	gdp_pc	electricity	ag
1127	China	CHN	2023	13021.2420	1410710000	65.530	12951.18	100.0	
1125	China	CHN	2021	12551.8645	1412360000	64.721	12887.44	100.0	
1126	China	CHN	2022	12518.6844	1412175000	65.218	12970.61	100.0	
1124	China	CHN	2020	11964.1285	1411100000	63.523	10627.46	100.0	
1123	China	CHN	2019	11813.0582	1407745000	62.710	10342.90	100.0	
1122	China	CHN	2018	11527.5117	1402760000	61.500	10085.66	100.0	
1121	China	CHN	2017	10999.4188	1396215000	60.240	8979.68	100.0	
1118	China	CHN	2014	10881.1042	1371860000	55.750	7781.07	100.0	
1120	China	CHN	2016	10773.7258	1387790000	58.840	8254.87	100.0	
1117	China	CHN	2013	10760.4300	1363240000	54.490	7147.04	100.0	

In [65]:
```
highest_in_2023 = panel[panel["year"] == 2023].sort_values("co2_total", asce
highest_in_2023
```

Loading [MathJax]/extensions/Safe.js

Out[65]:

	country	code	year	co2_total	population	urban	gdp_pc	electricity
1127	China	CHN	2023	13021.2420	1410710000	65.530	12951.18	100.0
5975	United States	USA	2023	4618.2675	336755052	80.072	82586.78	100.0
2639	India	IND	2023	3014.5226	1438069596	35.068	2434.45	99.5
4751	Russian Federation	RUS	2023	1948.3024	143826130	74.981	13987.00	100.0
2855	Japan	JPN	2023	1002.4382	124516650	92.083	35215.00	100.0
2687	Iran, Islamic Rep.	IRN	2023	816.1330	90608707	76.676	5049.30	100.0
2663	Indonesia	IDN	2023	772.5618	281190067	58.118	4876.30	99.4
4871	Saudi Arabia	SAU	2023	635.4338	33702731	84.296	36156.86	100.0
2999	Korea, Rep.	KOR	2023	590.3650	51712619	81.165	35674.10	100.0
2111	Germany	DEU	2023	589.6596	83287273	81.903	54776.77	100.0

Per person or per country?

One more question the regions make possible. What are a region's emissions **per person**?

Not the average of its countries' figures - that would let Luxembourg count as much as India. The region's total emissions divided by the region's total population. So: sum both columns within each region, then divide.

In [66]:
```
year_2023 = countries_only[countries_only["year"] == 2023]

region_totals = year_2023.groupby("region")[["co2_total", "population"]].sum
region_totals["co2_pc"] = region_totals["co2_total"] * 1_000_000 / region_to

region_totals.round(2)
```

Loading [MathJax]/extensions/Safe.js

Out[66]:

region	co2_total	population	co2_pc
East Asia & Pacific	17192.72	2361068202	7.28
Europe & Central Asia	6069.08	924805070	6.56
Latin America & Caribbean	1748.28	657616519	2.66
Middle East, North Africa, Afghanistan & Pakistan	3242.42	797801454	4.06
North America	5185.62	376868838	13.76
South Asia	3173.88	1662580579	1.91
Sub-Saharan Africa	871.01	1258809472	0.69

In [67]:
```
comparison = pd.DataFrame({
    "per_person": region_totals["co2_pc"],
    "mean_of_countries": year_2023.groupby("region")["co2_pc"].mean(),
})

comparison.round(2)
```

```
---------------------------------------------------------------------------
KeyError                                  Traceback (most recent call last)
Cell In[67], line 3
      1 comparison = pd.DataFrame({
      2     "per_person": region_totals["co2_pc"],
----> 3     "mean_of_countries": year_2023.groupby("region")["co2_pc"].mean
(),
      4 })
      6 comparison.round(2)

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/groupby/generi
c.py:1951, in DataFrameGroupBy.__getitem__(self, key)
   1944 if isinstance(key, tuple) and len(key) > 1:
   1945     # if len == 1, then it becomes a SeriesGroupBy and this is actua
lly
   1946     # valid syntax, so don't raise
   1947     raise ValueError(
   1948         "Cannot subset columns with a tuple with more than one eleme
nt. "
   1949         "Use a list instead."
   1950     )
-> 1951 return super().__getitem__(key)

File /opt/anaconda3/lib/python3.12/site-packages/pandas/core/base.py:244, in
SelectionMixin.__getitem__(self, key)
    242 else:
    243     if key not in self.obj:
--> 244         raise KeyError(f"Column not found: {key}")
    245     ndim = self.obj[key].ndim
    246     return self._gotitem(key, ndim=ndim)

KeyError: 'Column not found: co2_pc'
```

Loading [MathJax]/extensions/Safe.js

Mostly close, and then one row that is not: the Middle East and North Africa comes out at **4.09 per person against an unweighted mean of 9.21**. Both are arithmetically correct. The unweighted one is dragged up by Qatar, Bahrain and Kuwait - small populations, enormous emissions per head - each counting exactly as much as Pakistan's 248 million people.

Which one is right depends on the question: *"what does a typical country here look like?"* wants one, *"how much does a typical person here emit?"* wants the other. What matters is knowing that you chose.


And a look at what it bought us

Plotting is next time. But one line is worth it here, because it shows what all this work was for: a table nobody could total correctly at the start of the session, grouped into seven regions and followed across 24 years.

In [68]:
```
east_asia = regional[regional["region"] == "East Asia & Pacific"]

east_asia.plot(x="year", y="co2_total", title="East Asia & Pacific: total CO
```

Out[68]:
```
<Axes: title={'center': 'East Asia & Pacific: total CO₂, Mt'}, xlabel='yea
r'>
```



Loading [MathJax]/extensions/Safe.js

Worth being clear about how much of this session that one line depends on. The figure is only correct because the aggregates are gone, and they are only gone because the merge used a key that matched, and we only know the key matched because we counted the rows. Every silent failure in this notebook would have produced a chart that looked exactly as convincing as this one.

We come back to how to make figures worth showing somebody.

Additional resources

- Group by: split-apply-combine - the official account, including the full list of aggregation and transformation methods
- Merge, join, concatenate and compare - every way of putting two tables together, with diagrams
- Time series and date functionality - long, but the tables of `.dt` properties and of `resample` frequency codes are worth bookmarking
- strftime.org - a one-page reference for every date format code
- SKL401 - lesson 3.7 covers grouping and aggregation, 3.8 joining, and 3.9 dates

Next week: turning these tables into figures - what makes a chart readable, and how to write one function that draws the same plot for any country you hand it.

Loading [MathJax]/extensions/Safe.js