

Xolotl: An Intuitive and Approachable Neuron & Network Simulator in MATLAB

Alec Hoyland^{1†}, Srinivas Gorur-Shandilya^{1†}, and Eve Marder^{1*}

¹ *Volen Center and Biology Department
Brandeis University
Waltham, MA 02454
USA*

[†] *These authors have equally contributed to this article.*

Correspondence*:
Srinivas Gorur-Shandilya
Marder Lab
srinivas@brandeis.edu

An Intuitive Neuronal Simulator

2 ABSTRACT

`xolotl` is a free and open-source neuronal simulator written in C++ with MATLAB wrappers. Biophysically-detailed models of networks can be designed efficiently using an intuitive language tightly coupled to the object-based architecture of the underlying C++ code. Models can be specified by adding conductances to compartment objects. The structure is modular, serialized, and searchable, permitting high-level programmatic control over nearly all features of the models. C++ templates are provided for developing new conductances, compartments, and integration schemata. It also includes a customizable graphical user interface (GUI) for rapid prototyping and hand-tuning conductances in real-time. The modular structure and accessibility to all parameters, variables, and dynamics of the model network in MATLAB facilitate rapid construction and assessment of model networks. `xolotl` is freely available at <https://github.com/marderlab/xolotl>. This tool provides straightforward implementation and fast simulation of neuronal models while permitting full control over every aspect of the network and integration.

Keywords: simulator, MATLAB, C++, conductance-based, neuron, network, pedagogy

1 INTRODUCTION

Conductance-based models are the simplest biophysical representation of an electrically-excitable cell (Hodgkin and Huxley 1952a). Modeling studies now contribute significantly to mainstream research in small-circuit networks (E. Marder and Abbott 1995; Astrid A. Prinz 2006; Astrid A. Prinz 2010). Additionally, conductance-based models provide an approachable formalism based in electrophysiology for understanding salient principles of neuroscience. To this end, we have developed `xolotl` (<https://github.com/marderlab/xolotl>), a fast single-compartment and multi-compartment simulator in C++ with MATLAB wrappers. Written with an emphasis on ease-of-use, `xolotl` can simulate single-compartment conductance-based models, networks of these, and detailed multi-compartment models. `xolotl` exploits a novel automatic type system, `cpplab`, which binds MATLAB code to C++

header files, creating objects and classes *ad libitum* in MATLAB which reflect the underlying object-oriented code. `xolotl` implements `cpplab` to represent the nested structure of conductance-based models, and exploits the computational efficiency of the low-level programming language to quickly integrate models. For this reason, models can be implemented entirely in MATLAB with a few lines of code.

Models are specified in MATLAB by a nested structure. The `xolotl` object contains compartments which themselves contain conductances. Synapses belong to the `xolotl` object and connect compartments together. The high-level specification supports arbitrarily large network and multi-compartment morphologies.

The software has been implemented in MATLAB due to its ease-of-use and popularity among neuroscientists. `cpplab` provides a powerful backend for specifying and integrating models without relying on the significantly slower and limiting MATLAB `codegen`. While automated C++ transpiling from MATLAB using the proprietary `codegen` can drastically improve performance over loops through strong typing and memory pre-allocation, supervenience of MATLAB over C++ prevents efficient use of low-level features, such as passing by reference and object-oriented programming. Minimal experience with MATLAB is required to use `xolotl`, and all equations and integration methods are provided transparently to the end user. No string parsing of equations is required (Sherfey et al. 2018; Stimberg, D F M Goodman, et al. 2014; Stimberg, D F Goodman, et al. 2013)

`xolotl` comes packaged with visualization functions and a graphical user interface (GUI) for real-time manipulation of model parameters. Plotting of voltage, intracellular calcium, conductance gating functions, and time constants is provided by built-in `xolotl` methods. The GUI permits real-time tuning of any network parameters using numerical sliders in a graphical interface which displays the resultant membrane potential and intracellular calcium traces. The ease-of-use of these tools lends them to pedagogical applications and rapid exploration of toy models. This tool aims to simplify the investigation of dynamics of complex neural network models, facilitate collaborative modeling, and complement other tools being developed in the neuroinformatics community.

2 DESIGN GOALS

`xolotl` is designed to be easy-to-use without sacrificing speed.

The software has been designed in MATLAB due to its popularity among neuroscientists for pedagogy and research. `xolotl` capitalizes on MATLAB's straightforward structure array syntax to permit rapid prototyping and experimentation, especially for small neuronal networks of complex models. Parameters of conductances, neuronal compartments, and simulations may all be edited in the structure before any calls to integration functions. The underlying code is written in C++ for speed and memory optimization, and while models can indeed be integrated using the compiled binary, symbolic manipulations can be readily performed in MATLAB without ever touching the foundational code.

2.1 FEATURES

MATLAB provides a high level programmatic and graphical interface for implementing, manipulating, and visualizing models without sacrificing the enhancements of the underlying C++ code.

Modular structure. Models are specified by adding compartments and synapses to the `xolotl` object. Conductances are added to compartments and controllers can be added to conductances. This modular structure recapitulates the biophysics of the Hodgkin-Huxley formalism and obviates the need to explicitly write out equations, which in `xolotl` are contained within the conductance header files.

66 *Interface between C++ and MATLAB.* `xolotl` relies on `cpplab` constructions, which allow the user
 67 to exploit the efficiency of low-level C++ code. MATLAB treats `cpplab` objects as fully-typed variables
 68 allowing for symbolic manipulation using only the high-level programming language and graphical inter-
 69 faces. `xolotl` is fast because all time-intensive code is written in C++. While automated C++ transpiling
 70 from MATLAB using the proprietary `codegen` can drastically improve performance over loops through
 71 strong typing and memory pre-allocation, supervenience of MATLAB over C++ prevents efficient use of
 72 low-level features, such as passing by reference and object-oriented programming. C++ provides speed
 73 improvements beyond the benefits of translating MATLAB features into low-level code. For this reason,
 74 `cpplab` has been designed to provide an interface for constructing, transpiling, and compiling C++ code
 75 to be called from within MATLAB. `xolotl` simulations are run entirely from C++ executables.

76 *Automatic and efficient compiling.* `xolotl` automatically handles transpiling and compiling MATLAB
 77 code into C++. The MD5 algorithm hashes the network to compile a new binary and MEX bridge file only
 78 if needed and to confirm that the correct binary fetched during execution.

2.2 SYNTAX

79 MATLAB can easily control the `cpplab` objects using the standard, flexible data structure notation popular
 80 in high-level scripting languages.

81 *Adding features.* The `add` function creates a compartment, conductance, or controller and affixes it as
 82 a field in the `xolotl` network structure. This function generates a MATLAB `struct` that faithfully
 83 represents the underlying C++ code. Compartments add to the `xolotl` object and conductances add to
 84 compartments. Specific properties can be specified using key-value pair arguments (e.g. Figure 1A).

85 *Finding features.* `cpplab` comes with several features which simplify the handling of complex, nested
 86 models. The `find` function acquires a cell array of all properties of the network which satisfy a search
 87 condition. For example, one can find all paths to maximal conductances within the 'HH' compartment
 88 by:

```
89         x.find('HH*gbar');
```

90 To extract a vector of the maximal conductances:

```
91         gbars = x.get('HH*gbar');
```

92 To set the maximal conductances all at once:

```
93         x.set('HH*gbar', gbars)
```

94 *Compartments.* A model neuron consists of one or more compartments, each representing a section of
 95 membrane with capacitance and surface area. Isopotential models require one compartment, whereas
 96 models with multiple neurons, units, or non-trivial morphology require multiple compartments. All
 97 specifiable properties of compartments are shown in Table 1.

98 *Synapses.* `xolotl` provides some features for generating complex models. Synapses can be added with
 99 the `connect` function. Synapses possess identifiers to presynaptic and postsynaptic compartments and
 100 default to electrical synapses. All specifiable properties of synapses are shown in Table 2. To create axons
 101 or transport chains, the `slice` function splits a compartment into n discrete segments and adds these
 102 compartments to the network connected by electrical synapses.

103 *Conductances and controllers.* All conductances contain fields for maximal conductance and reversal
 104 potential. Conductances with activation and inactivation variables include them as m and h respectively.
 105 Gating functions and their respective time constants are contained within the conductance header file.
 106 `xolotl` comes packaged with conductances from several dozen papers (Table 3).

107 *Creating custom `cpplab` objects.* `xolotl` contains template header files for producing custom con-
 108 ductances. The template contains instructions on how to design novel conductances with arbitrary
 109 specifications.

110 *Simulation.* Models are simulated in `xolotl` with the `integrate` function which outputs as time series
 111 the membrane potentials, intracellular calcium concentrations, controller states, intrinsic currents, and
 112 synaptic currents. The `integrate` function also accepts an argument which specifies injected current or
 113 clamped voltage.

114 *Numerical integration.* `xolotl` uses the exponential Euler method for single compartment models, for-
 115 ward Euler for gating variables, and a Crank-Nicholson regime for electrically-coupled compartments
 116 (Butcher 2016; Dayan and Abbott 2001; Oh and French 2006) These defaults provide a mix of speed,
 117 accuracy, and stability, and are built into the `cpplab` header files. Custom `cpplab` header files can
 118 be customized with any iterative integration method. The simulation time-resolution can be specified to
 119 target arbitrary precision, and an output time step can be selected to support automatic down-sampling for
 120 memory considerations.

121 *‘Closed-loop’ vs. ‘open-loop.’* Simulations can be run in ‘closed-loop’ mode where each simulation be-
 122 gins by resetting all dynamical variables to their initial conditions at instantiation, or ‘open-loop’ mode
 123 which begins simulation with the current network state.

124 *Using the graphical interface to manipulate parameters.* `xolotl` comes packaged with a graphical user
 125 interface for visualizing parameter changes in real-time. The `manipulate` function opens the GUI,
 126 which displays a figure plotting the membrane potential and intracellular calcium concentration of all
 127 compartments as time series, and a dialog box with customizable sliders for all parameters of the model,
 128 much like the `Manipulate` function in Wolfram Mathematica. Moving the sliders integrates the
 129 model in ‘open-loop’ mode with the new parameters. The parameters available in the sliders can be cus-
 130 tomized by passing a cell array to `manipulate`. For example, to only see sliders for maximal conductances
 131 of the HH compartment, call `x.manipulate('HH*gbar')`. Closing the GUI saves the network state
 132 of the model to the `xolotl` object. This is particularly helpful for rapid prototyping of models.

133 *Optimizing parameters.* `xolotl` can use the Global Optimization toolbox for MATLAB to optimize any
 134 accessible `xolotl` parameters. The toolbox is algorithm-agnostic and accepts any function in MATLAB
 135 with a scalar first output as the objective function. Simulations run on multi-core processors or high-
 136 performance computing clusters using the Parallel Computing toolbox.

2.3 LIMITATIONS

137 The focus on ease-of-use and speed means some features were intentionally neglected in the streamlining
 138 process.

139 *Reliance on compiled C++ code.* While MATLAB comes with robust features for compiling C and C++
 140 code, `xolotl` cannot run without C++ compilation. For users, this necessitates the additional step of
 141 setting up the `mex` compiler which can be problematical, especially for nonstandard (e.g. Arch-based
 142 Linux). Secondly, compilation adds a small amount to total processing time. Longer simulations (> 1000
 143 time-steps) minimizes this effect. Adding new conductances also requires writing some C++ code. For
 144 model conductances in the Hodgkin-Huxley formalism (Dayan and Abbott 2001; Hodgkin, Huxley, and

145 Katz 1952) adjustments consist of changing default values in a template C++ header file. Implementing a
 146 new integration scheme requires much more in-depth usage of C++.

147 *Limited to conductance-based models.* `xolotl` has been developed specifically for conductance-based
 148 models. It does not currently support rate- or current-based models.

149 *Limited numerical integration strategies.* While the exponential Euler method performs well in neuronal
 150 models (Dayan and Abbott 2001; Oh and French 2006) it may be desirable to use other methods un-
 151 der certain conditions. `xolotl` does not currently support other integration schemes for its built-in
 152 conductances, nor does the software support error-sensitive variable step-sizes ‘out-of-the-box.’

153 *Inefficient tools for handling large networks.* While `xolotl` can integrate large networks (> 1000 com-
 154 partments), `xolotl` uses string-based comprehension for labeling compartments which is suited to
 155 descriptive naming, but prohibits vector operations over compartments.

3 USAGE EXAMPLES

156 In MATLAB, users create a `xolotl` object and populate it with `cpplab`-generated objects which describe
 157 compartments, conductances, synapses, and controllers. The model is integrated with the `integrate`
 158 function where the membrane potential, intracellular calcium concentration, controller states, intrinsic
 159 currents, and synaptic currents can be outputs.

160 `xolotl` comes packaged with a library of pre-existing conductance and synapse objects which greatly
 161 simplify the task of constructing model neurons. These objects can be referenced by name and added
 162 directly to a compartment. Novel conductance dynamics can be easily written by modifying a template
 163 header file contained in the `xolotl` distribution, or designed entirely from scratch.

3.1 SIMULATING A HODGKIN-HUXLEY MODEL

164 The seminal Hodgkin-Huxley model of action potentials in the squid giant axon (Hodgkin and Huxley
 165 1952b; Hodgkin, Huxley, and Katz 1952) contains a fast inactivating sodium conductance (NaV), a non-
 166 inactivating delayed rectifier (Kd), and a passive leak current (Figure 1A). A compartment, `HH`, with
 167 membrane capacitance (C_m) and surface area (A) can be specified by Figure 1B. Network properties can
 168 be set during construction or afterwards using dot-notation in MATLAB (e.g. `x.HH.Cm`). Figure 1C shows
 169 the MATLAB command prompt after invoking the `xolotl` object `x`, displaying the hierarchical structure
 170 inherent in conductance-based treatments of neurodynamics.

171 This model was constructed using conductances from Liu et al. 1998 based on electrophysiological
 172 recordings from the lobster stomatogastric ganglion (Turrigiano, LeMasson, and E. Marder 1995) In
 173 the absence of applied positive current, the model is quiescent. When 0.2 nA is injected, the model
 174 tonically spikes (Figure 1D). The `integrate` function takes the applied current as an argument (e.g.
 175 `x.integrate(Iapp)`), so that the `xolotl` object is agnostic to integration-specific perturbations.
 176 The `plot` function generates voltage and intracellular calcium traces, where the voltage trace is colored
 177 by the dominant current. If the membrane potential is increasing, the strongest instantaneous inward cur-
 178 rent colors the trace. Conversely, if the membrane potential is decreasing, the strongest outward current
 179 colors the trace instead. Figure 1F-I display the results of the `show` function. Activation and inactivation
 180 steady-states and the voltage-dependent time constants of these gating variables describe the conductance
 181 dynamics in absence of other channel types.

3.2 PERFORMING A VOLTAGE CLAMP EXPERIMENT *IN-SILICO*

xolotl can recapitulate the results of voltage clamp experiments (Destexhe and Bal 2009; Swensen and E. Marder 2000, 2001; Turrigiano, LeMasson, and E. Marder 1995) Figure 2 displays steps in the procedure to clamp the membrane potential of a cell with delayed rectifier potassium conductance. During an *in-vitro* experiment, confounding currents would be pharmacologically-blocked and two-electrode voltage clamp used to record tail currents at fixed membrane potential (Connor and Stevens 1971a,b)

A single-compartment model with a delayed-rectifier conductance is simulated at stepped membrane potentials. The model is simulated using the `integrate` function. The second argument determines the clamped voltage and the fourth output is the current trace.

```
[V, Ca, ~, I] = x.integrate([], clamped_voltage)
```

Currents under voltage clamp approach the steady-state holding current (Figure 2D-E). The current-voltage relation is the steady-state current over the clamped voltage, and the effective conductance is the derivative of that relation (Figure 2F-G). Since the effective conductance is the product of the maximal conductance and the gating variables (Dayan and Abbott 2001; Turrigiano, LeMasson, and E. Marder 1995) and the tail current is monotonically-increasing with time under voltage clamp, the current can be represented as non-inactivating. Fitting a sigmoid to various powers yields a model for the current dynamics (Figure 2H-I). These figures describe graphically the theoretical underpinnings of current analysis through voltage clamp and can serve as an effective pedagogical tool for computational and quantitative neuroscience.

3.3 SIMULATING NETWORK MODELS

Network models in xolotl consist of compartment objects connected by synapses. Synapses are stored in a vector array as a field of the xolotl object in MATLAB. Presynaptic and postsynaptic labels indicate the connectivity of the synapse. Figure 3 implements a model of the triphasic pyloric rhythm in the stomatogastric ganglion of crustaceans. The pyloric model contains three compartments and seven synapses (Figure 3A). This structure is reciprocated in the hierarchy of the xolotl object, where conductances are contained within compartments (Figure 3B).

Representing the network in xolotl requires constructing three compartments and eight conductances in each using the `add` function.

```
x.add('AB', 'compartment', 'Cm', 10, 'A', 0.628, ...)
x.AB.add('prinz/NaV', 'gbar', 1000, 'E', 50)
...
```

Synapses are upper-level properties of the network which point between two compartments (Figure 3C). This exploits vectorized operations in MATLAB and does not require each synapse to possess a unique name. The `connect` function adds synapses to the network. The first two arguments specify the presynaptic and postsynaptic compartments. The third dictates the type of synapse. All others follow the 'keyword', value paradigm and preset parameters of the synapse.

```
x.connect('AB', 'LP', 'Chol', 'gbar', 30)
```

3.4 SIMULATING INTEGRAL CONTROL

xolotl can implement homeostatic tuning rules as integral control. The controller computes an error signal (typically a function of intracellular calcium concentration), and adjusts the conductance or synapse it controls accordingly (O'Leary et al. 2013) In xolotl, integral controllers are `cpplab` objects added to the conductance or synapse they regulate.

In a demonstration adapted from O’Leary et al. 2013, integral control changes maximal conductances to bring a neuron from quiescence into a bursting regime. Calcium sensors supervene on maximal conductance density (Figure 4) to change neuronal activity. Each conductance in the `xolotl` structure contains a calcium-sensitive controller (Figure 4B-C). Maximal conductances increase from random initial conditions to a set which elicits the desired network output by minimizing the error signal (Figure 4D-F).

3.5 USING THE GUI TO MANIPULATE PARAMETERS

The `manipulate` function opens the GUI which permits visualization of changing parameters in real-time. Moving sliders representing the values of network parameters updates a plot (Figure 5B). By default, the function opens a figure displaying the results of the `plot` function, which shows the voltage and intracellular calcium traces for each compartment (Figure 5A). `manipulate` grants slider control over all `xolotl` parameters by default, but specific ones can be selected by passing them as arguments. For example, to manipulate only the maximal conductances and visualize using the `myPlot` function

```
x.manipulate('*gbar', @myplot)
```

4 BENCHMARKS

To assess speed and accuracy, `xolotl`, `DynaSim` (Sherfey et al. 2018) and `NEURON` (Hines and Carnevale 1997) were compared in simulations over varied time resolution, simulation time, and number of compartments (Figure 6).

Single-compartment Hodgkin-Huxley-like models were generated using conductance dynamics from Liu et al. 1998 in the simulation environments. `xolotl` uses the exponential Euler method for integrating membrane potential (Dayan and Abbott 2001) `DynaSim` was implemented with a 2nd-order Runge-Kutta integration scheme as recommended for high-performance in the documentation. `NEURON` used an implicit Euler regime (Hines and Carnevale 1997)

To compare the integration methods, models were simulated for 5 s at varying time-resolution (Figure 6A). The ratio between ‘simulated’ time and actual runtime was defined as the speed factor. Higher values indicate faster simulations. The coincidence factor determines the correlative overlap between two spike trains (Jolivet et al. 2008) To assess accuracy over decreasing time-resolution for the three simulation environments, spike trains at each resolution were compared to a ‘canonical’ spike train (exponential Euler at a time-step of $dt = 0.001$ ms).

To assess the performance of the simulators in absence of set-up overhead, models were simulated with a time-resolution of 0.1 ms over increasing simulation time (Figure 6B). The speed factor was defined as the ratio between time represented in the simulation and actual runtime (simulation-time). Therefore, the speed factor represents how many times faster the simulation is than a real-time observation.

Many simulators perform well in simulations of many compartments (Brette et al. 2007; Delorme and Thorpe 2003; Sherfey et al. 2018; Vitay, Dinkelbach, and Hamker 2015) Networks of up to 1,000 Hodgkin-Huxley cells were simulated for 5 s at a time-resolution of 0.1 ms (Figure 6C).

DESCRIBE BENCHMARK RESULTS

5 DISCUSSION

We envision `xolotl` will be helpful in teaching students how to

5.1 REPRODUCIBILITY

xolotl fosters reproducibility in science. While the availability of hosting sites with version control (viz. GitHub (<https://github.com>), GitLab (<https://gitlab.com/>), and Open Science Framework (<https://osf.io/>)) and the push for reproducibility in computational science (Baker 2016; Eklund, Nichols, and Knutsson 2016; Stodden et al. 2016) has resulted in the availability of source code, much of this code base is bespoke and difficult to implement (Sedano 2016; W Xu, D Xu, and Deng 2017)

To this end, xolotl provides an environment with readability and reproducibility in mind. Each network is hashed to provide a unique alphanumeric identifier. Conductance header files are easily viewed in the xolotl source files; conductances in MATLAB contain links to the full path of the generating file.

5.2 CIRCUMVENTING LANGUAGE TRADEOFFS

Executing C/C++ code in higher-level languages such as MATLAB or Python often provides speed improvements for iterative code in algorithms.

C is statically-typed, with procedural syntax that provides low-level access to memory (Kernighan and Ritchie 1978) providing significant advantages for time-intensive computations. Unfortunately, automatic code-generation is limited by the supervening language. MATLAB, for instance, cannot use pointers or pass by reference, which limits the efficiency of C code automatically generated from MATLAB. Conversely, custom C/C++ code provides significant increases in performance and memory conservation, but lacks the ease-of-use and flexibility of scripting languages.

xolotl handles this problem through symbolic manipulation of C++ objects in MATLAB. Built from the ground up in C++, xolotl maintains all the advantages of custom compiled code, but can run in MATLAB without the user having to touch the C++ code. xolotl represents compartment, conductance, synapse, and controllers as cpplab objects, which map to underlying C++ header files. In this way, properties of the xolotl network can be examined and changed using object-oriented paradigms. The object specifies the integrate function, not the other way around.

5.3 APPLICATIONS OF CPPLAB

NEED TO WRITE THIS

CONFLICT OF INTEREST STATEMENT

The authors declare that the research was conducted in the absence of any commercial or financial relationships that could be construed as a potential conflict of interest.

AUTHOR CONTRIBUTIONS

SG-S designed and implemented the core of the xolotl toolbox. AH contributed to the code base, created the online user documentation, and wrote the manuscript. EM supervised the project. All authors reviewed the paper.

FUNDING

AH received funding from National Institute on Drug Abuse (NIDA) through the undergraduate training grant in computational neuroscience (1R90DA033463-01).

ACKNOWLEDGMENTS

287 The authors would like to thank Mara CP Rue and Hillary Rodgers for beta-testing the `xolotl` software.
 288 Janis Li helped to prepare some conductance header files.

SUPPLEMENTAL DATA

289 Tables including all conductances packaged with `xolotl` should be put in the supplementary material.

DATA AVAILABILITY STATEMENT

290 The code to generate all figures is available at ([https://github.com/marderlab/](https://github.com/marderlab/xolotl-paper)
 291 `xolotl-paper`). `xolotl` is freely available at (<https://github.com/marderlab/xolotl>).

REFERENCES

- 292 Baker, Monya (2016) “Why Scientists Must Share Their Research Code”. In: *Nature*. DOI: 10.1038/
 293 nature.2016.20504.
 294 Brette, Romain, Michelle Rudolph, Ted Carnevale, Michael Hines, David Beeman, James M. Bower, et al.
 295 (2007) “Simulation of Networks of Spiking Neurons: A Review of Tools and Strategies”. In: *Journal of*
 296 *Computational Neuroscience* 23.3, pp. 349–398. DOI: 10.1007/s10827-007-0038-6.
 297 Butcher, J. C. (2016) “Numerical Differential Equation Methods”. In: *Numerical Methods for Ordinary*
 298 *Differential Equations*. Third. Wiley-Blackwell, pp. 55–142. DOI: 10.1002/9781119121534.
 299 ch2.
 300 Connor, J. A. and C. F. Stevens (1971a) “Inward and Delayed Outward Membrane Currents in Isolated
 301 Neural Somata under Voltage Clamp”. In: *The Journal of Physiology* 213.1, pp. 1–19. pmid: 5575338.
 302 — (1971b) “Voltage Clamp Studies of a Transient Outward Membrane Current in Gastropod Neural
 303 Somata”. In: *The Journal of Physiology* 213.1, pp. 21–30. DOI: 10.1113/jphysiol.1971.
 304 sp009365.
 305 Dayan, Peter and L. F. Abbott (2001) *Theoretical Neuroscience*. Computational neuroscience. Cambridge,
 306 Mass.: Massachusetts Institute of Technology Press. xv+460.
 307 Delorme, Arnaud and Simon J. Thorpe (2003) “SpikeNET: An Event-Driven Simulation Package for
 308 Modelling Large Networks of Spiking Neurons”. In: *Network: Computation in Neural Systems* 14.4,
 309 pp. 613–627. DOI: 10.1088/0954-898X_14_4_301. pmid: 14653495.
 310 Destexhe, Alain and Thierry Bal (2009) *Dynamic-Clamp: From Principles to Applications*. Springer
 311 Science & Business Media. 428 pp.
 312 Eklund, Anders, Thomas E. Nichols, and Hans Knutsson (2016) “Cluster Failure: Why fMRI Inferences
 313 for Spatial Extent Have Inflated False-Positive Rates”. In: *Proceedings of the National Academy of*
 314 *Sciences*, p. 201602413. DOI: 10.1073/pnas.1602413113. pmid: 27357684.
 315 Hines, M. L. and N. T. Carnevale (1997) “The NEURON Simulation Environment”. In: *Neural*
 316 *Computation* 9.6, pp. 1179–1209. DOI: 10.1162/neco.1997.9.6.1179.
 317 Hodgkin, A. L. and A. F. Huxley (1952a) “A Quantitative Description of Membrane Current and Its
 318 Application to Conduction and Excitation in Nerve”. In: *The Journal of Physiology* 117.4, pp. 500–544.
 319 pmid: 12991237.
 320 — (1952b) “The Components of Membrane Conductance in the Giant Axon of Loligo”. In: *The Journal*
 321 *of Physiology* 116.4, pp. 473–496. pmid: 14946714.
 322 Hodgkin, A. L., A. F. Huxley, and B. Katz (1952) “Measurement of Current-Voltage Relations in the
 323 Membrane of the Giant Axon of Loligo”. In: *The Journal of Physiology* 116.4, pp. 424–448. pmid:
 324 14946712.

- Jolivet, Renaud, Ryota Kobayashi, Alexander Rauch, Richard Naud, Shigeru Shinomoto, and Wulfram Gerstner (2008) “A Benchmark Test for a Quantitative Assessment of Simple Neuron Models”. In: *Journal of Neuroscience Methods* 169.2, pp. 417–424. DOI: 10.1016/j.jneumeth.2007.11.006. pmid: 18160135.
- Kernighan, Brian and Dennis M. Ritchie (1978) *The C Programming Language*. Prentice hall.
- Liu, Z., J. Golowasch, E. Marder, and L. F. Abbott (1998) “A Model Neuron with Activity-Dependent Conductances Regulated by Multiple Calcium Sensors”. In: *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience* 18.7, pp. 2309–2320. pmid: 9502792.
- Marder, E. and L. F. Abbott (1995) “Theory in Motion”. In: *Current Opinion in Neurobiology* 5.6, pp. 832–840. pmid: 8805418.
- O’Leary, Timothy, Alex H. Williams, Jonathan S. Caplan, and Eve Marder (2013) “Correlations in Ion Channel Expression Emerge from Homeostatic Tuning Rules”. In: *Proceedings of the National Academy of Sciences* 110.28, E2645–E2654. DOI: 10.1073/pnas.1309966110. pmid: 23798391.
- Oh, Jiyeon and Donald A. French (2006) “Error Analysis of a Specialized Numerical Method for Mathematical Models from Neuroscience”. In: *Applied Mathematics and Computation* 172.1, pp. 491–507. DOI: 10.1016/j.amc.2005.02.028.
- Prinz, Astrid A (2006) “Insights from Models of Rhythmic Motor Systems”. In: *Current Opinion in Neurobiology* 16.6, pp. 615–620. DOI: 10.1016/j.conb.2006.10.001.
- Prinz, Astrid A. (2010) “Computational Approaches to Neuronal Network Analysis”. In: *Philosophical Transactions of the Royal Society B: Biological Sciences* 365.1551, pp. 2397–2405. DOI: 10.1098/rstb.2010.0029. pmid: 20603360.
- Prinz, Astrid A., Cyrus P. Billimoria, and Eve Marder (2003) “Alternative to Hand-Tuning Conductance-Based Models: Construction and Analysis of Databases of Model Neurons”. In: *Journal of Neurophysiology* 90.6, pp. 3998–4015. DOI: 10.1152/jn.00641.2003. pmid: 12944532.
- Prinz, Astrid A., Dirk Bucher, and Eve Marder (2004) “Similar Network Activity from Disparate Circuit Parameters”. In: *Nature Neuroscience* 7.12, pp. 1345–1352. DOI: 10.1038/nn1352. pmid: 15558066.
- Sedano, T. (2016) “Code Readability Testing, an Empirical Study”. In: *2016 IEEE 29th International Conference on Software Engineering Education and Training (CSEET) 2016 IEEE 29th International Conference on Software Engineering Education and Training (CSEET)* pp. 111–117. DOI: 10.1109/CSEET.2016.36.
- Sherfey, Jason S., Austin E. Soplata, Salva Ardid, Erik A. Roberts, David A. Stanley, Benjamin R. Pittman-Polletta, et al. (2018) “DynaSim: A MATLAB Toolbox for Neural Modeling and Simulation”. In: *Frontiers in Neuroinformatics* 12. DOI: 10.3389/fninf.2018.00010.
- Stimberg, Marcel, Dan F. M. Goodman, Victor Benichoux, and Romain Brette (2014) “Equation-Oriented Specification of Neural Models for Simulations”. In: *Frontiers in Neuroinformatics* 8. DOI: 10.3389/fninf.2014.00006.
- Stimberg, Marcel, Dan FM Goodman, Victor Benichoux, and Romain Brette (2013) “Brian 2 - the Second Coming: Spiking Neural Network Simulation in Python with Code Generation”. In: *BMC Neuroscience* 14 (Suppl 1) P38. DOI: 10.1186/1471-2202-14-S1-P38. pmid: null.
- Stodden, Victoria, Marcia McNutt, David H. Bailey, Ewa Deelman, Yolanda Gil, Brooks Hanson, et al. (2016) “Enhancing Reproducibility for Computational Methods”. In: *Science* 354.6317, pp. 1240–1241. DOI: 10.1126/science.aah6168. pmid: 27940837.
- Swensen, A. M. and E. Marder (2000) “Multiple Peptides Converge to Activate the Same Voltage-Dependent Current in a Central Pattern-Generating Circuit”. In: *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience* 20.18, pp. 6752–6759. pmid: 10995818.
- (2001) “Modulators with Convergent Cellular Actions Elicit Distinct Circuit Outputs”. In: *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience* 21.11, pp. 4050–4058. pmid: 11356892.
- Turrigiano, G., G. LeMasson, and E. Marder (1995) “Selective Regulation of Current Densities Underlies Spontaneous Changes in the Activity of Cultured Neurons”. In: *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience* 15 (5 Pt 1) pp. 3640–3652. pmid: 7538565.

- 377 Vitay, Julien, Helge Ülo Dinkelbach, and Fred H. Hamker (2015) “ANNarchy: A Code Generation Ap-
 378 proach to Neural Simulations on Parallel Hardware”. In: *Frontiers in Neuroinformatics* 9. DOI: 10 .
 379 3389/fninf.2015.00019.
- 380 Xu, W., D. Xu, and L. Deng (2017) “Measurement of Source Code Readability Using Word Concrete-
 381 ness and Memory Retention of Variable Names”. In: *2017 IEEE 41st Annual Computer Software and*
 382 *Applications Conference (COMPSAC) 2017 IEEE 41st Annual Computer Software and Applications*
 383 *Conference (COMPSAC)* vol. 1, pp. 33–38. DOI: 10.1109/COMPSAC.2017.166.

FIGURE CAPTIONS




Figure 1: `xolotl` can quickly set up and simulate conductance-based models. (A) Cartoon of a Hodgkin-Huxley single-compartment neuron model with fast sodium, delayed rectifier, and leak currents. (B) Code snippet in MATLAB used to implement D, F-I. (C) `xolotl` schematic displayed in the MATLAB command prompt. (D) Simulated voltage trace of a Hodgkin-Huxley model with three conductances and 0.2 nA of injected current. Colors indicate the dominant current (gold is fast sodium, blue is delayed rectifier, red is leak). (E) Firing rate-input relation displaying firing rate as a function of injected current. (F-G) Steady-state gating functions for activation (m) and inactivation (h) gating variables. (H-I) Voltage-dependence of time constants for activation (m) and inactivation (h) gating variables.




Figure 2: Simulating a voltage-clamp experiment. (A) Cartoon of a cell with delayed rectifier potassium conductance (Liu et al. 1998) with experimentally-fixed voltage. (B) Structure of `xolotl` object in A. (C) Code snippet depicting integration under voltage clamp. (D-E) Current response to steps in voltage from a holding potential of $V_m = -60$ mV. (F) Current-voltage relation of the steady-state current ($t = 400$ ms) indicating a reversal potential of $E = -80$ mV and no inactivation. (G) Conductance-voltage relation at steady-state takes the form of a sigmoid. (H) Sigmoids m fit to the model as m^n data indicating that $n = 4$ is the best fit. (I) Goodness of fit vs. exponent n , suggesting $n = 4$ as the best fit to the data.




Figure 3: Simulating a network of conductance-based model neurons. (A) Diagram of a network model of the pyloric rhythm in the crustacean stomatogastric ganglion (Prinz *et al.* 2004). (B) Each neuron is modeled as a single compartment with 7-8 intrinsic conductances and 1-3 post-synaptic conductances. (C) *xolotl* implements conductances as fields of compartments and synapses as connections between compartments. (D-F) Simulated voltage trace of a model network for the three compartments. (G) Time series of synaptic currents in the simulated network can be obtained from the integration.




Figure 4: Simulating neurons under homeostatic regulation. (A) Cartoon of a model neuron (Liu et al. 1998) with integral control (O'Leary et al. 2013). (B) Hierarchical structure of a neuronal network considers controllers as components of compartments which act on conductances. (C) *xolotl* implements controllers as properties of conductances and synapses. (D) Calcium sensors change maximal conductances to move a neuron from quiescence to a bursting state. (E) Voltage trace shows regular bursting activity after integral control.




Figure 5: Using the GUI to manipulate neuron parameters. (A) Real-time output of the `plot` function displaying voltage (colored) and intracellular calcium (black) traces of a bursting neuron model (Astrid A. Prinz, Billimoria, and Eve Marder 2003; Astrid A. Prinz, Bucher, and Eve Marder 2004). Colors indicate the dominant current. (B) Sliders control the maximal conductances, which updates on the figure.




Figure 6: `xolotl` benchmarked against `DynaSim` and `NEURON`. (A) Ratio of 'simulated' time to runtime (speed factor) and accuracy, measured by spike train coincidence plotted against decreasing time-resolution. (B) Speed factor for models at increasing simulation times. (C) Speed factor over number of compartments.