

Contents

Table of Contents

Contents	1
Table of Contents	1
List of Acronyms	1
List of Figures	1
Introduction	2
State of art	3
Motivations & Work Objectives	6
Contents of the thesis	7
CHAPTER 1: Introductory concepts on guided waves, overview on numerical methods	9
1.1 Modelling of porous media	9
1.2 Methods for modelling metaporous structures	13
Appendices	16
A Implementing SAFE to compute the dispersion relation of Lamb modes	16
B Details on the root-finding algorithm	19
C Overview of activities and scientific works during the thesis	21
D Extended abstract in french	22

List of Acronyms

BEM Boundary Elements Method.	PEM Poroelastic material.
FEM Finite Elements Method.	PML Perfectly Matched Layer.
GEP Generalized Eigenvalue Problem.	SAFE Semi-analytical Finite Elements.
GM Global Method.	SCM Spectral Collocation Method.
JCA Johnson-Champoux-Allard.	SRR Split-Ring Resonator.
MST Multiple Scattering Theory.	TMM Transfer Matrix Method.

List of Figures

I.1	Periodic cells in 1, 2 and 3D. Image taken from Ref. ²⁷	3
I.2	Example of metaporous configurations	5
I.3	Diagram presenting a general layout for the configurations that will be studied in each chapter	7
1.1	Porous material structure	10
1.2	Wavenumbers in unbounded porous media. a) Equivalent fluid wavenumber. Wavenumbers and attenuation for each of the 3 Biot waves.	12
1.3	Diagram for the a) reflection, b) transmission problem. Scattering coefficients from a poroelastic layer (continuous) and equivalent fluid layer (dashed) for the c) reflection, b) transmission problem.	14
1.4	a) Dispersion relation for the Lamb modes with the root-finding results, alongside the spectral collocation and semi-analytical finite elements solutions. b) Convergence curve of the 2 methods at a given frequency $f = 4$ kHz. The multiple lines depicts the convergence of each wavenumber.	18
1.5	iteration muller	19
1.6	Description of the routine	20

Introduction

Noise is a major issue in our modern societies, ranging from everyday life inconveniences, work comfort problems to an actual pollution problem in severely affected areas. Sources of noise can be diverse; in urban environments, concerns are mostly on traffic and population noise. From industrial origins, noise can have various consequences, causing not only risks to the workers and the neighbouring populations, but also structural hazard to installations. Generally, motorized transport is a major issue in all environments, including aircraft, public transportation, roads, commercial vessel traffic, etc.

The European Environment Agency estimated in 2021 that 1 in 5 European resident are exposed to unhealthy levels of noise, its main cause being traffic. These noise exposures can have a strong impact on health¹ favoring impaired circadian rhythm, oxidative stress and cardiovascular dysfunction², as well as psychological consequences like anxiety and depression³. Moreover, anthropic noise pollution also affects biodiversity at large, causing stress, behaviour changes, and masking sensory perception⁴. Marine traffic was shown to generate stress on marine mammals and modify their behaviour by provoking area avoidance and vocalization disruption⁵.

Although sound intensity can be measured objectively, the impact of noise on individuals is in part shaped by social and cultural context. Studies show that expected behaviours norms and customs strongly influence reported annoyance⁶, with comparative surveys revealing clear cross-cultural differences. More recent work has linked collectivistic cultural norms to systematically higher everyday noise exposure as an example^{7,8}. Through these examples, we can conclude that noise is a very broad topic that raises complex questions in various scientific disciplines, regarding its impact on human life and biodiversity at large. In this work, we want to focus on noise mitigation using engineered structures in acoustics.

Most noise sources have emerged from the modernisation of societies through various innovations; with them come with the need to mitigate their noise impact up to our current capabilities, which is able to evolve thanks to research on noise barriers and acoustic insulation systems. Various strategies have been applied throughout the ages. Dating back to 4th century BC, acoustic jars were used to improve the room acoustics in Greek and Roman theatres as well as in the Middle Ages in Western Europe in churches⁹. These resonators are thought to be capable of reducing reverberation time in buildings, covering a frequency range matching that of human spoken voice. As another example, a famous roman amphitheater was shown to have a seat row disposition able to improve intelligibility of speeches from the stage¹⁰.

Contemporary to these antique devices, porous and fibrous materials have been traditionally used to absorb sound in the last century¹¹⁻¹⁶. Largely used in the industry, they are efficient at frequencies starting close to the quarter wavelength resonance frequency of the layer and have been extensively analyzed in the literature¹⁷⁻²¹. They can be found in natural occurrences or engineered and cover very large use cases of acoustic insulation such as industry, transport, aerospace, concert halls and many others.

State of art

Overview of Acoustic Metamaterials

In more recent years, the emergence of more complex engineered structures has disrupted the landscape of acoustic absorbers. Metamaterials are composite structures designed to exhibit physical effective properties that go beyond the capability of the sole material that composes the bulk. They can be created by a lot of various means, including engineered microstructure, a gradual evolution of the material properties, or repeating patterns or scatterers implemented in one or several directions in space and embedded in a host material as shown for various dimensions in Fig. I.1. Compared to homogeneous layers, they generally lead to more complex structures, and are able to achieve enhanced effects. Usually allowing for a tunable response, these structures offer great flexibility and open new perspectives in material design. This field has been initiated by Veselago, who has theoretically described the electrodynamics of materials having a negative refraction index (occurring in the case of a doubly-negative permittivity and permeability), now known as the Veselago lens in electromagnetic metamaterials²². These discoveries have subsequently sparked interest in various disciplines, such as photonics, optics²³ and in the case that concerns us, acoustics. Metamaterials can be used to design antennas and absorber for electromagnetic waves and seismic protection devices among others. In acoustic, they allow for various applications such as absorption, filtering, diffusion or cloaking.

Seminal works have been done on the study of the use of lattice arrangements or crystals for wave control applications. Photonic crystals are used to achieve the control of light and electromagnetic waves²⁴. Similarly in acoustics, phononic crystals have been developed for the control of elastic and acoustic waves as the 2D (or 3D) periodic distribution of scatterers in a solid host medium²⁵ as depicted on Fig. I.1. In the case where the host medium is constituted by a fluid, these structures are called sonic crystals²⁶. These structures are often studied through their band structure (also called dispersion diagram/relation when applied to the study of non-periodic geometries), which will be discussed in extensive details in Section [ref this in chap1](#). In the remaining of the literature overview, focus will be centered around metamaterials that involve periodicity in only one direction in most cases. These acoustic metamaterials can be divided into two main categories: the first concerns the so-called *reflection problem* where the case study is that of an incoming wave on some sample or panel which has a rigid-backing at the end. There, the consideration is focused on mitigating the reflected wave and achieving important acoustic absorption. The other case is that of a *transmission problem* where the incoming wave is able to transmit through the sample. In this case and depending on the application, either or both reflection and transmission are sought to be mitigated. In each of these cases respectively, the structures can be called metasurfaces and interfaces.




Fig. I.1: Periodic cells in 1, 2 and 3D. Image taken from Ref.²⁷

Structured materials that tackle the reflection problem can involve many various strategies. The combination of a perforated plate and coiled-up channels is able to achieve large broadband absorption underwater²⁸. Micro-perforated plate can also be used to achieve interesting absorption

properties for airborne acoustics²⁹. Materials structured from resonant building blocks with resonance frequencies in the sub-wavelength regime i.e., for frequencies which wavelength is much bigger than the typical size of the material, have also been studied^{30–32}. Large width elastic bandgaps have been achieved using locally resonant cells in the design of a sonic crystal³³. These resonances introduce strong dispersion of the waves and the properties of the system are thus dramatically affected. Together with the unavoidable losses, the resonant behaviour of metamaterials make them perfect candidates to design efficient absorbers at low frequencies with reduced dimensions^{34,35}. Balancing the dissipation and leakage of each resonance yields the recently described *critical coupling*. In this case, the reflection drops to zero³⁶. Perfect absorbers can thus be designed for reflection problems for both monochromatic waves^{34,37} and broad range of frequencies^{37–41}. This can be achieved by tuning the structure using the scattering matrix zeros plotted in the complex frequency plane; critical coupling would be achieved when the scattering matrix zero has a vanishing imaginary frequency. Similarly to these broadband absorbers, Yang *et al.* have realized the backing of a porous layer using Fabry-Pérot channels to design an efficient structure⁴².

One of the initial interests of the acoustic metamaterials community was the possibility of producing deeps in the transmission spectra at very low frequencies. This has been widely developed in the literature, a small subset of these works include Refs. ^{43–46}. These configurations are based on resonant elements and display a zero transmission in the lossless case at their resonance frequency. In reality, losses cannot be avoided and a small amount of the energy is always transmitted. Membrane-type acoustic metamaterials^{47–49}, or acoustic metamaterials made by Helmholtz resonators^{50–52} have been used to develop systems with high values of transmission loss for audible acoustics. Considering the vibroacoustic coupling allows for more precise depiction of real-life applications. Works on periodic soft inclusion in a soft solid matrix was done by Aberkane *et al.* showing improved transmission loss affected by the presence of soft inclusions in the solid layer. In this case, the presence of losses was able to improve the transmission loss at low frequencies. Also accounting for vibroacoustic coupling, attached resonators to walls have been also used to reduce the transmission loss of panels^{53,54}.

For the case of mirror-symmetric structures, it is worth noting here that if only a monopolar resonator (Helmholtz) or a dipolar resonator (membrane) is used to absorb waves, then only 50% of energy can be absorbed as shown in several articles^{55,56}. However, using a material made of slits loaded by an array of identical resonators creates an accumulation point close to the resonance frequency of the resonators allowing the accumulation of the resonances of the slit, thus placing together symmetric and antisymmetric resonances^{47,50,57}, although requiring for a compromise between absorption and thickness. A more complex approach consists in designing degenerate resonators. By using combinations of membrane and cavity resonators^{47,58} and with slits loaded with Helmholtz resonators⁵⁶, quasi-total absorption can be reached. In these systems, each resonator manages half of the problem, absorbing each one half of the energy and allowing a perfect absorption peak: all the energy that impinges on the system is dissipated within the system, i.e., the energy is neither reflected nor transmitted. The other alternative to obtain perfect absorption consists in breaking the symmetry of the system. These systems can achieve unidirectional perfect absorption, i.e., perfect absorption can be obtained from one of the two incidence sides⁵⁵. The principle of these systems consists in using two resonators, one that is used to reduce as much as possible the transmission and the other that impedance matches the system from one side^{34,37,49}. This concept has been exploited to develop broadband perfect absorbers using a cascade of the previous process giving rise to a rainbow absorber³⁸.

From porous layers to metaporous surfaces

As mentioned in the beginning of the introduction, porous materials have been traditionally widely used for their acoustic insulation performances. These materials are lossy: an airborne acoustic wave propagating through a porous layer is dissipated as it propagates in the bulk in the form of

viscous friction due to the drag between the air and the pore walls and in the form of heat due to the small ducts and the existence of a thermal boundary layer. These losses mechanisms are strongly dependant on the nature of the material, as they are mainly affect by the geometry of the microstructure. Common models usually account for homogenized effective parameters to characterize these materials as will be discussed in a further section. Since wave velocity in porous media tends to be smaller than that of air, allowing to lower slightly the frequency of the quarter-wavelength resonance, which corresponds due the frequency where such materials usually start to have an efficient acoustic absorption. Section 1.1 is dedicated to presenting the various models used for porous and poroelastic media modelling. Their absorption efficiency depends thus on their inherent losses but also on the impedance mismatch between the layer and the medium from which the impinging acoustic wave is originated (i.e usually air). The acoustic impedance mismatch leads to reflection at the interface, while the energy transmitted through the interface in the porous layer gets attenuated. In real-life applications, these materials are not closed systems and there is a need to account for their coupling irl to surrounding domains into which part of the acoustic energy is susceptible to be radiate back into the half-space.

In order to increase the capabilities of acoustic absorption of porous materials, some works can involve the modification of the core structure of porous and poroelastic materials by tuning of the microstructure, introducing a gradient of the properties, or by using anisotropic materials. Recently, with the increase of new fabrication techniques based on 3D printing, the structure of the porous materials can be controlled and tuned to design materials with better absorption capabilities at low frequencies, based on gradient properties^{59,60}, or on anisotropic materials^{61–64}. Recently, resonators filled with 3D printed porous materials have been developed to design perfect and broadband absorption⁶⁵. Other configurations have been studied, among them the periodic partitioning of the metaporous layer⁶⁶ or a labyrinthine channel embedded in a porous host⁶⁷, based on the idea of coiling up the space of the channel as was done for non-porous metamaterial designs. Recently, a hierarchical multilayer metaporous structure was proposed using an optimization procedure, giving rise to gradient and periodic designs⁶⁸.

Some studies involving porous layers embedding periodic arrays of inclusions were done during the last 15 years^{69–72}. These inclusions can have either resonances or not and they allow for an increased dissipation in the viscous regime. These structures are refered to as metaporous surfaces when used in reflection problems. The first works involving metaporous surfaces or interfaces were developed for transmission problems^{73,74}. In case of more than one inclusion per spatial period, several absorption peaks can be obtained for a particular arrangement along the porous thickness⁷⁰. Nevertheless, this rapidly leads to a thick structure. Near the inclusion resonance frequency, chosen to be in the viscous regime, an absorption peak occurs⁷⁵. The resonance frequency of the inclusions depends on the orientation of the resonators relative to the rigid boundary^{71,75}. Recently, 3D printed porous materials with embedded split-ring resonators have been modeled⁶³, designed and experimentally characterized showing perfect absorption peaks. More complex spiral-shaped slits have been embedded in a porous layer and have shown to be able to maintain a high absorption for large incidence angles⁷⁶. Xiong *et al.* have studied a metaporous liner with embedded resonator and shown the existence of an exceptional point when the geometry is tuned properly, leading to enhanced absorption⁷⁷.

Fig. I.2: Example of metaporous configurations

Previous metaporous layers studies have considered a host medium modelled as a rigid-frame porous layer; extensions of these structures to consider poroelastic materials have been done⁷⁸. Interesting properties were exhibited for thin elastic shell inclusions, and particularly in the case of a coupling between the trapped and the first volume mode leading to a high wide band absorption. While this previous study implements a semi-analytical model that makes use of Multiple Scattering

Theory (MST), it is worth noting here that different modelings exist as well, based on a Finite Elements Method (FEM) and MST have been validated for the case of an air-saturated metaporoelastic configuration with a solid inclusion and rubber coatings⁷⁹. This thesis is especially focused on the computation of the dispersion relation of such configurations. Therefore, a dedicated literature review dealing with the tools available to achieve such computation will be given in Chapter 1.

Wave propagation modelling and dispersion analysis

This section should introduce scattering problems vs dispersion problems

The analysis of wave propagation in periodic and complex media often relies on the computation tools. Two main topics are of interest in this thesis: the scattering of an incident wave by a structure as well as its dispersion relation. The first one is simply the acoustic response of a system while dispersion relations are diagrams that represent the wavenumber in a given direction against the frequency, thus informing on the evolution of the wave velocities in the structure and thus the dispersion within. In the context of metamaterials and periodic structures, they are often referred to as band structure.

A theoretical definition of a dispersion relation consists in the spectrum of all solutions of a set of equations given a set of parameters. It shows the possible existing states of a system. Generally the form of the dispersion relation, and the various modes that are uncovered can give very in-depth details about the modal behaviour of any structures. In ultrasonics and non-destructive testing, localizing zero-group velocity (ZGV) points in the dispersion relation is very helpful for a number of uses including defects localization and material characterization⁸⁰.

Scarce literature focuses on the computation of the dispersion relations of dissipative layers in general exists: the dispersion of waves in a single poroelastic layer has been studied by Boeckx *et al.*^{81,82} while an unpublished paper from Kiefer *et al.* took interest in Lamb waves in viscoelastic layer coupled to surrounding half-spaces⁸³. There is an interest in analogously studying the coupling between surrounding media and metaporous surfaces, as part of the acoustic energy of the wave propagating in the surface should radiate back into the domain, leading to more complex loss effects on the structure.

These aspects will be discussed in detail in the following chapter, both from the theoretical perspective of porous and poroelastic media (and their coupling to surrounding media) and in terms of the available numerical tools for their computation.

Motivations & Work Objectives

This thesis is dedicated to the numerical modeling of wave propagation in open-system structures comprised of stacks of layers, homogeneous or with embedded scatterers. As it has been seen in the previous section, these materials combine the dissipative characteristics of porous media with the geometric or structural features typical of acoustic metamaterials, thus offering advanced control over their scattering properties. Understanding and predicting the acoustic behavior of such systems is therefore essential for designing efficient structures. In particular, this work focuses in part on the calculation of the dispersion of waves in these structures, and understand how the propagating and evanescent modes that exist in these configurations are shaping the scattering properties. Thence, the development of efficient numerical strategies is critical to this study.

The tuning of metamaterials could be achieved in some studies by looking at the zeros of the reflection coefficient in the complex frequency plane, thus highlighting the zeros of the scattering matrix. However, the wavenumber might be able to give out additional informations regarding the acoustic behaviour of metaporous layers. Band structure gives useful informations concerning sonic and phononic crystals. However, the dispersion relation of a metaporous layer embedded in an open system has never been addressed; both mechanisms of energy leakage in the surrounding media and

dissipations in the porous layer should be investigated. However, this imply a heavy modification of the boundary conditions of the structure. It expected to have significant consequences on the propagation of modes therein. This work will be done on both homogeneous layers as well as periodic structures.

From these observations, we should review existing numerical methods able to compute the acoustic response of metaporous structures and consider ways to obtain a precise and robust method able to predict the scattering properties and acoustic responses of metaporous surface and interfaces. Additionnaly, we should evaluate methods that have been implemented for the computation of guided waves in layers and stacks of layers coupled to semi-infinite media. Confronting the dispersion relation, with the absorption coefficient should gelp highlighting the modal behaviour responsible for the various absorption peaks obtained by previously studied configurations and also highlight the full modes existing in the layers which might uncover additional phenomena.

Contents of the thesis

This introductory section has set the context as well as an overview of the literature in which this work is situated. We saw that acoustic metamaterials have emerged in the last decades and propose noise mitigation structures that are much more efficient that the traditional foams used for sound insulation. In particular, metaporous surfaces have shown to be promising options achieving one or multiple unitary absorption peaks at subwavelength frequency. Overall, a focus area has been identified towards identifying more precisely the modal behaviour of these configurations. Thus, in this thesis the main interest and final is to succesfully compute the dispersion relations of guided waves in such structures. The manuscript is split into four different chapters as follows,




Fig. I.3: Diagram presenting a general layout for the configurations that will be studied in each chapter

- CHAPTER 1 introduces the fundamental concepts necessary for the good understanding of the thesis. This chapter focuses on the scattering of waves on dissipative layers and the guided waves formalism that is used for the calculation of dispersion relations. Additional bibliography is proposed on these topics as well as a summary of usable numerical methods to compute such problems.
- CHAPTER 2 targets the study of the propagation of guided waves in multilayer arbitrary structures with dissipative layers. A simple numerical method, the Spectral Collocation Method (SCM) is implemented and extra steps allow for the local coupling of surrounding media allows for the computation of the dispersion relation for these configurations. This chapter is constituted from paper^{P1}.

- CHAPTER 3 is focused on several numerical strategies for the modelling of scattering properties of metaporous/metaporoelastic structures. A global method is coupled to a FEM. Results focused on the performance of the proposed method, compared to other similar frameworks is proposed. The convergence of this method is shown for various metaporoelastic surfaces, which geometries were studied in previous papers. This chapter is originally an article referenced as paper. [cite when submitted](#).
- In CHAPTER 4, the modal behaviour of metaporous structure is studied. The fem method from the previous chapter is adapted to describe this problem. Results are presented for the case of a rigid inclusion, as well as with embedded Split-Ring Resonator (SRR). Contents for this chapter were published in paper. [cite when submitted](#).

Contents

1.1	Modelling of porous media	9
1.1.1	Rigid-frame approximation	10
1.1.2	Elastic motion of the skeleton: Biot theory	11
	Formulations for the motion equations	11
1.2	Methods for modelling metaporous structures	13
1.2.1	Wave propagation in homogeneous layers	13
	Global Method: plane wave modelling	13
	Guided waves for dispersion problems	14
	Zoology of the wave solutions	14
	TMM	14
1.2.2	Wave propagation in periodic structures	15
	Media periodization	15
	Multiple scattering	15
	FE	15

This theoretical chapter lays the foundation for the thesis, giving some notions of the fundamental necessary aspects, in order to guide the reader through the various chapters that will follow. At first, an overview of the modelling in porous media is proposed.

1.1 | Modelling of porous media

Porous materials are constituted of two distinct domains: an elastic matrix Ω_s with a pore network Ω_f , which is filled by some saturating fluid, they are biphasic. A diagram of their structure is shown in Fig. 1.1. The porosity is defined as the fraction of fluid over the total volume of the material, as $\phi = V(\Omega_f)/V(\Omega)$. In the limit case, $\phi = 0$ the material becomes purely a solid while at $\phi = 1$, it becomes a fluid. The geometry of the fluid phase forms a complex microstructure at a microscopic level. Fortunately, at acoustic scales, these materials can often be considered at a meso-/macroscopic scale and therefore models have been developed to describe the large-scale motion of these materials. In this context, they can be regarded as homogeneous and described by a set of effective parameters that account for their complex inner geometry. The porous structure of these materials causes the incoming acoustic energy to be dissipated through friction (viscous losses), thermal exchanges and elastic dissipation when the skeleton and the fluid are coupled. These losses are thus dependant on the geometry, that is the porosity, pore network size, connectivity and shape, and the frame mechanical parameters.




Fig. 1.1: Porous material structure

1.1.1. Rigid-frame approximation

In the so-called rigid-frame case, the skeleton of the porous material is motionless. Therefore, the pore walls are rigid walls and the material can be modeled as an *equivalent fluid* which possesses complex effective properties in order to model the losses mechanisms. A harmonic acoustic propagation is assumed with a positive time convention $e^{i\omega t}$ throughout this manuscript (with the exception of Chapter ??) The Helmholtz equation governs the propagation,

$$(\nabla^2 + k_{eq}^2) p(\mathbf{x}) = 0, \quad (1.1)$$

where p is the pressure field and k_{eq} is the wavenumber of the equivalent fluid. In the case where porous or fibrous materials have a porosity close to 1 and the frequency range of interest is limited, the Delany-Bazley model was originally developed in 1970 to propose empirical expressions for the values of the complex wavenumber and characteristic impedances^{11,84} and later improved by Miki⁸⁵. Although limited in accuracy and validity domain, these models has been widely used since it only required the flow resistivity of the porous material. Later on, a more precise semi-phenomenological model additionnaly accounting for the viscous and inertial dissipative effects was developed from 1987 to 1991. It is the Johnson-Champoux-Allard (JCA) model which models the complex effective density $\rho_{eq}(\omega)$ accounts for the frequency dependant viscous losses and effective bulk modulus of the material K_{eq} accounting for thermal exchanges in the layer as,

$$\begin{aligned} \rho_{eq}(\omega) &= \frac{\rho_f \alpha_\infty}{\phi} \left(1 + \frac{i R_f \phi}{\rho_f \alpha_\infty \omega} \sqrt{1 - i \omega \rho_f \mu_f \left(\frac{2 \alpha_\infty}{R_f \phi \Lambda} \right)^2} \right), \\ K_{eq} &= \frac{\kappa P_0}{\phi} \left(\kappa - (\kappa - 1) / \left(1 + \frac{i R_f \phi}{\rho_f \alpha_\infty \text{Pr} \omega} \sqrt{1 - i \text{Pr} \omega \rho_f \mu_f \left(\frac{2 \alpha_\infty}{R_f \phi \Lambda'} \right)^2} \right) \right)^{-1}. \end{aligned} \quad (1.2)$$

These expressions involve a large number of effective parameters for the porous material; α_∞ is the tortuosity, R_f is the flow resistivity, Λ and Λ' are respectively the viscous and thermal characteristic length. The saturating fluid is characterized in this model by its heat capacity ratio κ (commonly also denoted γ), density ρ_f , kinematic viscosity μ_f , pressure P_0 and Prandtl number $\text{Pr} = c_p \mu_f / k$ with c_p is the specific heat and k the thermal conductivity. We can introduce also the Biot frequency $\omega_c = R_f \phi / (\rho_f \alpha_\infty)$ that defines the transition frequency between the inertial and viscous regimes.

1.1.2. Elastic motion of the skeleton: Biot theory

While the equivalent fluid formalism is able to accurately model porous material in specific sets of conditions, that is when the skeleton can be assumed to be motionless, this assumption can quickly become limited as soon as the said skeleton is subjected to an elastic deformation. This is the case when the saturating fluid of the PEM has a high density (e.g. water), when the skeleton is coupled to elastic plates or when the acoustic radiation has a wavelength comparable to the pore scale, although these are just examples. In this situation, the full elastic motion should be modeled, so that to account for the coupling between the solid matrix and its fluid filling. The Biot theory^{86–89} is a formalism that encompasses the theory of the deformation of porous material saturated by an incompressible fluid, used both in geophysics and acoustics. For sake of conciseness, the various models will be briefly presented along with the relevant physical quantities. A full derivation would be out of scope and is presented in existing works¹¹.

Before presenting the full Biot model, some quantities should be provided additionally to the equivalent fluid parameters. The frame is assumed to undergo elastic deformations, thus the common mechanical parameters used are the solid density of the frame material ρ_s as well as its apparent density $\rho_1 = (1 - \phi)\rho_s$. The bulk moduli are denoted K_b and K_s , respectively for the frame and the material. The shear modulus is also considered complex, accounting for structural losses as $\tilde{N} = N(1 + i\eta)$ with η the loss factor. Symbols written with a tilde denote complex expressions and therefore account for some sort of loss mechanisms. For the fluid, the apparent density is thus $\rho_2 = \phi\rho_f$ and the inertial interaction density defined by $\rho_{12} = -\phi\rho_f(\alpha_\infty - 1)$. A summary on Biot theory is also proposed in Chap. ??) with the tilde symbols omitted for ease of reading.

Formulations for the motion equations

The Biot poroelastic equations from the original 1956 formulation^{86,88,89} depend on the solid displacement vector $\mathbf{u}_s$ and the fluid displacement $\mathbf{u}_f$,

$$\begin{aligned}\nabla \cdot \boldsymbol{\sigma}_s(\mathbf{u}_s, \mathbf{u}_f) &= -\omega^2 \tilde{\rho}_{11} \mathbf{u}_s - \omega^2 \tilde{\rho}_{12} \mathbf{u}_f, \\ \nabla \cdot \boldsymbol{\sigma}_f(\mathbf{u}_s, \mathbf{u}_f) &= -\omega^2 \tilde{\rho}_{12} \mathbf{u}_s - \omega^2 \tilde{\rho}_{22} \mathbf{u}_f,\end{aligned}\tag{1.3}$$

where $\boldsymbol{\sigma}^s$ is the solid stress tensor, $\boldsymbol{\sigma}^f$ the fluid stress tensor and the apparent densities of the solid-phase is $\tilde{\rho}_{11}$, that of the fluid is $\tilde{\rho}_{22}$ and the coupling apparent density is $\tilde{\rho}_{12}$. They are complex quantities expression that also account for the contribution of viscous forces and are given as,

$$\tilde{\rho}_{22} = \phi^2 \tilde{\rho}_{eq}, \quad \tilde{\rho}_{12} = \rho_2 - \tilde{\rho}_{22}, \quad \tilde{\rho}_{11} = \rho_1 - \tilde{\rho}_{12}.\tag{1.4}$$

These coupled motion equations are associated to the stress-strain relation,

$$\begin{aligned}\boldsymbol{\sigma}_{s,ij} &= [(\tilde{P} - 2\tilde{N})\nabla \cdot \mathbf{u}_s + \tilde{Q}\nabla \cdot \mathbf{u}_f] \delta_{ij} + 2\tilde{N}\epsilon_{s,ij}, \\ \boldsymbol{\sigma}_{f,ij} &= (\tilde{Q}\nabla \cdot \mathbf{u}_s + \tilde{R}\nabla \cdot \mathbf{u}_f) \delta_{ij} - \phi p,\end{aligned}\tag{1.5}$$

where $\nabla \cdot \mathbf{u}_s$ and $\nabla \cdot \mathbf{u}_f$ correspond to the dilatation of the solid and fluid phases respectively and ϵ_s , is the solid-phase strain tensor. The Biot coefficients are denoted as $\tilde{P}$ for the solid elastic coefficient, $\tilde{Q}$ for the elastic-fluid coupling coefficient, and $\tilde{R}$ for the fluid-phase coefficient. In the context of a PEM saturated by a light fluid, their expressions are

$$\tilde{P} = K_b + \frac{4}{3}N + (1 - \phi)^2 \frac{\tilde{K}_{eq}}{\phi}, \quad \tilde{Q} = \tilde{K}_{eq}(1 - \phi), \quad \tilde{R} = \phi \tilde{K}_{eq}.\tag{1.6}$$

The full coefficients are generalized forms required when the limit $K_b/K_s \rightarrow 0$ no longer holds, as is the case for water-saturated PEM.

A different formulation, especially convenient for finite-elements discretization is known as the $(\mathbf{u}^s, p)$ formulation. First, new parameters in terms of the Biot elastic coefficients and apparent densities can be defined,

$$\hat{A} = \tilde{P} - 2\tilde{N}_s - \frac{\tilde{Q}^2}{\tilde{R}}, \quad \hat{\rho} = \tilde{\rho}_{11} - \frac{\tilde{\rho}_{12}^2}{\tilde{\rho}_{22}}, \quad \beta = \phi \left(\frac{\tilde{\rho}_{12}}{\tilde{\rho}_{22}} - \frac{\tilde{Q}}{\tilde{R}} \right). \quad (1.7)$$

β is another coupling coefficient, also denoted as $\tilde{\gamma}$ in the literature. Using the second row of Eq. (1.3) allows for the expression of the fluid displacement as, $\mathbf{u}^f = \phi / (\tilde{\rho}_{22}\omega^2) \nabla p - \tilde{\rho}_{12} / \tilde{\rho}_{22} \mathbf{u}^s$ and using that in Eq. (1.3) and Eq. (1.5) allow to rewrite the coupled motion equations. Using these, the so-called $(\mathbf{u}_s, p)$ formulation of the Biot theory⁹⁰ is expressed as,

$$\begin{aligned} \nabla \cdot \hat{\boldsymbol{\sigma}}_s + \hat{\rho}\omega^2 \mathbf{u}_s + \beta \nabla p &= 0, \\ \frac{\nabla^2 p}{\rho_{22}\omega^2} - \frac{\beta}{\phi^2} \nabla \cdot \mathbf{u}_s + \frac{1}{R} p &= 0, \end{aligned} \quad (1.8)$$

where $\hat{\boldsymbol{\sigma}}_s$ is the *in vacuo* solid stress tensor,

$$\hat{\boldsymbol{\sigma}}_{s,ij} = \boldsymbol{\sigma}_{s,ij} - \phi \frac{\tilde{Q}}{\tilde{R}} p \delta_{ij} = \hat{A} \nabla \cdot \mathbf{u}_s \delta_{ij} + 2N_s \epsilon_s \quad (1.9)$$




Fig. 1.2: Wavenumbers in unbounded porous media. a) Equivalent fluid wavenumber. Wavenumbers and attenuation for each of the 3 Biot waves.

These various formulations provide several way of modelling equivalently wave propagation in poroelastic media. It appears that PEM supports three waves: a compression and shear wave related to the solid phase as well as an additional compression wave related to the fluid phase. ++ **détails** Following the section 6.5 of Allard and Atalla textbook¹¹, the three wavenumbers of these waves are (denoted as δ_i , $i = 1, 2, 3$ in the text),

$$\begin{aligned} k_{p,a} &= \sqrt{\frac{1}{2} \left(\delta_2^2 + \delta_{eq}^2 \pm \delta_t \right)} \\ k_s &= \omega \sqrt{\frac{\hat{\rho}}{\tilde{N}}}, \end{aligned} \quad (1.10)$$

with,

$$\delta_{eq} = \omega \sqrt{\frac{\tilde{\rho}_{eq}}{\tilde{K}_{eq}}}, \quad \delta_1 = \omega \sqrt{\frac{\hat{\rho}}{\hat{P}}}, \quad \delta_2 = \omega \sqrt{\frac{\hat{\rho}_s}{\hat{P}}}, \quad \delta_t = \sqrt{(\delta_2^2 + \delta_{eq}^2)^2 - 4\delta_{eq}^2 \delta_1^2}. \quad (1.11)$$

The propagation characteristics, i.e. wavenumbers of the waves propagating in porous and poroelastic media are illustrated in Figure 1.2. As discussed in the previous sections, the wavenumber for the equivalent fluid as well as the three for the poroelastic layer are complex. Their real part accounts for the propagation of the phase flow, inversely proportional to the wave velocity and their imaginary part accounts for the attenuation that occurs due to the losses inherent to each of these materials.

1.2 | Methods for modelling metaporous structures

In the previous section, a formulation for rigid-frame porous media and two formulations for poroelastic media modelling have been presented. Concluding the presentation of these motion equations, some characteristics of wave propagation in unbounded porous and poroelastic have been studied and shown that these materials support for the propagation of respectively one and three distinct waves. The present section proposes the introduction of a geometry in the system, that is to say boundaries or interface conditions delimiting different domains characterized each by different type of material. Generally, the configurations studied in this work assume a monochromatic plane wave originated from a fluid half-space, i.e. air, which impinges at the surface of a structure and is scattered (reflected and transmitted) through each interface.

If the material in which the wave propagates is bounded by two parallel, free, and flat surfaces, i.e., a plate, then it is referred to as a layer. The waves propagate by reflecting alternately from one surface to the other; they are said to be guided along the layer. These observations of successive reflections and refractions lead to the concept of waveguides, but their analytical descriptions often pose problems that are difficult to solve. To determine the modes of a structure, one must seek to solve the propagation equations and the boundary conditions imposed at its boundaries.

1.2.1. Wave propagation in homogeneous layers

Introducing a simple problem, that of the scattering of an incident plane by a porous layer. The incident pressure field takes the form of,

$$p_i = ae^{-ik_1x_1}e^{-ik_2x_2}, \quad (1.12)$$

with wavenumbers such that they hold for the Snell-Descartes law,

$$k_1^2 + k_2^2 = k_0^2, \quad (1.13)$$

Global Method: plane wave modelling

The analytical description of the system amounts finally to a linear system built from the interface conditions, which unknown vector are the amplitudes of each of the existing waves in the system. The forcing right-hand side corresponds to the incident plane. The solution of the system yields all unknown amplitudes of the system, in particular the reflection and transmission coefficients.

A few results for the simple cases of the scattering of a plane wave by a rigidly-backed layer and in a symmetric configurations are represented by the diagrams in Figs 1.3a and b and results in Figs 1.3c and d, respectively. There, the layer for both porous and PEM are both $b = 5$ cm thick and the incident wave propagates with a $\theta = 30^\circ$ angle. The parameters for each material corresponds to




Fig. 1.3: Diagram for the a) reflection, b) transmission problem. Scattering coefficients from a poroelastic layer (continuous) and equivalent fluid layer (dashed) for the c) reflection, b) transmission problem.

the one used in Table ?? from Chapter ?. The first case, also referenced to as a reflection problem compares the equivalent fluid and the full Biot model response. The two curves follow the same trend but additional effects due to the skeleton motion can be observed on the continuous lines while the equivalent fluid response shows to be smoother. For all configurations, the low-frequency behaviour shows that the melamine layer is acoustically transparent at lower frequency and absorption can be noticed at slightly higher frequencies.

From the previously obtained linear system for the configurations, and removing the incident wave from the system, i.e. the forcing (right-hand side) term, an homogeneous linear system is obtained, representing the guiding of waves in the layer. This set of equations becomes singular when its determinant vanishes for a given parameter, allowing to identify the modes of the structure. Several formalism can be adopted: solving for frequencies while imposing the wavenumber or the other way around. The first one is useful when interested in the time-dependant effects the structure has on the propagation. In this work, we are interested in the losses generated by the structure and the material and as such frequency is fixed in order to solve wavenumbers.

Once the linear system is obtained, we are faced with either or two of these possibilities. Solving wavenumbers can be done through the writing and solving of a (possibly generalized) eigenvalue problem or by root-finding of solutions in the case where writing the first one appears impossible.

limited to homogeneous layers and complicated to solve dispersion relations

Guided waves for dispersion problems

1D discretization: SCM, SAFE, etc. mentionner chap jap, + annexes safe vs scm lamb configurations, dispersion in porous⁸² + groby2008

Zoology of the wave solutions

conservative systems - simple waveguide - guided, trapped - evanescent waves **non-dissipative**
leaky - leaky waveguide - quasi-guided, trapped, - leaky backward, leaky forward - incoming backward, forward **dissipative** **leaky** - same but no trapped modes exist? + séparation impossible entre incoming et leaky waves

TMM

instable, multiphysics coupling with interface matrices -> large systems. only for simple geometries, easy to implement. doutresTransferMatrixModeling2015

1.2.2. Wave propagation in periodic structures

As has been studied in the introduction, a large literature exists showing the enhancement of absorption properties by periodicizing the porous layers with embedded scatterers. Periodicity can be imposed in acoustic systems using the so-called Bloch-Floquet theory. There, the layer of infinite extent is limited to a single unit-cell, able to alone describe the full behaviour of the infinitely repeating periodic cell.

reciprocal wavenumber space, limit the study to the first Brillouin zone covering, $k_1 \in [0, \pi/d]$. opening of a Bragg bandgap: conditions of existence in classical metamaterial, can it happen with losses.

With these complex geometries comes the need for more advanced tools for the discretization of these structures. Introduce finite elements.

soft solids: aberkane phd

Media periodization

For more complex geometries, we must turn to alternative methods. As the 1D discretization used by the SCM and SAFE and the plane wave formalism used in TMM and the GM is not capable of providing a description of the geometry of inhomogeneous layers, in our case, the effects of the scatterer in the unit cell on wave propagation.

Multiple Scattering Theory is an analytical formalism developed for this purpose and is able to account for the scattering of each of the neighbouring obstacles. Tedious theoretical framework, shown to compute the acoustic response of metaporous⁷⁰ and metaporoelastic surfaces⁷⁸.

Finite Elements Method flexible and powerful able to

Multiple scattering

for forced problems

FE

for whatever

- guided waves formalism
- Lamb modes
- leaky modes, energy radiation: relevance of the imposition of a local coupling contrary to a full modelling of the surrounding media with some termination condition satisfying the Sommerfeld condition, PML or analogous.
- surface and guided waves - gm
- Reflection and transmission coefficient of a porous layer ? should involve some numerics

Appendices

Contents

A	Implementing SAFE to compute the dispersion relation of Lamb modes	16
A.1	Formalism	17
A.2	Results and convergence comparison	18
B	Details on the root-finding algorithm	19
B.1	The Müller method	19
B.2	A complete routine for the automated solving of dispersion relations . . .	19
C	Overview of activities and scientific works during the thesis	21
C.1	Publications	21
C.2	Conferences	21
C.3	Workshops and training schools	21
C.4	Teaching activities	21
D	Extended abstract in french	22

A | Implementing SAFE to compute the dispersion relation of Lamb modes

As discussed in Section. ??, the SAFE method is an alternative to SCM for the numerical computation of dispersion relation of guided waves in layers. They rely on a similar formalism, that is a 1D discretization across the thickness of each layer and an assumption of guided harmonic waves along the longitudinal direction. An analogous method to that presented in Chapter ?? could be developed using SAFE, the key difference being the location of nodes in the layer and the interpolation function used for discretization. There is a large bibliography dealing with these topics and applying this method to similar problem to ours.

The general theory of SAFE is explained in great details in Chapter 9 of Rose's textbook⁹¹ hence The present method is inspired from. Examples of SAFE application to dispersion curve calculation are illustrated by Predoi *et al.*⁹² where a numerical model was implemented to investigate periodic structure of infinite width with the addition of periodic boundary conditions allowing for the computation of guided wave modes. A similar approach was generalized for systems with arbitrary cross-sections and a coupling with infinite solid media by using the so-called absorbing region⁹³. Other description of the surrounding medium where leakage happens have also been investigated by using a PML⁹⁴. This has been done by Mazzotti *et al.* using BEM^{95,96}. A local coupling of the surrounding space was done in Ref.⁹⁷ by linearizing a non-linear GEP, a similar approach to that of Refs.^{91,98}.

In this appendix, we propose to quickly re-derive a SAFE method inspired from these previous papers to benchmark the two numerical methods regarding their respective performances. We will

use high-order Lobatto function as interpolating function of the finite-elements core of the method. The system studied here is the simple of Lamb modes: an elastic layer of infinite extent in the x_1 direction has two free edges at $x_2 = 0$ and $x_2 = b$, where a no-traction boundary condition is applied.

A.1. Formalism

Let us start with the general variational form for the elasticity equation

$$-\rho\omega^2 \int_{\Omega} u \delta u \, d\Omega + \int_{\Omega} \sigma(u) : \epsilon(\delta u) \, d\Omega = \int_{\partial\Omega} \sigma(\delta u) \cdot \mathbf{n} \, d\Gamma, \quad \forall \delta u, \quad (\text{A.1})$$

where the displacement fields is

$$\mathbf{u}(\mathbf{x}) = \mathbf{u}(x_2) e^{ik_1 x_1} e^{-i\omega t}, \quad (\text{A.2})$$

and the double-dot product is $\sigma(u) : \epsilon(\delta u^*) = \sigma_{ij}(u) \epsilon_{ij}(\delta u^*)$. σ designates the stress tensor while ϵ is the strain tensor. Developing this part of the volume term gives the expression,

$$\begin{aligned} \sigma_{11}\epsilon_{11} &= k_1^2(\lambda + 2\mu)u_1\delta u_1 + -ik_1\lambda\nabla u_2\delta u_1 \\ \sigma_{12}\epsilon_{12} &= \frac{\mu}{2} \left(-ik_1\nabla u_1\delta u_2 + \nabla u_1\delta\nabla u_1 + k_1^2u_2\delta u_2 + ik_1u_2\nabla\delta u_1 \right) \\ \sigma_{22}\epsilon_{22} &= ik_1\lambda u_1\nabla\delta u_2 + (\lambda + 2\mu)\nabla u_2\nabla\delta u_2. \end{aligned} \quad (\text{A.3})$$

Putting these terms back into Eq. A.1 yields,

$$\begin{aligned} \int_{\Omega} -\rho\omega^2 (u_1\delta u_1 + u_2\delta u_2) + k_1^2(\lambda + 2\mu)u_1\delta u_1 - ik_1\lambda\nabla u_2\delta u_1 - ik_1\mu\nabla u_1\delta u_2 + \mu\nabla u_1\delta\nabla u_1 \\ + \mu k_1^2u_2\delta u_2 + ik_1\mu u_2\nabla\delta u_1 + ik_1\lambda u_1\nabla\delta u_2 + (\lambda + 2\mu)\nabla u_2\nabla\delta u_2 \, d\Omega = 0 \quad \forall \delta u \end{aligned} \quad (\text{A.4})$$

where ∇u_i denotes differentiation of the i -th component of the displacement along x_2 . Note that the surface term initially expressed vanishes from the no-traction boundary condition.

The displacement fields can be discretized as

$$\mathbf{u}(\mathbf{x}) = \mathbf{N}(\xi)\mathbf{U}e^{ik_1 x_1} e^{-i\omega t}, \quad (\text{A.5})$$

with $\mathbf{N}$ containing the Lobatto shape functions, and $\mathbf{U}$ is the vector of displacement amplitudes. Following the same discretization, the test function thus becomes $\forall \delta \mathbf{U}$. By rearranging the terms of Eq. A.4 and writing the weak form for one element,

$$\begin{aligned} \int_{\Omega_e} k_1^2 \left(\mu \delta \mathbf{U}_2^T \mathbf{M}^{(e)} \mathbf{U}_2 + (\lambda + 2\mu) \delta \mathbf{U}_1^T \mathbf{M}^{(e)} \mathbf{U}_1 \right) + ik_1 \left(\mu \delta \mathbf{U}_2^T \mathbf{C}_1^{(e)} \mathbf{U} - \mu \delta \mathbf{U}_1^T \mathbf{C}_2^{(e)} \mathbf{U}_2 \right. \\ \left. + \lambda \delta \mathbf{U}_1^T \mathbf{C}_1^{(e)} \mathbf{U}_2 - \lambda \delta \mathbf{U}_2^T \mathbf{C}_2^{(e)} \mathbf{U}_1 \right) + \mu \delta \mathbf{U}_1^T \mathbf{K}^{(e)} \mathbf{U}_1 + (\lambda + 2\mu) \delta \mathbf{U}_2^T \mathbf{K}^{(e)} \mathbf{U}_2 \\ - \rho\omega^2 \delta \mathbf{U}_1^T \mathbf{M}^{(e)} \mathbf{U}_1 - \rho\omega^2 \delta \mathbf{U}_2^T \mathbf{M}^{(e)} \mathbf{U}_2 \, d\Omega_e = 0 \end{aligned} \quad (\text{A.6})$$

where the elementary matrices are,

$$\begin{aligned} \mathbf{M}^{(e)} &= \frac{b}{2} \int_{-1}^1 \mathbf{N}^T \mathbf{N} \, d\xi, \quad \mathbf{K}^{(e)} = \frac{2}{b} \int_{-1}^1 \nabla \mathbf{N}^T \nabla \mathbf{N} \, d\xi, \\ \mathbf{C}_1^{(e)} &= \int_{-1}^1 \mathbf{N}^T \nabla \mathbf{N} \, d\xi, \quad \mathbf{C}_2^{(e)} = \int_{-1}^1 \nabla^T \mathbf{N}^T \mathbf{N} \mathbf{U} \, d\xi, \end{aligned} \quad (\text{A.7})$$

In Eq. A.6, the dependance on k_1 was highlighted and terms were sorted depending on their order. The elementary matrices should be assembled into the global matrices and then, following an analogous procedure to Chapter. ??, the general form for the problem becomes,

$$\left(k_1^2 \mathbf{A}_2 + ik_1 \mathbf{A}_1 + \mathbf{A}_0 - \omega^2 \mathbf{M} \right) \mathbf{U} = 0. \quad (\text{A.8})$$

It can easily be rewritten as a generalized eigenvalue problem,

$$\left[\begin{pmatrix} -A_1 & A_0 - \omega^2 M \\ I & 0 \end{pmatrix} - k_1 \begin{pmatrix} A_2 & 0 \\ 0 & I \end{pmatrix} \right] \begin{pmatrix} k_1 U \\ U \end{pmatrix} = 0, \quad (\text{A.9})$$

which solving is thus quite straightforward.

A.2. Results and convergence comparison

Analytical results are obtained by applying the root-finding approach using the Müller method presented in the paper. Solutions are sought from the classical Lamb modes equations, derived in many books such as Royer. Figure 1.4a) shows the results of the three methods for a given frequency range. They all match well. In order to compare the two numerical methods in play, a brief convergence study has been done using the analytical results from the root-finding method as a reference.




Fig. 1.4: a) Dispersion relation for the Lamb modes with the root-finding results, alongside the spectral collocation and semi-analytical finite elements solutions. b) Convergence curve of the 2 methods at a given frequency $f = 4$ kHz. The multiple lines depicts the convergence of each wavenumber.

The convergence curve of the results given in Fig. 1.4b) is unsurprisingly in agreement with the literature. It is calculated at a frequency $f = 4$ kHz: the solutions along the dashed line in Fig 1.4a) are selected. The parameter n used for the discretization is shared between the two methods and corresponds to the number of elements taken for the discretization in each method. SAFE matrices have a size $2(2n + 1)$, while SCM matrices have a size $2n$. The discretization is swept from a number of nodes $n = 3$ to $n = 50$.

Matrix size for scm $4n$ while safe is $4(o \cdot n + 1)$ with o the order of Lobatto shape functions

The SCM convergence shows a steep slope and reaches a plateau around $n = 20$, while the SAFE curve follows the expected slope of a finite elements method that use second-order shape functions. When comparing at a given discretization order, the error from the SAFE is much lower than that of SCM by several orders of magnitude. In order to see comparable convergence, it would require to use higher-order shape functions or use spectral elements instead.

B | Details on the root-finding algorithm

B.1. The Müller method

equations, iterative scheme etc.

99

$$\begin{aligned}\Sigma_x &= \prod_{0 \leq i < j \leq 2} (x_j - x_i) = (x_0 - x_2)(x_1 - x_2)(x_0 - x_1) \\ a &= \frac{(x_1 - x_2)(f_0 - f_2) - (x_0 - x_2)(f_1 - f_2)}{\Sigma_x} \\ b &= \frac{(x_0 - x_2)^2(f_1 - f_2) - (x_1 - x_2)^2(f_0 - f_2)}{\Sigma_x} \\ c &= f_2\end{aligned}\tag{B.1}$$

$$f(x_3) = ax_3^2 + bx_3 + c\tag{B.2}$$

$$x_3 = x_2 - \frac{2c}{b + \text{sign}(b)\sqrt{b^2 - 4ac}}\tag{B.3}$$

$$\varepsilon_a = \left| \frac{x_3 - x_2}{x_3} \right|\tag{B.4}$$




Fig. 1.5: iteration muller

B.2. A complete routine for the automated solving of dispersion relations

In order to find solutions for modes in the form of complex wavenumbers k_1 , we use the previously derived system from Eq. (??), that can also be expressed as $\mathbf{M}(k_1, \omega)\mathbf{S} = 0$. The modes are found by finding the discrete set of k_1 that satisfy the singularity of $\mathbf{M}$ using Eq. ??

In practice, these solutions are found using a root-finding procedure, our own implementation of the Müller method¹⁰⁰. It is based on a parabolic interpolation to iteratively finds complex wavenumber solutions k_1 given a specific frequency ω from three initial guesses. Therefore, care has to be put into the initialization of the method. Since the system $\mathbf{M}$ is constructed from a finite elements scheme, computations will be all the more costly that a large number of iterations need to run before convergence is reached. The convergence criterion checks that threshold of the variation of the solution is below ε . In this paper, this criterion is taken with a magnitude around $\varepsilon = 10^{-13}$. Thus, the initialization of the method is done by evaluating the local minimas of a coarse mapping of the function in the complex plane. The latter is only computed every few frequency steps to save




Fig. 1.6: Description of the routine

computation time. Additionally, the matrix $\mathbf{D}_{ii}$ from Eq. (??) does not depend on k_1 and can thus be only evaluated once per frequency step, thus saving valuable computing resources.

Once the set of solutions has been obtained, each of the associated mode shapes can also be retrieved. Given a specific root $k_{1,j}$ that satisfies $\det(\mathbf{M}) = 0$, there is $\mathbf{M}(k_{1,j})\mathbf{S} = 0$, where the vector $\mathbf{S} = \ker(\mathbf{M}(k_{1,j}))$ is the nullspace of the matrix. In practice, the nullspace is computed using singular value decomposition (SVD), $\mathbf{M} = \mathbf{U}\mathbf{\Sigma}\mathbf{V}^\dagger$. The last right singular vectors, that is the last row of $\mathbf{V}^\dagger$ provide an orthonormal basis for the null space of $\mathbf{M}$, associated to the singular value $\sigma = \min(\mathbf{\Sigma})$. All state vectors among which S^t and S^b are obtained by selecting the appropriate rows of $\mathbf{V}^*$. By doing the whole procedure backwards, using Eq. (??) and then Eq. (??), we can retrieve the full degrees of freedom vector $\mathbf{p}$ (and normalized as $(p^i(x_1, x_2)/p^i(0, b))e^{ik_1x_1}$).

C

Overview of activities and scientific works during the thesis

C.1. Publications

- P1. M. Maréchal, A. Geslain, J.-P. Groby, V. Romero-García, and O. Dazel. “A General Spectral Collocation Method for Computing the Dispersion Relations of Guided Acoustic Waves in Multilayer Dissipative Structures”. *J. App. Phys.* 137.10 (2025), 104902.

C.2. Conferences

(ajouter titres des présentations)

- SAM 2022 Nimes, France, October 2022 (attendee)
- JJCAB Toulouse 2023, France, July 2023 (poster)
- SAPEM Sorrento, Italy, October 2023 (presenter)
- Séminaire de 2e année Centrale Nantes, France, April 2024 (presenter)
- SAM Aegina, Greece, May 2024 (presenter)
- INTERNOISE Nantes, France, August 2024 (attendee and volunteer)
- CFA 2025 Paris, France (presenter)

C.3. Workshops and training schools

- training school Acoustic Metamaterials Valencia Spain, UPV, November 2023
- lamb waves workshop

C.4. Teaching activities

D | Extended abstract in french

(en 10 à 15 k caractères)

References

1. M. Basner et al. "Auditory and Non-Auditory Effects of Noise on Health". *The Lancet* 383.9925 (2014), 1325–1332.
2. T. Münzel, F. P. Schmidt, S. Steven, J. Herzog, A. Daiber, and M. Sørensen. "Environmental Noise and the Cardiovascular System". *Journal of the American College of Cardiology* 71.6 (2018), 688–697.
3. O. Hahad et al. "Noise and Mental Health: Evidence, Mechanisms, and Consequences". *J Expo Sci Environ Epidemiol* 35.1 (2025), 16–23.
4. R. Sordello, O. Ratel, F. Flamerie De Lachapelle, C. Leger, A. Dambry, and S. Vanpeene. "Evidence of the Impact of Noise Pollution on Biodiversity: A Systematic Map". *Environ Evid* 9.1 (2020), 20.
5. C. Erbe, S. A. Marley, R. P. Schoeman, J. N. Smith, L. E. Trigg, and C. B. Embling. "The Effects of Ship Noise on Marine Mammals—A Review". *Front. Mar. Sci.* 6 (2019), 606.
6. J. M. Fields. "Effect of Personal and Situational Variables on Noise Annoyance in Residential Areas". *J. Acoust. Soc. Am.* 93.5 (1993), 2753–2763.
7. C. R. Benítez-Barrera, N. Ramirez-Esparza, A. García-Sierra, and E. Skoe. "Cultural Differences in Auditory Ecology". *JASA Express Letters* 3.8 (2023), 083601.
8. N. Ramírez-Esparza, S. Jiang, A. García-Sierra, E. Skoe, and C. R. Benítez-Barrera. "Effects of Cultural Dynamics on Everyday Acoustic Environments". *J. Acoust. Soc. Am.* 156.3 (2024), 1942–1951.
9. J.-C. Valière, B. Palazzo-Bertholon, J.-D. Polack, and P. Carvalho. "Acoustic Pots in Ancient and Medieval Buildings: Literary Analysis of Ancient Texts and Comparison with Recent Observations in French Churches". *Acta Acust.* 99.1 (2013), 70–81.
10. N. F. Declercq and C. S. A. Dekeyser. "Acoustic Diffraction Effects at the Hellenistic Amphitheater of Epidaurus: Seat Rows Responsible for the Marvelous Acoustics". *J. Acoust. Soc. Am.* 121.4 (2007), 2011–2022.
11. J.-F. Allard and N. Atalla. *Propagation of Sound in Porous Media: Modelling Sound Absorbing Materials*. 2nd ed. Hoboken, NJ: Wiley, 2009.
12. M. Bruneau. *Fundamentals of Acoustics*. London: ISTE, 2006.
13. J. Auriault, C. Geindreau, P. Royer, J. Bloch, C. Boutin, and J. Lewandowska. "Poromechanics II". *Rotterdam, Brookfield* (2002).
14. P. Liu and G.-F. Chen. *Porous materials: processing and applications*. Elsevier, 2014.
15. T. Bourbié, O. Coussy, and B. Zinszner. *Acoustique des milieux poreux*. 27. éditions Technip, 1986.
16. O. Coussy. *Mechanics and physics of porous solids*. John Wiley & Sons, 2011.
17. D. Lafarge. "Propagation du son dans les matériaux poreux à structure rigide saturés par un fluide viscothermique: Définition de paramètres géométriques, analogie électromagnétique, temps de relaxation". PhD thesis. Le Mans, 1993.
18. D. Lafarge, J. F. Allard, B. Brouard, C. Verhaegen, and W. Lauriks. "Characteristic dimensions and prediction at high frequencies of the surface impedance of porous layers". *The Journal of the Acoustical Society of America* 93.5 (1993), 2474–2478.
19. D. Lafarge, P. Lemarinier, J. F. Allard, and V. Tarnow. "Dynamic Compressibility of Air in Porous Structures at Audible Frequencies". *J. Acoust. Soc. Am.* 102.4 (1997), 1995–2006.
20. A. Duclos, D. Lafarge, V. Pagneux, and A. Cortis. "Multiple scattering and visco-thermal effects". *The Journal of the Acoustical Society of America* 120.5 (2006), 3282–3282.
21. B. Brouard, D. Lafarge, and J.-F. Allard. "A general method of modelling sound propagation in layered media". *Journal of Sound and Vibration* 183.1 (1995), 129–142.
22. V. G. Veselago. "THE ELECTRODYNAMICS OF SUBSTANCES WITH SIMULTANEOUSLY NEGATIVE VALUES OF ϵ AND μ ". *Sov. Phys. Usp.* 10.4 (1968), 509–514.
23. P. Russell. "Photonic Crystal Fibers". *Science* 299.5605 (2003), 358–362.
24. E. Yablonovitch. "Inhibited Spontaneous Emission in Solid-State Physics and Electronics". *Phys. Rev. Lett.* 58.20 (1987), 2059–2062.
25. M. Sigalas and E. Economou. "Elastic and Acoustic Wave Band Structure". *J. Sound Vib.* 158.2 (1992), 377–382.
26. R. Martínez-Sala, J. Sancho, J. V. Sánchez, V. Gómez, J. Llinares, and F. Meseguer. "Sound Attenuation by Sculpture". *Nature* 378.6554 (1995), 241–241.
27. N. Jiménez, O. Umnova, and J.-P. Groby, eds. *Acoustic Waves in Periodic Structures, Metamaterials, and Porous Media: From Fundamentals to Industrial Applications*. Vol. 143. Topics in Applied Physics. Cham: Springer International Publishing, 2021.
28. X. Zhou, X. Wang, and F. Xin. "Ultrathin Acoustic Metamaterial as Super Absorber for Broadband Low-Frequency Underwater Sound". *Sci Rep* 13.1 (2023), 7983.
29. I. Prasetyo, I. Sihar, and A. S. Sudarsono. "Realization of a Thin and Broadband Microperforated Panel (MPP) Sound Absorber". *Applied Acoustics* 183 (2021), 108295.
30. V. Romero-García and A. Hladky-Hennion. *Fundamentals and Applications of Acoustic Metamaterials: From Seismic to Radio Frequency*. ISTE Wiley, 2019.

31. P. A. Deymier. *Acoustic metamaterials and phononic crystals*. Vol. 173. Springer Science & Business Media, 2013.
32. N. Jiménez, O. Umnova, and J.-P. Groby. “Acoustic Waves in Periodic Structures, Metamaterials, and Porous Media” (2021).
33. Z. Liu et al. “Locally Resonant Sonic Materials” ().
34. N. Jiménez, V. Romero-García, A. Cebrecos, R. Picó, V. J. Sánchez-Morcillo, and L. M. Garcia-Raffi. “Broadband Quasi Perfect Absorption Using Chirped Multi-Layer Porous Materials”. *AIP Advances* 6.12 (2016), 121605.
35. Y. Li and B. M. Assouar. “Acoustic Metasurface-Based Perfect Absorber with Deep Subwavelength Thickness”. *Appl. Phys. Lett.* 108.6 (2016), 063502.
36. K. Y. Bliokh, Y. P. Bliokh, V. Freilikher, S. Savel'ev, and F. Nori. “Colloquium: Unusual resonators: Plasmonics, metamaterials, and random media”. *Reviews of Modern Physics* 80.4 (2008), 1201.
37. J.-P. Groby, R. Pommier, and Y. Aurégan. “Use of slow sound to design perfect and broadband passive sound absorbing materials”. *The Journal of the Acoustical Society of America* 139.4 (2016), 1660–1671.
38. N. Jiménez, V. Romero-García, V. Pagneux, and J.-P. Groby. “Rainbow-trapping absorbers: Broadband, perfect and asymmetric sound absorption by subwavelength panels for transmission problems”. *Scientific reports* 7.1 (2017), 1–12.
39. V. Romero-García, G. Theocharis, O. Richoux, and V. Pagneux. “Use of complex frequency plane to design broadband and subwavelength absorbers”. *The Journal of the Acoustical Society of America* 139.6 (2016), 3395–3403.
40. V. Romero-García, G. Theocharis, O. Richoux, A. Merkel, V. Tournat, and V. Pagneux. “Perfect and broadband acoustic absorption by critically coupled sub-wavelength resonators”. *Sci. Rep.* 6 (2016), 19519EP.
41. J. Guo, Y. Fang, R. Qu, Q. Liu, and X. Zhang. “An Extra-Broadband Compact Sound-Absorbing Structure Composing of Double-Layer Resonator with Multiple Perforations”. *J. Acoust. Soc. Am.* 150.2 (2021), 1370–1380.
42. M. Yang and P. Sheng. “Sound Absorption Structures: From Porous Media to Acoustic Metamaterials”. *Annual Review of Materials Research* 47.1 (2017), 83–114.
43. Y. Aurégan, M. Farooqui, and J.-P. Groby. “Low frequency sound attenuation in a flow duct using a thin slow sound material”. *The Journal of the Acoustical Society of America* 139.5 (2016), EL149–EL153.
44. J. Yang, J. S. Lee, H. R. Lee, Y. J. Kang, and Y. Y. Kim. “Slow-wave metamaterial open panels for efficient reduction of low-frequency sound transmission”. *Applied Physics Letters* 112.9 (2018), 091901.
45. J. Leng, F. Gautier, A. Pelat, R. Pico, J.-P. Groby, and V. Romero-García. “Limits of flexural wave absorption by open lossy resonators: reflection and transmission problems”. *New Journal of Physics* 21.5 (2019), 053003.
46. A. Lardeau, J.-P. Groby, and V. Romero-García. “Broadband transmission loss using the overlap of resonances in 3D sonic crystals”. *Crystals* 6.5 (2016), 51.
47. J. Yang, J. S. Lee, and Y. Y. Kim. “Metaporous Layer to Overcome the Thickness Constraint for Broadband Sound Absorption”. *J. Appl. Phys.* 117.17 (2015), 174903.
48. X. Wang, X. Luo, H. Zhao, and Z. Huang. “Acoustic perfect absorption and broadband insulation achieved by double-zero metamaterials”. *Applied Physics Letters* 112.2 (2018), 021901.
49. V. Romero-García, G. Theocharis, O. Richoux, and V. Pagneux. “Use of complex frequency plane to design broadband and subwavelength absorbers”. *The Journal of the Acoustical Society of America* 139.6 (2016), 3395–3403.
50. V. Romero-García et al. “Perfect absorption in mirror-symmetric acoustic metascreens”. *Physical Review Applied* 14.5 (2020), 054055.
51. H. Long, Y. Cheng, and X. Liu. “Asymmetric absorber with multiband and broadband for low-frequency sound”. *Applied Physics Letters* 111.14 (2017), 143502.
52. H. Long et al. “Tunable and broadband asymmetric sound absorptions with coupling of acoustic bright and dark modes”. *Journal of Sound and Vibration* 479 (2020), 115371.
53. M. Yang, G. Ma, Z. Yang, and P. Sheng. “Coupled Membranes with Doubly Negative Mass Density and Bulk Modulus”. *Phys. Rev. Lett.* 110.13 (2013), 134301.
54. Z. Yang, J. Mei, M. Yang, N. H. Chan, and P. Sheng. “Membrane-Type Acoustic Metamaterial with Negative Dynamic Mass”. *Phys. Rev. Lett.* 101.20 (2008), 204301.
55. A. Merkel, G. Theocharis, O. Richoux, V. Romero-García, and V. Pagneux. “Control of acoustic absorption in one-dimensional scattering by resonant scatterers”. *Applied Physics Letters* 107.24 (2015), 244102.
56. N. Jiménez, V. Romero-García, V. Pagneux, and J.-P. Groby. “Quasiperfect absorption by subwavelength acoustic panels in transmission using accumulation of resonances due to slow sound”. *Phys. Rev. B* 95 (1 2017), 014205.
57. J. R. Piper and S. Fan. “Total absorption in a graphene monolayer in the optical regime by critical coupling with a photonic crystal guided resonance”. *ACS Photonics* 1.4 (2014), 347–353.
58. C. Fu, X. Zhang, M. Yang, S. Xiao, and Z. Yang. “Hybrid membrane resonators for multiple frequency asymmetric absorption and reflection in large waveguide”. *Applied Physics Letters* 110.2 (2017), 021901.
59. J. Boulvert et al. “Optimally Graded Porous Material for Broadband Perfect Absorption of Sound”. *J. Appl. Phys.* 126.17 (2019), 175101.
60. J. Boulvert et al. “Acoustic modeling of micro-lattices obtained by additive manufacturing”. *Applied Acoustics* 164 (2020), 107244.
61. T. Cavalieri et al. “Acoustic wave propagation in effective graded fully anisotropic fluid layers”. *The Journal of the Acoustical Society of America* 146.5 (2019), 3400–3408.
62. T. Cavalieri et al. “Graded and Anisotropic Porous Materials for Broadband and Angular Maximal Acoustic Absorption”. *Materials* 13.20 (2020), 4605.
63. T. Cavalieri et al. “Rapid Additive Manufacturing of Optimized Anisotropic Metaporous Surfaces for Broadband Absorption”. *J. Appl. Phys.* 129.11 (2021), 115102.

64. A. Terroir, L. Schwan, T. Cavalieri, V. Romero-García, G. Gabard, and J.-P. Groby. “General method to retrieve all effective acoustic properties of fully-anisotropic fluid materials in three dimensional space”. *Journal of Applied Physics* 125.2 (2019), 025114.
65. J. Boulvert et al. “Folded metaporous material for sub-wavelength and broadband perfect sound absorption”. *Applied Physics Letters* 117.25 (2020), 251902.
66. J. Yang, J. S. Lee, and Y. Y. Kim. “Metaporous Layer to Overcome the Thickness Constraint for Broadband Sound Absorption”. *Journal of Applied Physics* 117.17 (2015).
67. X. Liu, M. Duan, M. Liu, F. Xin, and C. Zhang. “Acoustic Labyrinthine Porous Metamaterials for Subwavelength Low-Frequency Sound Absorption”. *Journal of Applied Physics* 129.19 (2021), 195103.
68. S. Kuznetsova, S. Deleplanque, F. Allein, B. Dubus, and M. Miniaci. “Hierarchical Meta-Porous Materials as Sound Absorbers”. *Proc. R. Soc. A* 480.2301 (2024), 20230831.
69. J.-P. Groby, O. Dazel, A. Duclos, L. Boeckx, and W. Lauriks. “Quasi-total absorption peak by use of a backed rigid frame porous layer with circular periodic inclusions embedded”. *arXiv preprint arXiv:1007.3177* (2010).
70. J.-P. Groby, O. Dazel, A. Duclos, L. Boeckx, and L. Kelders. “Enhancing the Absorption Coefficient of a Backed Rigid Frame Porous Layer by Embedding Circular Periodic Inclusions”. *J. Acoust. Soc. Am.* 130.6 (2011), 3771–3780.
71. C. Lagarrigue, J. P. Groby, V. Tournat, O. Dazel, and O. Umnova. “Absorption of Sound by Porous Layers with Embedded Periodic Arrays of Resonant Inclusions”. *J. Acoust. Soc. Am.* 134.6 (2013), 4670–4680.
72. J.-P. Groby, C. Lagarrigue, B. Brouard, O. Dazel, V. Tournat, and B. Nennig. “Using simple shape three-dimensional rigid inclusions to enhance porous layer absorption”. *The Journal of the Acoustical Society of America* 136.3 (2014), 1139–1148.
73. J.-P. Groby, A. Wirgin, and E. Ogam. “Acoustic response of a periodic distribution of macroscopic inclusions within a rigid frame porous plate”. *Waves in Random and Complex Media* 18.3 (2008), 409–433.
74. L. De Ryck et al. “Acoustic wave propagation and internal fields in rigid frame macroscopically inhomogeneous porous media”. *Journal of Applied Physics* 102.2 (2007), 024910.
75. J.-P. Groby, C. Lagarrigue, B. Brouard, O. Dazel, V. Tournat, and B. Nennig. “Enhancing the Absorption Properties of Acoustic Porous Plates by Periodically Embedding Helmholtz Resonators”. *J. Acoust. Soc. Am.* 137.1 (2015), 273–280.
76. Y. Zhou, D. Li, Y. Li, and T. Hao. “Perfect Acoustic Absorption by Subwavelength Metaporous Composite”. *Applied Physics Letters* 115.9 (2019), 093503.
77. L. Xiong, B. Nennig, Y. Aurégan, and W. Bi. “Sound Attenuation Optimization Using Metaporous Materials Tuned on Exceptional Points”. *J. Acoust. Soc. Am.* 142.4 (2017), 2288–2297.
78. T. Weisser et al. “Acoustic Behavior of a Rigidly Backed Poroelastic Layer with Periodic Resonant Inclusions by a Multiple Scattering Approach”. *J. Acoust. Soc. Am.* 139.2 (2016), 617–629.
79. M. Gaborit, L. Schwan, O. Dazel, J.-P. Groby, T. Weisser, and P. Göransson. “Coupling FEM, Bloch Waves and TMM in Meta Poroelastic Laminates”. *Acta Acust.* 104.2 (2018), 220–227.
80. C. Prada, D. Clorennec, and D. Royer. “Local Vibration of an Elastic Plate and Zero-Group Velocity Lamb Modes”. *The Journal of the Acoustical Society of America* 124.1 (2008), 203–212.
81. L. Boeckx, P. Leclaire, P. Khurana, C. Glorieux, W. Lauriks, and J. F. Allard. “Guided Elastic Waves in Porous Materials Saturated by Air under Lamb Conditions”. *J. Appl. Phys.* 97.9 (2005), 094911.
82. L. Boeckx, P. Leclaire, P. Khurana, C. Glorieux, W. Lauriks, and J. F. Allard. “Investigation of the Phase Velocities of Guided Acoustic Waves in Soft Porous Layers”. *J. Acoust. Soc. Am.* 117.2 (2005), 545–554.
83. D. A. Kiefer, M. Ponschab, and S. J. Rupitsch. “From Lamb Waves to Quasi-Guided Waves: On the Wave Field and Radiation of Elastic and Viscoelastic Plates”. *Unpublished* (2020).
84. M. Delany and E. Bazley. “Acoustical Properties of Fibrous Absorbent Materials”. *Applied Acoustics* 3.2 (1970), 105–116.
85. Y. Miki. “Acoustical Properties of Porous Materials. Modifications of Delany-Bazley Models”. *J. Acoust. Soc. Jpn. (E), J Acoust Soc Jpn E* 11.1 (1990), 19–24.
86. M. A. Biot. “Theory of Stress-Strain Relations in Anisotropic Viscoelasticity and Relaxation Phenomena”. *J. Appl. Phys.* 25.11 (1954), 1385–1391.
87. M. A. Biot. “Theory of Propagation of Elastic Waves in a Fluid-Saturated Porous Solid. II. Higher Frequency Range”. *en. The Journal of the Acoustical Society of America* 28.2 (1956), 179–191.
88. M. A. Biot. “Theory of Propagation of Elastic Waves in a Fluid-Saturated Porous Solid. I. Low-Frequency Range”. *J. Acoust. Soc. Am.* 28.2 (1956), 168–178.
89. M. A. Biot. “Theory of Propagation of Elastic Waves in a Fluid-Saturated Porous Solid. II. Higher Frequency Range”. *J. Acoust. Soc. Am.* 28.2 (1956), 179–191.
90. N. Atalla, R. Panneton, and P. Debergue. “A Mixed Displacement-Pressure Formulation for Poroelastic Materials”. *J. Acoust. Soc. Am.* 104.3 (1998), 1444–1452.
91. J. L. Rose. *Ultrasonic Guided Waves in Solid Media*. 1st ed. Cambridge University Press, 2014.
92. M. V. Predoi, M. Castaings, B. Hosten, and C. Bacon. “Wave Propagation along Transversely Periodic Structures”. *J. Acoust. Soc. Am.* 121.4 (2007), 1935–1944.
93. M. Castaings and M. Lowe. “Finite Element Model for Waves Guided along Solid Systems of Arbitrary Section Coupled to Infinite Solid Media”. *J. Acoust. Soc. Am.* 123.2 (2008), 696–708.
94. P. Zuo and Z. Fan. “SAFE-PML Approach for Modal Study of Waveguides with Arbitrary Cross Sections Immersed in Inviscid Fluid”. *J. Sound Vib.* 406 (2017), 181–196.
95. M. Mazzotti, I. Bartoli, A. Marzani, and E. Viola. “A Coupled SAFE-2.5D BEM Approach for the Dispersion Analysis of Damped Leaky Guided Waves in Embedded Waveguides of Arbitrary Cross-Section”. *Ultrasonics* 53.7 (2013), 1227–1241.
96. M. Mazzotti, A. Marzani, and I. Bartoli. “Dispersion Analysis of Leaky Guided Waves in Fluid-Loaded Waveguides of Generic Shape”. *Ultrasonics* 54.1 (2014), 408–418.

References

- 97. T. Hayashi and D. Inoue. “Calculation of Leaky Lamb Waves with a Semi-Analytical Finite Element Method”. *Ultrasonics* 54.6 (2014), 1460–1469.
- 98. D. A. Kiefer, M. Ponschab, S. J. Rupitsch, and M. Mayle. “Calculating the Full Leaky Lamb Wave Spectrum with Exact Fluid Interaction”. *J. Acoust. Soc. Am.* 145.6 (2019), 3341–3350.
- 99. S. C. Chapra and R. P. Canale. *Numerical Methods for Engineers*. 6th ed. Boston: McGraw-Hill Higher Education, 2010.
- 100. D. E. Muller. “A Method for Solving Algebraic Equations Using an Automatic Computer”. *Math. Comp.* 10.56 (1956), 208.