

Algorithm 1 SGD with spectral normalization

- Initialize $\tilde{\mathbf{u}}_l \in \mathcal{R}^{d_l}$ for $l = 1, \dots, L$ with a random vector (sampled from isotropic distribution).
- For each update and each layer l :

1. Apply power iteration method to a unnormalized weight W^l :

$$\tilde{\mathbf{v}}_l \leftarrow (W^l)^T \tilde{\mathbf{u}}_l / \|(W^l)^T \tilde{\mathbf{u}}_l\|_2 \quad (20)$$

$$\tilde{\mathbf{u}}_l \leftarrow W^l \tilde{\mathbf{v}}_l / \|W^l \tilde{\mathbf{v}}_l\|_2 \quad (21)$$

2. Calculate \bar{W}_{SN} with the spectral norm:

$$\bar{W}_{\text{SN}}^l(W^l) = W^l / \sigma(W^l), \text{ where } \sigma(W^l) = \tilde{\mathbf{u}}_l^T W^l \tilde{\mathbf{v}}_l \quad (22)$$

3. Update W^l with SGD on mini-batch dataset \mathcal{D}_M with a learning rate α :

$$W^l \leftarrow W^l - \alpha \nabla_{W^l} \ell(\bar{W}_{\text{SN}}^l(W^l), \mathcal{D}_M) \quad (23)$$