

Assignment Kit for Size Counting Standard



Personal Software Process for Engineers: Part I

The Software Engineering Institute (SEI)
is a federally funded research and development center
sponsored by the U.S. Department of Defense and
operated by Carnegie Mellon University.

This material approved for public release.
Distribution is limited by the Software Engineering Institute to attendees.

Personal Software Process for Engineers: Part I

Assignment Kit for the Size Counting Standard

Overview

Overview This assignment kit covers the following topics.

Section	See Page
Prerequisites	2
Objectives	2
Size counting standard requirements	3
Example 1: Pascal size counting standard	4
Example 2: C++ size counting standard	6
Example 3: another size counting standard	8
Evaluation criteria and suggestions	10
Size counting standard template	11

Prerequisites Prerequisite reading

- Chapter 3

Objectives The objectives of Size Counting standard are to

- define the size counting standards that are appropriate for the programming language and environment that you will use
- provide a basis for developing a coding standard
- prepare for developing a program to count program size

Size counting standard requirements

Size counting standard requirements

Produce and document a standard for counting program size for the language and environment that you will use in this course.

Submit the completed standard using the format in the template on page 11 with your program 2 assignment package.

Example 1: Pascal size counting standard

Overview

The template is a simplified version of the SEI measurement framework.

- Use this template to describe important items.
- Tailor it to fit your needs or language.

We'll walk through two example size counting standards. The first example is for logical LOC for Pascal programs.

Completing the header

Complete the header as follows:

- the name you give this standard
 - the language you are using
 - your name
 - the date you produced this standard (or revision)
-

Count type

Choices are logical and physical LOC.

- Logical LOC counts language elements.
- Physical LOC counts text lines.

For this counting standard, you are counting logical LOC.

Statement type

Use this section to define how you will count various types of statements.

Consider the following:

- How are you going to count procedure declarations and function prototypes?
 - How will you count compiler directives?
 - Will you count blank lines or comments? Why or why not?
-

Clarifications

A fully operational standard generally requires many notes and comments. Use the clarification section for this purpose.

Continued on next page

Pascal LOC Counting Standard Template

Definition Name: *Example Pascal LOC Std.*

Language: *Pascal*

Author: *W. S. Humphrey*

Date: *12/20/93*

Count Type	Type	Comments
Physical/Logical	<i>Logical</i>	
Statement Type	Included	Comments
Executable	<i>yes</i>	
Nonexecutable:		
Declarations	<i>yes</i>	
Compiler Directives	<i>yes</i>	
Comments	<i>no</i>	
Blank lines	<i>no</i>	
Other elements		
Clarifications		Examples/Cases
<i>Nulls</i>	<i>yes</i>	<i>continues, no-ops, ...</i>
<i>Empty statements</i>	<i>yes</i>	<i>“;;”, lone ;’s, etc.</i>
<i>Generic instantiators</i>		
<i>Begin...end</i>	<i>note 1</i>	<i>when executable</i>
<i>Begin...end</i>	<i>note 1</i>	<i>when not executable</i>
<i>Test conditions</i>	<i>yes</i>	
<i>Expression evaluation</i>	<i>yes</i>	<i>when used as sub program arguments</i>
<i>End symbols</i>	<i>notes 1,2</i>	<i>when terminating executable statements</i>
<i>End symbols</i>	<i>notes 1,2</i>	<i>when terminating declarations or bodies</i>
<i>Then, else, otherwise</i>	<i>note 1</i>	
<i>Elseif</i>	<i>note 1</i>	
<i>Keywords</i>	<i>notes 1,2</i>	<i>procedure division, interface, implementation</i>
<i>Labels</i>	<i>yes</i>	<i>branch destinations when on separate lines</i>
Note 1		<i>unless followed by ; or. or included in {}, count the following keywords once: BEGIN, CASE, DO, ELSE, END, IF, RECORD, REPEAT, THEN, UNTIL</i>
Note 2		<i>count every ; and . that is not within a {} or ()</i>
Note 3		<i>count each , between USES and the next ; or between VAR and the next ;</i>

Example 2: C++ LOC counting standard

**How many
LOC?**

Using the C++ LOC counting standard on page 7, how many LOC are in the following program fragment?

```
#include <stdio.h>

void main (void)
{
    int i,j;

    for (i = 0; i < 10; i++)
        for (j = 0; j < 10; j++)
            cout << i << ", " << j << endl;
}
```

Continued on next page

Example C++ Size Counting Standard

Definition Name: *Example C++ LOC std.*

Language: *C++*

Author: *W.S. Humphrey*

Date: *12/20/93*

Count Type	Type	Comments
Physical/Logical	<i>Logical</i>	
Statement Type	Included	Comments
Executable	<i>Yes</i>	
Nonexecutable:		
Declarations	<i>Yes, Notes 3, 4</i>	
Compiler Directives	<i>Yes, Note 4</i>	
Comments	<i>No</i>	
Blank lines	<i>No</i>	
Other elements		
Clarifications		Examples/Cases
<i>Empty statements</i>	<i>yes</i>	<i>";;", lone ;'s, etc.</i>
<i>Begin...end</i>	<i>note 1</i>	
<i>Expression evaluation</i>	<i>yes</i>	<i>when used as sub program arguments</i>
<i>End symbols</i>	<i>notes 1,2</i>	<i>for terminating executable statements, declarations, bodies</i>
<i>Then, else, otherwise</i>	<i>note 1</i>	
<i>Elseif</i>	<i>yes</i>	
<i>Keywords</i>	<i>yes</i>	<i>procedure division, interface, implementation</i>
<i>Labels</i>	<i>yes</i>	<i>branch destinations when on separate lines</i>
<i>Note 1</i>		<i>Count once every occurrence of the following key words: CASE, DO, ELSE, ENUM, FOR, IF, PRIVATE, PUBLIC, STRUCT, SWITCH, UNION, WHILE</i>
<i>Note 2</i>		<i>count once every occurrence of the following: ; , {} or {};</i>
<i>Note 3</i>		<i>count each variable or parameter declaration</i>
<i>Note 4</i>		<i>count once each #define, #ifdef, #include, etc. statement</i>

Example 3: another size counting standard

Overview

For this example standard, the class will select from among the following product categories.

- documents
- interface screens and forms
- database program elements
- maintenance fixes
- any other requested category

We'll then walk through developing the selected size counting standard.

Completing the standard

We'll then walk through the completion of the standard as a class exercise.

Continued on next page

Size Counting Standard Template

Definition Name: Programa 5

Language: Java

Author: Marely Jacome Hernandez

10/12/25

Date:

Count Type	Type	Comments
Physical/Logical	Logical	Se cuenta una línea de código lógica por cada sentencia completa del programa, independientemente de cuántas líneas físicas de texto ocupe en el archivo. Una sentencia dividida en varias líneas físicas se cuenta como 1.
Statement Type	Included	Comments
Executable	si	Se incluyen todas las sentencias que producen acción en tiempo de ejecución: asignaciones, llamadas a métodos, sentencias de control (if, else, for, while, return, break, etc.). Cada sentencia lógica cuenta como 1 LOC ejecutable.
Nonexecutable:	si	Se incluyen las declaraciones de clases, métodos, variables y constantes. Cada declaración cuenta como 1 LOC no ejecutable. Ejemplos: encabezado de clase <code>public class Logic</code> , encabezado de método <code>public void logica()</code> , declaración de variable <code>double dblPObjetivo;</code>
Declarations	si	Se incluyen las declaraciones de clases, métodos, variables y constantes.
Compiler Directives	no	El lenguaje Java no usa directivas de compilador del tipo <code>#define</code> o <code>#include</code> . Esta categoría no se cuenta en este programa.
Comments	no	Ningún comentario se cuenta como LOC. Incluye comentarios de una línea <code>//</code> y bloques <code>/* ... */</code> . Su propósito es documentar, no forman parte de la lógica ejecutable o declarativa.
Blank lines	no	Las líneas en blanco solo se usan para mejorar la legibilidad. No se cuentan como LOC, aunque contengan espacios o tabulaciones.
Other elements	si	Se cuentan llaves que están en una sola línea
Clarifications		Examples/Cases
		// Ejemplo: 1 LOC ejecutable aunque use 4 líneas físicas <code>pX = objSimpson.integrate(intNumSeg, dblX, intDOF);</code> // Conteo: 1 LOC ejecutable

		if (dblError > 0.0) { // 1 LOC ejecutable dblX = dblX + dblD; // 1 LOC ejecutable } else { // 1 LOC ejecutable (por el else) dblX = dblX - dblD; // 1 LOC ejecutable } // 0 LOC (solo llave)
		double dblPObjetivo; // 1 LOC no ejecutable (la declaración) dblPObjetivo = 0.20; // 1 LOC ejecutable dblX = dblX + dblD; // suma d a x // 1 LOC ejecutable (el comentario no agrega LOC)
Note		
Note		
Note		
Note		

Evaluation criteria and suggestions

Evaluation criteria

Your standard must be

- complete
 - legible
-

Suggestions

Keep your standards simple and short.

Do not hesitate to copy or build on the PSP materials.

Size Counting Standard Template

Definition Name: _____ Language: _____
 Author: _____ Date: _____

Count Type	Type	Comments
Physical/Logical		
Statement Type	Included	Comments
Executable		
Nonexecutable:		
Declarations		
Compiler Directives		
Comments		
Blank lines		
Other elements		
Clarifications		Examples/Cases
Note		
Note		
Note		
Note		