

Package ‘ezfun’

June 7, 2018

Title Emily C. Zabor's functions

Version 0.1.3

Date 2016-12-10

Description This package contains a number of functions that generate and format results of common procedures for clinical projects into table form for printing in R Markdown Word documents. A few basic utility functions for common procedures are also included.

Depends R (>= 3.1.0)

License GPL-2

LazyData TRUE

Imports survival, aod, cmprsk, clinfun, shiny, lme4

RoxygenNote 6.0.1

Author Emily Zabor [aut, cre]

Maintainer Emily Zabor <zabore@mskcc.org>

R topics documented:

bycont	2
ez_pal	2
lowerchar	3
mvcoxres	3
mvcrres	4
mvlogitres	4
ph2simonApp	5
scale_colour_ez	5
sdp	6
tab1	6
tab1_re	7
tabna	8
theme_ezbasic	8
todate	9
uvcoxph	10
uverr	11
uvlm	11
uvlogit	12
uvsurv	13
Index	14

bycont	<i>Table of one or more categorical variables by a single continuous variable</i>
--------	---

Description

bycont takes a list of categorical variables and returns median(min, max) of the single continuous variable within each level of each categorical variable. Computes Kruskal-Wallis p-values.

Usage

```
bycont(catvars, contvar, dat, pval = TRUE)
```

Arguments

catvars	is a list of the categorical variables for the rows of the table e.g. list('Gene1', 'Gene2')
contvar	is the continuous variable you want summarized by each categorical variable. Must be in quotes.
dat	is the dataset to use for analysis
pval	takes the value TRUE or FALSE indicating whether p-values should be computed. Defaults to TRUE. When TRUE, Kruskal-Wallis p-values are produced.

Value

Returns a dataframe

Author(s)

Emily C Zabor <zabore@mskcc.org>

ez_pal	<i>A custom color scale made by Emily Zabor, with help from Coolors app</i>
--------	---

Description

Basically copying code from hrbrmstr/hrbrthemes colors.r

Usage

```
ez_pal()
```

Examples

```
library(scales)
scales::show_col(ez_pal()(9))
```

lowerchar	<i>Convert to lowercase</i>
-----------	-----------------------------

Description

lowerchar converts the levels of character variables from upper or mixed case to lower case

Usage

```
lowerchar(dfname)
```

Arguments

dfname is the name of the dataframe on which to perform the action

Value

Nothing is returned from lowerchar, the action is simply performed on the columns of dataframe dfname

Author(s)

Emily C Zabor <zabore@mskcc.org>

mvcoxres	<i>Format results from multivariable Cox regression model</i>
----------	---

Description

mvcoxres takes a multivariable Cox regression object and formats the resulting HR (95% CI) and p-values into a table

Usage

```
mvcoxres(mod)
```

Arguments

mod is a multivariable Cox regression object

Value

Returns a dataframe

Author(s)

Emily C Zabor <zabore@mskcc.org>

`mvcrres`*Format results from multivariable competing risks regression model*

Description

`mvcrres` takes a multivariable competing risks regression object and puts the resulting HR (95% CI) and p-values into a table

Usage

```
mvcrres(mod)
```

Arguments

`mod` is a multivariable Cox regression object

Value

Returns a dataframe

Author(s)

Emily C Zabor <zabore@mskcc.org>

`mvlogitres`*Format results from multivariable Cox regression model*

Description

`mvlogitres` takes a multivariable logistic regression object and formats the resulting OR (95% CI) and p-values into a table

Usage

```
mvlogitres(mod)
```

Arguments

`mod` is a multivariable logistic regression object from `glm`

Value

Returns a dataframe

Author(s)

Emily C Zabor <zabore@mskcc.org>

`ph2simonApp`*Interactive Simon's 2-stage Shiny app*

Description

`ph2simonApp` is simply a Shiny interface for the `ph2simon` function from the `clinfun` package. No arguments need to be passed to the function.

Usage

```
ph2simonApp()
```

Value

The output includes 1) fields to enter the design parameters for the Simon 2-stage Phase II design, 2) R output with `ph2simon` results, 3) a paragraph interpreting the results, and 4) a plot of maximum versus expected number of patients indicating the optimal and minimax results.

`scale_colour_ez`*Discrete color & fill scales based on the ez palette*

Description

See `ez_pal`.

Usage

```
scale_colour_ez(...)
```

```
scale_color_ez(...)
```

```
scale_fill_ez(...)
```

Arguments

... Other arguments passed on to `discrete_scale` to control name, limits, breaks, labels and so forth.

sdp	<i>Get p-value from survdiff()</i>
-----	------------------------------------

Description

sdp returns the p-value from the survdiff function

Usage

```
sdp(sd)
```

Arguments

sd is a survdiff object

Value

Returns a p-value rounded to 3 digits or "<.001" if the p-value is <.001

Author(s)

Emily C Zabor <zabore@mskcc.org>

tab1	<i>Table 1</i>
------	----------------

Description

tab1 takes lists of continuous and/or categorical variables and returns Median (spread) for continuous variables and N (%) for categorical variables. Produces a table with both an overall column and columns by another variable.

Usage

```
tab1(contvars, catvars, byvar, dat, col = TRUE, spread = "range",
     pval = TRUE, fisher = TRUE)
```

Arguments

contvars	is a list of the continuous variables you want in the rows e.g. list('Age'). Can be NULL.
catvars	is a list of the categorical variables you want in the rows e.g. list('Gender','Race'). Can be NULL.
byvar	is the categorical variable you want to tabulate by across the columns (needs to be in quotes). Can be NULL.
dat	is the dataset to use for analysis
col	takes the value TRUE or FALSE indicating whether you want column percent (TRUE, default) or row percent (FALSE)

spread	takes the value "range" or "iqr" indicating whether you want (min, max) or (Q1, Q3) in summaries of continuous variables. Defaults to "range".
pval	takes the value TRUE or FALSE indicating whether p-values should be included. Defaults to TRUE. If TRUE, <code>kruskal.test</code> p-values are produced for continuous variables and either <code>fisher.test</code> or <code>chisq.test</code> p-values are produced for categorical variables. See <code>param</code> for testing details for categorical variables.
fisher	takes the value TRUE or FALSE. If TRUE, <code>fisher.test</code> p-values are produced. If FALSE, <code>chisq.test</code> p-values are produced.

Value

Returns a dataframe. If there are warnings or errors from `kruskal.test`, `fisher.test`, or `chisq.test` then NA is returned in place of the p-value.

Author(s)

Emily C Zabor <zabore@mskcc.org>

tab1_re	<i>Table 1 with random effects model p-values</i>
---------	---

Description

`tab1_re` takes lists of continuous and/or categorical variables and returns Median (spread) for continuous variables and N (%) for categorical variables. Produces a table with both an overall column and columns by another variable. For a binary by variable only, it produces p-values from a random effects model.

Usage

```
tab1_re(contvars, catvars, byvar, re, dat, col = TRUE, spread = "range")
```

Arguments

contvars	is a list of the continuous variables you want in the rows e.g. <code>list('Age')</code> . Can be NULL.
catvars	is a list of the categorical variables you want in the rows e.g. <code>list('Gender','Race')</code> . Can be NULL.
byvar	is the categorical variable you want to tabulate by across the columns (needs to be in quotes). MUST BE 0/1 since it will be used as the outcome variable in <code>glmer</code> .
dat	is the dataset to use for analysis
col	takes the value TRUE or FALSE indicating whether you want column percent (TRUE, default) or row percent (FALSE)
spread	takes the value "range" or "iqr" indicating whether you want (min, max) or (Q1, Q3) in summaries of continuous variables. Defaults to "range".

Value

Returns a dataframe. If there are warnings or errors from `glmer` then NA is returned in place of the p-value.

Author(s)

Emily C Zabor <zabore@mskcc.org>

tabna	<i>Cross-tabulation with useNA = "ifany"</i>
-------	--

Description

tabna is an implementation of table with argument useNA = "ifany"

Usage

```
tabna(...)
```

Arguments

... the function takes any standard arguments to table

Details

See the help file for table for detailed information about possible arguments to the function

Value

tabna returns a contingency table with NAs included, if any

Author(s)

Emily C Zabor <zabore@mskcc.org>

theme_ezbasic	<i>Basic theme preferences for ggplot</i>
---------------	---

Description

Basic theme preferences for ggplot. Functionally a crib of <https://github.com/hrbrmstr/hrbrthemes/blob/master/R/theme-ipsum.r> with some default changes

Usage

```
theme_ezbasic(base_size = 11.5, plot_title_size = 16,
  plot_title_face = "plain", plot_title_margin = 10, subtitle_size = 13,
  subtitle_face = "plain", subtitle_margin = 15, strip_text_size = 12,
  strip_text_face = "plain", caption_size = 9, caption_face = "plain",
  caption_margin = 10, axis_text_size = base_size, axis_title_size = 9,
  axis_title_face = "plain", axis_title_just = "lt",
  plot_margin = margin(10, 10, 10, 10), grid_col = "#cccccc", grid = TRUE,
  axis_col = "#cccccc", axis = FALSE, ticks = FALSE,
  legend_title = FALSE, legend_bottom = TRUE, legend_just = "left")
```


Arguments

base_size	base font size
plot_title_face, plot_title_size, plot_title_margin	plot title face, size and margin
subtitle_face, subtitle_size	plot subtitle face and size
subtitle_margin	plot subtitle margin bottom (single numeric value)
strip_text_face, strip_text_size	facet label font face and size
caption_face, caption_size, caption_margin	plot caption face, size and margin
axis_text_size	font size of axis text
axis_title_face, axis_title_size	axis title font face and size
axis_title_just	axis title font justification, one of 'blmcr'.
plot_margin	plot margin (specify with [ggplot2::margin()])
grid_col, axis_col	grid & axis colors; both default to '#cccccc'
grid	panel grid ('TRUE', 'FALSE', or a combination of 'X', 'x', 'Y', 'y')
axis	add x or y axes? 'TRUE', 'FALSE', "'xy'"
ticks	ticks if 'TRUE' add ticks
legend_title	includes legend title if 'TRUE', defaults to 'FALSE'
legend_bottom	places legend at bottom if 'TRUE', places legend to default position if 'FALSE'
legend_just	legend justification, one of 'right', 'left', 'center'. Defaults to 'left'.

todate	<i>Convert to date format</i>
--------	-------------------------------

Description

todate converts any POSIXct format variables in the dataframe to date format

Usage

```
todate(dfname)
```

Arguments

dfname is the name of the dataframe on which to perform the action

Details

Note that this function will mainly apply to dataframes imported using the read_excel function from the readxl package. Dataframes imported using, for example, read.csv instead will have dates in character format and therefore todate will not apply.

Value

Nothing is returned from todote, the action is simply performed on the columns of dataframe dfname

Author(s)

Emily C Zabor <zabore@mskcc.org>

uvcoxph	<i>Table of univariable Cox regression results</i>
---------	--

Description

uvcoxph takes lists of continuous and/or categorical variables, runs a univariable coxph model for each, and puts the resulting HR (95% CI) and p-value into a table suitable for printing in a Word R Markdown file.

Usage

```
uvcoxph(contvars, catvars, event, time, dat, strata = NULL)
```

Arguments

contvars	is a list of the continuous variables you want in the rows e.g. list('Age')
catvars	is a list of the categorical variables you want in the rows e.g. list('Gender','Race')
event	is the event indicator (needs to be in quotes)
time	is the survival time variables (needs to be in quotes)
dat	is the dataset for analysis
strata	is a possible strata term for use in calculating the log-rank p-values. Defaults to NULL. Entries should be in quotes, e.g. "Surgeon"

Value

Returns a dataframe. If there are warnings or errors from coxph then blank rows are returned.

Author(s)

Emily C Zabor <zabore@mskcc.org>

uvcrr

*Table of univariable competing risks regression results***Description**

uvcrr takes lists of continuous and/or categorical variables, runs a univariable crr model for each, and puts the resulting HR (95% CI) and p-value into a table suitable for printing in a Word R Markdown file.

Usage

```
uvcrr(contvars, catvars, event, time, dat)
```

Arguments

contvars	is a list of the continuous variables you want in the rows e.g. list('Age')
catvars	is a list of the categorical variables you want in the rows e.g. list('Gender','Race')
event	is the event indicator (needs to be in quotes)
time	is the survival time variables (needs to be in quotes)
dat	is the dataset for analysis

Details

uvcrr uses all function defaults to crr. For example, the failure code is set to 1. See the help file for crr for additional details.

Value

Returns a dataframe. If there are warnings or errors from crr then blank rows are returned.

Author(s)

Emily C Zabor <zabore@mskcc.org>

uvlm

*Table of univariable linear regression results***Description**

uvlm takes lists of continuous and/or categorical variables, calls lm to run a linear regression model for each, and returns a table with Est (SE) and p-value for each variable that is suitable for printing in a Word R Markdown file.

Usage

```
uvlm(contvars, catvars, out, dat)
```

Arguments

contvars	is a list of the continuous variables you want in the rows e.g. list('Age')
catvars	is a list of the categorical variables you want in the rows e.g. list('Gender','Race')
out	is the continuous outcome variable (needs to be in quotes)
dat	is the dataset for analysis

Value

Returns a dataframe. If there are warnings or errors from `lm` then blank rows are returned.

Author(s)

Emily C Zabor <zabore@mskcc.org>

uvlogit

Table of univariable logistic regression results

Description

uvlogit takes lists of continuous and/or categorical variables, calls `glm` to run a logistic regression model for each, and returns a table with OR (95 Word R Markdown file).

Usage

```
uvlogit(contvars, catvars, out, dat)
```

Arguments

contvars	is a list of the continuous variables you want in the rows e.g. list('Age')
catvars	is a list of the categorical variables you want in the rows e.g. list('Gender','Race')
out	is the binary outcome variable. Must be coded 0/1. (needs to be in quotes)
dat	is the dataset for analysis

Value

Returns a dataframe. If there are warnings or errors from `glm` then blank rows are returned.

Author(s)

Emily C Zabor <zabore@mskcc.org>

uvsurv

Table of univariable survival analysis results

Description

uvsurv takes lists of continuous and/or categorical variables. For continuous variables, coxph returns HR (95% CI) and log-rank p-values. For categorical variables, coxph returns HR (95% CI) and log-rank p-values and survfit produces median survival (95% CI) and a survival estimate at a specified time. Results are put into a table suitable for printing in a Word R Markdown file.

Usage

```
uvsurv(contvars, catvars, event, time, test, dat, strata = NULL)
```

Arguments

contvars	is a list of the continuous variables you want in the rows e.g. list('Age')
catvars	is a list of the categorical variables you want in the rows e.g. list('Gender','Race')
event	is the survival event indicator (needs to be in quotes)
time	is the survival time variable (needs to be in quotes)
test	is the timepoint you would like to estimate, in whatever units the survival time is in
dat	is the dataset to use for analysis
strata	is a possible strata term for use in calculating the log-rank p-values. Defaults to NULL. Entries should be in quotes, e.g. "Surgeon"

Value

Returns a dataframe

Author(s)

Emily C Zabor <zabore@mskcc.org>

Index

bycont, [2](#)

discrete_scale, [5](#)

ez_pal, [2](#)

lowerchar, [3](#)

mvcoxres, [3](#)

mvccrrres, [4](#)

mvlogitres, [4](#)

ph2simonApp, [5](#)

scale_color_ez (scale_colour_ez), [5](#)

scale_colour_ez, [5](#)

scale_fill_ez (scale_colour_ez), [5](#)

sdp, [6](#)

tab1, [6](#)

tab1_re, [7](#)

tabna, [8](#)

theme_ezbasic, [8](#)

todate, [9](#)

uvcoxph, [10](#)

uvccrr, [11](#)

uvlm, [11](#)

uvlogit, [12](#)

uvsurv, [13](#)