

# Algorithms

## Lecture 20: Approximation Algorithms (Part 2)

Anxiao (Andrew) Jiang

## CH 35. Approximation Algorithms

### Traveling Salesman Problem (TSP)

**Input:** An undirected complete graph  $G=(V,E)$ ,  
where every edge  $(u, v) \in E$  has a  
non-negative integer weight  $w(u, v)$ .

**Output:** A Hamiltonian cycle of minimum weight.

#### TSP with Triangle Inequality

**Input:** An undirected complete graph  $G=(V,E)$ ,  
where every edge  $(u, v) \in E$  has a  
non-negative integer weight  $w(u, v)$ .

The edge weights satisfy the triangle inequality.


**Output:** A Hamiltonian cycle of minimum weight.

## CH 35. Approximation Algorithms

### Traveling Salesman Problem (TSP)

**Input:** An undirected complete graph  $G=(V,E)$ , where every edge  $(u,v) \in E$  has a non-negative integer weight  $w(u,v)$ .

**Output:** A Hamiltonian cycle of minimum weight.




Does this general TSP have any approximation algorithm?

#### TSP with Triangle Inequality

**Input:** An undirected complete graph  $G=(V,E)$ , where every edge  $(u,v) \in E$  has a non-negative integer weight  $w(u,v)$ .

The edge weights satisfy the triangle inequality.

**Output:** A Hamiltonian cycle of minimum weight.



The TSP with triangle inequality has a polynomial-time 2-approximation algorithm.

**Theorem:** If  $P \neq NP$ , then for **any constant**  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.

Even if  $\rho = 999^{999^{999^{999}}}$  (or any other huge number),  
there still cannot exist a polynomial-time  $\rho$ -approximation algorithm for TSP,  
unless  $P \neq NP$  (which most people consider to be unlike).

**Theorem:** If  $P \neq NP$ , then for **any constant**  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.

How to prove it? A hint: if we let  $\rho = 1$ ,  
the theorem becomes:

If  $P \neq NP$ , then TSP has no polynomial-time 1-approximation algorithm.



If  $P \neq NP$ , then TSP is not polynomial-time solvable.




$TSP \in NPC$ .

So the above **theorem** can actually be a generalization of proving TSP to be NP-Complete.


**Theorem:** If  $P \neq NP$ , then for **any constant**  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.

Proof:

Hamiltonian Cycle Problem:



Traveling Salesman Problem:




**Theorem:** If  $P \neq NP$ , then for **any constant**  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.

**Proof:** By contradiction: assume the  $\rho$ -approximation algorithm exists.


**Hamiltonian Cycle Problem:**

$G' = (V, E')$



**Traveling Salesman Problem:**

$G = (V, E)$



Black edges: weight 1

Red edges: weight  $\rho |V| + 1$


$G'$  has a Hamiltonian cycle  $\rightarrow$   $G$  has a Hamiltonian cycle of weight  $|V|$   $\rightarrow$  Using the  $\rho$ -approximation algorithm, we can find a Hamiltonian cycle of weight  $\leq \rho |V|$  in polynomial time.

**Theorem:** If  $P \neq NP$ , then for **any constant**  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.

**Proof:** By contradiction: assume the  $\rho$ -approximation algorithm exists.

**Hamiltonian Cycle Problem:**

**Traveling Salesman Problem:**




$G'$  has a Hamiltonian cycle  $\rightarrow$   $G$  has a Hamiltonian cycle of weight  $|V|$   $\rightarrow$  Using the  $\rho$ -approximation algorithm, we can find a Hamiltonian cycle of weight  $\leq \rho |V|$  in  $G$  in polynomial time.

$G'$  has no Hamiltonian cycle  $\rightarrow$  Any Hamiltonian cycle in  $G$  needs to use at least one red edge  
 $\rightarrow$  Any Hamiltonian cycle in  $G$  has weight  $\geq \rho |V| + 1 + |V| - 1 = (\rho + 1) |V|$   $\rightarrow$  Using the  $\rho$ -approximation algorithm, we find a Hamiltonian cycle of weight  $\geq (\rho + 1) |V|$  in  $G$  in polynomial time.





**Theorem:** If  $P \neq NP$ , then for **any constant**  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.




**Proof:** By contradiction: assume the  $\rho$ -approximation algorithm exists.

**Hamiltonian Cycle Problem:**  **Traveling Salesman Problem:**  
 $G' = (V, E')$   $G = (V, E)$

---

$G'$  has a Hamiltonian cycle   $G$  has a Hamiltonian cycle of weight  $|V|$   Using the  $\rho$ -approximation algorithm, we can find a Hamiltonian cycle of weight  $\leq \rho |V|$  in  $G$  in polynomial time.


---

$G'$  has no Hamiltonian cycle  Any Hamiltonian cycle in  $G$  needs to use at least one red edge  
 Any Hamiltonian cycle in  $G$  has weight  $\geq \rho |V| + 1 + |V| - 1 = (\rho + 1) |V|$   Using the  $\rho$ -approximation algorithm, we find a Hamiltonian cycle of weight  $\geq (\rho + 1) |V|$  in  $G$  in polynomial time.

---

**Theorem:** If  $P \neq NP$ , then for **any constant**  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.

**Proof:** By contradiction: assume the  $\rho$ -approximation algorithm exists.

**Hamiltonian Cycle Problem:**  $G' = (V, E')$   **Traveling Salesman Problem:**  $G = (V, E)$

---



$G'$  has a Hamiltonian cycle    Using the  $\rho$ -approximation algorithm, we can find a Hamiltonian cycle of weight  $\leq \rho |V|$  in  $G$  in polynomial time.

---

$G'$  has no Hamiltonian cycle    Using the  $\rho$ -approximation algorithm, we find a Hamiltonian cycle of weight  $\geq (\rho + 1) |V|$  in  $G$  in polynomial time.


---

We can solve the Hamiltonian Cycle Problem “exactly” in polynomial time by solving TSP approximately using the polynomial-time  $\rho$ -approximation algorithm:

- 1) If we find a Hamiltonian cycle of weight  $\leq \rho |V|$  in  $G$    $G'$  has a Hamiltonian cycle
- 2) If we find a Hamiltonian cycle of weight  $\geq (\rho + 1) |V|$  in  $G$    $G'$  has no Hamiltonian cycle

Theorem: If  $P \neq NP$ , then for any constant  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.




Proof: By contradiction: assume the  $\rho$ -approximation algorithm exists.

Hamiltonian Cycle Problem:  $G' = (V, E')$   Traveling Salesman Problem:  $G = (V, E)$

---

$G'$  has a Hamiltonian cycle    Using the  $\rho$ -approximation algorithm, we can find a Hamiltonian cycle of weight  $\leq \rho |V|$  in  $G$  in polynomial time.



---

$G'$  has no Hamiltonian cycle    Using the  $\rho$ -approximation algorithm, we find a Hamiltonian cycle of weight  $\geq (\rho + 1) |V|$  in  $G$  in polynomial time.

---

**We can solve the Hamiltonian Cycle Problem “exactly” in polynomial time**

by solving TSP approximately using the polynomial-time  $\rho$ -approximation algorithm:

- 1) If we find a Hamiltonian cycle of weight  $\leq \rho |V|$  in  $G$    $G'$  has a Hamiltonian cycle
- 2) If we find a Hamiltonian cycle of weight  $\geq (\rho + 1) |V|$  in  $G$    $G'$  has no Hamiltonian cycle

Theorem: If  $P \neq NP$ , then for any constant  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.

Proof: By contradiction: assume the  $\rho$ -approximation algorithm exists.

We can solve the Hamiltonian Cycle Problem “exactly” in polynomial time.

Theorem: If  $P \neq NP$ , then for any constant  $\rho \geq 1$ , there is NO polynomial-time  $\rho$ -approximation algorithm for the general TSP.

Proof: By contradiction: assume the  $\rho$ -approximation algorithm exists.

We can solve the Hamiltonian Cycle Problem “exactly” in polynomial time.

But we know the Hamiltonian Cycle Problem is NP-complete.

So it has to be

$$P = NP$$

which is a contradiction.


Q.E.D.

**Technique:** Linear Programming and Rounding for approximation

**Weighted Vertex Cover Problem:**

**Input:** An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has a weight  $w(v) > 0$ .

**Output:** A vertex cover of minimum total weight.




**Technique:** Linear Programming and Rounding for approximation

**Weighted Vertex Cover Problem:**

**Input:** An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has a weight  $w(v) > 0$ .

**Output:** A vertex cover of minimum total weight.

Weight of vertex cover: 6



## Technique: Linear Programming and Rounding for approximation

### Weighted Vertex Cover Problem:

**Input:** An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has weight  $w(v) > 0$ .

**Output:** A vertex cover of minimum total weight.

Our technique:

1. Formulate the problem as an integer programming problem.

Define variables:

For every node  $v \in V$ , define a variable

$$x(v) = \begin{cases} 1 & \text{if } v \text{ is in vertex cover} \\ 0 & \text{otherwise} \end{cases}$$



## Technique: Linear Programming and Rounding for approximation

### Weighted Vertex Cover Problem:

**Input:** An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has weight  $w(v) > 0$ .

**Output:** A vertex cover of minimum total weight.

Our technique:

1. Formulate the problem as an integer programming problem.

Define variables:

For every node  $v \in V$ , define a variable

$$x(v) = \begin{cases} 1 & \text{if } v \text{ is in vertex cover} \\ 0 & \text{otherwise} \end{cases}$$

Integer Programming Problem:

$$\text{minimize } \sum_{v \in V} w(v)x(v)$$

$$\text{s.t. for every edge } (u, v) \in E, \quad x(u) + x(v) \geq 1$$
$$\text{for every node } v \in V, \quad x(v) \in \{0,1\}$$

## Technique: Linear Programming and Rounding for approximation

### Weighted Vertex Cover Problem:

**Input:** An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has weight  $w(v) > 0$ .

**Output:** A vertex cover of minimum total weight.

Our technique:

1. Formulate the problem as an integer programming problem.
2. Relax condition to turn it into an LP.

### Integer Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad x(v) \in \{0, 1\} \end{aligned}$$



### Linear Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

## Technique: Linear Programming and Rounding for approximation

Weighted Vertex Cover Problem:

Input: An undirected graph  $G=(V,E)$ ,  
where every vertex  $v \in V$   
has weight  $w(v) > 0$ .


Output: A vertex cover of minimum  
total weight.

Our technique:

1. Formulate the problem as an integer programming problem.
2. Relax condition to turn it into an LP.
3. Solve the LP, then turn the LP solution to a solution of the original integer programming problem using “rounding”.

Integer Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad x(v) \in \{0, 1\} \end{aligned}$$



Linear Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

## Technique: Linear Programming and Rounding for approximation

Weighted Vertex Cover Problem:

Input: An undirected graph  $G=(V,E)$ ,  
where every vertex  $v \in V$   
has weight  $w(v) > 0$ .


Output: A vertex cover of minimum  
total weight.

Our technique:

1. Formulate the problem as an integer programming problem.
2. Relax condition to turn it into an LP.
3. Solve the LP, then turn the LP solution to a solution of the original integer programming problem using “rounding”.

Integer Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad x(v) \in \{0, 1\} \end{aligned}$$



Linear Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

## Technique: Linear Programming and Rounding for approximation

Weighted Vertex Cover Problem:

Input: An undirected graph  $G=(V,E)$ ,  
where every vertex  $v \in V$   
has weight  $w(v) > 0$ .

Output: A vertex cover of minimum  
total weight.

Our technique:

1. Formulate the problem as an integer programming problem.
2. Relax condition to turn it into an LP.
3. Solve the LP, then turn the LP solution to a solution of the original integer programming problem using “rounding”.

Integer Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad x(v) \in \{0,1\} \end{aligned}$$

Linear Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

Get a solution to the Integer  
Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$


## Technique: Linear Programming and Rounding for approximation

Weighted Vertex Cover Problem:

Input: An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has weight  $w(v) > 0$ .

Output: A vertex cover of minimum total weight.

Example:



Integer Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u,v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad x(v) \in \{0,1\} \end{aligned}$$

Linear Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u,v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$


## Technique: Linear Programming and Rounding for approximation

Weighted Vertex Cover Problem:

Input: An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has weight  $w(v) > 0$ .

Output: A vertex cover of minimum total weight.

Example:



Integer Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad x(v) \in \{0, 1\} \end{aligned}$$

Linear Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$


## Technique: Linear Programming and Rounding for approximation

Weighted Vertex Cover Problem:

Input: An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has weight  $w(v) > 0$ .

Output: A vertex cover of minimum total weight.

Example:



Integer Programming Problem:

$$\begin{aligned} &\text{minimize} \quad \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} \quad \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &\quad \quad \forall v \in V, \quad x(v) \in \{0, 1\} \end{aligned}$$

Linear Programming Problem:

$$\begin{aligned} &\text{minimize} \quad \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} \quad \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &\quad \quad \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$




## Technique: Linear Programming and Rounding for approximation

Weighted Vertex Cover Problem:

Input: An undirected graph  $G=(V,E)$ , where every vertex  $v \in V$  has weight  $w(v) > 0$ .

Output: A vertex cover of minimum total weight.

Example:



Integer Programming Problem:

$$\begin{aligned} &\text{minimize} \quad \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} \quad \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &\quad \quad \forall v \in V, \quad x(v) \in \{0, 1\} \end{aligned}$$

Linear Programming Problem:

$$\begin{aligned} &\text{minimize} \quad \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} \quad \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &\quad \quad \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

## Technique: Linear Programming and Rounding for approximation

Weighted Vertex Cover Problem:

Input: An undirected graph  $G=(V,E)$ ,  
where every vertex  $v \in V$   
has weight  $w(v) > 0$ .

Output: A vertex cover of minimum  
total weight.

Integer Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad x(v) \in \{0,1\} \end{aligned}$$

Linear Programming Problem:

$$\begin{aligned} &\text{minimize} && \sum_{v \in V} w(v)x(v) \\ &\text{s.t.} && \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ &&& \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{aligned}$$

Get a solution to the Integer  
Programming Problem:


$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

Why is this indeed a vertex cover?


Integer Programming Problem:

$$\begin{array}{ll}\text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad x(v) \in \{0, 1\}\end{array}$$



Linear Programming Problem:

$$\begin{array}{ll}\text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad 0 \leq x(v) \leq 1\end{array}$$



Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$


Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

---

**Theorem:** The above algorithm is a polynomial-time **2-approximation** algorithm.


Integer Programming Problem:

$$\begin{array}{ll}\text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad x(v) \in \{0, 1\}\end{array}$$



Linear Programming Problem:

$$\begin{array}{ll}\text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad 0 \leq x(v) \leq 1\end{array}$$



Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

---


**Theorem:** The above algorithm is a polynomial-time **2-approximation** algorithm.

Proof: **Weight of LP solution**

$$\bar{C} = \sum_{v \in V} w(v)\bar{x}(v)$$


Integer Programming Problem:

$$\begin{array}{ll} \text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad x(v) \in \{0, 1\} \end{array}$$



Linear Programming Problem:

$$\begin{array}{ll} \text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{array}$$



Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

---

**Theorem:** The above algorithm is a polynomial-time **2-approximation** algorithm.


Proof: **Weight of LP solution**

$$\bar{C} = \sum_{v \in V} w(v)\bar{x}(v)$$

**Weight of optimal vertex cover:  $C^*$**


Integer Programming Problem:

$$\begin{array}{ll}\text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad x(v) \in \{0, 1\}\end{array}$$



Linear Programming Problem:

$$\begin{array}{ll}\text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad 0 \leq x(v) \leq 1\end{array}$$



Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$

Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

---

**Theorem:** The above algorithm is a polynomial-time **2-approximation** algorithm.

Proof: **Weight of LP solution**

$$\bar{C} = \sum_{v \in V} w(v)\bar{x}(v)$$

**Weight of optimal vertex cover:  $C^*$**

$$\bar{C} \leq C^*$$


**Why?**

Integer Programming Problem:

$$\begin{array}{ll} \text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad x(v) \in \{0, 1\} \end{array}$$


Linear Programming Problem:

$$\begin{array}{ll} \text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{array}$$



Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$



Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

---

**Theorem:** The above algorithm is a polynomial-time **2-approximation** algorithm.

Proof: **Weight of LP solution**

$$\bar{C} = \sum_{v \in V} w(v)\bar{x}(v)$$

**Weight of optimal vertex cover:  $C^*$**

$$\bar{C} \leq C^*$$

**Weight of integer program solution**


$$C = \sum_{v \in V} w(v)x(v)$$

Integer Programming Problem:

$$\begin{array}{ll} \text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad x(v) \in \{0, 1\} \end{array}$$


Linear Programming Problem:

$$\begin{array}{ll} \text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{array}$$



Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$



Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

---

**Theorem:** The above algorithm is a polynomial-time **2-approximation** algorithm.

Proof: **Weight of LP solution**

$$\bar{C} = \sum_{v \in V} w(v)\bar{x}(v)$$

**Weight of optimal vertex cover:  $C^*$**

$$\bar{C} \leq C^*$$

**Weight of integer program solution**

$$C = \sum_{v \in V} w(v)x(v) \leq 2 \sum_{v \in V} w(v)\bar{x}(v)$$

**Why?**




Integer Programming Problem:

$$\begin{array}{ll} \text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad x(v) \in \{0, 1\} \end{array}$$


Linear Programming Problem:

$$\begin{array}{ll} \text{minimize} & \sum_{v \in V} w(v)x(v) \\ \text{s.t.} & \forall (u, v) \in E, \quad x(u) + x(v) \geq 1 \\ & \forall v \in V, \quad 0 \leq x(v) \leq 1 \end{array}$$



Get a solution to the Integer Programming Problem:

$$\forall v \in V, \quad x(v) = \begin{cases} 1 & \text{if } \bar{x}(v) \geq 0.5 \\ 0 & \text{if } \bar{x}(v) < 0.5 \end{cases}$$



Optimal solution to LP:  $\bar{x}(v) \quad \forall v \in V$

---

**Theorem:** The above algorithm is a polynomial-time **2-approximation** algorithm.

Proof: **Weight of LP solution**

$$\bar{C} = \sum_{v \in V} w(v)\bar{x}(v)$$

**Weight of optimal vertex cover:**  $C^*$

$$\bar{C} \leq C^*$$

**Weight of integer program solution**

$$C = \sum_{v \in V} w(v)x(v) \leq 2 \sum_{v \in V} w(v)\bar{x}(v) = 2\bar{C} \leq 2C^*$$

Vertex Cover Problem: 2-approximation.

TSP with triangle inequality: 2-approximation.

General TSP: no constant ratio approximation unless P=NP.

Set Covering Problem:  $\rho(n)$ -approximation

$$\rho(n) \rightarrow \infty \text{ as } n \rightarrow \infty$$

Subset Sum Problem:  $(1 + \epsilon)$ -approximation

$$\text{Time complexity } \text{poly}\left(n, \frac{1}{\epsilon}\right)$$

## CH. 35.4 Randomized Algorithm

Consider a maximization problem.

Let  $C^* > 0$  be the cost of an optimal solution.

Let  $C > 0$  be the expected cost of the solution of a randomized algorithm.

If for all instances, we have  $\frac{C^*}{C} \leq \rho$ ,

then the randomized algorithm is called a  $\rho$ -approximation randomized algorithm.

## CH. 35.4 Randomized Algorithm

Consider a **minimization** problem.

Let  $C^* > 0$  be the cost of an optimal solution.

Let  $C > 0$  be the expected cost of the solution of a randomized algorithm.

If for all instances, **we have**  $\frac{C}{C^*} \leq \rho$ ,

then the randomized algorithm is called a  $\rho$ -approximation randomized algorithm.

## CH. 35.4 Randomized Algorithm

### Max 3-CNF SAT Problem

**Input:** A 3-CNF Boolean formula of  $n$  variables and  $k$  clauses,  
Where every clause is the OR of 3 literals.

The 3 variables involved in each clause are distinct.

**Output:** A solution to the variables that maximizes the number of satisfied clauses.

## CH. 35.4 Randomized Algorithm

### Max 3-CNF SAT Problem

**Input:** A 3-CNF Boolean formula of  $n$  variables and  $k$  clauses,  
Where every clause is the OR of 3 literals.

The 3 variables involved in each clause are distinct.

**Output:** A solution to the variables that maximizes the number of satisfied clauses.

**Randomized Algorithm:**

For each variable, let it be 0 or 1 with probability 0.5 and 0.5.

## CH. 35.4 Randomized Algorithm

### Max 3-CNF SAT Problem

**Input:** A 3-CNF Boolean formula of  $n$  variables and  $k$  clauses,  
Where every clause is the OR of 3 literals.

The 3 variables involved in each clause are distinct.

**Output:** A solution to the variables that maximizes the number  
of satisfied clauses.

### Randomized Algorithm:

For each variable, let it be 0 or 1  
with probability 0.5 and 0.5.

**Theorem:** The algorithm is a polynomial-time  $\frac{8}{7}$ -approximation randomized algorithm.

## CH. 35.4 Randomized Algorithm

### Max 3-CNF SAT Problem

**Input:** A 3-CNF Boolean formula of  $n$  variables and  $k$  clauses,  
Where every clause is the OR of 3 literals.

The 3 variables involved in each clause are distinct.

**Output:** A solution to the variables that maximizes the number  
of satisfied clauses.

### Randomized Algorithm:

For each variable, let it be 0 or 1  
with probability 0.5 and 0.5.

**Theorem:** The algorithm is a polynomial-time  $\frac{8}{7}$ -approximation randomized algorithm.

**Proof:** Consider any clause in the 3-CNF formula.

Example of a clause

$$x_1 \vee \bar{x}_2 \vee \bar{x}_3$$



## CH. 35.4 Randomized Algorithm

### Max 3-CNF SAT Problem

**Input:** A 3-CNF Boolean formula of  $n$  variables and  $k$  clauses,  
Where every clause is the OR of 3 literals.

The 3 variables involved in each clause are distinct.

**Output:** A solution to the variables that maximizes the number  
of satisfied clauses.

### Randomized Algorithm:

For each variable, let it be 0 or 1  
with probability 0.5 and 0.5.

**Theorem:** The algorithm is a polynomial-time  $\frac{7}{8}$ -approximation randomized algorithm.

**Proof:** Consider any clause in the 3-CNF formula.

Probability that the clause is satisfied =  $\frac{7}{8}$

Example of a clause

$$x_1 \vee \bar{x}_2 \vee \bar{x}_3$$

## CH. 35.4 Randomized Algorithm

### Max 3-CNF SAT Problem

**Input:** A 3-CNF Boolean formula of  $n$  variables and  $k$  clauses,  
Where every clause is the OR of 3 literals.

The 3 variables involved in each clause are distinct.

**Output:** A solution to the variables that maximizes the number  
of satisfied clauses.

### Randomized Algorithm:

For each variable, let it be 0 or 1  
with probability 0.5 and 0.5.

**Theorem:** The algorithm is a polynomial-time  $\frac{7}{8}$ -approximation randomized algorithm.

**Proof:** Consider any clause in the 3-CNF formula.

Probability that the clause is satisfied =  $\frac{7}{8}$

Expected number of satisfied clauses  $C = \frac{7}{8} \cdot n$

Example of a clause

$$x_1 \vee \bar{x}_2 \vee \bar{x}_3$$

## CH. 35.4 Randomized Algorithm

### Max 3-CNF SAT Problem

**Input:** A 3-CNF Boolean formula of  $n$  variables and  $k$  clauses,  
Where every clause is the OR of 3 literals.

The 3 variables involved in each clause are distinct.

**Output:** A solution to the variables that maximizes the number  
of satisfied clauses.

### Randomized Algorithm:

For each variable, let it be 0 or 1  
with probability 0.5 and 0.5.

**Theorem:** The algorithm is a polynomial-time  $\frac{7}{8}$ -approximation randomized algorithm.

**Proof:** Consider any clause in the 3-CNF formula.

Probability that the clause is satisfied =  $\frac{7}{8}$

Expected number of satisfied clauses  $C = \frac{7}{8} \cdot n$

Number of satisfied clauses for an optimal solution  $C^* \leq n$

### Example of a clause

$$x_1 \vee \bar{x}_2 \vee \bar{x}_3$$

## CH. 35.4 Randomized Algorithm

### Max 3-CNF SAT Problem

**Input:** A 3-CNF Boolean formula of  $n$  variables and  $k$  clauses,  
Where every clause is the OR of 3 literals.

The 3 variables involved in each clause are distinct.

**Output:** A solution to the variables that maximizes the number  
of satisfied clauses.

### Randomized Algorithm:

For each variable, let it be 0 or 1  
with probability 0.5 and 0.5.

**Theorem:** The algorithm is a polynomial-time  $\frac{8}{7}$ -approximation randomized algorithm.

**Proof:** Consider any clause in the 3-CNF formula.

Probability that the clause is satisfied =  $\frac{7}{8}$

Expected number of satisfied clauses  $C = \frac{7}{8} \cdot k$

Number of satisfied clauses for an optimal solution  $C^* \leq k$

$$\frac{C^*}{C} \leq \frac{k}{\frac{7}{8} \cdot k} = \frac{8}{7} \approx 1.14$$

Example of a clause

$$x_1 \vee \bar{x}_2 \vee \bar{x}_3$$