

1. Classical Supervised ML

Model	Abbreviations / Variants	Notes
Logistic Regression	LR, L1, Two-Class LR	Most common (17/25 studies)
Decision Tree	DT, CART, Two-Class BDT	Simple, interpretable
Random Forest	RF, Two-Class DF, Bagging	Popular ensemble
Support Vector Machine	SVM, linear + RBF	High-dimensional data
K-Nearest Neighbors	KNN, k-NN	Non-parametric
Naive Bayes	NB, GNB, BNB	Gaussian / Bernoulli
Linear Discriminant Analysis	LDA	Rarely used
Nearest Centroid	NC	Rarely used

2. Ensemble Methods

Model	Variants	Notes
Gradient Boosting	GB, GBM	Boosting ensemble
XGBoost	XGB	Widely used boosting method
AdaBoost	AB	Boosting weak learners
LightGBM	LGBM	Fast GBM variant
CatBoost	GA-CatBoost	Handles categorical data
Bagging / Random Forest	—	RF is bagging-based
Stacking / Voting	—	Combines multiple models
TreeNet	—	Rarely used

3. Deep Learning / Neural Networks

Model	Notes
Feedforward Neural Networks / MLP / DNN	Main model for tabular data
CNN / Custom 7-layer CNN / DenseNet	Used for images (e.g., diabetic retinopathy)
RNN / LSTM	Time-series glucose / CGM data
Stack ANN / Stack CNN / Stack LSTM	Meta-model ensembles
DBN	Appears in related work only

4. Other / Rare Models

Model	Notes
CN2 rule inducer	Rule-based ML
SGD	Stochastic Gradient Descent (training method)
ET	Extra Trees (ensemble variant)