

We use IActionResult not ActionResult Because

It provides generalization and allows an action to return different types of results

```
public IActionResult mix(int x)
{
    if (x % 2 == 0)
        return View("view1");
    else
        return Content("Hi from Content");
}
```

Here it returned both ViewResult and ContentResult

HTTP Request (client to server)

URL : the resource

Method

Header

Body

Query string such as ?id=3

HTTP Response (server to client)

Status code

Headers

Body

HTTP Vs HTTPS

S stands for secure and it means transfer data using encryption to protect it instead of just transfer it using http

Builder Vs Dependency injection

Builder: used to configure and prepare the application before it runs

Dependency injection: providing a class with the objects it needs instead of creating them itself

Razor, mvc

Razor pages: page-focused , each page has its own UI

Mvc: separate the application into model,view,controller to achieve maintainability, reusability, cleaner code

Razor can handle a simple website while a complex/large system needs mvc

What is content type in response message

It tells the client what type of data the http response contains

Example:

/html →html page

/PNG →image

Minification:

Removes unnecessary spaces, comments, characters from css/js (smaller files= faster download)

Web bundling:

Combines multiple css/js files into fewer files (fewer files= fewer http requests = faster loading)

webpack:

a tool that bundles/optimizes js,css,and other

Lazy Loading:

Loads resources only when they are needed instead of loading everything initially (less data transferred at first = faster load for initial page)