


Fig. 2.— UKIDSS charts of the targets



4.2. Frame reduction.

IRpipe_gen.pro

- 1 read the log of the run (e.g. ../RAW/run-17B/IRframes/logall.out)
- 2 loop through the objects
- 3 quick fix of the fits header (add CRVAL1,CRVAL2,CTYPE1,CTYPE2,CRPIX1,CRPIX2). Subroutine: fixradec.pro. Using the Telescope Right Ascension and Declination (very rough, but enough to later identify pairs of stars in the 2MASS catalog).
- 4 Subroutine createsky. Reads the set of frames inherent to the observation considered(e.g. from binir171003.0078.fits to binir171003.0085.fits). Create a sky image with the routine resistant_mean (2 sigma clipping). Save the sky image (e.g. binir171003.0078.sky.fits). Subtract the sky from every frame (e.g. binir171003.0078.sub.fits) and divide by the flatfield (e.g. binir171003.0078.subff.fits). Flat-fields are automatically associated with the Julian day.

4.3. Source detection: IRpipen2_gen.pro

Organization of the database: pick the right files.

- read the list of runs ../MERGERUNS/rawtables.tab
- repeated observations of a target in the same run are identified and run one after another.
- run: algo, "star17ij", runnumber, flag_createastrometry(=0,1)
- read masterfile for the specified run e.g.,
../RAW/run-16B/IRframes/logall.out.edited
- read the masterfile "../MERGERUNS/master.tab"
to uniquely link the names to the coordinates
(Several obs carried by changing coordinates in the same OB, i.e. name remained unchanged).
This way we assign a name to a coordinates initially and any further associations is based on
coordinates. How many macros rewrite master.tab? several.
- read the 2mass catalog
(current catalog location in run1, but some stars are not in run1, then uses run2)
new directory to be tested IR/REDUCED/twomass/
- identify the star field in the localrun log
cc= number of observations
pp= indexes in the localrunlog
- looping trough the observations of the selected star
if the star was observed and of good quality (flagloc=1 in localrun log),
then continue
- run the submodule irpipen2 (irpipen2old+irpipen3old)
- mypairs (external) : find pairs of stars between the 2mass catalog and the detected
stars, to perform astrometric wcs. Do it only once and keep it [switch on with if(pair eq 1)]
- calibphot (external): performs a first guess calibration using the 2MASS pairs

4.3.1. Source detection: *IRpipen2.pro*

APERTURE photometry, relative shifts of tables, master table (x,y) (manual inspection of charts)

IRpipen2_gen.pro daophot list extracted in each frame (independently). Shift frame by frame located. masterlist should fix the problem. But you have to apply reverse shift.

- irpipen2,pp[j],input1, dirin,dirout
e,g, 9 ../RAW/run-16B/IRframes/logall.out.edited ../RAW/run-16B/IRframesRED/ ../RAW/run-16B/IRframesRED/
- Detections of stars with DAOPHOT-find per frame, in principle better than masterfile, best points per frame taken
- Aperture DAOPHOT-phot
fwhm=5
apr=[fwhm/2.0+1.5]
skyrad=[fwhm/2.0+2.0,fwhm/2.0+4.0]
- Typical every star is always observed with the same DIT and NDIT. ATTENTION DAOPHOT provides $\text{maginstrum} = -2.5 * \log(\text{counts}) + 25$.
 $\text{mag}[\text{xc}] = \text{mag}[\text{xc}] + 2.5 * \log_{10}(\text{time})$ taking into account the exposure times
- Shifting the coordinates over the reference coordinates (first frame,rough fix only one star)
- Register. Crosscorrelation, average xshift and yshift.
- Write table and save shift (also position of target star, meanwhile identify on a chart and click on it)
cursor, xstar, ystar
- input:../RAW/IRframes/logall.out.edited and frame.subff.fits
output: frame.subff.phot.tab

binir160809.0196.subff.phot.tab
binir160809.0197.subff.phot.tab
binir160809.0198.subff.phot.tab
binir160809.0199.subff.phot.tab
binir160809.0200.subff.phot.tab
binir160809.0201.subff.phot.tab

binir160809.0202.subff.phot.tab

binir160809.0203.subff.phot.tab

X	Y	mag	magerr	sky	skyerr	deltax	deltay	xxstar_ref	yystar_ref	sharp	round
310.	8.	21.	0.	-0.227	0.767	0.000	0.000	229.014	229.715	0.566	-0.613
213.	35.	20.	0.	1.362	0.810	0.000	0.000	229.014	229.715	0.516	-0.391

4.3.2. Source detection: *IRpipen3-gen.pro*

- `irpipen3_gen,pp[j],input1, dirin,dirout`
e.g, 9 `../RAW/run-16B/IRframes/logall.out.edited ../REDUCED/run-16B/IRframesRED/`
`../REDUCED/run-16B/IRframesRED/`
- for each field, loop through the frame-tables (`file.'subff.phot.tab',image.subff.fits`)
and crosscorrelate with the reference one, and build vector of multimeasures
- add missing stars (`xref, yref`)
- print a final list of stars detected at least in 3 frames (average and std are provided,
(e.g. `binir160809.0196.ave.tab`)
N X Y magave magerr skyave errsky nflux starxref staryref OBJECT
1 373.748 22.831 19.353 0.034 1.939 0.152 5 237.756 230.140 star86ij
2 450.623 139.334 19.337 0.025 2.160 0.199 7 237.756 230.140 star86ij
`magerr=sqrt(magave)/sqrt(n_elements(la))`
`skyave=sqrt(skyave)/sqrt(n_elements(la))`
- keep a file with the individual measurements,
(e.g.) `binir160809.0196.listall.tab`
- input: `../IRframes/logall.out.edited`
`frame.subff.phot.tab`
`image.subff.fits`
- output: `frame+'ave.tab'` average of collected measurements
`frame+'listall.tab'` list of all collected measurements

4.3.3. *Source detection: mypairs_gen.pro*

- 1) fix wcs of the reference frame
mypairs,pp[j],input1, dirin,dirout,dir2mass,root2mass
- input= ../IRframes/logall.out.edited
file.'subff.fits'
frame+ave.tab
root2mass=twomass.'+rooto+' .tab
- output= frame+'pairs.tab.edited'
RA-2mass DEC-2mass X Y N
273.993005 -16.974407 229.014 229.715 1
273.995133 -16.968340 306.073 258.522 2
274.001456 -16.968794 296.052 338.301 3
- fixwcsnewedited, ffhh, ffm, pairsfile
create frame0+subff_wcs.fits

4.3.4. Source detection: *calibphot.pro*

This macro performs a first calibration of the frames on 2MASS magnitudes. After, it follows a recabibration frame by frame (with respect to the first). To make sure we cut the catalogs roughly at the same point before crosscorrelating.

- `if(magx[pp[j]] gt 0 and flagx[pp[j]] eq 1) then begin`
- `calibphot,pp,input1,dirin,dirout,root2mass`
extract ra,dec, and Jmag of reference stars
- `input=../IRframes/logall.out.edited`
`frame.subff.fits`
`frame+'pairs.tab.edited'`
`frame+ave.tab`
- `fixwcs, dirout,ffhh, ffit, xfind, yfind,mag,raselt,decselt,jmagselt,jerrselt,root+string(newind,f='(f05.0)'),n`
2MASS precut at `sel =where(Jmag lt 15,cc)`
`ind=where(raselt ne 99.99d0 and jmagselt lt cutcal and jmagselt gt cutmax[pp])`
`res=moment(j2MASS[ind]-magInst[ind])` (magInst have been normalized to `texp=1s`)
2 sigma clipping in DELTA
used points are marked in red in the eps
`deltamag=res[0]=zeropoint`
- `print, eps files and updated final calibrated file of stars`
`output=frame+subff_wcs.fits` (for all frames)
`frame.ave2.tab` (added wcs)
`frame+ave2.eps` (delta J vs J2mass)
`frame+ave2.chart.eps` (map)
- `binir160809.0196.ave2.tab`
`id X Y mag magerr sky skyerr nframe xstarREF ystarREF starname rafind decfind raselt`
`decselt jmagselt jerrselt deltamag stddelta`
`deltamag=res[0]=zeropoint`

