

OS Lab 4

22F-3168

Mariam Fatima

Task 1:

```
#include<stdio.h>

#include<sys/types.h>

#include<unistd.h>

int main()

{

pid_t pid1, pid2;

int num1=5,num2=5;

//First fork to creat p1

pid1 = fork();

if (pid1 == 0)

{

    printf("this is child process p1 with pid: %d\n", getpid());

    int sum = num1+num2;

    printf("Sum of the two numbers is: %d\n", sum);

}

else{

    //Parent process P forks again to create P2

    pid2= fork();

    if(pid2==0)

    {

        printf("This is Child process P with pid: %d\n", getpid());

        int prd = num1*num2;

        printf("Product of the two numbers is: %d\n",prd);
```

```

    }

    else

    {

        printf("This is parent Process P wit Pid: %d\n",getpid());

    }

}
}

```

```

ns3@ns3-virtual-machine: ~
GNU nano 2.9.3 task1.c

#include<stdio.h>
#include<sys/types.h>
#include<unistd.h>
int main()
{
    pid_t pid1, pid2;
    int num1=5,num2=5;
    //First fork to creat p1
    pid1 = fork();
    if (pid1 == 0)
    {
        printf("this is child process p1 with pid: %d\n", getpid());
        int sum = num1+num2;
        printf("Sum of the two numbers is: %d\n", sum);
    }

    else{
        //Parent process P forks again to create P2
        pid2= fork();
        if(pid2==0)
        {
            printf("This is Child process P with pid: %d\n", getpid());
            int prd = num1*num2;
            printf("Product of the two numbers is: %d\n",prd);
        }
        else
        {
            printf("This is parent Process P wit Pid: %d\n",getpid());
        }
    }
}

```

Wrote 30 lines

^G Get Help ^O Write Out ^W Where Is ^K Cut Text ^J Justify ^C Cur Pos
 ^X Exit ^R Read File ^\ Replace ^U Uncut Text ^T To Spell ^_ Go To Line

: or press Ctrl+G.

```
task1.c (~/) - gedit
task1.c
Save

#include<stdio.h>
#include<sys/types.h>
#include<unistd.h>
int main()
{
    pid_t pid1, pid2;
    int num1=5,num2=5;
    //First fork to creat p1
    pid1 = fork();
    if (pid1 == 0)
    {
        printf("this is child process p1 with pid: %d\n", getpid());
        int sum = num1+num2;
        printf("Sum of the two numbers is: %d\n", sum);
    }
    else{
        //Parent process P forks again to create P2
        pid2= fork();
        if(pid2==0)
        {
            printf("This is Child process P with pid: %d\n", getpid());
            int prd = num1*num2;
            printf("Product of the two numbers is: %d\n",prd);
        }
        else
        {
            printf("This is parent Process P wit Pid: %d\n",getpid());
        }
    }
}
```

```
Tab Width: 8
Ln 1, Col 1
INS

ns3@ns3-virtual-machine:~$ nano task1.c
ns3@ns3-virtual-machine:~$ gcc -o q1 task1.c
ns3@ns3-virtual-machine:~$ ./q1
This is parent Process P wit Pid: 13222
ns3@ns3-virtual-machine:~$ This is Child process P with pid: 13224
Product of the two numbers is: 25
this is child process p1 with pid: 13223
Sum of the two numbers is: 10
```

Task2:

```
#include<stdio.h>
```

```
#include<sys/types.h>
```

```
#include<unistd.h>
```

```
int main() {  
    pid_t p, p1;  
    p = fork();  
    if (p == 0) {  
        printf("I am the P1 child Process %d and my parent id %d\n", getpid(), getppid());  
  
        p1 = fork();  
        if (p1 == 0) {  
            printf("I am the P2 child Process %d and my parent id %d\n", getpid(), getppid());  
        }  
    }  
    else if (p > 0) {  
        printf("I am the Parent Process P with PID %d\n", getpid());  
    }  
}
```

```
#include<stdio.h>  
#include<sys/types.h>  
#include<unistd.h>  
  
int main() {  
    pid_t p, p1;  
    p = fork();  
    if (p == 0) {  
        printf("I am the P1 child Process %d and my parent id %d\n", getpid(), getppid());  
  
        p1 = fork();  
        if (p1 == 0) {  
            printf("I am the P2 child Process %d and my parent id %d\n", getpid(), getppid());  
        }  
    }  
    else if (p > 0) {  
        printf("I am the Parent Process P with PID %d\n", getpid());  
    }  
}
```

```
ns3@ns3-virtual-machine:~$ gcc -o q2 task2.c
ns3@ns3-virtual-machine:~$ ./q2
I am the Parent Process P with PID 10990
ns3@ns3-virtual-machine:~$ I am the P1 child Process 10991 and my parent id 1544
I am the P2 child Process 10992 and my parent id 10991
```

Task 3:

```
#include<stdio.h>
```

```
#include <unistd.h>
```

```
int main() {
    printf("This is the initial program.\n");
```

```
    execl("./q3","q3",(char *)NULL);
```

```
}
```

```
#include <stdio.h>
```

```
int main() {
    int a = 5, b = 3;
    printf("This is the multiplication program.\n");
    printf("Multiplication of %d and %d is %d\n", a, b, a * b);
    return 0;
}
```

```
ns3@ns3-virtual-machine:~$ gcc -o q3_i task3_initial.c
ns3@ns3-virtual-machine:~$ gcc -o q3 task3.c
ns3@ns3-virtual-machine:~$ ./q3_i
This is the initial program.
This is the multiplication program.
Multiplication of 5 and 3 is 15
ns3@ns3-virtual-machine:~$
```

Task 4:

```
#include <stdio.h>

#include <sys/types.h>

#include <unistd.h>

#include <sys/wait.h>

int main() {

    pid_t pid1;

    pid1 = fork();

    if (pid == 0) {

        // Child process

        printf("C) Child is having ID %d\n", getpid());    // C

        printf("D) My Parent ID is %d\n", getppid());    // D

    } else {

        // Parent process

        printf("A) Parent (P) is having ID %d\n", getpid()); // A

        // Wait for the child process to complete

        wait(NULL);

        printf("B) ID of P's Child is %d\n", pid);    // B

    }

}
```

```
task4.c (~/) - gedit
Open task4.c Save

task3.c × task4.c ×

#include <stdio.h>
#include <sys/types.h>
#include <unistd.h>
#include <sys/wait.h>

int main() {
    pid_t pid1;
    pid1 = fork();

    if (pid1 == 0) {
        // Child process
        printf("C) Child is having ID %d\n", getpid()); // C
        printf("D) My Parent ID is %d\n", getppid()); // D
    } else {
        // Parent process
        printf("A) Parent (P) is having ID %d\n", getpid()); // A

        // Wait for the child process to complete
        wait(NULL);

        printf("B) ID of P's Child is %d\n", pid1); // B
    }
}
```

```
ns3@ns3-virtual-machine:~$ gcc -o q4 task4.c
ns3@ns3-virtual-machine:~$ ./q4
A) Parent (P) is having ID 11736
C) Child is having ID 11737
D) My Parent ID is 11736
B) ID of P's Child is 11737
ns3@ns3-virtual-machine:~$
```