


© 2020 The Coding School  
All rights reserved

Use of this recording is for personal use only. Copying, reproducing, distributing, posting or sharing this recording in any manner with any third party are prohibited under the terms of this registration. All rights not specifically licensed under the registration are reserved.




INTRO TO QUANTUM COMPUTING

LECTURE #10

# THE QUANTUM STACK & MATH REVIEW

FRANCISCA VASCONCELOS

1/10/2021



# Welcome to Semester 2!

Connect with us on **social media**, and let us know what you're most looking forward to!

- ★ **Facebook:** @thecodingschool
- ★ **Instagram:** @the\_coding\_school
- ★ **LinkedIn:** @the-coding-school
- ★ **Twitter:** @qubitbyqubit
- ★ **#QxQ #FutureQuantumLeader**

# ANNOUNCEMENTS

1. All course announcements will be communicated to students through **Canvas**
  - **Check Canvas** AT LEAST 1-2 times weekly
  - Change your Canvas **notification settings** to make sure you receive emails when we post an announcement
2. **Labs** begin this week! (starting Tuesday, going through Saturday)
  - Remember to submit your **attendance quiz** during lab! Attendance is mandatory
  - 3 excused absences, won't affect your grade

# ANNOUNCEMENTS

3. **Grades:** homework and attendance are both **required**
  - **Homework:** Your homework this week: Technical Assessment (only a *completion grade!*)
4. Course resources
  - **Piazza** for content-related questions answered by TAs
  - **Student Assistant Office Hours** (Fridays from 8:00 am-2:00 pm EST. Info posted later this week on Canvas).
  - **Friday Homework Review** (Fridays from 4:00-5:00 pm EST. Zoom link to be posted on Canvas).
5. Use **Discord** to participate in the course community [optional]

# ABOUT YOUR INSTRUCTOR, FRAN



MIT Engineering Quantum Systems (EQuS)

Intern at  
Rigetti Computing  
and  
Microsoft Research  
Quantum!



Teaching Quantum Computing at MIT!



MSc in Statistics at Oxford  
& teaching for Qubit x Qubit!



# TODAY'S LECTURE

## 1. The Quantum Stack

- a) Classical Software
- b) Quantum Software
- c) Quantum Program Compiler
- d) Classical Control Hardware
- e) Quantum Hardware

## 2. Math Review

- a) Vectors
- b) Complex Numbers & Exponentials
- c) Matrices
- d) Probability
- e) Quantum States & Dirac Notation
- f) Quantum Operations & Gates
- g) Vector & Hilbert Spaces
- h) Bases
- i) Eigenvectors & Eigenvalues



# THE QUANTUM STACK

# BEGINNING OF LAST SEMESTER...

## Lecture #1 (Classical Computing):

We learned abstractly and theoretically how computation is performed on classical computers...

- Binary Representation
- Boolean Logic

## Lecture #2 (Quantum Computing in the Abstract):

We learned abstractly, *from a physics perspective*, how quantum computers work and compare to classical computers...

- Qubits
- Quantum Superposition
- Quantum Gates
- Quantum Entanglement



**WATCH THIS LECTURE IF  
YOU HAVEN'T ALREADY!!!**

# TODAY'S LECTURE

We are going to learn abstractly, *from an EECS perspective*, how quantum computers work and compare to classical computers...





# FULL-STACK?

**Definition:** the entirety of a computer **system** or application, comprising both the **front end** and the **back end**.




# STACK?

How do computers work, from the highest ***level of abstraction*** (programming) to the lowest level of abstraction (transistors)?



# THE CLASSICAL COMPUTING STACK




# HARDWARE AND SOFTWARE

## HOW COMPUTERS WORK

### HARDWARE & SOFTWARE



<https://youtu.be/xnyFYiK2rSY>




# COMPILERS

A **compiler** is a program that translates computer code written in a source programming language to a target programming language. Oftentimes, the target language is machine code.

## PYTHON PROGRAM COMPIRATION TO MACHINE CODE



# THE CLASSICAL VS QUANTUM STACK



# THE QUANTUM COMPUTING STACK


QUANTUM SOFTWARE

CLASSICAL SOFTWARE

QUANTUM PROGRAM COMPILER

CLASSICAL CONTROL HARDWARE

QUANTUM HARDWARE



# THIS COURSE

QUANTUM SOFTWARE

CLASSICAL SOFTWARE



QUANTUM PROGRAM COMPILER

CLASSICAL CONTROL HARDWARE


QUANTUM HARDWARE

# QUANTUM HARDWARE


What will be the '*quantum transistor*'? Are we still in the '*quantum vacuum tube*' era?




Nuclear Magnetic Resonance




Trapped Ion




Majorana/Topological




Superconducting



Diamond NV Centers




Photonics




Neutral Atoms

# QUANTUM HARDWARE



1969 Four-Phase Systems AL1 Processor.



(Classical)




2017 IBM 7-Qubit Device

(Quantum)

# QUANTUM HARDWARE


IBM Q 5 Tenerife [ibmqx4]		ACTIVE: USERS
 		
Last Calibration: 2019-01-28 06:40:05		<b>Frequency (GHz)</b>
		<b>T1 (μs)</b>
		<b>T2 (μs)</b>
		<b>Gate error (<math>10^{-3}</math>)</b>
		<b>Readout error (<math>10^{-2}</math>)</b>
		<b>MultiQubit gate error (<math>10^{-2}</math>)</b>
		<b>Q0</b> <b>Q1</b> <b>Q2</b> <b>Q3</b> <b>Q4</b>
		5.25    5.30    5.35    5.43    5.18
		53.90    43.70    44.20    48.70    54.90
		39.60    26.20    31.00    19.60    13.70
		<b>CX1_0</b> <b>CX2_0</b> <b>CX3_2</b> <b>CX4_2</b>
		3.32    2.82    7.64    6.43
		<b>CX2_1</b> <b>CX3_4</b>
		3.86    4.82

# CLASSICAL CONTROL HARDWARE



Superconducting qubits are controlled via microwave pulse sequences. Different pulse shapes and lengths correspond to different quantum gates.

**Quantum Engineer's Guide to Superconducting Qubits [arXiv: [1904.06560](https://arxiv.org/abs/1904.06560)]**




ENIAC (first classical computer)  
**1950**




MIT EQuS Control Room (for quantum computers)  
**2020**

# QUANTUM PROGRAM COMPILER



# CLASSICAL SOFTWARE



PYTHON

## VARIABLE INSTANTIATION

```
string = "QxQ"  
integer = 5  
float = 6.7  
boolean = True
```

## FUNCTIONS

```
def add(a, b, c):  
    return a + b + c
```

## DATA STRUCTURES

```
list = [4, 'a', False, -20.9]
```

## FOR LOOPS

```
for a in ['hello', 'world', '!']:  
    print(a)
```

# CLASSICAL SOFTWARE

Python



SciPy and Numpy are Python **libraries** for scientific and numerical computations.




SciPy




NumPy

# QUANTUM SOFTWARE




## IBM QUANTUM EXPERIENCE


How can we implement large, complex circuits?



What about when we have large-scale quantum computers?



# QUANTUM SOFTWARE



**IBM QISKit**



a Python library for  
quantum computing!

```
Entrée [1]: from qiskit import *
# Generate a quantum circuit
qr = QuantumRegister(2)
cr = ClassicalRegister(2)
qc = QuantumCircuit(qr, cr)

qc.h(0)
qc.cx(0, 1)
qc.measure(qr, cr)

qc.draw(output='latex')
```

Out[1]:



# THE QUANTUM COMPUTING STACK


QUANTUM SOFTWARE



CLASSICAL SOFTWARE

QUANTUM PROGRAM COMPILER


CLASSICAL CONTROL HARDWARE

QUANTUM HARDWARE





# BREAK TIME!



# **SEMESTER 1**

# **MATH REVIEW**

# WHY ALL THE MATH?

*Quantum mechanics is a beautiful generalization of the laws of probability: a generalization based on the 2-norm rather than the 1-norm, and on complex numbers rather than nonnegative real numbers. It can be studied completely separately from its applications to physics (and indeed, doing so provides a good starting point for learning the physical applications later). This generalized probability theory leads naturally to a new model of computation – the quantum computing model – that challenges ideas about computation once considered *a priori*, and that theoretical computer scientists might have been driven to invent for their own purposes, even if there were no relation to physics. In short, while quantum mechanics was invented a century ago to solve technical problems in physics, today it can be fruitfully explained from an extremely different perspective: as part of the history of ideas, in math, logic, computation, and philosophy, about the limits of the knowable.*

**- Professor Scott Aaronson (UT Austin)**


(excerpt from *Quantum Computing Since Democritus*)



Image Source: ETH Zurich

# QUANTUM BIG IDEA

*Quantum states are represented mathematically as **complex vectors**!*



# LECTURE #3 - VECTORS

Vector Representation:

$$\vec{v} = \begin{pmatrix} v_1 \\ v_2 \\ \vdots \\ v_n \end{pmatrix}$$

***Every vector has a direction and a magnitude!***

2D Vector Direction:

$$\angle \vec{v} = \tan^{-1} \left( \frac{v_y}{v_x} \right)$$

Vector Magnitude:

$$\|\vec{v}\| = \sqrt{v_1^2 + v_2^2 + \cdots + v_n^2}$$

Vector Addition:

$$\vec{a} + \vec{b} = \begin{pmatrix} a_1 + b_1 \\ a_2 + b_2 \\ \vdots \\ a_n + b_n \end{pmatrix}$$

Vector-Scalar Multiplication:

$$c * \vec{v} = \begin{pmatrix} c * v_1 \\ c * v_2 \\ \vdots \\ c * v_n \end{pmatrix}$$

# LECTURE #3 – COMPLEX NUMBERS

The Imaginary Unit:

$$i = \sqrt{-1}$$

$$i^2 = -1$$

Complex Number:

$$a + i b$$

Complex Conjugation:

$$\overline{(a + i b)} = (a + ib)^* = (a - ib)$$

Complex Modulus:

$$|a + ib| = \sqrt{a^2 + b^2}$$


Complex  
Addition:

$$(a + i b) + (c + id) = (a + c) + i(b + d)$$

Complex  
Mult.:

$$(a + i b) * (c + id) = (ac - bd) + i(ad + bc)$$

# LECTURE #3 – COMPLEX EXPONENTIALS



Euler's formula:

$$e^{i\varphi} = \cos \varphi + i \sin \varphi$$

$$r = |z| = \sqrt{x^2 + y^2}$$

(vector radius)

Polar representation of complex numbers!

$$z = x + iy = |z|(\cos \varphi + i \sin \varphi) = re^{i\varphi}$$

$$\varphi = \tan^{-1} \left( \frac{y}{x} \right)$$

(vector angle)

Trig Relations:

$$\cos \varphi = \frac{e^{i\varphi} + e^{-i\varphi}}{2}$$

$$\sin \varphi = \frac{e^{i\varphi} - e^{-i\varphi}}{2i}$$

Multiplication:

$$e^{i\varphi} e^{i\theta} = e^{i(\varphi+\theta)}$$

Complex Conjugation:

$$\overline{e^{i\varphi}} = e^{-i\varphi}$$

Modulus

$$|z| = |re^{i\varphi}| = |r|$$

# LECTURE #4 – VECTOR SHAPE

VECTOR SHAPE:

( # rows × # cols )

COLUMN VECTOR

$$\begin{pmatrix} c_1 \\ c_2 \\ \vdots \\ c_n \end{pmatrix}$$

ROW VECTOR

$$(r_1 \quad r_2 \quad \dots \quad r_m)$$

SHAPE:

$$(n \times 1)$$

$$(1 \times m)$$


If  $\vec{v} = \begin{pmatrix} v_1 \\ v_2 \\ \vdots \\ v_n \end{pmatrix}$ , then its **transpose** is  $\vec{v}^T = (v_1 \quad v_2 \quad \dots \quad v_n)$

If  $\vec{w} = (w_1 \quad w_2 \quad \dots \quad w_n)$ , then its transpose is

$$\vec{w}^T = \begin{pmatrix} w_1 \\ w_2 \\ \vdots \\ w_n \end{pmatrix}$$

# QUANTUM BIG IDEA

The **inner product** enables us to compare quantum states and determine their **orthogonality**!



$$\langle \psi | \phi \rangle$$

# LECTURE #4 – INNER PRODUCT

The **inner product** is:

$$\langle \vec{v}, \vec{w} \rangle = \vec{v} \cdot \vec{w}^T = \sum_{i=1}^n v_i w_i$$

1. **vector x vector to scalar** mapping
2. tool for calculating vector **magnitude**
3. tool for vector **normalization**
4. tool for **geometrically comparing** vectors
5. tool for determining vector **orthogonality**

**MAGNITUDE:**

$$\langle \vec{v}, \vec{v} \rangle = \|\vec{v}\|^2$$

**NORMALIZATION:**

$$\frac{\vec{v}}{\sqrt{\langle \vec{v}, \vec{v} \rangle}} = \frac{\vec{v}}{\|\vec{v}\|}$$


**GEOMETRIC COMPARISON & VECTOR ORTHOGONALITY:**

$$\langle \vec{x}, \vec{y} \rangle = \|\vec{x}\| \|\vec{y}\| \cos(\theta)$$


where  $\theta = \angle(\vec{x}, \vec{y})$  is the angle between  $\vec{x}$  and  $\vec{y}$

$$\theta = \cos^{-1} \left( \frac{\langle \vec{x}, \vec{y} \rangle}{\|\vec{x}\| \|\vec{y}\|} \right)$$


**PARALLEL**



**ORTHOGONAL (PERPENDICULAR)**



**ANTI-PARALLEL**



$$\theta = 0^\circ$$

$$\langle \vec{x}, \vec{y} \rangle =$$

$$\theta = 90^\circ$$


$$\langle \vec{x}, \vec{y} \rangle =$$

$$\theta = 180^\circ$$

$$\langle \vec{x}, \vec{y} \rangle =$$

# QUANTUM BIG IDEA

A **linear combination** of quantum states is a **superposition**!



# LECTURE #4 – LINEAR COMBINATIONS



LINEAR COMBINATION OF FRUITS :


$$= 6 * \text{Strawberry} + 10 * \text{Green Olive} + 6 * \text{Blueberries} + \dots$$

LINEAR COMBINATION OF VECTORS :


$$\vec{v} = a_1 \vec{v}_1 + a_2 \vec{v}_2 + \dots + a_n \vec{v}_n = \sum_{i=1}^n a_i \vec{v}_i$$

# QUANTUM BIG IDEA

*The coefficients in a quantum superposition are **probability amplitudes**!*



$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle$$



# LECTURE #4 – COMPLEX VECTOR MANIPULATION

CONJUGATE TRANSPOSE:


$$\vec{v}^\dagger = (\vec{v}^T)^* = (\vec{v}^*)^T$$

To avoid negative and complex magnitudes (not physically possible!), we use the ***complex inner product***:

$$\langle \vec{v}, \vec{w} \rangle = \vec{v}^\dagger \vec{w} = v_1^* w_1 + \cdots + v_n^* w_n = \sum_{i=1}^n v_i^* w_i$$

# QUANTUM BIG IDEA

Quantum operations perform the computation in a quantum computer and are represented mathematically as **matrices**!



# LECTURE #4 – MATRICES

An  $(n \times m)$  matrix is written as,

$$X = \begin{pmatrix} x_{11} & x_{12} & \cdots & x_{1m} \\ x_{21} & x_{22} & \cdots & x_{2m} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \cdots & x_{nm} \end{pmatrix}$$

**MATRIX TRANSPOSE:**

$$X^T = \begin{pmatrix} x_{11} & x_{21} & \cdots & x_{n1} \\ x_{12} & x_{22} & \cdots & x_{n2} \\ \vdots & \vdots & \ddots & \vdots \\ x_{1m} & x_{2m} & \cdots & x_{nm} \end{pmatrix}$$

**MATRIX SHAPE:**

( # rows  $\times$  # cols )

$$X = \begin{pmatrix} x_{11} & x_{12} & \cdots & x_{1m} \\ x_{21} & x_{22} & \cdots & x_{2m} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \cdots & x_{nm} \end{pmatrix} \quad X = \begin{pmatrix} x_{11} & x_{12} & \cdots & x_{1m} \\ x_{21} & x_{22} & \cdots & x_{2m} \\ \vdots & \vdots & \ddots & \vdots \\ x_{n1} & x_{n2} & \cdots & x_{nm} \end{pmatrix}$$

**MATRIX CONJUGATE TRANSPOSE:**

$$X^\dagger = \begin{pmatrix} x_{11}^* & x_{21}^* & \cdots & x_{n1}^* \\ x_{12}^* & x_{22}^* & \cdots & x_{n2}^* \\ \vdots & \vdots & \ddots & \vdots \\ x_{1m}^* & x_{2m}^* & \cdots & x_{nm}^* \end{pmatrix}$$

# LECTURE #4 – MATRICES

MATRIX ADDITION:

$$A + B = \begin{pmatrix} a_{11} + b_{11} & a_{12} + b_{12} & \cdots & a_{1m} + b_{1m} \\ a_{21} + b_{21} & a_{22} + b_{22} & \cdots & a_{2m} + b_{2m} \\ \vdots & \vdots & \ddots & \vdots \\ a_{n1} + b_{n1} & a_{n2} + b_{n2} & \cdots & a_{nm} + b_{nm} \end{pmatrix}$$

MATRIX-VECTOR MULTIPLICATION:

$$A\vec{x} = \begin{pmatrix} \langle \vec{a}_1, \vec{x} \rangle \\ \langle \vec{a}_2, \vec{x} \rangle \\ \vdots \\ \langle \vec{a}_n, \vec{x} \rangle \end{pmatrix}$$

SCALAR-MATRIX MULTIPLICATION:

$$c * A = \begin{pmatrix} c * a_{11} & c * a_{12} & \cdots & c * a_{1m} \\ c * a_{21} & c * a_{22} & \cdots & c * a_{2m} \\ \vdots & \vdots & \ddots & \vdots \\ c * a_{n1} & c * a_{n2} & \cdots & c * a_{nm} \end{pmatrix}$$

MATRIX-MATRIX MULTIPLICATION:

$$AB = \begin{pmatrix} \langle \vec{a}_1, \vec{b}_1 \rangle & \langle \vec{a}_1, \vec{b}_2 \rangle & \cdots & \langle \vec{a}_1, \vec{b}_k \rangle \\ \langle \vec{a}_2, \vec{b}_1 \rangle & \langle \vec{a}_2, \vec{b}_2 \rangle & \cdots & \langle \vec{a}_2, \vec{b}_k \rangle \\ \vdots & \vdots & \ddots & \vdots \\ \langle \vec{a}_n, \vec{b}_1 \rangle & \langle \vec{a}_n, \vec{b}_2 \rangle & \cdots & \langle \vec{a}_n, \vec{b}_k \rangle \end{pmatrix}$$

MATRIX/VECTOR MULTIPLICATION SHAPE CHECK:  $(n \times m)(m \times k)$

# LECTURE #4 – MATRICES

IDENTITY MATRIX:

$$\mathbb{I} = \begin{pmatrix} 1 & 0 & \cdots & 0 \\ 0 & 1 & \cdots & 0 \\ \vdots & \vdots & \ddots & \vdots \\ 0 & 0 & \cdots & 1 \end{pmatrix}$$

$$\begin{aligned} X \mathbb{I} &= X \\ \vec{x} \mathbb{I} &= \vec{x} \\ \mathbb{I} Y &= Y \\ \mathbb{I} \vec{y} &= \vec{y} \end{aligned}$$

MATRIX INVERSION:


$$XX^{-1} = X^{-1}X = \mathbb{I}$$

# QUANTUM BIG IDEA

*Quantum measurement is **probabilistic**!*




Quantum State



# LECTURE #5 – SETS


Comparing sets:

$$A \subset B$$



Set **A** is a **subset** of set **B**.


$$A = B$$



$$A \subseteq B$$

$$A \supseteq B$$

$$A \supset B$$




Set **A** is **equal** to set **B**.

Set **A** is a **superset** of set **B**.


Operations on sets:

$$A \cup B$$




UNION (OR)

$$A \cap B$$



INTERSECT (AND)

$$A^c$$




COMPLEMENT (SUBTRACT)

# LECTURE #5 – PROBABILISTIC MODEL

A **probabilistic model** is a way to mathematically describe an unknown situation.

There are two key components: (1) **sample space** and (2) **probability law**.



# LECTURE #5 – AXIOMS OF PROBABILITY

Every probability law must satisfy the following axioms:

1. **NONNEGATIVITY** : The probability of every event in the sample space must be greater than or equal to zero.

$$\mathbb{P}(A) \geq 0, \text{ for every event } A$$

2. **ADDITIVITY** : If  $A$  and  $B$  are two *disjoint* events, then the probability of their union is the sum of their individual probabilities.


$$\mathbb{P}(A \cup B) = \mathbb{P}(A) + \mathbb{P}(B)$$

3. **NORMALIZATION** : The probability of the entire sample space ( $\Omega$ ) is equal to 1.

$$\mathbb{P}(\Omega) = 1$$

# LECTURE #5 – RANDOM VARIABLES

Experiment




EXPECTATION:

$$\langle X \rangle = \mathbb{E}[X] = \sum_x x \mathbb{P}(X = x)$$

VARIANCE:

$$\text{var}(X) = \mathbb{E}[(X - \mathbb{E}[X])^2] = \mathbb{E}[X^2] - \mathbb{E}[X]^2 = \sum_x (x - \mathbb{E}[X])^2 \mathbb{P}(X = x)$$

Law of Large Numbers



# QUANTUM BIG IDEA

**Dirac (*bra-ket*) notation** is how we mathematically represent quantum states!  
(An alternative linear algebra notation...)



# LECTURE #8 – DIRAC NOTATION & QUANTUM STATES

**Quantum states:**

Inputs and outputs of a quantum computer

A **ket** is simply a column vector!

$$|\psi\rangle = \begin{pmatrix} v_1 \\ v_2 \\ \vdots \\ v_n \end{pmatrix}$$

A **bra** is the conjugate transpose of a ket (row vector)!

$$\langle \psi | = |\psi\rangle^\dagger = (v_1 \quad v_2 \quad \cdots \quad v_n)$$

**Superposition:**

$$|\psi\rangle = \alpha |0\rangle + \beta |1\rangle$$

**Overlap between two quantum states:**

braket (bra+ket):

$$\langle \psi | \phi \rangle$$

**Expectation** of quantum operation  $A$  with respect to state  $|\psi\rangle$ :


$$\langle \psi | A | \psi \rangle$$

States  $|\psi\rangle$  and  $|\phi\rangle$  are **orthogonal** if:  $\langle \psi | \phi \rangle =$

State  $|\psi\rangle$  is **normal** if:  $\langle \psi | \psi \rangle =$

# QUANTUM BIG IDEA

*Many quantum gates are **Hermitian** and **unitary**!*



Operator	Gate(s)	Matrix
Pauli-X (X)		$\oplus$ $\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$
Pauli-Y (Y)		$\begin{bmatrix} 0 & -i \\ i & 0 \end{bmatrix}$
Pauli-Z (Z)		$\begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix}$
Hadamard (H)		$\frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}$
Phase (S, P)		$\begin{bmatrix} 1 & 0 \\ 0 & i \end{bmatrix}$
$\pi/8$ (T)		$\begin{bmatrix} 1 & 0 \\ 0 & e^{i\pi/4} \end{bmatrix}$
Controlled Not (CNOT, CX)		$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{bmatrix}$
Controlled Z (CZ)		$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & -1 \end{bmatrix}$
SWAP		$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \end{bmatrix}$
Toffoli (CCNOT, CCX, TOFF)		$\begin{bmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 \end{bmatrix}$


# LECTURE #8 -QUANTUM OPERATIONS & GATES

## Quantum operations:


Perform the computation in a quantum computer

## Pauli operators:


$$\sigma_x = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix} \quad \text{Pauli-X}$$



$$\sigma_y = \begin{pmatrix} 0 & -i \\ i & 0 \end{pmatrix} \quad \text{Pauli-Y}$$



$$\sigma_z = \begin{pmatrix} 1 & 0 \\ 0 & -1 \end{pmatrix} \quad \text{Pauli-Z}$$



## Quantum operation properties:

- Linearity
- Can be composed
- Order matters

All observable operators are **Hermitian**:

$$A = A^\dagger$$

(operator is equal to its own conjugate transpose)


All reversible operations are **unitary**:

$$AA^\dagger = A^\dagger A = I$$

(conjugate transpose is matrix inverse)

# QUANTUM BIG IDEA

*Quantum states lie in **Hilbert spaces!***



# LECTURE #9 – VECTOR & HILBERT SPACES

A **vector space** is a collection of vectors which can be added and multiplied, adhering to the following axioms:

For all

$\vec{x}, \vec{y}, \vec{z} \in \mathcal{V}$

(where  $\mathcal{V}$  is a vector space)

$a, b \in \mathbb{C}$


1.  $\vec{x} + \vec{y} = \vec{y} + \vec{x}$
2.  $\vec{x} + (\vec{y} + \vec{z}) = (\vec{x} + \vec{y}) + \vec{z}$
3. There is a unique zero vector ( $\vec{0}$ ), such that  $\vec{x} + \vec{0} = \vec{x}$
4. For each  $\vec{x}$  there is a unique  $-\vec{x}$ , such that  $\vec{x} + (-\vec{x}) = \vec{0}$
5.  $1\vec{x} = \vec{x}$
6.  $(ab)\vec{x} = a(b\vec{x})$
7.  $a(\vec{x} + \vec{y}) = a\vec{x} + b\vec{x}$
8.  $(a + b)\vec{x} = a\vec{x} + b\vec{x}$

EXAMPLES

Quantum states lie in **Hilbert spaces**, which are just **vector space equipped with an inner product!**

# QUANTUM BIG IDEA

The **eigenvectors** of the Pauli matrices form **bases** for the quantum Hilbert space, corresponding to different measurement frames.



# LECTURE #9 – BASES

A **basis** for the vector space  $\mathcal{V}$  is the set of vectors  $\{\vec{v}_1, \vec{v}_2, \dots, \vec{v}_k\}$  having the following two properties at once:

1. The vectors are **linearly independent** (not too many vectors):

$$c_1\vec{v}_1 + c_2\vec{v}_2 + \cdots + c_k\vec{v}_k = \vec{0} \text{ only when } c_1 = c_2 = \cdots = c_k = 0$$

[Note: orthogonal vectors are linearly independent!!]

1. The vectors **span**  $\mathcal{V}$  (not too few vectors):

every vector  $\vec{v} \in \mathcal{V}$  can be expressed as  $\vec{v} = c_1\vec{v}_1 + c_2\vec{v}_2 + \cdots + c_k\vec{v}_k$

Thus, every vector in the vector space  $\mathcal{V}$  is a **unique** linear combination of the basis vectors.

However, every vector space has **infinitely** many bases...


# LECTURE #9 – EIGENVECTORS & EIGENVALUES

$$A\vec{v} = \lambda\vec{v}$$

*If  $v$  is an eigenvector of  $A$ , our matrix-vector multiplication simplifies to a scalar-vector multiplication!*

# INTRO TO QUANTUM MECHANICS...





© 2020 The Coding School  
All rights reserved

Use of this recording is for personal use only. Copying, reproducing, distributing, posting or sharing this recording in any manner with any third party are prohibited under the terms of this registration. All rights not specifically licensed under the registration are reserved.