```
mar@DESKTOP-C26IRMG:~$ mysqldump -u admin -p MARIANA > data-dump.sql
Enter password:
mar@DESKTOP-C26IRMG:~$ head -n 5 data-dump.sql
-- MariaDB dump 10.19  Distrib 10.6.12-MariaDB, for debian-linux-gnu (x86_64)
--
-- Host: localhost    Database: MARIANA
-- ------------------------------------------------------
-- Server version       10.6.12-MariaDB-0ubuntu0.22.04.1
mar@DESKTOP-C26IRMG:~$ sudo mysql -u admin -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 99
Server version: 10.6.12-MariaDB-0ubuntu0.22.04.1 Ubuntu 22.04

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> use MARIANA;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
MariaDB [MARIANA]> SHOW TABLES;
+-------------------+
| Tables_in_MARIANA |
+-------------------+
| products          |
| users             |
+-------------------+
2 rows in set (0.001 sec)
```

```
MariaDB [MARIANA]> SELECT * FROM products;
+----+--------+-------+-------+
| id | name   | price | level |
+----+--------+-------+-------+
|  1 | Salt   | 19.00 |     2 |
|  2 | Sugar  | 32.00 |     3 |
|  3 | Bread  | 17.00 |     0 |
|  4 | Butter | 55.00 |     1 |
|  5 | Milk   | 32.00 |     2 |
+----+--------+-------+-------+
5 rows in set (0.001 sec)

MariaDB [MARIANA]> SELECT * FROM users;
+----+-----------+-------------------+
| id | full_name | email             |
+----+-----------+-------------------+
|  1 | John Doe  | john.doe@john.doe |
|  2 | Jane Doe  | jane.doe@john.doe |
|  3 | Jiiiiiiii | john.doe@john.doe |
|  4 | Jfffffff  | jane.doe@john.doe |
|  5 | Jfffffff  | jane.doe@john.doe |
+----+-----------+-------------------+
5 rows in set (0.001 sec)

MariaDB [MARIANA]> exit;
Bye
```

```
mar@DESKTOP-C26IRMG:~$ sudo mysql -u root -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 105
Server version: 10.6.12-MariaDB-0ubuntu0.22.04.1 Ubuntu 22.04

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> CREATE DATABASE mariana_new;
Query OK, 1 row affected (0.006 sec)

MariaDB [(none)]> exit;
Bye
mar@DESKTOP-C26IRMG:~$ mysql -u admin -p mariana_new < data-dump.sql
Enter password:
mar@DESKTOP-C26IRMG:~$ mariadb -u admin -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 107
Server version: 10.6.12-MariaDB-0ubuntu0.22.04.1 Ubuntu 22.04

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]>
MariaDB [(none)]> use mariana_new;
Reading table information for completion of table and column names
You can turn off this feature to get a quicker startup with -A

Database changed
```

```
MariaDB [mariana_new]> SHOW TABLES;
+-----------------------+
| Tables_in_mariana_new |
+-----------------------+
| products              |
| users                 |
+-----------------------+
2 rows in set (0.001 sec)

MariaDB [mariana_new]> exit;
Bye
mar@DESKTOP-C26IRMG:~$
```