

Lab 7

Medical Imaging

IST 2020-2021

Load the MRI raw data (`rawdata.mat`) obtained from a phantom using a spin-warp imaging pulse sequence using either `load` in Matlab or `loadmat` in Python. Assign one of the image dimensions to the readout direction and the other to the phase-encoding direction.

1. Display the magnitude and phase of the 2D k -space data.
2. Reconstruct the image by Fourier transform (using `fftshift(iff2(rawdata))` in Matlab and the equivalent `numpy` functions in Python). Display the magnitude and phase of the reconstructed image.
3. Repeat 1-2, by truncating the k -space data (i.e., reducing k_{\max} and leaving Δk unchanged), by one half, one fourth and one eighth, along the phase-encoding direction.
4. Repeat 1-2, by under-sampling the k -space data (i.e., leaving k_{\max} unchanged and increasing Δk) by half along the phase-encoding direction.
5. Repeat 1-2, by considering half Fourier imaging along the phase-encoding direction, i.e., sampling only half the phase-encoding steps and then using Hermitian symmetry to obtain a full k -space before image reconstruction:

$$M(-k_x, -k_y) = M^*(k_x, k_y)$$

6. Repeat 5, by considering 5/8 partial Fourier imaging. i.e., by adding 1/8 of the data points in the unsampled half of k -space. Explain the observed differences relative to 5.